

Photometric test report

Family
Silica® 21



Order number: **51MX33TAT7W**
EAN: **4058352685600**

LP number
59332_30

serial
documentation
03.05.2023

Version Suspended luminaire, with homogeneous illumination, prismatic cover, direct-/ indirect distribution, extremely wide distribution, $UGR \leq 16$ ($L65 \leq 3000 \text{ cd/m}^2$), tunable white

Lamps LED 4000 K | CRI ≥ 80

Controlgear ECG-DALI

Setting factory setting

Rated values Net luminous flux = 5740 lm
Power consumption = 56.5 W
Luminous efficacy = 101.6 lm/W


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 358 cd/klm



Classifications

DIN 5040 C 6 2
CIE N1=78 N2=96 N3=99
N4=56 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 56.2%
 ϕ_o 43.8%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Silica® 21	Order number: 51MX33TAT7W EAN: 4058352685600	LP number 59332_30
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	354.9	354.9	354.9	354.9	354.9	354.9	354.9	2.1	2.1
5°	357.6	358.3	358.1	358.3	357.8	357.0	356.1	17.1	19.2
10°	345.2	344.3	344.5	346.4	350.1	350.3	350.6	33.1	52.3
15°	340.0	338.8	336.2	336.1	338.1	341.2	341.0	48.0	100.3
20°	328.0	327.2	323.2	324.1	322.5	324.8	329.3	60.9	161.2
25°	307.9	308.7	306.4	306.5	306.8	306.6	312.0	71.2	232.5
30°	287.2	287.0	283.4	284.9	285.2	284.2	286.2	78.2	310.6
35°	247.5	247.0	244.6	246.0	246.7	245.6	246.4	77.4	388.0
40°	182.5	182.1	183.5	184.7	186.1	185.9	187.0	65.0	453.0
45°	111.7	111.4	112.8	114.1	115.4	116.9	119.1	44.3	497.3
50°	52.4	60.7	68.3	62.5	56.3	66.9	74.7	26.5	523.8
55°	21.3	28.6	27.1	30.9	23.3	32.2	30.0	12.6	536.4
60°	14.3	14.9	15.7	14.6	14.6	15.6	16.3	7.2	543.6
65°	11.8	11.7	12.2	11.9	12.4	12.3	12.4	6.0	549.6
70°	8.5	8.7	9.0	9.0	9.2	9.3	9.8	4.7	554.2
75°	5.9	6.2	6.8	6.5	6.6	7.0	7.1	3.5	557.7
80°	3.6	3.8	4.2	4.6	4.2	4.7	4.8	2.3	560.0
85°	1.8	1.8	1.8	2.1	2.2	2.6	2.7	1.2	561.2
90°	6.2	6.0	6.3	6.0	3.5	1.2	0.4	2.4	563.6
95°	22.4	22.9	24.7	23.8	15.7	8.2	4.2	9.9	573.5
100°	39.4	40.6	41.5	37.2	25.7	14.7	9.7	16.6	590.1
105°	56.7	58.1	58.0	51.0	35.4	22.2	16.2	23.0	613.1
110°	77.6	78.3	74.6	63.1	45.4	29.8	23.1	29.3	642.4
115°	96.2	95.7	89.3	74.3	55.1	37.6	30.6	34.4	676.8
120°	112.0	110.6	101.9	83.7	64.3	45.2	37.9	38.0	714.8
125°	124.0	121.0	110.5	92.7	72.3	52.4	45.6	39.9	754.8
130°	129.8	127.1	115.2	98.2	78.4	59.6	53.3	39.9	794.7
135°	130.8	128.1	117.0	101.7	82.9	66.3	61.0	38.2	832.9
140°	128.7	126.6	117.2	103.9	86.2	72.4	69.0	35.5	868.4
145°	125.8	124.5	116.6	104.5	89.3	78.0	75.4	32.1	900.6
150°	122.1	121.5	114.3	103.4	91.6	83.4	81.3	28.1	928.7
155°	117.5	116.9	110.1	102.0	93.3	88.1	86.5	23.6	952.4
160°	111.2	110.8	105.7	100.5	94.8	91.7	91.2	18.9	971.3
165°	105.4	104.8	102.1	98.7	96.3	94.6	94.6	14.1	985.4
170°	101.1	100.5	99.8	98.3	97.2	96.9	96.9	9.4	994.7
175°	98.4	98.3	97.7	97.5	97.5	97.5	97.5	4.7	999.4
180°	97.7	97.7	97.7	97.7	97.7	97.7	97.7	0.6	1000.0

Photometric test report

Family Silica® 21		Order number: 51MX33TAT7W EAN: 4058352685600							LP number 59332_30	
UGR-Table		Standard room							siteco	
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		View crosswise (C0)					View endwise (C90)			
x	y									
2H	2H	15.4	16.3	16.3	17.2	18.3	15.6	16.5	16.5	17.4
	3H	15.3	16.1	16.2	17.0	18.1	15.6	16.4	16.5	17.3
	4H	15.3	16.0	16.2	16.9	18.1	15.6	16.3	16.5	17.2
	6H	15.2	15.8	16.1	16.8	17.9	15.6	16.2	16.5	17.1
	8H	15.1	15.7	16.1	16.7	17.9	15.5	16.0	16.4	17.0
	12H	15.0	15.6	16.0	16.5	17.8	15.5	16.0	16.4	17.0
4H	2H	15.2	15.9	16.1	16.8	17.9	15.3	16.0	16.2	16.9
	3H	15.2	15.8	16.1	16.7	17.9	15.4	16.0	16.3	16.9
	4H	15.2	15.7	16.1	16.7	17.9	15.4	16.0	16.4	16.9
	6H	15.2	15.6	16.1	16.6	17.8	15.5	15.9	16.5	16.9
	8H	15.1	15.5	16.1	16.5	17.8	15.5	15.9	16.5	16.9
	12H	15.1	15.4	16.1	16.4	17.7	15.5	15.9	16.5	16.8
8H	4H	15.1	15.5	16.0	16.4	17.7	15.3	15.7	16.2	16.6
	6H	15.1	15.5	16.1	16.5	17.7	15.4	15.7	16.4	16.7
	8H	15.1	15.4	16.1	16.4	17.7	15.5	15.8	16.5	16.8
	12H	15.1	15.3	16.1	16.3	17.6	15.6	15.8	16.6	16.8
12H	4H	15.0	15.3	16.0	16.3	17.6	15.2	15.5	16.2	16.5
	6H	15.1	15.3	16.1	16.3	17.6	15.3	15.6	16.4	16.6
	8H	15.1	15.3	16.1	16.3	17.6	15.4	15.7	16.5	16.7

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 1200 B = 50	
C-planes	γ	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°
			Luminance in cd/m²				
45° 50° 55° 60°	γ	15106.7	15074.0	15263.2	15443.0	15610.3	15809.5
		7801.6	9038.1	10164.1	9302.1	8383.0	9956.2
		3547.1	4778.0	4513.3	5156.1	3894.2	5377.3
		2745.3	2849.0	3011.4	2791.4	2801.7	2979.6
65° 70° 75° 80°	γ	2667.1	2646.2	2752.2	2684.9	2798.8	2794.5
		2385.9	2430.7	2529.1	2528.9	2568.9	2598.2
		2190.8	2273.9	2505.7	2393.0	2448.4	2573.3
		1978.9	2096.3	2312.2	2516.6	2334.3	2604.2
85°	γ	1924.2	1950.5	2027.4	2346.8	2464.2	2819.9

Photometric test report

Family
Silica® 21

Order number: **51MX33TAT7W**
EAN: **4058352685600**

LP number
59332_30

Luminance values in cd/m²

γ 65°

γ 70°

γ 75°

γ 80°

γ 85°

siteco

