


Photometric test report

Family Licross® Spot 31	Order number: 51SL32DA45B EAN: 4058352864937	LP number 59381_28
	Version reflector, cover, polycarbonate, narrow distribution, luminaire housing, aluminium, black	serial documentation 12.07.2023
	Lamps LED 4000 K CRI ≥ 90 Controlgear ECG-DALI Setting factory setting: DIP-Step=7 Rated values Net luminous flux = 5140 lm Power consumption = 43.9 W Luminous efficacy = 117.1 lm/W	

siteco

Luminous intensity in cd/klm C180-0 **Imax: 4501 cd/klm**



Classifications	
DIN 5040	A 7 0
CIE	N1=93 N2=97 N3=99 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
 DIN EN 13032 and DIN 5032

Photometric test report

Family Licross® Spot 31	Order number: 51SL32DA45B EAN: 4058352864937	LP number 59381_28
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm		Luminous flux in lm/klm
0°	4500.5	1.1	1.1
1°	4480.3	8.6	9.7
2°	4437.5	17.0	26.6
3°	4362.0	25.0	51.7
4°	4236.1	32.4	84.1
5°	4010.1	38.3	122.4
6°	3672.5	42.1	164.5
7°	3309.8	44.2	208.7
8°	2898.6	44.2	253.0
9°	2482.5	42.6	295.6
10°	2122.6	40.4	336.0
11°	1782.7	37.3	373.3
12°	1538.7	35.1	408.4
13°	1327.4	32.7	441.1
14°	1130.4	30.0	471.1
15°	985.0	28.0	499.1
16°	859.9	26.0	525.0
17°	761.9	24.4	549.5
18°	683.9	23.2	572.6
19°	616.9	22.0	594.7
20°	570.3	21.4	616.1
21°	532.3	20.9	637.0
22°	498.2	20.5	657.4
23°	472.4	20.2	677.7
24°	451.2	20.1	697.8
25°	433.6	20.1	717.9
26°	418.4	20.1	738.0
27°	405.2	20.2	758.2
28°	393.9	20.3	778.5
29°	380.9	20.3	798.7
30°	356.4	19.5	818.3
31°	326.4	18.4	836.7
32°	294.9	17.1	853.8
33°	256.7	15.3	869.2
34°	220.2	13.5	882.7
35°	180.4	11.3	894.0
36°	146.1	9.4	903.4
37°	111.1	7.3	910.8
38°	79.1	5.3	916.1
39°	56.1	3.9	920.0
40°	40.9	2.9	922.8
41°	37.1	2.7	925.5
42°	35.5	2.6	928.1
43°	33.6	2.5	930.6
44°	33.1	2.5	933.2
45°	33.1	2.6	935.7
46°	32.9	2.6	938.3

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm		Luminous flux in lm/klm
47°	33.1	2.7	941.0
48°	33.6	2.7	943.7
49°	34.5	2.9	946.6
50°	35.6	3.0	949.6
51°	36.2	3.1	952.6
52°	35.7	3.1	955.7
53°	33.7	2.9	958.7
54°	30.9	2.7	961.4
55°	27.6	2.5	963.9
56°	23.6	2.1	966.1
57°	21.0	1.9	968.0
58°	19.1	1.8	969.8
59°	17.3	1.6	971.4
60°	16.3	1.5	972.9
61°	15.8	1.5	974.5
62°	15.5	1.5	976.0
63°	15.1	1.5	977.4
64°	14.4	1.4	978.9
65°	14.1	1.4	980.3
66°	13.7	1.4	981.6
67°	13.0	1.3	982.9
68°	12.9	1.3	984.3
69°	12.5	1.3	985.5
70°	12.0	1.2	986.8
71°	11.4	1.2	988.0
72°	11.1	1.2	989.1
73°	10.6	1.1	990.2
74°	10.1	1.1	991.3
75°	9.5	1.0	992.3
76°	8.7	0.9	993.2
77°	7.7	0.8	994.0
78°	6.8	0.7	994.8
79°	6.5	0.7	995.5
80°	6.1	0.7	996.1
81°	5.4	0.6	996.7
82°	5.2	0.6	997.3
83°	4.8	0.5	997.8
84°	4.1	0.5	998.2
85°	3.8	0.4	998.7
86°	3.1	0.3	999.0
87°	3.1	0.3	999.3
88°	2.5	0.3	999.6
89°	2.2	0.2	999.9
90°	2.5	0.3	1000.1

Photometric test report

Family Licross® Spot 31	Order number: 51SL32DA45B EAN: 4058352864937	LP number 59381_28
-----------------------------------	---	------------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	22.2	23.2	22.5	23.5	23.9	22.2	23.2	22.5	23.5	23.9
	3H	22.7	23.7	23.1	24.0	24.3	22.7	23.7	23.1	24.0	24.3
	4H	23.1	24.0	23.5	24.3	24.7	23.1	24.0	23.5	24.3	24.7
	6H	23.4	24.2	23.8	24.5	24.9	23.4	24.2	23.8	24.5	24.9
	8H	23.7	24.3	24.1	24.7	25.1	23.7	24.3	24.1	24.7	25.1
	12H	23.7	24.4	24.2	24.8	25.2	23.7	24.4	24.2	24.8	25.2
4H	2H	22.3	23.1	22.7	23.5	23.8	22.3	23.1	22.7	23.5	23.8
	3H	23.1	23.7	23.5	24.1	24.6	23.1	23.7	23.5	24.1	24.6
	4H	23.6	24.2	24.0	24.6	25.0	23.6	24.2	24.0	24.6	25.0
	6H	24.0	24.5	24.4	25.0	25.4	24.0	24.5	24.4	25.0	25.4
	8H	24.2	24.7	24.7	25.1	25.6	24.2	24.7	24.7	25.1	25.6
	12H	24.4	24.8	24.9	25.3	25.8	24.4	24.8	24.9	25.3	25.8
8H	4H	23.7	24.2	24.2	24.6	25.1	23.7	24.2	24.2	24.6	25.1
	6H	24.3	24.7	24.8	25.2	25.7	24.3	24.7	24.8	25.2	25.7
	8H	24.6	24.9	25.1	25.4	26.0	24.6	24.9	25.1	25.4	26.0
	12H	24.9	25.2	25.4	25.7	26.3	24.9	25.2	25.4	25.7	26.3
12H	4H	23.7	24.1	24.2	24.6	25.1	23.7	24.1	24.2	24.6	25.1
	6H	24.3	24.7	24.8	25.1	25.7	24.3	24.7	24.8	25.1	25.7
	8H	24.7	25.0	25.2	25.5	26.0	24.7	25.0	25.2	25.5	26.0


Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm: D = 79
------------------------	---	---

C-planes	0°
γ	Luminance in cd/m²
45°	49056.8
50°	58138.6
55°	50537.4
60°	34220.7
65°	34988.1
70°	36718.0
75°	38433.1
80°	36564.8
85°	46213.3

Photometric test report

Family Licross® Spot 31	Order number: 51SL32DA45B EAN: 4058352864937	LP number 59381_28
--	---	-------------------------------------

Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85°



Photometric test report

Family
Licross® Spot 31

Order number: 51SL32DA45B
EAN: 4058352864937

LP number
59381_28

Multilumen Table

environmental temperature: 25°C

siteco

DIP-Step	Switch Setting			Luminous flux [lm]	Power consumption [W]
	1	2	3		
7	ON	ON	ON	5140	43.9
6	OFF	ON	ON	4930	41.7
5	ON	OFF	ON	4730	39.5
4	OFF	OFF	ON	4500	37.3
3	ON	ON	OFF	4310	35.1
2	OFF	ON	OFF	4090	33.0
1	ON	OFF	OFF	3850	30.8
0	OFF	OFF	OFF	3650	28.6