



Photometric test report

Family Licross® 11 Protected	Order number: 51TD11DN4F5S EAN: 4058352928561	LP number 58525_182
	Version prismatic cover, frosted, narrow distribution Lamps LED 4000 K CRI ≥ 80 Controlgear ECG-DALI Rated values Net luminous flux = 15510 lm Power consumption = 87.3 W Luminous efficacy = 177.7 lm/W	serial documentation 14.09.2023





Luminous intensity in cd/klm C180-0 C270-90 **Imax: 2130 cd/klm**



Classifications	
DIN 5040	A 7 1
CIE	N1=84 N2=94 N3=98 N4=99 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	99.1%
ϕ_o	0.9%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Licross® 11 Protected	Order number: 51TD11DN4F5S EAN: 4058352928561	LP number 58525_182
Table of values for luminous intensities		Maximum luminous intensity
		sITeco

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm								Luminous flux in lm/klm	
0°	2130.5	2130.5	2130.5	2130.5	2130.5	2130.5	2130.5	12.7	12.7
5°	1990.0	1982.4	1972.8	1980.9	1991.5	1994.0	1997.3	94.9	107.6
10°	1609.4	1602.7	1594.9	1604.0	1616.7	1623.6	1628.9	153.3	260.9
15°	1156.5	1152.7	1146.1	1151.7	1161.7	1170.4	1176.7	164.3	425.2
20°	757.1	754.5	751.0	754.8	760.5	766.7	772.3	142.2	567.4
25°	464.1	463.3	461.4	464.7	468.5	471.4	475.4	108.1	675.5
30°	281.8	280.0	276.3	277.8	280.6	282.2	284.6	76.7	752.2
35°	178.8	175.8	169.5	168.1	169.9	172.0	174.0	54.1	806.3
40°	123.8	119.7	111.6	107.8	108.9	112.2	115.0	39.9	846.2
45°	92.5	87.9	79.0	74.1	74.5	78.8	82.8	31.1	877.3
50°	72.9	68.3	60.1	54.9	54.7	59.1	63.7	25.6	902.9
55°	58.5	54.5	47.8	42.9	42.0	45.8	50.2	21.5	924.4
60°	46.6	43.5	38.6	34.6	32.9	35.6	39.1	18.0	942.5
65°	36.7	34.5	31.1	28.0	26.1	27.3	29.5	14.9	957.4
70°	28.5	27.0	24.6	22.5	20.4	20.1	21.2	12.0	969.4
75°	21.8	20.7	19.0	17.5	15.4	14.0	14.0	9.2	978.6
80°	16.2	15.4	14.3	12.9	10.9	8.9	8.1	6.7	985.3
85°	11.7	11.2	10.3	9.1	7.1	4.7	3.5	4.6	989.8
90°	8.1	7.7	6.9	5.8	3.9	1.7	0.3	2.8	992.6
95°	6.9	6.6	5.8	4.7	3.0	1.1	0.2	2.3	994.8
100°	6.0	5.6	4.9	3.8	2.2	0.6	0.2	1.8	996.7
105°	5.1	4.8	4.0	2.9	1.5	0.3	0.2	1.4	998.1
110°	4.3	4.0	3.2	2.2	0.9	0.2	0.2	1.1	999.2
115°	3.6	3.2	2.5	1.6	0.5	0.3	0.3	0.8	1000.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Licross® 11 Protected	Order number: 51TD11DN4F5S EAN: 4058352928561	LP number 58525_182
--	--	-------------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	17.6	18.8	17.9	19.1	19.4	17.2	18.4	17.6	18.7	19.1
	3H	18.7	19.7	19.0	20.1	20.4	18.1	19.2	18.5	19.5	19.9
	4H	19.2	20.2	19.6	20.5	20.9	18.5	19.5	18.9	19.9	20.2
	6H	19.6	20.5	20.1	20.9	21.3	18.8	19.7	19.2	20.1	20.5
	8H	20.0	20.7	20.4	21.1	21.5	19.0	19.7	19.4	20.1	20.5
	12H	20.1	20.8	20.6	21.2	21.6	19.0	19.7	19.5	20.1	20.5
4H	2H	17.8	18.8	18.2	19.2	19.6	17.5	18.5	17.9	18.9	19.2
	3H	19.1	19.9	19.5	20.3	20.7	18.6	19.4	19.0	19.8	20.2
	4H	19.7	20.5	20.2	20.9	21.3	19.1	19.8	19.5	20.2	20.7
	6H	20.4	21.0	20.8	21.4	21.9	19.5	20.1	19.9	20.5	21.0
	8H	20.7	21.2	21.2	21.7	22.2	19.6	20.2	20.1	20.6	21.1
	12H	21.0	21.4	21.5	21.9	22.4	19.7	20.2	20.2	20.7	21.2
8H	4H	19.9	20.5	20.4	20.9	21.4	19.3	19.9	19.8	20.3	20.8
	6H	20.7	21.1	21.2	21.6	22.1	19.9	20.3	20.4	20.8	21.3
	8H	21.1	21.5	21.6	22.0	22.5	20.0	20.5	20.6	20.9	21.5
	12H	21.5	21.8	22.0	22.3	22.9	20.2	20.5	20.7	21.1	21.6
12H	4H	20.0	20.4	20.5	20.9	21.4	19.4	19.8	19.9	20.3	20.8
	6H	20.8	21.1	21.3	21.6	22.1	20.0	20.3	20.5	20.8	21.3
	8H	21.2	21.5	21.7	22.0	22.6	20.2	20.5	20.7	21.0	21.6


Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 1480	H(C0) = 13	H(C180) = 13
			B = 78	H(C90) = 0	H(C270) = 0

C-planes	γ	Luminance in cd/m ²							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
45°		15069.6	14378.4	13120.3	12597.4	13071.2	14357.1	15723.3	
50°		12713.7	11980.6	10725.3	10068.6	10391.9	11755.4	13305.6	
55°		11075.6	10386.4	9281.8	8604.7	8786.0	10113.2	11761.0	
60°		9726.9	9148.9	8297.6	7711.0	7735.8	8907.1	10506.6	
65°		8597.1	8154.1	7559.3	7115.9	7045.4	7931.9	9367.9	
70°		7673.6	7345.9	6921.5	6667.0	6535.8	7073.6	8318.2	
75°		6961.9	6703.8	6405.7	6296.4	6100.6	6244.1	7274.3	
80°		6454.0	6244.8	6078.5	5987.6	5709.6	5504.7	6231.6	
85°		6225.1	6060.7	5989.3	5998.0	5577.2	4898.1	5383.1	

Photometric test report

Family Licross® 11 Protected	Order number: 51TD11DN4F5S EAN: 4058352928561	LP number 58525_182
---	--	--------------------------------------

Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85° **siteco**



Photometric test report

Family Licross® 11 Protected	Order number: 51TD11DN4F5S EAN: 4058352928561	LP number 58525_182
--	--	--------------------------------------

Dimming levels table	environmental temperature: 25°C	sITeco
-----------------------------	---------------------------------	---------------

Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]
100	254	254	15510	87.3
95	240	252	14728	82.4
90	226	250	13934	77.5
85	213	248	13189	72.9
80	200	245	12435	68.3
75	186	243	11617	63.6
70	173	240	10850	59.1
65	160	237	10079	54.7
60	147	234	9300	50.2
55	134	231	8512	45.9
50	122	227	7781	41.9
45	109	223	6983	37.7
40	96	218	6176	33.4
35	84	213	5425	29.4
30	72	208	4666	25.7
25	60	201	3901	21.8
20	48	193	3128	17.9
15	36	182	2351	14.0
10	24	168	1568	10.1
5	12	142	777	6.4
2	4	102	247	4.0