

Photometric test report

Family
Licross® 11 Recessed

Order number: 51TE117N485G
EAN: 4058352929049

LP number
58785_348



Version cover frosted, narrow distribution
Lamps LED 4000 K | CRI ≥ 80
Controlgear ECG
Rated values Net luminous flux = 8810 lm
 Power consumption = 48.5 W
 Luminous efficacy = 181.6 lm/W

serial
documentation
11.10.2023


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 2627 cd/klm



Classifications

DIN 5040 A 7 0
 CIE N1=89 N2=96 N3=99
 N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 100.0%
 ϕ_o 0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Licross® 11 Recessed	Order number: 51TE117N485G EAN: 4058352929049	LP number 58785_348
Table of values for luminous intensities		Maximum luminous intensity

siteco

C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	2627.4	2627.4	2627.4	2627.4	2627.4	2627.4	2627.4	15.7	15.7
5°	2520.2	2503.8	2487.8	2499.1	2508.6	2505.8	2505.2	119.6	135.3
10°	2060.7	2047.7	2044.6	2066.8	2086.2	2092.0	2094.5	196.9	332.2
15°	1373.4	1369.0	1375.7	1399.2	1421.9	1432.7	1437.2	198.7	530.9
20°	791.8	790.8	796.4	808.8	818.0	819.0	819.4	151.2	682.1
25°	418.1	420.5	425.4	427.2	423.4	413.4	409.3	97.4	779.6
30°	215.7	218.7	224.8	222.9	213.7	202.3	197.8	58.9	838.4
35°	112.4	114.3	119.3	116.0	107.4	103.1	102.4	35.0	873.4
40°	70.3	69.7	69.6	67.8	65.2	68.3	71.3	24.2	897.6
45°	52.4	50.5	46.9	47.4	48.4	54.1	61.4	19.6	917.2
50°	46.4	44.6	38.1	38.0	38.3	44.7	54.3	17.8	935.0
55°	42.3	42.2	36.7	33.4	32.3	38.6	47.1	17.1	952.1
60°	32.7	32.9	34.3	30.2	28.0	32.6	38.2	15.3	967.4
65°	23.6	23.8	26.4	25.7	24.0	26.1	29.3	12.6	980.0
70°	15.1	15.6	18.2	19.4	18.6	19.5	20.9	9.4	989.4
75°	8.3	8.7	10.8	13.0	12.9	13.2	13.7	6.1	995.5
80°	4.0	4.1	5.0	6.6	7.3	7.2	7.2	3.2	998.7
85°	1.6	1.6	1.9	2.5	2.6	2.7	2.5	1.2	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Licross® 11 Recessed	Order number: 51TE117N485G EAN: 4058352929049	LP number 58785_348
--------------------------------	--	------------------------

UGR-Table		Standard room							siteco		
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	14.9	16.0	15.3	16.3	16.7	14.8	16.0	15.2	16.3	16.6
	3H	15.8	16.8	16.2	17.2	17.5	16.2	17.2	16.6	17.6	17.9
	4H	16.1	17.0	16.5	17.3	17.7	16.8	17.7	17.2	18.0	18.4
	6H	16.2	17.0	16.6	17.3	17.7	17.1	17.9	17.5	18.3	18.7
	8H	16.3	16.9	16.7	17.3	17.7	17.3	17.9	17.7	18.3	18.7
	12H	16.3	16.9	16.7	17.3	17.7	17.3	17.9	17.8	18.3	18.7
4H	2H	15.4	16.3	15.8	16.7	17.0	15.4	16.2	15.8	16.6	17.0
	3H	16.5	17.3	17.0	17.7	18.1	16.9	17.6	17.3	18.0	18.4
	4H	16.8	17.5	17.3	17.9	18.4	17.5	18.2	17.9	18.6	19.0
	6H	17.0	17.5	17.5	18.0	18.4	17.9	18.5	18.4	18.9	19.4
	8H	17.0	17.5	17.5	17.9	18.4	18.1	18.5	18.5	19.0	19.5
	12H	17.0	17.4	17.5	17.9	18.4	18.1	18.5	18.6	19.0	19.5
8H	4H	17.1	17.6	17.6	18.0	18.5	17.7	18.2	18.2	18.6	19.1
	6H	17.3	17.7	17.8	18.1	18.6	18.2	18.6	18.7	19.1	19.6
	8H	17.3	17.6	17.8	18.1	18.7	18.3	18.7	18.9	19.2	19.7
	12H	17.3	17.6	17.9	18.1	18.7	18.5	18.7	19.0	19.2	19.8
12H	4H	17.1	17.5	17.6	18.0	18.5	17.7	18.1	18.2	18.6	19.1
	6H	17.3	17.6	17.8	18.1	18.6	18.2	18.5	18.7	19.0	19.6
	8H	17.4	17.6	17.9	18.1	18.7	18.4	18.7	18.9	19.2	19.7

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 1500 B = 58		
C-planes	γ	0°	15°	30°	45°	60°	75°	90°
		180°	165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°	
Luminance in cd/m²								
45°		7509.6	7227.8	6714.7	6782.5	6926.2	7754.1	8792.3
50°		7314.6	7028.6	5995.6	5992.2	6030.6	7047.4	8549.2
55°		7474.0	7453.0	6478.8	5891.3	5709.2	6816.4	8307.7
60°		6619.4	6660.0	6945.5	6119.4	5665.9	6592.5	7735.4
65°		5644.3	5707.3	6325.5	6166.9	5753.8	6252.4	7009.6
70°		4473.4	4610.5	5403.1	5732.1	5518.9	5774.7	6189.8
75°		3259.2	3411.0	4223.2	5087.5	5055.0	5155.6	5354.3
80°		2304.6	2386.9	2931.5	3841.3	4250.1	4178.9	4214.5
85°		1879.9	1906.6	2225.0	2884.9	3048.8	3119.6	2859.4

Photometric test report

Family Licross® 11 Recessed	Order number: 51TE117N485G EAN: 4058352929049	LP number 58785_348	
Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85°			

