




Photometric test report

Family Licross® 11 Recessed	Order number: 51TL11MN4AXG EAN: 4058352929520	LP number 58785_345
	Version cover frosted, narrow distribution Lamps LED 4000 K CRI ≥ 80 Controlgear ECG Multilumen Rated values Net luminous flux = 10130 lm Power consumption = 55.2 W Luminous efficacy = 183.5 lm/W	serial documentation 11.10.2023
		

Luminous intensity in cd/klm C180-0 C270-90 **Imax: 2627 cd/klm**



Classifications	
DIN 5040	A 7 0
CIE	N1=89 N2=96 N3=99 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Licross® 11 Recessed	Order number: 51TL11MN4AXG EAN: 4058352929520	LP number 58785_345
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm							Luminous flux in lm/klm		
0°	2627.4	2627.4	2627.4	2627.4	2627.4	2627.4	2627.4	15.7	15.7
5°	2520.2	2503.8	2487.8	2499.1	2508.6	2505.8	2505.2	119.6	135.3
10°	2060.7	2047.7	2044.6	2066.8	2086.2	2092.0	2094.5	196.9	332.2
15°	1373.4	1369.0	1375.7	1399.2	1421.9	1432.7	1437.2	198.7	530.9
20°	791.8	790.8	796.4	808.8	818.0	819.0	819.4	151.2	682.1
25°	418.1	420.5	425.4	427.2	423.4	413.4	409.3	97.4	779.6
30°	215.7	218.7	224.8	222.9	213.7	202.3	197.8	58.9	838.4
35°	112.4	114.3	119.3	116.0	107.4	103.1	102.4	35.0	873.4
40°	70.3	69.7	69.6	67.8	65.2	68.3	71.3	24.2	897.6
45°	52.4	50.5	46.9	47.4	48.4	54.1	61.4	19.6	917.2
50°	46.4	44.6	38.1	38.0	38.3	44.7	54.3	17.8	935.0
55°	42.3	42.2	36.7	33.4	32.3	38.6	47.1	17.1	952.1
60°	32.7	32.9	34.3	30.2	28.0	32.6	38.2	15.3	967.4
65°	23.6	23.8	26.4	25.7	24.0	26.1	29.3	12.6	980.0
70°	15.1	15.6	18.2	19.4	18.6	19.5	20.9	9.4	989.4
75°	8.3	8.7	10.8	13.0	12.9	13.2	13.7	6.1	995.5
80°	4.0	4.1	5.0	6.6	7.3	7.2	7.2	3.2	998.7
85°	1.6	1.6	1.9	2.5	2.6	2.7	2.5	1.2	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Licross® 11 Recessed	Order number: 51TL11MN4AXG EAN: 4058352929520	LP number 58785_345
--	--	--------------------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	15.4	16.5	15.8	16.8	17.1	15.3	16.4	15.7	16.8	17.1
	3H	16.3	17.3	16.7	17.6	18.0	16.7	17.7	17.1	18.0	18.4
	4H	16.6	17.4	16.9	17.8	18.2	17.3	18.1	17.7	18.5	18.9
	6H	16.7	17.4	17.1	17.8	18.2	17.6	18.4	18.0	18.8	19.2
	8H	16.8	17.4	17.2	17.8	18.2	17.8	18.4	18.2	18.8	19.2
	12H	16.8	17.3	17.2	17.7	18.2	17.8	18.4	18.2	18.8	19.2
4H	2H	15.9	16.8	16.3	17.2	17.5	15.8	16.7	16.2	17.1	17.5
	3H	17.0	17.8	17.5	18.2	18.6	17.4	18.1	17.8	18.5	18.9
	4H	17.3	18.0	17.8	18.4	18.8	18.0	18.6	18.4	19.1	19.5
	6H	17.5	18.0	17.9	18.4	18.9	18.4	19.0	18.9	19.4	19.9
	8H	17.5	18.0	18.0	18.4	18.9	18.5	19.0	19.0	19.5	20.0
	12H	17.5	17.9	18.0	18.4	18.9	18.6	19.0	19.1	19.5	20.0
8H	4H	17.6	18.1	18.1	18.5	19.0	18.2	18.7	18.7	19.1	19.6
	6H	17.7	18.1	18.2	18.6	19.1	18.7	19.1	19.2	19.6	20.1
	8H	17.8	18.1	18.3	18.6	19.1	18.8	19.2	19.3	19.7	20.2
	12H	17.8	18.1	18.3	18.6	19.1	18.9	19.2	19.5	19.7	20.3
12H	4H	17.6	18.0	18.1	18.5	19.0	18.2	18.6	18.7	19.0	19.5
	6H	17.8	18.1	18.3	18.6	19.1	18.7	19.0	19.2	19.5	20.0
	8H	17.8	18.1	18.4	18.6	19.2	18.9	19.1	19.4	19.6	20.2

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 1500
			B = 58

C-planes	γ	Luminance in cd/m ²							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
45°		8634.8	8310.7	7720.7	7798.8	7963.9	8915.9	10109.7	
50°		8410.5	8081.7	6894.0	6890.0	6934.2	8103.3	9830.1	
55°		8593.9	8569.7	7449.5	6774.0	6564.7	7837.7	9552.4	
60°		7611.2	7657.8	7986.2	7036.3	6514.9	7580.3	8894.4	
65°		6490.0	6562.4	7273.3	7090.9	6615.9	7189.2	8059.9	
70°		5143.7	5301.3	6212.7	6590.9	6345.8	6639.9	7117.2	
75°		3747.5	3922.0	4856.0	5849.8	5812.4	5928.0	6156.6	
80°		2649.9	2744.5	3370.8	4416.8	4886.8	4805.0	4845.9	
85°		2161.6	2192.3	2558.4	3317.2	3505.6	3587.1	3287.8	


Photometric test report

Family Licross® 11 Recessed	Order number: 51TL11MN4AXG EAN: 4058352929520	LP number 58785_345
--	--	--------------------------------------

Luminance values in cd/m²

γ 65°
 γ 70°
 γ 75°
 γ 80°
 γ 85°

siteco



Photometric test report

Family Licross® 11 Recessed	Order number: 51TL11MN4AXG EAN: 4058352929520	LP number 58785_345
--	--	--------------------------------------

Multilumen Table	environmental temperature: 25°C	
-------------------------	---------------------------------	---

DIP-Step	Switch Setting			Luminous flux [lm]	Power consumption [W]
	1	2	3		
1	A	C	E	10130	55.2
2	A	C	F	9690	52.5
3	A	D	E	9160	49.3
4	A	D	F	8640	46.2
5	B	C	E	7880	41.7
6	B	C	F	7650	40.4
7	B	D	E	7110	37.4
8	B	D	F	6650	34.8