

Photometric test report

Family
DL 11 iQ

Order number: 5XA5565KF108P00022
EAN: 4058352956021

LP number
59375_88

serial
documentation
01.02.2024



Version luminaire insert LED, Siteco® metallic grey (DB 702S), post-top- or mounting to wall arm
Optic asymmetric, wide distribution (ST1.2a)
Cover cover transparent, PMMA
Lamps LED 4000 K | CRI ≥ 70
Controlgear ECG SITECO iQ
Rated values Net luminous flux = 4810 lm
Power consumption = 33.6 W
Luminous efficacy = 143.2 lm/W

siteco

Luminous intensity in cd/klm


C180-0

C200-20

C205-25

C270-90

Imax: 769 cd/klm



Luminaire output ratios

Eta	100.0%
Eta 0° - 90°	98.8%
Eta 90° - 180°	1.2%

Luminous intensity class acc. to EN13201-2

Class:	G1
Imax 70°	670.6
Imax 80°	166.8
Imax 90°	10.3
Imax >90°	5.5
Imax >95°	4.0

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family
DL 11 iQ

Order number: 5XA5565KF108P00022
EAN: 4058352956021

LP number
59375_88

Envelope curve in cd/klm


KMK 62.5°

KMK 60°

KMK 57.5°

KMK 55°

siteco



Photometric test report

Family DL 11 iQ	Order number: 5XA5565KF108P00022 EAN: 4058352956021	LP number 59375_88
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	5° 175°	10° 170°	15° 165°	20° 160°	25° 155°	30° 150°	35° 145°	40° 140°	45° 135°	50° 130°	55° 125°	60° 120°
γ	Luminous intensity in cd/klm												
0,0°	19.1	19.1	19.1	19.1	19.1	19.1	19.1	19.1	19.1	19.1	19.1	19.1	19.1
2,5°	20.5	19.5	19.6	20.2	20.8	21.5	22.2	23.0	22.8	22.6	22.7	22.7	22.4
5,0°	31.2	33.0	35.2	36.8	38.0	38.5	38.0	36.5	36.5	34.9	35.7	36.1	36.9
7,5°	45.2	45.1	45.8	47.8	47.7	48.3	50.4	49.7	49.4	52.0	52.7	53.4	54.4
10,0°	64.6	66.7	67.0	63.5	67.2	72.4	75.5	73.4	76.0	73.8	75.5	78.7	79.8
12,5°	91.1	94.9	94.9	102.6	96.0	97.3	90.6	87.7	84.8	91.6	101.6	107.7	111.3
15,0°	120.9	125.4	152.5	131.3	129.9	134.9	132.9	140.9	144.9	145.5	135.5	131.1	136.7
17,5°	139.7	142.8	153.8	159.8	157.1	173.3	154.7	141.3	140.7	143.7	148.3	151.1	158.5
20,0°	145.7	154.9	159.9	166.6	161.7	170.3	168.5	161.2	162.4	174.0	159.5	164.2	167.0
22,5°	174.1	171.2	179.5	165.1	173.1	165.9	165.4	170.5	182.3	173.1	179.9	195.4	200.6
25,0°	170.9	179.0	188.5	188.9	191.0	190.3	195.4	183.7	188.1	195.8	183.6	194.6	214.1
27,5°	211.9	206.1	196.7	198.6	201.2	211.7	215.5	210.5	209.0	219.6	208.0	211.1	229.1
30,0°	195.1	212.5	233.6	231.3	222.8	217.3	222.0	215.1	224.5	230.2	222.9	220.6	244.4
32,5°	228.6	216.0	203.5	218.0	232.4	255.0	260.8	255.0	271.0	274.9	256.1	255.3	276.0
35,0°	254.4	266.3	272.3	262.1	251.2	265.0	275.3	273.2	278.0	293.6	291.5	274.6	294.4
37,5°	267.2	263.1	260.8	271.7	293.0	309.3	289.8	287.1	299.2	312.6	312.0	297.6	321.7
40,0°	271.3	276.2	274.3	281.0	293.0	325.4	347.9	331.8	324.3	328.7	320.5	307.4	333.2
42,5°	287.0	284.5	287.3	298.0	318.0	352.3	369.2	349.5	350.9	371.7	359.0	328.3	338.4
45,0°	305.4	298.9	309.1	316.9	350.4	380.6	384.3	378.1	378.1	383.9	367.3	335.6	348.8
47,5°	319.7	314.0	338.2	352.1	377.7	414.7	419.2	417.2	399.5	396.0	382.6	353.6	365.0
50,0°	338.3	348.8	377.1	400.8	416.8	466.2	472.2	450.2	425.1	417.4	396.6	363.4	357.0
52,5°	345.7	374.3	422.4	489.1	494.7	530.7	525.6	501.1	451.4	435.7	405.3	373.7	345.0
55,0°	356.1	412.3	450.4	561.6	584.8	591.8	600.2	525.5	495.1	437.5	393.6	364.4	316.3
57,5°	373.3	444.7	509.2	635.5	666.2	665.2	632.8	566.5	518.4	434.8	377.5	344.5	297.3
60,0°	358.2	451.1	540.6	663.7	742.1	705.5	651.2	601.3	529.6	428.9	362.8	316.5	269.6
62,5°	337.3	436.7	538.0	644.0	768.6	759.1	679.0	627.8	534.3	435.0	353.1	296.6	238.4
65,0°	300.4	388.3	534.2	661.6	755.4	765.5	698.4	609.5	519.5	428.4	337.5	280.2	210.8
67,5°	285.7	339.7	496.1	630.1	736.2	715.5	677.5	590.6	494.9	397.3	323.1	259.3	181.3
70,0°	290.9	360.7	477.8	628.0	670.6	649.7	636.9	528.9	440.6	366.8	295.3	228.8	158.0
72,5°	256.2	369.0	419.6	582.0	631.0	589.9	501.1	444.8	365.2	282.3	224.5	174.3	133.9
75,0°	184.2	300.6	381.2	494.0	504.5	480.2	362.2	321.0	229.6	188.2	181.3	164.0	127.5
77,5°	116.8	178.9	256.2	331.5	334.6	268.3	206.8	175.0	148.0	129.3	127.4	121.4	104.7
80,0°	73.4	97.3	132.9	158.7	166.8	137.5	130.6	129.7	102.1	68.2	52.9	41.1	39.7
82,5°	45.3	51.0	62.0	72.8	81.0	66.8	82.8	93.7	66.4	43.1	25.3	18.2	10.9
85,0°	25.6	27.4	25.8	26.5	25.5	31.0	51.1	59.1	39.2	21.2	15.5	11.2	8.5
87,5°	12.1	12.7	13.2	14.5	15.3	15.0	15.2	12.9	11.3	9.2	8.3	7.3	6.5
90,0°	9.0	8.4	8.6	8.8	8.8	8.6	8.6	7.4	6.8	6.2	5.8	5.6	5.5
92,5°	5.3	5.4	5.5	5.5	5.5	5.5	5.4	5.3	5.3	5.1	5.1	4.9	4.9
95,0°	4.5	4.6	4.6	4.6	4.6	4.4	4.4	4.3	4.2	4.2	3.9	3.8	3.7
97,5°	3.8	3.9	4.0	3.9	3.8	3.8	3.8	3.7	3.6	3.5	3.4	3.3	3.1
100,0°	3.6	3.6	3.6	3.6	3.5	3.4	3.4	3.1	3.1	2.9	2.9	2.9	2.9
102,5°	3.1	3.1	3.1	3.1	3.1	2.9	2.9	2.9	2.7	2.7	2.7	2.6	2.5
105,0°	2.9	2.9	2.9	2.9	2.8	2.7	2.7	2.5	2.5	2.5	2.5	2.2	2.2
107,5°	2.7	2.7	2.7	2.7	2.6	2.5	2.5	2.2	2.2	2.2	2.2	2.0	2.0
110,0°	2.5	2.5	2.5	2.5	2.4	2.2	2.2	2.1	2.0	2.0	2.0	2.0	2.0
112,5°	2.4	2.4	2.2	2.2	2.1	2.1	2.0	2.0	2.0	1.9	1.8	1.8	1.8

Photometric test report

Family DL 11 iQ	Order number: 5XA5565KF108P00022 EAN: 4058352956021	LP number 59375_88
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	65° 115°	70° 110°	75° 105°	80° 100°	85° 95°	90°	185° 355°	190° 350°	195° 345°	200° 340°	205° 335°	210° 330°	215° 325°
γ	Luminous intensity in cd/klm												
0,0°	19.1	19.1	19.1	19.1	19.1	19.1	19.1	19.1	19.1	19.1	19.1	19.1	19.1
2,5°	22.3	22.6	22.8	23.1	23.2	23.3	19.8	19.6	19.8	20.0	20.2	20.3	20.0
5,0°	37.3	37.8	38.9	39.2	39.6	39.5	28.3	25.0	23.6	21.7	18.9	18.7	18.9
7,5°	56.5	58.0	58.7	61.7	62.6	62.6	43.2	42.1	43.4	43.0	40.7	36.1	34.3
10,0°	83.1	85.7	87.3	91.4	95.8	96.7	61.7	51.5	51.1	47.9	47.8	47.4	48.0
12,5°	116.0	113.4	109.3	108.8	109.5	110.2	88.8	99.4	89.3	91.5	80.8	80.2	68.5
15,0°	131.8	132.2	141.0	151.8	156.1	162.5	107.3	94.6	90.0	92.7	88.8	87.3	79.8
17,5°	166.2	184.3	199.0	201.1	193.5	194.4	128.2	117.5	108.4	106.4	91.8	78.7	73.8
20,0°	174.4	188.8	217.5	245.4	247.2	239.3	125.6	122.1	105.5	92.0	84.1	78.1	71.7
22,5°	209.5	225.4	249.0	257.1	254.3	246.2	170.9	153.2	132.8	108.9	99.2	74.2	57.4
25,0°	235.2	247.1	268.8	296.2	300.3	298.3	166.3	166.8	148.6	113.4	96.2	71.8	49.4
27,5°	247.2	253.3	284.5	301.7	304.9	306.6	183.5	159.4	140.2	117.2	98.8	79.9	45.0
30,0°	269.2	274.1	297.2	304.6	299.3	301.0	202.9	197.5	172.1	129.6	97.3	66.9	38.4
32,5°	290.6	294.5	310.1	317.6	318.6	322.1	220.2	192.4	166.9	124.7	96.0	59.0	35.7
35,0°	309.0	322.0	336.4	339.4	337.9	339.6	247.0	218.7	181.8	129.7	92.9	53.2	34.5
37,5°	334.8	355.3	357.1	358.4	361.6	370.6	252.9	224.1	183.2	146.3	90.0	51.9	36.3
40,0°	350.3	374.0	365.8	368.8	375.6	391.0	259.4	240.3	179.1	142.8	82.0	47.9	36.9
42,5°	356.8	374.1	369.2	375.9	382.4	387.9	275.8	244.7	179.3	135.5	78.6	44.0	38.8
45,0°	368.8	378.8	372.4	382.8	389.3	392.8	296.4	256.3	182.6	120.5	69.4	44.6	41.3
47,5°	379.1	373.2	378.9	392.6	395.5	396.4	303.5	258.6	178.6	109.3	57.0	44.9	41.6
50,0°	371.4	360.8	367.2	382.6	386.3	385.9	306.8	262.5	169.8	94.2	45.0	41.3	37.4
52,5°	350.6	345.7	358.5	368.1	379.7	378.7	306.4	267.6	162.2	83.9	40.2	36.7	33.2
55,0°	314.1	322.6	338.6	352.1	365.6	370.6	312.2	266.3	149.4	75.3	39.7	33.6	30.4
57,5°	287.2	288.9	295.6	316.8	343.0	349.9	305.3	242.1	126.7	60.6	36.7	31.0	28.2
60,0°	250.6	255.8	236.2	261.9	297.9	307.1	298.2	209.1	106.2	48.9	35.2	29.7	28.1
62,5°	198.0	205.3	185.4	202.0	220.6	240.0	261.6	173.5	93.4	52.0	38.0	28.7	27.5
65,0°	165.0	153.0	129.3	144.6	156.0	150.6	222.4	145.5	91.8	57.6	37.7	30.4	28.6
67,5°	136.1	105.8	75.9	85.2	88.9	85.3	201.1	132.5	87.0	55.7	37.1	32.3	29.1
70,0°	112.6	75.6	42.1	36.6	39.3	45.1	193.2	131.9	83.7	51.5	37.9	32.4	29.3
72,5°	93.0	45.0	24.1	17.2	16.2	17.3	170.4	131.1	82.2	48.0	38.3	32.0	29.0
75,0°	71.0	20.3	14.7	11.4	10.9	10.6	129.3	97.1	74.1	46.9	42.4	34.7	31.0
77,5°	32.7	12.9	10.0	8.8	8.6	8.5	78.5	64.8	62.7	42.4	39.4	35.6	31.4
80,0°	11.4	8.6	7.6	7.4	7.3	7.2	58.6	56.5	51.7	40.1	35.4	33.8	30.5
82,5°	8.1	6.8	6.4	6.2	6.2	6.1	42.9	41.9	38.4	32.8	32.2	31.2	28.8
85,0°	6.7	6.2	5.8	5.5	5.4	5.4	23.9	25.8	27.5	28.6	29.0	27.7	24.9
87,5°	5.9	5.5	5.2	4.8	4.6	4.5	11.6	11.8	11.8	13.6	14.8	16.5	15.9
90,0°	5.3	5.1	4.8	4.4	4.3	4.0	8.6	8.4	8.3	8.5	9.5	10.3	8.4
92,5°	4.8	4.6	4.4	3.9	3.8	3.8	5.3	5.2	5.1	4.9	4.8	4.8	4.7
95,0°	3.6	3.5	3.4	3.4	3.4	3.4	4.4	4.4	4.2	4.2	4.0	3.9	3.8
97,5°	3.1	3.1	3.1	3.0	2.9	2.9	3.8	3.8	3.6	3.5	3.5	3.3	3.3
100,0°	2.7	2.7	2.7	2.7	2.7	2.7	3.4	3.4	3.3	3.3	3.1	3.0	3.0
102,5°	2.5	2.5	2.5	2.5	2.5	2.5	3.1	3.1	2.9	2.9	2.9	2.8	2.8
105,0°	2.2	2.2	2.2	2.2	2.2	2.2	2.9	2.8	2.7	2.7	2.7	2.6	2.6
107,5°	2.0	2.0	2.0	2.0	2.0	2.0	2.7	2.6	2.5	2.5	2.5	2.5	2.4
110,0°	2.0	2.0	2.0	2.0	2.0	2.0	2.5	2.5	2.4	2.2	2.2	2.2	2.4
112,5°	1.8	1.8	1.8	1.8	1.8	1.8	2.4	2.2	2.2	2.2	2.2	2.2	2.2

Photometric test report

Family DL 11 iQ				Order number: 5XA5565KF108P00022 EAN: 4058352956021								LP number 59375_88	
Table of values for luminous intensities										Maximum luminous intensity		siteco	
C-planes	220° 320°	225° 315°	230° 310°	235° 305°	240° 300°	245° 295°	250° 290°	255° 285°	260° 280°	265° 275°	270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm										Luminous flux in lm/klm		
0,0°	19.1	19.1	19.1	19.1	19.1	19.1	19.1	19.1	19.1	19.1	19.1	0.0	0.0
2,5°	20.1	20.4	20.8	20.7	20.5	20.7	21.4	22.3	22.8	22.9	22.9	0.3	0.3
5,0°	20.0	20.8	21.4	21.5	21.7	21.9	21.9	22.3	22.8	23.2	23.3	0.7	1.0
7,5°	31.0	31.6	36.7	36.1	35.4	31.9	27.6	23.8	21.2	19.5	19.1	1.5	2.5
10,0°	48.6	43.4	43.8	46.7	44.7	38.9	37.3	37.8	36.7	36.7	37.9	2.9	5.5
12,5°	59.8	61.6	65.4	68.8	62.0	56.3	52.0	45.9	43.2	43.0	41.1	5.0	10.5
15,0°	75.1	66.6	65.0	67.2	65.1	58.6	56.0	51.2	51.3	57.6	58.1	7.6	18.0
17,5°	70.9	66.4	63.7	64.9	59.9	52.5	54.2	56.7	51.6	54.7	54.5	9.9	28.0
20,0°	61.8	56.6	56.5	56.6	54.2	52.4	44.6	44.7	38.6	43.7	44.4	11.8	39.7
22,5°	48.4	44.2	43.9	43.8	41.4	39.8	35.8	35.4	32.8	34.6	36.6	14.1	53.8
25,0°	38.3	35.6	34.2	32.9	31.4	31.2	29.9	29.0	29.3	33.4	32.5	16.5	70.3
27,5°	36.4	32.1	29.5	28.1	27.3	26.0	27.3	23.5	23.2	24.5	25.1	18.9	89.2
30,0°	33.6	30.2	28.1	26.7	24.6	23.1	22.8	19.5	18.0	18.6	18.4	21.5	110.7
32,5°	32.5	30.3	28.1	26.0	23.6	21.0	19.5	17.6	15.5	15.3	15.5	24.7	135.4
35,0°	31.8	29.1	27.0	24.5	21.7	19.1	17.7	15.9	14.3	13.8	13.9	28.6	164.0
37,5°	33.1	28.5	25.3	23.3	21.3	18.6	16.7	15.0	13.5	12.7	13.0	32.2	196.1
40,0°	33.4	30.0	24.9	22.0	19.4	17.6	16.0	14.6	13.2	12.5	12.6	35.5	231.6
42,5°	35.0	29.7	24.8	22.2	18.9	16.9	15.4	14.0	12.9	12.2	12.1	38.8	270.4
45,0°	36.4	29.9	24.5	21.0	18.5	17.2	15.5	13.9	12.7	11.8	11.7	42.2	312.7
47,5°	35.5	29.2	23.9	21.9	20.3	18.5	16.7	14.7	12.9	11.7	11.4	45.9	358.5
50,0°	32.1	26.5	22.7	23.0	23.8	22.8	21.2	19.4	17.1	15.4	15.0	49.5	408.0
52,5°	28.6	24.2	22.3	24.5	26.0	25.8	25.3	24.5	22.6	20.8	20.4	53.6	461.6
55,0°	26.7	23.7	22.3	24.9	27.4	28.3	28.3	27.3	25.5	24.9	25.1	57.1	518.6
57,5°	25.7	23.8	22.8	25.0	27.3	29.0	29.9	28.5	26.0	24.9	25.1	59.6	578.2
60,0°	24.9	22.4	21.8	24.8	27.8	30.0	30.4	28.7	26.3	24.8	24.7	60.1	638.3
62,5°	24.7	22.6	21.8	23.9	27.3	29.6	30.9	28.7	25.9	24.8	24.7	58.9	697.2
65,0°	25.6	23.2	22.3	23.2	25.5	27.3	29.2	27.5	24.9	24.9	24.7	56.5	753.8
67,5°	26.3	23.9	23.8	23.6	24.8	25.6	26.4	24.8	22.7	21.9	22.2	52.7	806.5
70,0°	27.8	25.0	24.6	23.1	22.6	22.6	21.9	21.4	20.7	20.2	20.9	49.1	855.6
72,5°	27.0	26.2	24.6	22.9	20.8	18.9	18.1	17.5	17.3	17.5	17.7	43.1	898.6
75,0°	28.6	25.8	24.0	22.2	18.4	15.0	15.0	15.0	15.0	15.2	15.3	34.6	933.3
77,5°	28.6	26.4	23.1	20.7	15.0	11.8	12.0	12.1	12.6	12.8	12.6	23.1	956.4
80,0°	26.9	24.2	22.6	17.6	13.1	9.3	9.4	9.7	10.0	10.1	9.7	13.8	970.2
82,5°	26.5	21.9	19.6	14.8	11.8	7.4	7.5	7.6	7.7	8.1	7.6	8.6	978.8
85,0°	20.9	18.3	15.2	11.1	9.1	6.2	6.2	6.3	6.3	6.4	5.8	5.3	984.1
87,5°	13.2	12.6	10.7	8.1	6.4	5.5	5.3	5.2	5.3	5.5	4.7	2.7	986.8
90,0°	7.4	7.2	6.7	5.8	5.3	4.8	4.8	4.7	4.6	4.8	4.3	1.9	988.7
92,5°	4.7	4.7	4.6	4.5	4.4	4.3	4.2	4.2	3.9	4.0	3.6	1.3	990.0
95,0°	3.8	3.7	3.7	3.5	3.4	3.3	3.1	3.0	2.9	2.8	2.5	1.0	991.1
97,5°	3.3	3.3	3.0	2.9	2.8	2.8	2.7	2.6	2.5	2.5	2.2	0.9	992.0
100,0°	2.9	2.8	2.8	2.7	2.7	2.6	2.4	2.4	2.2	2.2	2.0	0.8	992.8
102,5°	2.7	2.6	2.6	2.5	2.5	2.4	2.2	2.1	2.0	2.0	2.0	0.7	993.5
105,0°	2.6	2.6	2.5	2.4	2.2	2.1	2.1	2.0	2.0	1.9	1.8	0.7	994.1
107,5°	2.4	2.4	2.2	2.2	2.1	2.1	2.0	1.9	1.8	1.8	1.8	0.6	994.7
110,0°	2.2	2.2	2.2	2.1	2.0	2.0	1.9	1.8	1.8	1.8	1.8	0.6	995.3
112,5°	2.2	2.2	2.1	2.0	2.0	1.9	1.9	1.8	1.8	1.8	1.6	0.5	995.8

Photometric test report

Family DL 11 iQ	Order number: 5XA5565KF108P00022 EAN: 4058352956021	LP number 59375_88
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	5° 175°	10° 170°	15° 165°	20° 160°	25° 155°	30° 150°	35° 145°	40° 140°	45° 135°	50° 130°	55° 125°	60° 120°
γ	Luminous intensity in cd/klm												
115,0°	2.2	2.2	2.2	2.1	2.1	2.0	2.0	1.8	1.8	1.8	1.8	1.8	1.8
117,5°	2.1	2.2	2.1	2.0	2.0	1.9	1.8	1.8	1.8	1.6	1.6	1.6	1.6
120,0°	2.1	2.1	2.0	2.0	1.9	1.8	1.8	1.7	1.6	1.6	1.6	1.6	1.6
122,5°	2.0	2.0	1.9	1.9	1.8	1.7	1.6	1.6	1.6	1.6	1.6	1.6	1.6
125,0°	2.0	1.9	1.9	1.8	1.7	1.6	1.6	1.6	1.6	1.5	1.3	1.3	1.3
127,5°	1.8	1.8	1.7	1.6	1.6	1.5	1.5	1.3	1.3	1.3	1.3	1.3	1.3
130,0°	1.6	1.6	1.6	1.5	1.3	1.3	1.3	1.3	1.1	1.1	1.1	1.1	1.1
132,5°	1.5	1.3	1.3	1.3	1.2	1.1	1.1	1.1	1.1	1.0	0.9	0.9	0.9
135,0°	1.3	1.3	1.3	1.2	1.1	1.1	1.1	1.0	1.0	0.9	0.9	0.9	0.9
137,5°	1.3	1.2	1.1	1.1	1.1	1.1	1.0	0.9	0.9	0.9	0.9	0.9	0.9
140,0°	1.1	1.1	1.1	1.1	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.8
142,5°	1.1	1.1	1.1	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.8	0.8	0.8
145,0°	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.7	0.7	0.7	0.7	0.7
147,5°	0.9	0.9	0.9	0.9	0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.6
150,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Photometric test report

Family DL 11 iQ	Order number: 5XA5565KF108P00022 EAN: 4058352956021	LP number 59375_88
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	65° 115°	70° 110°	75° 105°	80° 100°	85° 95°	90°	185° 355°	190° 350°	195° 345°	200° 340°	205° 335°	210° 330°	215° 325°
γ	Luminous intensity in cd/klm												
115,0°	1.8	1.8	1.8	1.8	1.8	1.8	2.2	2.2	2.2	2.2	2.2	2.2	2.2
117,5°	1.6	1.6	1.6	1.7	1.6	1.6	2.2	2.2	2.2	2.2	2.2	2.2	2.2
120,0°	1.6	1.6	1.6	1.6	1.6	1.6	2.1	2.1	2.1	2.1	2.1	2.1	2.1
122,5°	1.5	1.6	1.5	1.6	1.6	1.6	2.0	2.0	2.0	2.0	2.0	2.0	2.0
125,0°	1.3	1.3	1.3	1.3	1.3	1.3	2.0	2.0	2.0	2.0	2.0	2.0	2.0
127,5°	1.3	1.3	1.3	1.3	1.3	1.3	1.8	1.8	1.8	1.8	1.9	1.9	2.0
130,0°	1.1	1.1	1.1	1.1	1.1	1.1	1.7	1.7	1.8	1.8	1.8	1.8	1.8
132,5°	0.9	0.9	0.9	0.9	0.9	0.9	1.6	1.6	1.6	1.6	1.6	1.6	1.6
135,0°	0.9	0.9	0.9	0.9	0.9	0.9	1.5	1.6	1.6	1.6	1.6	1.6	1.6
137,5°	0.9	0.9	0.9	0.9	0.9	0.9	1.3	1.3	1.3	1.3	1.3	1.3	1.5
140,0°	0.8	0.9	0.9	0.8	0.9	0.7	1.1	1.1	1.1	1.1	1.3	1.3	1.3
142,5°	0.7	0.7	0.7	0.7	0.7	0.7	1.1	1.1	1.1	1.1	1.1	1.1	1.3
145,0°	0.7	0.7	0.7	0.7	0.7	0.7	1.0	1.0	1.0	1.1	1.1	1.1	1.1
147,5°	0.6	0.6	0.6	0.6	0.4	0.4	0.9	0.9	0.9	0.9	0.9	0.9	0.9
150,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Photometric test report

Family DL 11 iQ	Order number: 5XA5565KF108P00022 EAN: 4058352956021	LP number 59375_88
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	220° 320°	225° 315°	230° 310°	235° 305°	240° 300°	245° 295°	250° 290°	255° 285°	260° 280°	265° 275°	270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm											Luminous flux in lm/klm	
115,0°	2.2	2.2	2.2	2.1	2.0	1.9	1.9	1.8	1.8	1.8	1.8	0.5	996.3
117,5°	2.1	2.1	2.0	2.0	2.0	1.9	1.8	1.8	1.8	1.7	1.8	0.5	996.7
120,0°	2.1	2.1	2.0	2.0	2.0	1.9	1.8	1.7	1.6	1.6	1.6	0.4	997.2
122,5°	2.0	2.0	2.0	2.0	1.9	1.8	1.8	1.6	1.6	1.6	1.6	0.4	997.6
125,0°	2.0	2.0	2.0	1.8	1.8	1.8	1.7	1.6	1.6	1.6	1.6	0.4	998.0
127,5°	1.9	1.9	1.8	1.8	1.8	1.7	1.6	1.6	1.6	1.6	1.6	0.3	998.3
130,0°	1.8	1.8	1.8	1.8	1.7	1.6	1.6	1.6	1.5	1.6	1.6	0.3	998.6
132,5°	1.6	1.7	1.6	1.6	1.6	1.6	1.6	1.5	1.3	1.3	1.3	0.3	998.9
135,0°	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.3	1.3	1.3	1.3	0.2	999.1
137,5°	1.6	1.5	1.6	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	0.2	999.4
140,0°	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.2	1.1	1.1	1.1	0.2	999.6
142,5°	1.3	1.3	1.3	1.2	1.3	1.1	1.1	1.1	1.1	1.1	1.1	0.2	999.7
145,0°	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	0.1	999.9
147,5°	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.0	1.1	0.1	1000.0
150,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
152,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
157,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
162,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
167,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
172,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
177,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family DL 11 iQ	Order number: 5XA5565KF108P00022 EAN: 4058352956021	LP number 59375_88
Dimming levels table		environmental temperature: 25°C



Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W] start of lifetime	Power consumption [W] end of lifetime	Power consumption [W] average
100	254	254	4810	33.6	35.9	34.8
95	241	252	4564	31.4	33.5	32.4
90	229	250	4337	29.4	31.4	30.4
85	216	248	4090	27.4	29.2	28.3
80	203	246	3844	25.5	27.1	26.3
75	190	243	3598	23.6	25.2	24.4
70	178	241	3371	21.9	23.3	22.6
65	165	238	3125	20.2	21.5	20.8
60	152	235	2878	18.5	19.6	19.0
55	140	232	2651	16.9	18.0	17.4
50	127	229	2405	15.3	16.2	15.8
45	114	225	2159	13.7	14.5	14.1
40	102	221	1932	12.3	13.0	12.6
35	89	216	1685	10.8	11.4	11.1
30	76	210	1439	9.3	9.8	9.6
25	63	203	1193	7.8	8.2	8.0
20	51	195	966	6.6	6.9	6.8
15	38	184	720	5.2	5.5	5.4
11	28	173	530	4.1	4.4	4.2