

Photometric test report

Family
Lunis 41



Order number: 51DR10DDGBB
EAN: 4069025152015

Version

Lamps

Controlgear

Setting

Rated values

recessed luminaire, diffuse cover, extremely wide distribution, adjustable color temperature: 3000 K | 4000 K

LED 4000 K | CRI ≥ 80

ECG Multilumen


factory setting: DIP-Step=3, colour temperature 4000K

Net luminous flux = 1750 lm
Power consumption = 14.0 W
Luminous efficacy = 125 lm/W

LP number
59234_18

serial
documentation
16.01.2025

siteco



Classifications		Luminaire light output ratios	
DIN 5040	A 4 0	η_{LB}	100.0%
CIE	N1=49 N2=80 N3=96	ϕ_u	100.0%
	N4=100 N5=100	ϕ_o	0.0%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Lunis 41	Order number: 51DR10DDGGB EAN: 4069025152015	LP number 59234_18
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	368.6	368.6	368.6	368.6	368.6	368.6	368.6	2.2	2.2
5°	367.2	366.8	366.3	365.8	365.5	365.3	365.0	17.5	19.7
10°	362.1	361.4	360.8	360.1	359.5	358.9	358.3	34.3	54.0
15°	354.2	353.1	351.9	350.8	350.1	349.3	348.6	49.8	103.8
20°	342.9	341.5	340.1	338.8	337.8	336.9	336.0	63.6	167.3
25°	327.9	326.3	324.6	323.0	321.8	320.6	319.4	74.9	242.3
30°	310.7	308.8	306.8	304.8	303.5	302.2	300.8	83.7	325.9
35°	290.5	288.3	286.2	284.0	282.5	281.0	279.5	89.4	415.4
40°	267.0	264.6	262.3	260.0	258.4	256.8	255.2	91.8	507.2
45°	242.2	239.7	237.3	234.8	233.0	231.3	229.5	91.2	598.4
50°	215.7	213.2	210.6	208.1	206.2	204.3	202.4	87.6	686.0
55°	186.3	184.1	181.9	179.7	177.4	175.1	172.8	80.7	766.6
60°	157.1	154.5	151.9	149.2	146.6	144.0	141.4	70.8	837.5
65°	128.1	125.1	122.0	118.9	116.8	114.6	112.5	59.4	896.9
70°	96.9	93.9	90.9	87.9	85.9	83.8	81.7	45.6	942.5
75°	66.8	64.2	61.7	59.2	57.0	54.7	52.5	31.5	974.0
80°	40.0	39.6	39.2	38.8	35.1	31.4	27.8	19.6	993.6
85°	16.1	14.5	12.9	11.3	10.3	9.3	8.3	6.4	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Lunis 41			Order number: 51DR10DDGGB EAN: 4069025152015							LP number 59234_18	
UGR-Table			Standard room							siteco	
Reflection factor of ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Reflection factor of walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reflection factor of floor		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	25.7	27.4	26.1	27.7	28.0	25.4	27.0	25.7	27.3	27.7
	3H	27.3	28.8	27.7	29.1	29.5	26.8	28.3	27.1	28.6	29.0
	4H	27.9	29.3	28.3	29.7	30.1	27.3	28.7	27.6	29.0	29.4
	6H	28.4	29.7	28.8	30.1	30.5	27.6	28.9	28.0	29.3	29.6
	8H	28.6	29.8	29.0	30.2	30.6	27.7	28.9	28.1	29.3	29.7
	12H	28.7	29.8	29.1	30.2	30.6	27.7	28.9	28.1	29.3	29.7
4H	2H	26.4	27.8	26.8	28.2	28.5	26.1	27.5	26.5	27.9	28.3
	3H	28.1	29.4	28.6	29.7	30.1	27.7	28.9	28.1	29.3	29.7
	4H	28.9	30.0	29.3	30.4	30.8	28.3	29.4	28.7	29.8	30.2
	6H	29.5	30.4	29.9	30.8	31.3	28.7	29.7	29.2	30.1	30.6
	8H	29.7	30.6	30.2	31.0	31.5	28.9	29.7	29.3	30.2	30.6
	12H	29.8	30.6	30.3	31.1	31.5	28.9	29.7	29.4	30.1	30.6
8H	4H	29.2	30.0	29.6	30.5	30.9	28.6	29.5	29.1	29.9	30.4
	6H	29.9	30.6	30.4	31.1	31.6	29.2	29.9	29.7	30.4	30.9
	8H	30.2	30.8	30.7	31.3	31.8	29.4	30.0	29.9	30.5	31.0
	12H	30.4	30.9	30.9	31.4	31.9	29.5	30.0	30.0	30.5	31.0
12H	4H	29.2	30.0	29.7	30.4	30.9	28.7	29.5	29.2	29.9	30.4
	6H	30.0	30.6	30.5	31.1	31.6	29.3	29.9	29.8	30.4	30.9
	8H	30.3	30.8	30.8	31.3	31.8	29.5	30.0	30.0	30.5	31.1

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		D = 125	
C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
γ	Luminance in cd/m²						
45°	48846.5	48350.0	47853.7	47357.0	46998.6	46640.4	46282.0
50°	47855.6	47292.6	46729.7	46166.7	45744.0	45321.9	44899.5
55°	46323.0	45774.3	45225.1	44676.1	44102.0	43527.7	42953.7
60°	44800.7	44054.9	43309.6	42563.8	41818.3	41072.5	40326.9
65°	43240.6	42195.9	41150.9	40106.2	39395.3	38684.3	37973.4
70°	40382.6	39144.3	37905.9	36668.0	35800.0	34932.3	34064.6
75°	36792.5	35393.5	33995.7	32597.3	31380.2	30164.2	28947.1
80°	32828.1	32494.7	32160.5	31827.1	28825.5	25824.8	22823.3
85°	26286.9	23711.6	21137.9	18562.5	16901.8	15241.1	13578.7

Photometric test report

Family
Lunis 41

Order number: 51DR10DDGGBB
EAN: 4069025152015

LP number
59234_18

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Lunis 41	Order number: 51DR10DDGGBB EAN: 4069025152015	LP number 59234_18
Multilumen Table	environmental temperature: 25°C	siteco

DIP-Step	Switch Setting		Luminous flux [lm]	Power consumption [W]
	1	2		
3	ON	ON	1750	14.0
2	OFF	ON	1580	12.6
1	ON	OFF	1300	10.5
0	OFF	OFF	1050	8.5