


Photometric test report

Family Lunis 31 	Order number: 51DN167G32 EAN: 4058352556009	LP number 59322_4
	Version cover, diffuse, wide distribution Lamps LED 3000 K CRI ≥ 80 Controlgear ECG Rated values Net luminous flux = 2000 lm Power consumption = 17.0 W Luminous efficacy = 117.6 lm/W	serial documentation 15.06.2022



Luminous intensity in cd/klm C180-0 **Imax: 509 cd/klm**



Classifications	
DIN 5040	A 5 0
CIE	N1=64 N2=93 N3=99 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Lunis 31	Order number: 51DN167G32 EAN: 4058352556009	LP number 59322_4
---------------------------	--	-----------------------------



Table of values for luminous intensities	Maximum luminous intensity
---	-----------------------------------

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm	Luminous flux in lm/klm	
0,0°	509.2	0.8	0.8
2,5°	507.8	6.1	6.8
5,0°	505.4	12.1	18.9
7,5°	501.7	18.0	36.9
10,0°	496.8	23.6	60.5
12,5°	490.8	29.1	89.6
15,0°	483.3	34.3	123.9
17,5°	474.7	39.1	163.1
20,0°	464.4	43.5	206.6
22,5°	452.4	47.5	254.1
25,0°	438.6	50.8	304.9
27,5°	422.8	53.5	358.4
30,0°	405.0	55.5	413.9
32,5°	384.6	56.7	470.6
35,0°	362.4	57.0	527.5
37,5°	339.5	56.7	584.2
40,0°	315.3	55.6	639.7
42,5°	287.7	53.3	693.0
45,0°	257.7	50.0	743.0
47,5°	226.8	45.8	788.8
50,0°	196.0	41.2	830.0
52,5°	166.3	36.2	866.1
55,0°	138.0	31.0	897.1
57,5°	111.4	25.8	922.9
60,0°	86.8	20.6	943.5
62,5°	65.4	15.9	959.4
65,0°	47.0	11.7	971.1
67,5°	32.2	8.1	979.2
70,0°	22.8	5.9	985.1
72,5°	17.7	4.6	989.7
75,0°	13.7	3.6	993.3
77,5°	10.2	2.7	996.1
80,0°	7.1	1.9	998.0
82,5°	4.5	1.2	999.2
85,0°	2.3	0.6	999.9
87,5°	0.5	0.1	1000.0
90,0°	0.0	0.0	1000.0

Photometric test report

Family Lunis 31	Order number: 51DN167G32 EAN: 4058352556009	LP number 59322_4
---------------------------	--	-----------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	21.3	22.8	21.6	23.1	23.4	21.3	22.8	21.6	23.1	23.4
	3H	21.5	22.8	21.8	23.1	23.5	21.5	22.8	21.8	23.1	23.5
	4H	21.5	22.7	21.9	23.1	23.4	21.5	22.7	21.9	23.1	23.4
	6H	21.5	22.6	21.9	23.0	23.4	21.5	22.6	21.9	23.0	23.4
	8H	21.5	22.5	22.0	22.9	23.3	21.5	22.5	22.0	22.9	23.3
	12H	21.5	22.5	21.9	22.9	23.3	21.5	22.5	21.9	22.9	23.3
4H	2H	21.5	22.7	21.9	23.1	23.4	21.5	22.7	21.9	23.1	23.4
	3H	21.7	22.7	22.1	23.1	23.5	21.7	22.7	22.1	23.1	23.5
	4H	21.7	22.7	22.2	23.1	23.5	21.7	22.7	22.2	23.1	23.5
	6H	21.8	22.5	22.2	23.0	23.4	21.8	22.5	22.2	23.0	23.4
	8H	21.8	22.5	22.2	22.9	23.4	21.8	22.5	22.2	22.9	23.4
	12H	21.8	22.4	22.3	22.8	23.3	21.8	22.4	22.3	22.8	23.3
8H	4H	21.7	22.4	22.2	22.9	23.4	21.7	22.4	22.2	22.9	23.4
	6H	21.8	22.3	22.3	22.8	23.3	21.8	22.3	22.3	22.8	23.3
	8H	21.8	22.3	22.3	22.8	23.3	21.8	22.3	22.3	22.8	23.3
	12H	21.8	22.2	22.3	22.7	23.2	21.8	22.2	22.3	22.7	23.2
12H	4H	21.7	22.3	22.2	22.8	23.3	21.7	22.3	22.2	22.8	23.3
	6H	21.8	22.2	22.3	22.7	23.3	21.8	22.2	22.3	22.7	23.3
	8H	21.8	22.2	22.3	22.7	23.2	21.8	22.2	22.3	22.7	23.2

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm: D = 204
------------------------	---	--

C-planes	0°
γ	Luminance in cd/m²
45,0°	22301.3
50,0°	18656.7
55,0°	14718.0
60,0°	10619.0
65,0°	6805.0
70,0°	4080.5
75,0°	3232.3
80,0°	2513.9
85,0°	1638.6

Photometric test report

Family Lunis 31	Order number: 51DN167G32 EAN: 4058352556009	LP number 59322_4
---------------------------	--	-----------------------------

Luminance values in cd/m²
γ 65°
γ 70°
γ 75°
γ 80°
γ 85°
siteco

