

Photometric test report

Family
Licross® Protected

Order number: 51TP11DN49XFD
EAN: 4058352418413

LP number
58526_24




Version prismatic cover, frosted, narrow distribution
Lamps LED 4000 K | CRI ≥ 80
Controlgear ECG-DALI
Setting DC mode (central or group accumulator) initial emergency light level
Rated values Net luminous flux = 1440 lm
 Power consumption = 10.2 W
 Luminous efficacy = 141.2 lm/W

serial
documentation
26.08.2020

siteco

Luminous intensity in cd/klm **C180-0** **C270-90**

Imax: 1742 cd/klm



Classifications

DIN 5040 A 7 0
 CIE N1=83 N2=94 N3=98
 N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 100.0%
 ϕ_o 0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Licross® Protected	Order number: 51TP11DN49XFD EAN: 4058352418413	LP number 58526_24
Table of values for luminous intensities		Maximum luminous intensity
		sITeco

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm							Luminous flux in lm/klm		
0°	1742.2	1742.2	1742.2	1742.2	1742.2	1742.2	1742.2	10.4	10.4
5°	1666.1	1675.3	1660.6	1665.8	1671.6	1669.6	1670.7	79.7	90.1
10°	1438.7	1454.0	1443.6	1449.9	1452.8	1449.1	1448.5	137.9	228.0
15°	1099.0	1113.1	1114.3	1128.7	1137.3	1134.2	1132.4	159.4	387.5
20°	752.6	761.9	768.4	788.3	803.8	805.8	803.7	147.1	534.5
25°	477.8	482.8	489.1	506.4	523.2	529.8	529.1	117.2	651.7
30°	296.4	297.2	300.0	310.9	324.6	332.2	333.5	85.9	737.6
35°	189.3	187.5	185.3	189.4	198.7	205.9	208.7	61.1	798.7
40°	131.6	127.9	121.5	120.2	125.3	132.4	136.6	44.7	843.4
45°	99.4	94.4	85.5	81.0	83.2	90.3	95.8	34.4	877.7
50°	79.8	74.4	64.7	58.7	59.3	65.8	72.1	27.9	905.7
55°	65.2	60.1	51.3	45.2	44.8	50.3	56.0	23.4	929.0
60°	52.4	48.1	41.3	36.1	35.0	38.9	43.4	19.6	948.6
65°	41.2	37.9	33.1	29.2	27.7	29.8	32.8	16.1	964.7
70°	31.9	29.5	26.2	23.4	21.7	22.1	23.6	12.9	977.6
75°	24.4	22.6	20.2	18.2	16.5	15.4	15.7	10.0	987.6
80°	18.3	17.0	15.2	13.6	11.8	9.9	9.2	7.3	994.9
85°	13.3	12.5	11.1	9.7	7.7	5.4	4.2	5.0	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Licross® Protected	Order number: 51TP11DN49XFD EAN: 4058352418413	LP number 58526_24
-------------------------------------	---	------------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	9.8	11.1	10.2	11.4	11.7	9.7	10.9	10.1	11.3	11.6
	3H	11.0	12.1	11.3	12.4	12.7	10.6	11.7	11.0	12.0	12.4
	4H	11.5	12.5	11.9	12.8	13.2	11.0	12.0	11.4	12.3	12.7
	6H	12.0	12.9	12.4	13.3	13.7	11.3	12.2	11.7	12.5	12.9
	8H	12.3	13.1	12.7	13.5	13.9	11.5	12.2	11.9	12.6	13.0
	12H	12.5	13.2	13.0	13.6	14.1	11.5	12.2	12.0	12.6	13.0
4H	2H	10.1	11.1	10.5	11.4	11.8	10.0	11.0	10.3	11.3	11.7
	3H	11.4	12.2	11.8	12.6	13.0	11.0	11.8	11.4	12.2	12.7
	4H	12.0	12.8	12.5	13.2	13.6	11.5	12.2	11.9	12.7	13.1
	6H	12.7	13.3	13.2	13.8	14.2	11.9	12.5	12.4	13.0	13.4
	8H	13.0	13.6	13.5	14.0	14.5	12.0	12.6	12.5	13.1	13.5
	12H	13.4	13.8	13.9	14.3	14.8	12.2	12.7	12.7	13.1	13.6
8H	4H	12.2	12.8	12.7	13.2	13.7	11.7	12.3	12.2	12.7	13.2
	6H	13.0	13.4	13.5	13.9	14.4	12.2	12.7	12.7	13.2	13.7
	8H	13.4	13.8	13.9	14.3	14.8	12.4	12.9	13.0	13.4	13.9
	12H	13.9	14.2	14.4	14.7	15.3	12.7	13.0	13.2	13.5	14.0
12H	4H	12.2	12.7	12.7	13.2	13.7	11.8	12.2	12.3	12.7	13.2
	6H	13.1	13.4	13.6	13.9	14.4	12.3	12.7	12.8	13.2	13.7
	8H	13.5	13.8	14.0	14.4	14.9	12.6	12.9	13.1	13.4	14.0

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 1480	H(C0) = 13	H(C180) = 13
			B = 78	H(C90) = 0	H(C270) = 0

C-planes	γ	Luminance in cd/m ²								
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°		
45°		1503.4	1434.5	1317.6	1278.7	1355.5	1526.9	1689.4		
50°		1292.0	1210.8	1071.6	999.1	1046.6	1215.3	1398.9		
55°		1144.8	1062.1	925.5	841.3	871.2	1030.2	1218.7		
60°		1014.1	939.3	824.6	747.1	762.2	903.2	1082.4		
65°		896.5	832.4	746.8	687.7	693.1	806.2	968.9		
70°		798.7	745.0	684.2	644.0	645.3	719.3	859.6		
75°		725.2	680.4	634.2	609.1	607.1	640.4	758.9		
80°		674.4	638.1	599.8	586.1	574.3	570.9	660.0		
85°		653.8	630.6	600.0	591.6	567.8	520.7	595.7		

Photometric test report

Family Licross® Protected	Order number: 51TP11DN49XFD EAN: 4058352418413	LP number 58526_24
--	---	-------------------------------------

Luminance values in cd/m²

γ 65°
 γ 70°
 γ 75°
 γ 80°
 γ 85°

