




Photometric test report

Family Floodlight FL21 mini	Order number: 5XA7772C1B1A EAN: 4058352654798	LP number 59238_61
	Version mounting bracket Optic symmetric distribution RS12 Cover toughened safety glass Lamps LED 2200 K CRI ≥ 70 Controlgear ECG SITECO iQ Rated values Net luminous flux = 10220 lm Power consumption = 87.2 W Luminous efficacy = 117.2 lm/W	serial documentation 26.08.2022



Luminaire output ratios	
Eta	100.0%
Eta 0° - 90°	100.0%
Eta 90° - 180°	0.0%


Luminous intensity class acc. to EN13201-2	
Class:	G6
Imax 70°	36.4
Imax 80°	9.1
Imax 90°	0.0
Imax >90°	0.0
Imax >95°	0.0

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Floodlight FL21 mini	Order number: 5XA7772C1B1A EAN: 4058352654798	LP number 59238_61
---------------------------------------	--	------------------------------

Envelope curve in cd/klm KMK 2.5° KMK 0° siteco



Photometric test report

Family Floodlight FL21 mini	Order number: 5XA7772C1B1A EAN: 4058352654798	LP number 59238_61
---------------------------------------	--	------------------------------



Table of values for luminous intensities	Maximum luminous intensity
---	-----------------------------------

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm	Luminous flux in lm/klm	
0,0°	2868.8	4.3	4.3
2,5°	2873.2	34.4	38.6
5,0°	2722.5	65.0	103.7
7,5°	2292.0	82.0	185.7
10,0°	1852.6	88.2	273.9
12,5°	1427.9	84.7	358.6
15,0°	1018.5	72.3	430.9
17,5°	552.2	45.5	476.4
20,0°	453.7	42.5	518.9
22,5°	454.7	47.7	566.6
25,0°	454.2	52.6	619.2
27,5°	400.1	50.6	669.9
30,0°	317.0	43.5	713.3
32,5°	178.5	26.3	739.6
35,0°	121.9	19.2	758.8
37,5°	96.3	16.1	774.9
40,0°	86.4	15.2	790.1
42,5°	78.8	14.6	804.7
45,0°	75.0	14.5	819.2
47,5°	74.2	15.0	834.2
50,0°	76.8	16.1	850.4
52,5°	82.1	17.9	868.2
55,0°	87.5	19.7	887.9
57,5°	89.5	20.7	908.6
60,0°	83.0	19.7	928.3
62,5°	67.2	16.3	944.6
65,0°	57.1	14.2	958.8
67,5°	43.9	11.1	969.9
70,0°	36.4	9.4	979.3
72,5°	27.1	7.1	986.4
75,0°	21.2	5.6	992.0
77,5°	13.7	3.7	995.6
80,0°	9.1	2.5	998.1
82,5°	4.7	1.3	999.4
85,0°	1.8	0.5	999.9
87,5°	0.5	0.1	1000.0
90,0°	0.0	0.0	1000.0

Photometric test report

Family Floodlight FL21 mini	Order number: 5XA7772C1B1A EAN: 4058352654798	LP number 59238_61
---------------------------------------	--	------------------------------

Dimming levels table	environmental temperature: 25°C	siteco
-----------------------------	---------------------------------	---------------

Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]	Power consumption [W]	Power consumption [W]
				start of lifetime	end of lifetime	average
100	254	254	10220	87.2	92.1	89.6
95	241	252	9697	81.8	86.5	84.2
90	229	250	9214	77.1	81.4	79.2
85	216	248	8691	72.0	76.0	74.0
80	203	246	8168	67.1	70.7	68.9
75	190	243	7645	62.2	65.7	64.0
70	178	241	7162	57.9	61.0	59.4
65	165	238	6639	53.2	56.1	54.6
60	152	235	6116	48.5	51.3	49.9
55	140	232	5633	44.4	46.8	45.6
50	127	229	5110	40.1	42.2	41.2
45	114	225	4587	35.8	37.7	36.8
40	102	221	4104	31.9	33.5	32.7
35	89	216	3581	27.8	29.2	28.5
30	76	210	3058	23.8	25.0	24.4
25	63	203	2535	20.0	20.9	20.4
20	51	195	2052	16.4	17.2	16.8
16	40	186	1609	13.2	13.9	13.6