

Photometric test report

Family
Floodlight FL21 mini

Order number: 5XA7772C4B1A
EAN: 4058352655399

LP number
59238_64



Version mounting bracket
Optic direct, symmetric ellipsoid distribution
 R120004
Cover toughened safety glass
Lamps LED 4000 K | CRI ≥ 70
Controlgear ECG SITECO iQ
Rated values Net luminous flux = 12860 lm
 Power consumption = 87.2 W
 Luminous efficacy = 147.5 lm/W


serial
documentation
26.08.2022

siteco

Luminous intensity in cd/klm

C180-0

Imax: 2873 cd/klm



Luminaire output ratios

Eta	100.0%
Eta 0° - 90°	100.0%
Eta 90° - 180°	0.0%

Luminous intensity class acc. to EN13201-2

Class:	G6
Imax 70°	36.4
Imax 80°	9.1
Imax 90°	0.0
Imax >90°	0.0
Imax >95°	0.0


Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Floodlight FL21 mini	Order number: 5XA7772C4B1A EAN: 4058352655399	LP number 59238_64
--	--	-------------------------------------

Envelope curve in cd/klm KMK 2.5° KMK 0° siteco



Photometric test report

Family Floodlight FL21 mini	Order number: 5XA7772C4B1A EAN: 4058352655399	LP number 59238_64
---------------------------------------	--	------------------------------

siteco

Table of values for luminous intensities	Maximum luminous intensity
---	-----------------------------------

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm	Luminous flux in lm/klm	
0,0°	2868.8	4.3	4.3
2,5°	2873.2	34.4	38.6
5,0°	2722.5	65.0	103.7
7,5°	2292.0	82.0	185.7
10,0°	1852.6	88.2	273.9
12,5°	1427.9	84.7	358.6
15,0°	1018.5	72.3	430.9
17,5°	552.2	45.5	476.4
20,0°	453.7	42.5	518.9
22,5°	454.7	47.7	566.6
25,0°	454.2	52.6	619.2
27,5°	400.1	50.6	669.9
30,0°	317.0	43.5	713.3
32,5°	178.5	26.3	739.6
35,0°	121.9	19.2	758.8
37,5°	96.3	16.1	774.9
40,0°	86.4	15.2	790.1
42,5°	78.8	14.6	804.7
45,0°	75.0	14.5	819.2
47,5°	74.2	15.0	834.2
50,0°	76.8	16.1	850.4
52,5°	82.1	17.9	868.2
55,0°	87.5	19.7	887.9
57,5°	89.5	20.7	908.6
60,0°	83.0	19.7	928.3
62,5°	67.2	16.3	944.6
65,0°	57.1	14.2	958.8
67,5°	43.9	11.1	969.9
70,0°	36.4	9.4	979.3
72,5°	27.1	7.1	986.4
75,0°	21.2	5.6	992.0
77,5°	13.7	3.7	995.6
80,0°	9.1	2.5	998.1
82,5°	4.7	1.3	999.4
85,0°	1.8	0.5	999.9
87,5°	0.5	0.1	1000.0
90,0°	0.0	0.0	1000.0

Photometric test report

Family Floodlight FL21 mini	Order number: 5XA7772C4B1A EAN: 4058352655399	LP number 59238_64
---------------------------------------	--	-------------------------------------

Dimming levels table	environmental temperature: 25°C	sITeco
-----------------------------	---------------------------------	---------------

Luminous flux [%]	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]start of lifetime	Power consumption [W]end of lifetime	Power consumption [W]average
100	254	254	12860	87.2	92.1	89.6
95	241	252	12202	81.9	86.5	84.2
90	229	250	11594	77.1	81.4	79.2
85	216	248	10936	72.1	76.1	74.1
80	203	246	10278	67.2	70.8	69.0
75	190	243	9620	62.3	65.8	64.0
70	178	241	9012	58.0	61.1	59.6
65	165	238	8354	53.3	56.2	54.8
60	152	235	7696	48.6	51.4	50.0
55	140	232	7088	44.5	46.9	45.7
50	127	229	6430	40.2	42.3	41.2
45	114	225	5772	35.9	37.8	36.8
40	102	221	5164	32.0	33.6	32.8
35	89	216	4506	27.9	29.3	28.6
30	76	210	3848	23.9	25.1	24.5
25	63	203	3190	20.0	21.0	20.5
20	51	195	2582	16.5	17.3	16.9
16	40	186	2025	13.3	13.9	13.6