

Photometric test report

Family Streetlight 21 mini LED

Order number: 5XE2F43S08HB
EAN: 4058352725771

LP number
59110_280



Version	post-top or side-entry mounting, Smart Interface up
Optic	direct, asymmetric, left wide distribution ZCL0003
Cover	toughened safety glass
Lamps	LED 4000 K CRI ≥ 70
Controlgear	EVG-Smart Interface
Rated values	Net luminous flux = 8590 lm Power consumption = 66.0 W Luminous efficacy = 130.2 lm/W

serial
documentation
18.07.2022

siteco

Luminous intensity in cd/klm


C180-0

C270-90

C297.5-117.5

C300-120

Imax: 1354 cd/klm



Luminaire output ratios

Eta	100.0%
Eta 0° - 90°	100.0%
Eta 90° - 180°	0.0%

Luminous intensity class acc. to EN13201-2


Class:	G3
Imax 70°	751.7
Imax 80°	80.9
Imax 90°	0.0
Imax >90°	0.0
Imax >95°	0.0

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Streetlight 21 mini LED	Order number: 5XE2F43S08HB EAN: 4058352725771	LP number 59110_280
Envelope curve in cd/klm KMK 60° KMK 59° KMK 58° KMK 57°		siteco



Photometric test report

Family Streetlight 21 mini LED	Order number: 5XE2F43S08HB EAN: 4058352725771	LP number 59110_280
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0,0°	2,5°	5,0°	7,5°	10,0°	12,5°	15,0°	17,5°	20,0°	22,5°	25,0°	27,5°	30,0°	32,5°	35,0°	37,5°	40,0°
γ	Luminous intensity in cd/klm																
0,0°	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3
2,5°	237.0	237.3	237.6	237.5	237.5	237.5	237.5	237.5	237.8	237.8	238.0	238.0	238.0	238.1	238.1	238.0	238.0
5,0°	226.6	226.8	227.3	227.2	227.7	227.5	228.2	228.3	229.2	229.5	230.4	230.9	231.9	232.3	233.3	233.8	234.7
7,5°	218.3	218.5	219.1	219.1	219.6	219.7	220.6	221.2	222.2	222.8	223.7	224.3	225.2	225.8	226.6	227.4	228.2
10,0°	210.1	210.5	210.8	211.0	211.1	211.3	211.6	212.2	212.8	213.4	214.4	215.4	217.1	218.6	220.7	222.2	224.1
12,5°	200.4	200.1	201.3	201.1	202.5	202.9	204.7	205.5	207.6	208.4	210.4	211.4	213.0	214.0	215.3	215.8	217.0
15,0°	180.8	180.5	181.8	182.2	184.2	185.2	188.0	189.5	192.0	193.8	196.5	198.4	201.6	204.0	207.2	209.3	211.6
17,5°	159.8	159.9	160.6	161.1	162.3	163.6	165.7	167.8	171.0	173.7	177.7	181.5	186.2	189.8	193.9	197.1	200.8
20,0°	145.9	145.4	146.6	146.6	148.4	149.3	151.8	153.4	156.4	158.1	161.5	163.6	167.3	170.4	176.4	181.1	188.3
22,5°	128.3	128.5	129.1	129.6	131.0	132.3	134.8	137.2	140.8	143.5	147.6	150.8	154.9	158.3	162.4	165.9	170.7
25,0°	125.9	126.3	126.6	126.8	127.3	127.6	127.8	128.0	127.8	128.7	131.2	133.6	139.6	144.2	150.0	154.0	159.8
27,5°	116.5	116.6	117.5	118.5	120.1	121.4	123.5	125.4	126.9	128.1	128.7	128.7	129.0	130.6	134.7	140.3	147.1
30,0°	104.6	105.0	106.0	107.2	109.1	110.6	112.8	114.7	117.8	120.6	124.2	127.3	128.8	129.7	129.2	130.4	133.8
32,5°	94.2	94.4	96.1	97.6	100.0	101.9	104.5	106.4	109.2	111.6	114.9	117.8	122.6	126.5	129.6	130.4	130.2
35,0°	83.0	83.7	85.7	88.3	91.3	94.6	97.6	100.7	103.8	106.3	109.1	111.4	114.5	117.9	123.4	128.5	130.4
37,5°	72.3	73.3	75.5	78.3	81.9	85.6	90.1	94.2	98.5	102.0	105.2	107.8	110.3	112.4	115.5	119.5	125.8
40,0°	69.0	69.9	71.4	73.4	75.8	78.7	82.1	86.1	91.2	95.8	100.2	103.6	106.7	109.1	111.1	113.0	116.7
42,5°	69.6	70.3	71.7	73.8	76.1	78.5	80.9	83.4	86.2	89.3	93.1	96.9	100.9	103.7	106.9	109.7	112.6
45,0°	69.4	70.0	71.1	72.4	74.0	75.8	77.9	80.3	83.0	85.5	88.6	91.5	94.9	98.3	102.9	107.4	111.6
46,0°	69.2	69.7	70.7	72.1	73.4	74.8	76.7	78.6	80.9	83.3	86.4	89.5	93.0	97.0	101.2	106.2	110.8
47,0°	69.0	69.5	70.4	71.4	72.6	74.0	75.5	77.0	78.9	81.1	83.8	86.9	91.3	95.4	99.5	104.1	109.1
48,0°	68.7	69.2	69.9	70.7	71.7	72.8	74.1	75.5	77.4	79.1	81.5	84.4	89.1	93.4	97.6	101.9	106.8
49,0°	68.3	68.5	69.4	70.0	71.1	71.7	72.9	73.8	75.7	77.0	79.4	81.8	86.2	90.0	95.4	99.3	103.9
50,0°	67.7	67.8	68.5	69.2	70.0	70.7	71.6	72.3	73.6	75.0	77.0	79.4	82.6	86.1	91.7	96.5	100.4
51,0°	66.8	67.0	67.7	68.2	68.8	69.5	70.2	70.7	71.7	72.9	75.0	76.7	79.2	82.0	87.1	92.5	97.1
52,0°	65.6	65.8	66.5	66.8	67.5	68.0	68.5	69.0	69.9	70.9	72.6	74.0	75.8	77.9	81.8	87.2	93.2
53,0°	63.9	64.2	64.8	65.3	66.1	66.5	67.0	67.3	68.0	68.8	70.2	71.4	73.3	74.3	77.2	82.3	89.0
54,0°	61.9	62.0	62.7	63.4	64.1	64.8	65.1	65.4	66.1	67.0	68.0	69.4	70.7	71.1	73.1	77.4	84.4
55,0°	59.3	59.5	60.2	60.7	61.7	62.4	63.1	63.4	64.2	64.9	65.6	67.0	68.5	68.0	69.0	72.3	79.4
56,0°	56.7	56.9	57.6	58.1	59.1	59.8	60.7	61.2	62.5	63.2	63.7	64.9	67.7	65.1	65.8	68.0	75.0
57,0°	54.5	54.4	55.2	55.6	56.6	57.1	58.5	59.0	60.7	61.5	62.4	63.4	67.7	63.1	62.5	63.7	70.4
58,0°	52.3	52.5	53.0	53.3	54.4	54.7	55.7	56.7	58.3	59.5	60.7	62.4	68.2	62.0	59.3	60.0	65.1
59,0°	50.3	50.3	51.0	51.3	52.3	52.7	53.5	54.2	55.7	56.9	58.6	61.0	68.3	61.9	56.4	56.4	60.2
60,0°	47.7	47.7	48.4	48.6	49.6	50.1	50.8	51.3	52.5	53.7	55.7	59.5	67.5	62.2	53.5	52.7	55.6
61,0°	45.2	45.0	45.5	45.8	46.9	47.4	48.2	48.4	49.6	50.3	52.7	57.4	65.6	62.0	51.0	49.9	52.3
62,0°	41.9	41.8	42.4	42.8	43.8	44.3	45.0	45.3	46.2	46.9	49.4	55.2	62.4	60.5	48.6	47.9	49.8
63,0°	37.7	37.7	38.5	38.9	39.9	40.6	41.6	41.8	42.8	43.6	46.4	52.3	58.6	57.8	46.5	45.8	47.4
64,0°	34.4	34.4	35.3	35.8	36.6	37.7	38.7	39.0	40.0	41.1	44.0	49.6	55.2	54.7	44.8	44.0	45.5
65,0°	31.9	31.9	32.7	33.1	34.3	34.9	36.3	36.6	38.0	38.9	42.1	46.9	51.8	50.6	42.8	41.9	43.5
66,0°	30.0	30.0	30.8	31.4	32.0	33.1	34.1	34.8	36.0	37.1	40.2	44.8	48.4	46.9	40.4	40.2	41.2
67,0°	28.5	28.5	29.1	29.7	30.3	31.0	32.0	32.9	34.3	35.6	38.9	42.6	45.3	43.1	38.5	38.5	39.2
68,0°	26.6	26.8	27.3	27.6	28.3	29.0	30.0	30.8	32.4	33.9	37.3	40.2	41.9	39.4	36.3	36.3	36.8
69,0°	25.1	25.1	25.7	26.1	26.6	27.3	28.1	29.0	30.5	32.4	36.0	38.0	38.9	36.3	34.3	34.1	34.3
70,0°	23.7	23.5	24.2	24.4	24.9	25.2	26.4	27.1	28.6	30.7	34.4	35.8	36.1	33.2	32.2	31.5	31.7
71,0°	21.8	21.8	22.3	22.7	23.0	23.5	24.5	25.4	26.8	29.0	32.4	33.7	33.2	30.8	29.7	29.1	29.3
72,0°	19.9	19.9	20.3	20.6	21.0	21.5	22.7	23.7	25.1	27.3	30.5	31.5	30.7	28.3	27.3	26.8	27.1
73,0°	18.1	18.1	18.4	18.6	18.9	19.4	20.4	21.6	23.3	25.4	28.3	29.0	27.9	25.6	24.7	24.2	24.9

Photometric test report

Family Streetlight 21 mini LED	Order number: 5XE2F43S08HB EAN: 4058352725771	LP number 59110_280
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	42,5°	45,0°	47,5°	50,0°	52,5°	55,0°	57,5°	60,0°	62,5°	65,0°	67,5°	70,0°	72,5°	75,0°	77,5°	80,0°	82,5°
γ	Luminous intensity in cd/klm																
0,0°	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3
2,5°	238.0	237.9	237.7	237.5	237.6	237.7	237.7	237.8	237.9	238.1	238.3	238.7	238.9	239.3	239.8	240.3	240.5
5,0°	235.3	236.4	236.9	237.5	238.1	238.6	238.7	239.1	239.4	239.4	239.6	239.6	240.1	240.6	241.3	242.0	242.7
7,5°	229.0	230.1	231.2	232.6	234.1	235.7	237.1	238.8	240.2	241.3	242.0	242.5	242.7	243.0	243.9	244.7	245.8
10,0°	225.4	227.0	228.3	229.9	230.7	231.9	233.6	236.0	238.4	241.0	242.8	244.2	244.9	245.2	245.9	247.1	248.6
12,5°	218.1	220.7	222.8	225.9	227.8	229.9	231.7	233.5	235.6	238.9	241.9	244.7	246.1	246.5	247.3	249.0	250.9
15,0°	214.2	216.8	217.6	219.3	221.5	225.4	228.9	231.9	234.7	237.2	240.8	244.7	246.9	247.8	248.6	250.8	253.4
17,5°	204.4	208.4	211.7	215.7	218.4	220.5	224.2	229.1	233.2	237.1	240.6	245.0	248.0	249.1	250.5	253.1	256.1
20,0°	192.7	197.7	202.1	207.9	212.0	217.4	221.4	225.4	230.9	236.5	241.0	245.7	249.3	250.5	252.5	255.4	259.0
22,5°	176.7	184.6	191.9	198.3	204.0	210.3	216.6	223.1	227.8	234.6	240.9	246.7	250.6	252.1	254.8	258.4	262.8
25,0°	164.3	169.9	176.7	187.3	195.1	202.6	209.9	218.1	226.0	232.9	240.3	247.8	251.9	254.1	257.8	261.9	267.2
27,5°	153.3	159.9	166.1	173.0	182.5	193.8	203.0	212.3	221.1	230.8	238.7	248.3	253.1	256.3	261.1	266.5	272.1
30,0°	140.6	147.9	155.8	163.9	170.7	181.1	194.3	205.2	215.4	226.6	236.5	246.9	253.2	257.8	264.1	271.1	277.8
32,5°	131.5	136.2	143.4	152.2	161.0	169.3	180.1	195.1	206.5	219.7	232.6	244.2	252.3	258.7	266.9	275.7	283.7
35,0°	130.2	130.9	133.3	140.4	147.9	158.5	167.3	180.8	196.1	211.6	226.0	241.5	251.2	259.9	269.8	280.2	289.5
37,5°	129.3	129.4	129.7	131.7	137.5	145.0	156.5	167.5	184.0	202.3	219.5	237.3	249.7	261.6	273.1	285.2	295.7
40,0°	122.9	127.5	127.8	128.7	130.4	135.8	144.7	158.1	171.1	191.5	210.3	230.7	245.9	260.4	274.0	288.0	300.1
42,5°	115.6	120.7	124.7	126.3	127.9	130.7	134.6	145.2	158.1	176.0	195.2	218.0	237.0	254.2	271.0	288.3	303.2
45,0°	114.0	115.7	119.3	122.7	124.6	125.3	127.1	130.2	142.6	158.5	178.1	202.6	225.8	247.4	269.2	291.1	310.3
46,0°	113.7	114.9	117.4	120.5	122.2	123.0	123.9	125.3	136.2	152.5	171.9	197.0	221.9	245.9	269.8	294.0	315.3
47,0°	112.5	113.3	115.2	117.4	118.6	119.8	119.8	120.3	129.0	146.7	165.5	191.5	218.5	245.7	272.7	299.7	324.1
48,0°	110.6	111.6	112.6	114.0	115.0	116.2	115.9	116.6	123.5	142.0	160.7	188.0	217.1	247.6	277.9	308.6	336.6
49,0°	107.7	109.6	109.2	110.1	110.8	112.3	112.0	113.7	118.8	138.0	156.9	185.9	218.1	252.0	287.6	321.4	355.1
50,0°	104.5	106.2	105.5	105.5	106.0	107.5	108.4	111.1	116.0	135.6	155.1	185.7	221.0	259.9	299.7	339.5	376.8
51,0°	100.5	101.9	100.9	100.9	101.4	103.1	104.8	109.1	114.9	135.0	154.7	186.9	225.4	268.7	313.2	358.9	401.5
52,0°	95.6	96.6	95.9	95.8	96.1	98.5	101.2	106.8	115.0	135.6	155.9	188.5	229.7	277.1	326.7	378.6	426.5
53,0°	91.3	91.7	91.2	91.0	91.7	94.6	98.2	105.0	116.0	136.8	156.8	188.6	231.8	282.2	335.9	393.5	446.0
54,0°	87.4	87.2	86.9	86.6	87.8	91.2	95.8	103.6	117.2	137.5	156.8	186.9	231.1	283.9	340.3	402.7	459.9
55,0°	83.2	83.3	82.8	82.5	83.8	88.1	93.6	102.4	118.6	137.9	155.4	182.7	226.6	280.8	339.1	405.9	467.4
56,0°	79.6	80.4	79.8	79.6	81.1	85.7	92.0	101.6	119.5	137.9	153.2	176.7	218.8	273.0	331.4	401.7	466.2
57,0°	75.7	77.9	77.4	77.7	78.9	84.0	90.7	101.1	120.3	137.5	149.3	168.7	206.9	260.7	316.4	389.9	455.0
58,0°	71.2	74.6	75.5	76.3	77.7	82.6	89.8	100.9	120.5	136.7	144.8	157.6	191.5	240.8	293.3	364.5	431.5
59,0°	66.3	71.2	73.4	75.2	77.0	81.6	89.3	101.1	120.1	135.0	138.4	144.5	171.3	214.5	260.9	329.1	393.0
60,0°	60.8	66.8	70.4	73.8	76.5	80.8	89.1	101.4	118.6	131.6	129.3	128.0	146.7	182.7	221.4	281.7	339.6
61,0°	56.6	62.4	66.8	71.4	75.5	80.3	89.3	101.4	116.6	127.1	120.8	114.0	127.3	156.6	189.5	241.3	294.5
62,0°	53.2	58.3	62.7	68.3	74.0	79.8	89.6	100.7	113.7	122.7	114.3	104.1	113.3	137.7	166.7	211.3	261.2
63,0°	50.1	54.5	58.5	64.4	71.6	79.2	89.8	99.3	110.8	118.4	109.2	97.8	103.8	125.8	151.7	192.2	239.1
64,0°	47.5	51.3	55.0	60.8	68.8	78.6	89.5	97.8	107.9	115.0	105.7	94.2	98.0	117.8	140.8	178.4	224.3
65,0°	45.0	48.2	51.3	57.3	65.8	77.9	88.4	95.1	103.8	110.8	101.2	90.7	91.9	109.9	129.9	166.5	210.8
66,0°	42.6	45.2	47.9	53.3	62.7	76.3	86.1	90.8	98.5	103.8	95.6	85.4	85.5	100.4	118.3	150.6	196.3
67,0°	40.0	42.1	44.8	50.1	59.8	73.4	82.0	85.7	91.7	95.8	88.1	79.1	77.9	89.6	102.2	130.4	172.6
68,0°	37.1	38.9	41.4	47.0	56.2	68.8	76.5	79.4	82.8	84.7	76.9	68.3	65.4	73.6	81.3	102.1	139.1
69,0°	34.6	36.1	38.7	44.1	52.7	63.9	70.5	72.4	73.8	73.8	66.3	58.8	56.4	62.0	67.3	83.7	116.6
70,0°	32.0	33.7	36.1	41.2	48.7	58.3	63.4	65.4	64.6	63.9	56.6	51.1	48.2	52.7	54.9	67.8	93.9
71,0°	29.8	31.4	33.7	38.2	44.8	52.3	56.9	58.5	57.8	55.4	48.7	43.6	41.9	44.5	46.4	54.4	76.5
72,0°	27.8	29.1	31.2	35.1	40.4	47.0	51.6	53.2	51.5	48.6	41.9	37.8	36.8	38.9	40.2	45.7	62.5
73,0°	25.4	26.6	28.1	31.4	36.1	41.9	46.4	48.4	46.5	43.3	36.3	33.2	31.9	33.7	34.4	38.2	50.3

Photometric test report

Family Streetlight 21 mini LED	Order number: 5XE2F43S08HB EAN: 4058352725771	LP number 59110_280
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	85,0°	87,5°	90,0°	92,5°	95,0°	97,5°	100,0°	102,5°	105,0°	107,5°	110,0°	112,5°	115,0°	117,5°	120,0°	122,5°	125,0°
γ	Luminous intensity in cd/klm																
0,0°	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3
2,5°	241.0	241.6	242.1	242.8	243.3	243.6	243.8	244.1	244.4	244.9	245.3	246.0	246.2	246.8	247.0	247.5	247.8
5,0°	243.5	244.5	245.7	246.9	247.8	248.6	249.3	250.3	251.0	252.0	252.9	253.9	254.4	255.3	255.6	256.5	257.0
7,5°	246.9	248.6	250.2	252.0	253.5	255.0	256.1	257.4	258.5	260.1	261.3	262.8	263.8	265.1	265.9	267.2	268.1
10,0°	250.3	252.4	254.6	257.1	259.2	261.1	262.4	264.5	266.3	268.6	270.3	272.1	273.7	275.9	278.1	280.3	282.0
12,5°	253.0	255.8	258.7	261.8	263.9	266.3	268.5	271.2	273.5	276.4	278.9	282.3	284.8	288.4	291.0	293.7	293.8
15,0°	256.0	259.4	262.9	266.0	268.4	271.6	274.2	277.6	280.8	284.9	289.0	293.4	296.7	297.9	295.8	292.8	291.2
17,5°	259.5	263.4	267.0	270.2	273.2	276.9	280.4	284.5	289.5	295.4	299.7	300.2	297.6	295.7	296.3	298.1	299.9
20,0°	263.1	267.4	270.9	274.9	278.4	283.0	287.3	294.1	300.8	304.3	302.1	300.1	300.9	304.3	306.9	309.6	309.8
22,5°	267.5	272.1	276.1	281.0	285.9	291.5	298.1	306.0	307.7	305.9	306.3	309.6	313.1	316.4	318.1	318.6	317.6
25,0°	272.3	277.9	282.5	289.5	295.1	303.7	310.8	312.9	311.2	314.4	318.5	323.4	326.0	328.0	327.4	327.0	324.5
27,5°	278.5	284.8	291.3	299.4	307.0	316.5	318.7	318.1	321.6	327.4	332.6	336.1	337.8	338.0	336.7	334.3	330.9
30,0°	285.3	292.8	301.3	310.0	320.5	325.8	325.0	328.4	334.7	341.0	345.6	348.0	348.7	348.0	344.9	341.7	337.6
32,5°	292.3	302.2	313.0	323.0	331.7	332.6	335.2	342.1	348.7	355.2	358.5	360.7	360.1	358.4	354.1	350.4	346.1
35,0°	299.2	310.8	323.4	334.0	338.8	340.3	347.0	355.3	362.8	367.7	370.8	372.7	372.5	369.6	365.2	361.1	357.2
37,5°	307.5	321.0	334.8	345.0	347.2	352.9	361.0	370.0	376.8	380.7	383.6	386.1	386.1	383.6	379.0	374.8	370.7
40,0°	313.6	328.4	342.9	353.3	357.3	366.4	375.6	385.3	391.3	394.7	397.4	401.0	401.5	399.9	395.7	392.3	388.9
42,5°	318.5	333.7	347.9	358.5	366.7	377.5	388.2	399.1	405.7	410.8	414.6	419.3	420.8	421.7	420.2	419.6	420.4
45,0°	328.5	344.4	357.9	368.8	378.1	388.5	399.4	411.4	420.4	428.7	436.8	443.1	448.2	452.3	457.2	463.8	474.9
46,0°	335.0	351.9	365.2	376.6	385.3	394.8	405.1	417.0	426.7	436.9	447.3	455.7	461.3	468.5	476.6	488.4	504.6
47,0°	345.8	364.3	377.8	389.7	396.9	404.9	413.4	425.0	434.9	447.3	460.3	472.5	482.9	492.0	503.2	520.1	540.7
48,0°	359.9	380.9	394.7	406.9	412.4	418.9	425.2	435.2	444.4	458.6	474.4	491.8	505.3	520.3	533.5	554.7	577.5
49,0°	379.3	405.2	417.7	432.5	434.0	440.8	442.4	452.6	459.1	475.8	492.8	519.6	536.4	560.5	571.7	599.8	617.9
50,0°	406.8	434.0	449.0	462.1	464.4	467.9	468.3	475.3	482.3	498.6	521.4	555.9	581.8	607.0	622.8	647.7	663.9
51,0°	435.7	465.7	483.1	497.2	499.3	501.3	499.6	505.8	511.9	531.2	561.2	606.1	638.9	666.3	680.3	702.6	709.6
52,0°	466.1	499.3	520.6	536.8	540.7	542.6	540.5	546.3	553.8	578.4	621.0	679.4	717.4	744.0	752.5	768.2	761.4
53,0°	490.1	526.9	552.3	571.5	578.2	581.4	581.4	589.1	601.5	635.5	693.6	764.1	805.9	827.2	829.9	835.8	811.8
54,0°	509.0	549.6	579.0	602.1	612.4	618.2	621.0	632.9	654.5	705.7	784.9	864.1	903.3	918.7	919.0	910.1	862.3
55,0°	521.4	566.6	601.5	630.0	644.5	653.7	660.2	681.3	716.7	794.4	896.0	982.9	1013.8	1027.7	1019.0	992.3	913.6
56,0°	524.9	574.3	613.8	646.9	665.8	679.2	691.0	722.7	776.2	884.6	1003.5	1089.4	1111.9	1127.4	1110.4	1061.0	948.1
57,0°	520.1	572.4	618.1	655.0	677.9	695.8	713.2	759.0	834.1	981.4	1105.4	1189.3	1198.5	1224.7	1192.5	1115.0	958.4
58,0°	500.7	556.6	608.0	648.4	678.7	699.9	727.0	784.0	893.1	1060.8	1195.2	1259.1	1279.1	1300.0	1259.5	1132.5	934.9
59,0°	463.7	520.8	578.0	621.1	658.8	684.2	721.5	793.2	932.3	1116.7	1241.8	1294.6	1325.4	1349.1	1285.2	1107.3	875.9
60,0°	407.8	463.5	523.7	567.3	611.8	642.1	691.0	778.6	945.8	1129.1	1238.7	1285.7	1334.3	1354.4	1258.8	1030.3	775.7
61,0°	356.3	410.7	466.6	510.2	555.5	589.6	645.2	748.8	929.4	1097.4	1192.0	1238.0	1299.0	1305.0	1179.1	925.5	665.3
62,0°	317.1	369.6	419.7	461.3	501.9	538.5	597.6	714.7	897.7	1045.3	1125.9	1171.2	1226.3	1213.3	1060.1	801.8	552.3
63,0°	293.1	344.2	389.0	426.4	461.8	496.7	557.4	685.7	865.7	987.9	1057.9	1097.3	1128.4	1076.6	912.0	659.8	435.9
64,0°	280.0	333.3	378.1	414.1	446.8	480.2	542.2	679.4	849.0	950.9	1007.1	1034.0	1034.2	940.0	772.8	534.9	344.7
65,0°	271.3	328.2	375.9	413.8	447.3	484.1	550.9	700.4	850.2	929.9	968.3	968.6	933.7	796.3	636.0	412.9	270.9
66,0°	260.7	324.1	376.4	417.3	455.2	497.8	577.5	731.2	861.4	918.5	942.0	910.5	817.6	667.8	498.3	320.4	211.6
67,0°	242.1	309.6	370.6	413.8	457.9	506.5	598.6	749.6	856.5	895.8	909.5	846.8	716.1	549.4	388.9	251.4	171.6
68,0°	207.7	278.8	346.3	392.1	438.6	495.5	601.0	737.0	817.1	839.4	839.8	749.3	599.0	427.4	295.7	193.6	140.2
69,0°	185.6	265.7	338.8	389.0	432.3	495.9	605.3	724.9	782.9	784.0	760.7	650.3	496.7	332.8	225.3	156.6	121.0
70,0°	163.3	252.9	336.2	393.6	440.2	512.4	621.0	719.1	751.7	730.2	687.8	549.4	403.7	257.7	179.3	127.3	102.8
71,0°	139.7	241.0	336.6	398.1	448.0	523.2	628.5	701.6	707.2	676.3	608.0	461.5	312.5	203.3	146.6	110.1	89.0
72,0°	119.5	227.5	335.4	398.6	449.2	521.8	615.3	661.7	649.4	608.2	527.4	378.0	243.0	162.9	123.4	95.4	78.9
73,0°	99.2	207.2	323.9	387.5	433.9	495.2	569.7	587.2	566.1	520.3	431.0	286.6	180.0	129.0	102.4	81.3	65.9

Photometric test report

Family Streetlight 21 mini LED	Order number: 5XE2F43S08HB EAN: 4058352725771	LP number 59110_280
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	127,5°	130,0°	132,5°	135,0°	137,5°	140,0°	142,5°	145,0°	147,5°	150,0°	152,5°	155,0°	157,5°	160,0°	162,5°	165,0°	167,5°
γ	Luminous intensity in cd/klm																
0,0°	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3
2,5°	248.5	248.6	249.2	249.3	249.6	249.6	250.3	250.5	250.9	250.9	251.3	251.3	251.7	251.6	251.9	251.8	252.1
5,0°	257.8	258.2	259.2	259.4	260.0	260.4	261.4	261.6	262.4	262.4	263.1	263.1	263.8	263.8	264.5	264.3	265.0
7,5°	269.6	270.5	272.2	273.2	274.4	275.3	276.9	277.5	278.6	279.0	280.0	280.2	281.1	281.1	281.5	281.4	281.7
10,0°	284.4	285.9	288.0	289.0	289.9	289.5	288.7	287.3	284.9	283.6	281.9	281.0	280.0	279.5	279.0	278.8	278.4
12,5°	293.0	291.3	289.2	287.9	287.0	286.6	286.7	286.2	286.4	285.8	285.9	285.1	285.0	284.2	284.1	283.4	283.1
15,0°	291.6	292.4	294.0	294.5	295.1	294.8	294.3	293.3	292.6	291.6	290.5	289.5	288.5	287.5	286.5	285.4	284.6
17,5°	301.4	302.0	302.0	301.5	300.9	299.7	298.4	296.9	295.5	294.1	292.8	291.2	289.7	288.3	287.1	285.8	284.5
20,0°	310.0	308.9	307.8	306.2	304.9	303.2	301.3	299.4	297.5	295.7	293.8	291.9	290.0	288.3	286.6	285.1	283.6
22,5°	316.4	314.4	312.1	309.9	307.6	305.3	303.0	300.8	298.6	296.4	294.2	292.0	289.9	287.9	286.0	284.2	282.6
25,0°	321.9	318.8	315.9	312.7	310.1	307.4	304.7	302.1	299.7	297.2	294.8	292.6	290.7	289.0	287.8	286.3	285.4
27,5°	327.4	323.9	320.3	316.8	313.6	310.4	307.2	304.4	302.2	300.5	299.4	298.9	299.5	300.3	301.8	302.6	303.7
30,0°	334.0	330.3	326.3	322.4	318.8	315.4	312.9	311.0	311.2	312.9	316.4	319.7	323.9	326.3	329.2	329.7	330.3
32,5°	342.9	338.8	335.4	331.3	328.7	326.5	328.5	331.0	338.7	343.5	351.1	354.1	358.3	358.4	359.9	358.0	357.8
35,0°	354.3	351.6	347.8	345.2	346.3	351.0	359.4	367.7	376.8	383.1	388.2	390.1	389.7	387.3	384.3	380.5	376.4
37,5°	368.8	367.7	368.5	372.2	381.7	392.5	405.1	413.7	421.0	423.5	423.4	418.6	412.3	404.0	396.9	390.3	384.6
40,0°	389.7	392.8	403.9	416.6	433.9	446.3	458.1	462.3	463.5	457.7	449.7	438.3	427.7	417.2	408.5	400.6	394.2
42,5°	428.7	442.5	464.7	482.8	500.1	508.2	511.7	505.5	493.9	479.3	464.4	448.7	433.3	418.5	404.1	392.3	380.8
45,0°	495.0	518.4	541.6	555.9	562.3	556.7	541.7	522.3	498.6	474.9	450.6	426.4	403.4	382.9	363.8	348.1	334.2
46,0°	528.1	551.8	571.2	580.2	579.4	565.8	543.3	518.7	490.6	463.3	435.1	408.5	383.8	362.1	342.5	326.5	312.5
47,0°	566.9	586.9	601.2	602.1	591.0	568.1	538.5	508.5	475.3	444.6	412.6	383.4	357.0	335.2	315.3	299.9	284.9
48,0°	602.9	616.4	624.0	616.0	594.0	564.2	527.9	493.3	454.6	421.2	385.8	356.7	328.9	307.8	286.5	272.1	257.1
49,0°	641.6	643.6	642.9	623.5	590.0	553.8	508.5	470.7	424.1	391.1	350.9	324.6	292.6	275.5	252.2	241.8	224.9
50,0°	674.8	669.4	653.3	623.5	578.7	534.4	483.1	437.3	389.0	352.2	314.1	285.4	257.8	239.3	220.0	208.4	195.5
51,0°	707.9	688.3	656.8	613.8	559.6	508.2	447.8	397.7	347.8	311.2	274.7	247.8	222.2	205.3	188.0	178.1	167.5
52,0°	741.4	703.3	651.5	593.2	527.8	468.1	399.4	349.5	301.3	266.9	233.3	207.9	185.2	170.6	156.6	148.6	140.8
53,0°	770.4	710.6	636.6	563.4	485.7	418.7	350.9	303.0	258.5	226.1	195.6	172.1	153.2	140.8	129.9	124.1	118.8
54,0°	795.0	708.4	610.6	521.4	434.9	365.9	302.6	257.8	216.6	187.6	160.7	140.2	124.6	115.2	106.8	103.3	98.8
55,0°	810.1	690.0	566.8	467.3	376.4	309.6	250.2	211.1	174.5	150.5	127.0	111.1	99.2	92.2	85.5	83.5	79.8
56,0°	804.0	654.0	513.8	413.2	323.1	260.0	206.5	173.3	141.1	122.0	103.1	91.0	81.5	75.7	70.0	68.5	65.9
57,0°	768.5	603.1	449.5	358.9	269.9	218.1	167.7	143.0	115.0	102.2	86.7	78.0	68.3	63.9	58.6	58.5	56.2
58,0°	710.6	531.0	386.8	299.6	224.4	177.6	140.6	120.0	100.2	89.3	76.9	67.5	59.5	55.2	52.1	51.8	51.1
59,0°	633.9	458.1	323.6	247.1	182.3	148.1	124.1	107.7	92.5	81.8	69.4	59.8	53.0	50.3	48.6	48.4	47.9
60,0°	537.0	378.3	259.2	193.2	145.4	126.1	114.3	102.1	88.3	75.5	62.2	53.2	48.4	47.0	46.0	45.8	45.3
61,0°	445.4	306.9	205.5	155.9	123.4	113.0	108.6	99.7	84.4	70.4	56.4	48.9	45.7	44.6	43.8	43.6	43.1
62,0°	359.9	237.9	159.3	128.5	109.6	105.1	102.8	94.6	80.3	64.9	52.1	45.5	42.3	41.2	40.2	39.7	39.0
63,0°	276.4	173.6	114.3	104.3	98.5	97.5	94.9	86.9	74.0	60.2	48.9	40.2	37.8	37.5	37.8	37.7	37.8
64,0°	216.4	136.0	89.8	83.8	86.7	88.6	86.7	79.1	68.0	56.9	46.7	38.0	36.0	36.8	37.8	39.5	39.4
65,0°	171.1	113.5	78.6	70.9	68.7	78.4	76.9	70.7	61.2	53.7	44.5	36.5	34.3	36.1	36.8	37.8	36.3
66,0°	142.5	99.2	72.4	63.9	58.3	63.2	65.9	61.3	55.2	50.3	42.8	35.1	33.2	34.4	34.6	34.9	34.1
67,0°	123.2	89.5	67.0	59.5	52.7	52.5	53.3	53.5	50.6	47.0	40.9	34.1	32.4	32.9	33.1	33.1	32.2
68,0°	106.5	79.1	61.2	55.0	47.9	45.7	45.2	46.5	46.2	43.5	38.3	32.9	31.4	31.7	31.5	31.4	30.5
69,0°	95.3	71.6	56.4	50.3	43.3	41.8	41.6	42.4	42.3	40.0	35.4	31.2	29.8	30.2	29.7	29.5	28.6
70,0°	84.7	65.4	49.8	44.8	39.9	38.7	38.5	38.9	37.5	36.1	31.9	29.1	27.8	28.1	27.4	27.4	26.4
71,0°	73.3	57.4	45.3	40.6	37.7	35.4	34.8	34.6	33.4	31.9	28.8	26.6	25.7	25.6	25.1	24.9	24.0
72,0°	63.4	48.9	40.7	38.2	36.0	32.4	30.8	30.7	29.8	28.6	26.1	24.4	23.5	23.2	22.7	22.3	21.6
73,0°	53.0	42.8	37.0	36.6	33.2	29.0	26.9	26.4	26.2	25.4	23.3	22.0	21.1	20.6	19.9	19.4	18.7

Photometric test report

Family Streetlight 21 mini LED	Order number: 5XE2F43S08HB EAN: 4058352725771	LP number 59110_280
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	170,0°	172,5°	175,0°	177,5°	180,0°	182,5°	185,0°	187,5°	190,0°	192,5°	195,0°	197,5°	200,0°	202,5°	205,0°	207,5°	210,0°
γ	Luminous intensity in cd/klm																
0,0°	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3
2,5°	251.9	252.1	251.9	252.3	252.1	252.5	252.1	252.1	251.4	251.4	250.8	250.8	250.4	250.4	249.9	249.8	249.1
5,0°	264.6	265.0	264.6	265.3	265.0	265.5	265.0	265.0	264.0	264.0	263.1	263.1	262.4	262.3	261.2	260.9	259.9
7,5°	281.5	281.5	281.3	281.6	281.6	281.9	281.5	281.3	280.7	280.3	279.7	279.6	279.0	278.5	277.3	276.6	275.2
10,0°	278.1	277.8	277.8	277.8	277.9	277.9	277.8	277.4	277.1	276.7	276.6	276.4	276.6	276.6	276.9	277.3	278.4
12,5°	282.4	282.1	281.7	281.9	281.7	281.9	281.4	281.2	280.6	280.3	280.0	280.0	279.6	279.5	278.8	278.6	278.1
15,0°	283.7	282.9	282.5	282.2	282.2	281.9	281.7	281.3	281.0	280.7	280.8	281.0	281.0	281.0	280.8	281.0	281.2
17,5°	283.2	282.1	281.6	281.2	280.9	280.6	280.3	279.8	279.6	279.5	279.7	279.9	280.1	280.2	280.3	280.7	281.3
20,0°	282.0	280.8	280.2	279.5	279.3	278.8	278.6	278.1	277.9	277.9	278.3	278.6	279.1	279.5	279.8	280.3	281.0
22,5°	280.9	279.6	278.7	278.2	277.9	277.6	277.2	276.7	276.4	276.4	276.7	277.3	277.8	278.3	279.0	279.9	281.0
25,0°	284.1	283.9	282.7	283.2	282.2	282.5	281.2	280.7	279.3	279.0	278.3	278.3	278.3	278.6	279.1	280.0	281.2
27,5°	303.8	304.2	303.9	304.1	303.8	303.4	302.2	300.9	299.1	296.9	294.2	291.9	289.2	286.9	284.8	283.8	283.6
30,0°	329.4	329.2	328.2	328.0	327.4	327.2	326.3	326.0	324.6	323.4	320.9	318.8	314.6	310.7	305.0	299.9	295.1
32,5°	355.0	354.3	352.2	352.1	350.7	351.0	350.0	350.2	348.7	348.7	347.0	346.9	344.4	343.6	338.9	334.9	326.6
35,0°	371.3	367.4	364.8	363.0	361.8	361.3	361.4	362.3	363.5	365.2	367.1	368.9	370.3	372.0	371.7	370.0	365.5
37,5°	378.9	374.7	371.5	369.2	367.9	367.5	367.4	368.0	369.4	371.7	374.8	378.8	384.4	391.2	397.6	402.8	404.4
40,0°	387.3	382.4	378.5	375.7	374.4	373.7	374.0	375.1	376.8	379.7	383.4	388.7	395.9	404.7	415.1	426.4	436.2
42,5°	371.9	362.8	357.6	352.4	351.7	350.7	353.3	355.6	361.3	367.3	375.9	385.0	397.2	410.2	425.3	440.8	456.7
45,0°	322.8	312.2	305.7	300.4	298.9	298.6	301.1	305.4	312.7	321.6	333.3	346.6	364.3	383.9	407.4	431.8	457.2
46,0°	300.4	289.9	283.2	278.1	276.6	275.9	279.1	283.4	291.2	300.8	312.7	326.5	345.1	366.0	391.8	418.9	447.8
47,0°	273.8	262.8	257.3	251.7	251.0	250.2	253.2	257.1	265.5	275.2	288.2	301.8	321.4	343.0	370.6	399.9	432.5
48,0°	247.1	236.4	232.3	226.6	226.6	225.4	229.0	232.1	240.4	249.1	262.4	275.5	296.3	317.6	346.6	377.1	413.4
49,0°	219.0	206.5	206.0	198.5	201.6	198.0	203.8	203.3	213.5	218.0	233.8	243.0	266.7	284.2	317.5	345.1	387.5
50,0°	188.3	180.1	177.9	173.5	174.5	172.8	176.0	177.6	183.7	189.8	201.3	212.2	231.8	251.2	280.0	310.3	350.4
51,0°	161.9	155.1	153.5	149.8	150.6	149.4	152.0	152.9	158.5	163.1	173.0	182.0	199.7	217.3	244.9	272.8	311.7
52,0°	136.7	131.7	130.4	127.5	128.0	127.1	128.7	129.5	133.4	137.3	144.8	152.7	167.5	182.8	206.7	233.5	268.7
53,0°	115.5	112.1	110.9	108.7	109.2	108.6	109.7	110.4	113.5	116.4	121.8	128.0	139.7	153.0	173.6	197.8	230.6
54,0°	96.3	94.1	93.2	91.9	92.5	92.0	92.7	92.9	95.3	97.0	101.4	106.0	115.0	125.3	142.3	163.1	193.1
55,0°	78.2	77.4	77.5	76.9	77.7	77.0	77.0	76.3	77.4	78.0	81.6	84.5	91.7	99.3	112.3	128.7	154.4
56,0°	65.6	65.4	66.5	66.3	67.1	66.3	65.9	64.1	64.1	63.6	66.5	68.0	73.8	79.6	90.1	102.2	123.5
57,0°	57.1	56.4	58.5	57.8	59.3	57.4	57.4	54.5	54.7	52.8	55.0	55.4	60.8	64.2	73.6	82.0	99.7
58,0°	51.3	51.0	51.6	51.5	52.0	51.0	50.3	48.4	47.9	47.0	47.9	48.4	51.3	55.0	61.9	69.7	82.3
59,0°	47.9	47.2	47.4	47.0	47.2	46.2	45.7	44.5	44.1	43.8	44.3	44.5	46.4	48.7	54.7	61.9	73.1
60,0°	45.0	44.3	44.3	43.8	43.8	42.9	42.4	41.6	41.6	41.2	41.8	41.9	42.9	44.3	48.6	55.4	65.1
61,0°	42.8	42.1	41.8	41.2	41.2	40.4	40.2	39.5	39.7	39.5	39.9	40.2	40.7	41.4	44.3	49.9	58.5
62,0°	38.7	37.8	37.3	36.8	36.8	36.1	36.0	35.4	36.0	35.8	36.3	36.5	37.3	38.2	41.1	45.2	51.8
63,0°	37.7	36.6	36.0	35.4	35.1	34.6	34.4	34.3	34.6	34.1	33.7	33.7	33.6	33.6	35.3	40.9	44.1
64,0°	39.0	38.2	37.3	37.1	36.8	36.5	36.8	36.5	36.8	36.1	34.9	34.6	32.7	31.7	32.7	37.5	38.0
65,0°	36.6	35.4	35.4	33.9	33.7	33.1	33.9	33.1	34.3	33.7	34.4	34.3	32.9	30.0	31.2	33.9	34.4
66,0°	33.6	32.7	32.4	31.5	31.0	30.7	31.0	30.7	31.0	31.0	31.9	31.9	30.8	29.0	29.7	31.2	32.2
67,0°	31.7	30.8	30.3	29.7	29.1	28.8	29.1	29.0	29.1	29.1	30.0	29.8	29.0	28.1	28.6	29.7	30.7
68,0°	30.0	29.0	28.5	27.8	27.3	26.9	27.1	26.9	27.4	27.6	28.5	28.5	28.1	27.3	27.6	28.5	29.3
69,0°	28.1	27.1	26.6	25.9	25.6	25.1	25.4	25.1	25.6	26.1	26.9	27.1	27.1	26.4	26.8	27.3	28.1
70,0°	26.1	25.1	24.9	24.0	23.7	23.2	23.5	23.0	23.7	23.9	25.1	25.1	25.4	24.9	25.4	25.4	26.6
71,0°	23.9	23.0	22.8	22.2	21.6	21.3	21.3	21.1	21.6	22.0	22.7	22.8	23.2	23.0	23.3	23.3	24.4
72,0°	21.3	20.8	20.4	19.9	19.6	19.1	19.1	18.9	19.3	19.6	20.3	20.4	20.8	21.0	21.3	21.3	22.3
73,0°	18.6	18.1	17.9	17.4	17.0	16.5	16.7	16.4	16.7	16.9	17.4	17.7	18.1	18.6	19.1	19.1	19.9

Photometric test report

Family Streetlight 21 mini LED	Order number: 5XE2F43S08HB EAN: 4058352725771	LP number 59110_280
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	212,5°	215,0°	217,5°	220,0°	222,5°	225,0°	227,5°	230,0°	232,5°	235,0°	237,5°	240,0°	242,5°	245,0°	247,5°	250,0°	252,5°
γ	Luminous intensity in cd/klm																
0,0°	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3
2,5°	249.1	248.6	248.6	248.1	248.0	247.5	247.3	246.8	246.7	246.2	245.9	245.2	245.0	244.5	244.1	243.5	243.2
5,0°	259.5	258.7	258.3	257.5	257.0	256.1	255.6	254.8	254.2	253.4	252.5	251.5	251.0	250.2	249.5	248.5	247.8
7,5°	274.3	272.7	271.6	270.0	268.8	267.3	266.1	264.6	263.3	261.7	260.2	258.8	257.4	256.0	254.7	253.2	252.0
10,0°	279.3	280.8	281.5	281.9	281.9	280.8	279.5	277.3	275.0	272.1	269.6	267.2	265.0	262.6	260.7	258.5	256.8
12,5°	277.9	277.3	276.7	276.2	276.1	277.2	278.3	280.4	281.5	281.4	280.3	277.5	274.9	271.0	268.2	264.9	262.5
15,0°	281.3	281.3	281.2	281.0	280.7	279.8	278.8	277.3	276.6	276.9	279.1	282.0	282.7	281.0	277.6	273.3	269.9
17,5°	281.9	282.4	282.7	283.1	283.6	283.9	284.2	284.2	283.0	281.4	279.9	279.4	280.6	283.1	284.3	282.5	278.6
20,0°	281.9	282.7	283.7	284.8	285.8	286.8	288.2	288.8	289.7	289.7	289.4	287.1	285.4	283.6	284.8	287.3	287.1
22,5°	282.3	283.6	284.8	286.2	287.7	289.4	291.2	293.0	294.9	296.3	297.7	298.0	296.7	293.8	291.1	289.8	291.1
25,0°	282.7	284.2	286.1	288.0	289.9	291.6	294.3	296.9	300.1	302.8	306.1	307.6	308.6	306.4	303.5	298.9	296.5
27,5°	284.4	285.9	288.0	290.1	292.5	295.1	298.1	301.5	305.5	309.5	313.6	317.0	319.1	318.7	316.2	311.8	306.9
30,0°	292.6	291.6	292.4	294.1	296.9	299.9	303.5	307.1	311.5	315.9	320.9	325.3	328.5	329.4	328.0	323.6	318.7
32,5°	320.5	312.1	308.1	305.0	306.0	307.7	310.9	314.1	318.7	322.9	328.4	333.1	337.6	339.2	338.9	335.1	330.1
35,0°	359.6	350.7	340.8	331.1	324.5	321.6	321.6	323.6	326.8	330.8	335.9	341.2	345.6	348.1	348.0	344.7	339.6
37,5°	403.0	396.8	388.4	376.1	363.1	350.4	342.2	338.7	339.1	341.5	345.4	350.0	354.8	357.5	357.0	353.3	347.8
40,0°	443.9	444.6	440.7	429.4	416.3	398.2	380.4	365.5	358.5	356.3	358.0	361.1	365.0	367.1	366.0	361.6	356.0
42,5°	472.3	484.2	490.9	487.7	478.7	461.4	440.8	417.6	397.6	383.8	378.6	377.4	378.3	378.6	377.2	372.7	367.5
45,0°	479.5	500.1	518.0	531.0	535.8	529.1	512.4	490.4	463.7	436.9	416.1	404.5	399.1	395.7	392.8	388.4	382.2
46,0°	473.7	498.1	520.1	538.7	550.9	551.3	539.5	520.9	495.5	466.1	439.3	421.1	411.2	405.4	401.1	395.5	388.2
47,0°	461.8	490.3	516.5	540.5	560.5	570.0	566.9	553.0	531.3	501.2	468.8	444.3	429.1	418.9	412.2	403.4	391.8
48,0°	445.8	478.8	508.3	537.0	563.0	581.1	586.7	579.2	561.8	533.5	499.6	469.6	449.5	433.9	422.3	408.1	391.4
49,0°	420.2	461.3	493.7	528.8	559.1	586.2	601.9	599.5	591.3	564.9	535.8	498.6	475.3	450.0	431.8	410.0	387.3
50,0°	388.2	432.3	472.4	512.9	550.1	584.7	607.8	615.2	612.1	594.9	567.5	530.5	498.1	466.7	438.5	408.8	379.5
51,0°	348.5	395.0	440.0	489.4	533.9	575.3	605.8	622.5	626.9	615.7	591.3	552.8	516.2	478.8	440.3	400.8	361.9
52,0°	303.5	347.5	394.8	449.4	503.7	553.5	594.9	621.6	633.6	626.4	602.1	562.3	521.3	479.0	428.7	376.8	328.4
53,0°	262.6	303.2	348.1	403.2	460.6	520.8	573.8	610.1	629.0	621.8	595.4	553.1	505.9	459.6	401.3	341.3	286.6
54,0°	222.7	259.7	300.9	350.9	407.6	474.8	538.1	587.4	614.3	603.8	570.5	525.2	470.5	421.6	359.6	296.7	240.6
55,0°	180.5	214.0	248.8	293.1	345.8	411.9	483.6	549.4	582.8	567.1	522.8	474.9	414.6	365.0	305.2	245.2	192.6
56,0°	144.5	173.8	201.4	242.5	289.2	351.0	424.0	500.5	536.6	519.2	466.6	419.9	358.5	310.8	256.3	204.0	159.2
57,0°	113.7	137.7	156.3	193.4	231.6	295.3	358.2	441.9	475.8	465.7	407.6	368.1	306.9	266.3	219.1	178.1	144.0
58,0°	92.2	105.7	118.6	138.2	183.0	240.4	301.6	374.4	414.3	406.6	360.1	321.4	273.0	236.2	203.8	171.4	148.8
59,0°	78.6	84.9	83.5	98.8	142.3	195.8	250.8	317.6	354.4	354.3	321.9	290.5	253.9	226.3	205.7	183.4	167.0
60,0°	69.7	67.1	61.3	73.8	108.4	151.3	202.3	262.3	298.6	303.2	290.7	270.8	247.4	230.2	222.2	209.6	196.8
61,0°	60.8	54.0	53.3	62.0	87.1	121.3	163.1	218.6	254.9	265.7	265.8	262.1	248.8	241.6	244.7	240.8	230.2
62,0°	50.1	47.5	49.4	56.4	75.7	100.5	133.8	179.6	218.1	234.8	243.5	253.7	253.6	257.3	270.6	274.9	267.4
63,0°	41.9	42.9	46.0	52.5	69.4	87.9	110.6	146.9	182.3	204.8	221.9	238.6	257.8	275.9	300.3	312.7	310.7
64,0°	37.8	39.9	43.3	49.4	65.8	82.5	98.2	124.2	155.8	179.6	202.1	222.2	254.6	292.4	326.0	345.2	348.3
65,0°	34.9	37.5	40.4	47.0	62.0	79.6	90.8	109.1	131.7	157.5	177.4	206.7	244.4	300.8	350.7	373.4	383.8
66,0°	33.1	35.1	38.2	44.5	59.0	76.0	86.2	98.5	115.9	136.7	155.8	188.0	229.7	298.0	361.9	397.7	409.1
67,0°	31.4	33.4	36.1	42.1	55.4	71.9	81.5	91.7	103.9	121.2	136.8	165.3	212.7	286.3	359.7	409.8	427.9
68,0°	30.0	31.5	34.1	39.7	50.6	66.3	75.5	83.8	93.0	105.0	118.1	140.6	186.9	264.5	344.9	407.3	436.8
69,0°	29.0	30.3	32.0	37.0	46.4	60.3	68.8	76.5	84.9	94.7	102.8	119.5	160.4	237.9	322.1	393.3	430.5
70,0°	27.6	29.3	30.3	34.4	41.1	53.2	61.7	70.4	78.2	86.9	92.0	102.6	133.3	206.4	289.4	369.4	410.2
71,0°	25.9	27.3	28.8	31.7	36.6	45.2	55.0	63.9	71.2	79.1	84.0	90.1	112.8	173.3	254.1	330.6	368.9
72,0°	23.7	24.9	26.2	29.1	32.7	38.2	47.4	55.6	62.9	71.2	76.5	80.9	96.5	144.2	213.2	286.6	329.7
73,0°	21.3	22.3	23.2	25.9	29.1	32.4	38.5	46.4	54.4	62.4	67.5	70.0	81.1	116.4	173.8	239.9	282.5

Photometric test report

Family Streetlight 21 mini LED	Order number: 5XE2F43S08HB EAN: 4058352725771	LP number 59110_280
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	255,0°	257,5°	260,0°	262,5°	265,0°	267,5°	270,0°	272,5°	275,0°	277,5°	280,0°	282,5°	285,0°	287,5°	290,0°	292,5°	295,0°
γ	Luminous intensity in cd/klm																
0,0°	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3
2,5°	242.7	242.4	241.9	241.4	241.0	240.5	240.4	240.2	239.6	238.9	238.2	237.6	237.2	236.9	236.7	236.4	236.2
5,0°	246.9	246.1	244.9	243.9	242.8	242.0	241.3	240.6	239.6	238.6	237.5	236.7	236.2	235.8	235.7	235.5	235.3
7,5°	250.8	249.5	247.9	246.4	245.0	243.6	242.4	241.0	239.6	238.1	236.8	235.8	235.5	235.2	235.1	234.7	234.1
10,0°	254.9	253.1	251.0	249.1	247.4	245.6	243.7	242.0	240.1	237.9	236.4	235.5	234.8	234.7	234.1	232.9	231.1
12,5°	259.5	257.2	254.6	252.5	250.4	248.5	246.2	243.9	241.4	238.9	236.8	235.7	234.8	234.3	233.0	230.6	227.8
15,0°	266.2	262.8	259.4	256.8	254.4	252.4	249.8	247.1	244.2	241.5	238.6	236.9	235.8	235.0	232.4	229.4	225.8
17,5°	274.0	269.6	265.1	261.4	258.7	256.2	253.7	250.8	247.7	244.2	240.9	238.6	237.5	236.3	233.1	229.5	225.1
20,0°	282.9	277.9	271.6	266.9	262.8	259.9	257.0	254.2	250.7	246.6	242.8	240.3	238.9	237.4	233.8	229.4	223.7
22,5°	291.1	287.6	280.9	274.3	268.7	264.6	261.2	257.8	254.0	249.5	245.3	241.9	240.2	238.2	234.1	228.0	221.4
25,0°	296.3	296.3	291.7	284.6	277.1	271.5	266.5	262.4	257.7	253.1	248.3	244.2	241.5	239.3	233.8	226.1	219.3
27,5°	302.6	301.5	300.4	294.6	286.9	279.3	272.9	267.2	261.7	256.3	251.2	246.2	242.5	239.4	232.6	224.4	215.5
30,0°	312.2	306.9	305.2	303.0	295.7	286.8	278.8	271.5	265.0	258.8	253.1	247.1	241.6	237.5	229.2	220.3	208.7
32,5°	322.8	315.3	309.3	307.9	303.5	294.5	285.1	276.5	268.5	261.7	254.8	247.7	240.5	234.7	225.4	213.9	201.5
35,0°	333.1	324.5	315.4	311.0	309.3	301.8	291.6	282.0	272.8	264.3	256.6	248.1	239.1	231.2	220.5	207.0	192.0
37,5°	341.4	333.3	323.1	315.5	313.1	308.4	298.4	289.1	278.3	267.9	258.4	248.1	236.8	227.6	213.9	198.4	181.1
40,0°	349.8	343.4	333.5	324.8	319.3	315.6	306.1	296.3	284.1	271.5	259.9	246.9	233.3	222.4	205.7	188.3	169.2
42,5°	361.9	355.7	345.8	335.6	326.9	320.5	310.5	299.7	286.7	272.1	257.8	241.8	225.7	211.9	193.2	174.4	155.7
45,0°	374.6	365.7	353.8	341.7	330.6	320.4	309.6	297.5	284.4	268.4	251.5	232.8	214.0	198.2	176.5	157.5	139.9
46,0°	377.6	366.2	352.7	339.6	327.9	316.3	305.0	292.8	279.8	263.5	246.1	226.5	206.9	189.0	168.5	150.1	133.8
47,0°	376.8	362.8	348.5	334.5	322.6	310.1	298.7	286.1	273.2	256.5	238.7	218.1	198.2	179.3	159.0	141.4	126.4
48,0°	373.0	357.0	342.0	327.7	315.6	302.1	290.4	276.9	264.3	247.1	229.5	208.6	189.0	171.3	150.0	133.3	119.6
49,0°	366.5	347.1	332.6	315.1	303.8	285.9	275.2	257.8	247.9	228.3	214.7	192.6	176.7	156.8	140.2	124.1	112.8
50,0°	353.6	330.4	311.7	291.9	277.4	258.5	245.4	228.3	216.8	200.4	187.4	170.1	156.3	140.6	127.0	114.7	105.7
51,0°	329.9	300.8	279.5	256.0	240.8	219.8	206.7	189.5	179.6	164.3	155.1	141.3	132.2	120.3	110.8	103.1	98.5
52,0°	289.5	257.0	233.1	209.8	193.2	174.2	160.9	146.6	137.0	125.4	118.4	110.4	105.0	97.6	91.9	89.8	90.1
53,0°	245.4	212.0	188.5	166.7	151.7	135.3	124.1	112.5	104.6	95.9	91.5	87.1	84.2	79.8	76.5	78.9	83.8
54,0°	199.9	168.9	148.1	129.7	117.9	105.8	98.2	90.0	83.8	77.5	74.3	72.1	70.4	67.3	65.1	71.1	79.9
55,0°	156.8	131.7	116.6	104.5	97.5	90.8	86.1	80.8	75.8	70.4	67.3	65.4	63.7	60.3	58.3	66.6	78.0
56,0°	131.6	114.2	104.3	98.0	93.9	90.5	86.7	82.3	77.0	71.6	67.5	65.3	62.5	58.6	56.1	65.6	77.4
57,0°	124.4	114.0	106.2	103.3	99.2	97.3	92.5	88.3	81.6	75.8	70.4	67.5	63.6	58.8	55.9	65.9	77.0
58,0°	133.6	124.7	116.6	113.3	109.4	106.8	101.9	96.3	89.0	82.0	75.2	70.7	65.6	59.6	56.6	66.5	76.7
59,0°	151.8	141.8	130.9	127.0	122.0	119.5	113.5	107.0	98.2	89.8	81.1	75.0	68.2	61.2	57.6	66.8	76.0
60,0°	179.6	165.6	151.3	146.0	140.2	137.0	129.5	121.7	110.9	100.4	89.3	80.6	71.7	63.2	59.0	66.5	74.6
61,0°	210.1	192.4	174.0	167.0	160.2	156.3	147.4	137.5	124.6	111.4	97.6	86.4	75.5	65.6	60.3	65.6	72.3
62,0°	245.9	223.2	200.9	190.9	182.8	177.2	167.3	154.7	139.6	123.0	106.5	92.4	79.2	68.0	61.5	64.1	68.8
63,0°	288.5	261.2	233.5	219.7	209.3	201.4	189.7	174.2	155.9	135.5	115.7	98.3	83.2	70.5	62.5	62.4	64.6
64,0°	328.2	297.7	264.6	246.8	233.3	223.2	209.3	191.4	169.9	145.9	123.0	102.9	85.9	72.3	63.2	60.8	61.2
65,0°	365.5	336.9	295.8	275.4	256.1	245.2	226.8	208.1	182.2	155.2	129.0	106.5	87.8	73.6	63.7	60.0	58.6
66,0°	398.9	369.4	327.0	299.4	278.3	262.8	243.7	220.3	192.2	161.2	133.1	108.2	88.4	74.0	64.1	59.6	57.4
67,0°	421.9	396.2	352.4	319.9	295.8	276.9	255.4	229.2	198.2	164.3	134.6	108.2	88.1	73.6	63.9	59.5	56.7
68,0°	437.3	416.8	374.2	337.7	310.3	288.5	264.8	234.7	200.7	164.1	133.3	106.3	86.6	72.6	63.4	58.8	55.6
69,0°	441.9	426.0	387.7	349.0	319.2	294.6	269.2	235.8	199.5	160.9	129.7	102.9	84.2	71.1	62.2	57.6	54.0
70,0°	434.5	419.5	388.9	344.6	316.3	284.6	261.6	223.2	189.8	149.3	121.8	96.1	80.6	68.7	60.7	55.7	52.3
71,0°	391.1	385.8	360.9	322.2	294.5	268.4	242.0	209.1	172.6	135.1	107.9	86.2	72.9	63.6	57.3	53.0	50.3
72,0°	357.3	362.6	342.9	310.1	281.7	257.1	232.1	196.3	160.0	123.9	97.6	78.6	67.3	59.0	53.0	49.2	46.9
73,0°	308.9	316.3	309.1	276.2	250.3	230.7	208.4	173.6	138.5	106.3	84.2	68.0	59.8	53.5	48.7	45.7	43.1

Photometric test report

Family Streetlight 21 mini LED	Order number: 5XE2F43S08HB EAN: 4058352725771	LP number 59110_280
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	297,5°	300,0°	302,5°	305,0°	307,5°	310,0°	312,5°	315,0°	317,5°	320,0°	322,5°	325,0°	327,5°	330,0°	332,5°	335,0°	337,5°
γ	Luminous intensity in cd/klm																
0,0°	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3
2,5°	235.8	235.7	235.5	235.4	235.3	235.3	235.2	235.2	235.2	235.2	235.2	235.3	235.2	235.2	235.2	235.2	235.2
5,0°	235.2	235.0	234.7	234.3	233.8	233.3	232.6	232.1	231.2	230.7	229.9	229.5	228.5	228.2	227.3	227.2	226.5
7,5°	233.2	232.1	230.7	229.3	227.8	226.5	225.3	224.4	223.5	223.1	222.3	221.8	221.1	220.7	220.1	219.7	219.1
10,0°	229.2	227.2	225.1	223.4	222.2	221.5	220.3	219.3	218.0	216.9	215.2	213.9	212.2	211.3	210.1	209.6	209.1
12,5°	225.0	223.1	221.1	219.3	217.1	215.3	212.5	211.1	209.3	208.8	208.0	207.8	206.8	206.4	205.3	204.9	203.4
15,0°	222.9	220.0	217.1	213.5	209.9	208.1	206.7	205.7	203.8	201.9	199.5	197.8	195.5	194.1	192.0	190.5	188.1
17,5°	221.0	216.8	212.7	209.3	206.4	203.4	199.6	196.5	193.2	190.3	186.8	183.7	180.0	176.6	172.9	169.8	166.7
20,0°	218.6	214.0	209.6	204.7	199.5	195.3	190.2	185.9	180.5	176.0	169.0	165.0	159.8	157.6	154.7	153.4	151.0
22,5°	216.1	209.8	203.6	197.3	191.5	185.8	178.7	171.6	164.1	158.9	154.4	151.4	147.9	145.0	141.9	139.2	136.3
25,0°	211.3	203.3	196.0	189.0	181.1	173.0	162.9	157.1	152.2	148.3	142.5	138.9	133.4	129.9	125.4	123.5	122.2
27,5°	205.8	196.3	188.1	178.1	167.3	158.6	152.3	146.6	140.3	134.8	128.7	124.0	121.3	120.5	120.9	121.7	121.9
30,0°	198.4	188.1	177.4	164.1	155.6	148.8	140.9	134.3	127.3	121.8	119.3	119.1	120.0	120.1	118.9	116.4	114.3
32,5°	189.2	176.6	162.4	152.3	144.3	136.4	128.6	122.7	118.9	118.3	118.7	118.4	115.5	112.7	109.6	107.4	105.1
35,0°	178.2	161.9	150.3	141.1	132.1	125.3	119.1	117.9	117.6	118.1	115.0	111.6	107.5	105.0	102.6	101.1	99.3
37,5°	164.4	149.2	139.0	128.7	122.7	117.9	117.1	117.1	116.3	112.2	108.0	104.6	102.2	100.9	99.3	97.4	95.0
40,0°	151.7	138.5	127.0	120.5	116.0	115.5	115.4	114.5	109.6	105.5	101.7	100.2	99.3	98.2	95.9	92.9	89.3
42,5°	140.2	127.0	119.5	114.9	113.2	112.1	111.1	106.3	101.3	98.4	97.7	97.2	95.3	93.6	91.3	87.6	83.6
45,0°	125.9	115.7	113.7	111.6	109.9	107.5	102.6	97.6	92.5	90.0	90.5	91.7	90.8	88.6	85.4	82.5	79.6
46,0°	119.6	112.0	110.9	109.7	107.7	105.0	99.5	94.2	89.3	86.9	87.6	88.4	88.6	86.7	82.6	79.6	77.5
47,0°	112.6	107.9	107.4	106.8	104.8	101.4	95.9	90.8	86.1	83.8	84.4	85.5	85.7	83.3	79.2	76.5	75.0
48,0°	106.5	104.3	103.9	103.6	101.4	97.6	92.9	87.9	83.2	81.1	81.8	83.5	82.5	79.1	76.0	73.8	72.6
49,0°	100.4	100.4	99.7	99.7	96.8	93.9	89.3	84.9	80.3	78.6	79.4	80.9	77.9	74.6	72.4	71.4	70.2
50,0°	96.1	96.3	95.6	94.7	91.7	89.1	85.9	82.0	77.9	76.3	77.0	77.2	73.3	70.5	69.2	69.0	68.2
51,0°	92.7	92.9	91.5	89.6	86.2	84.4	82.1	79.1	75.8	74.3	74.1	72.8	68.8	67.5	66.5	66.6	66.5
52,0°	89.5	89.3	86.9	83.8	80.4	79.1	77.7	75.8	74.0	71.9	70.7	68.0	64.8	64.4	64.1	64.2	64.4
53,0°	87.1	86.4	83.0	78.7	75.3	74.5	73.6	73.1	71.9	70.0	67.7	63.9	61.9	62.4	62.2	62.2	62.5
54,0°	85.2	83.7	79.2	73.8	70.4	70.0	69.5	70.2	69.7	67.8	64.4	60.5	59.6	61.0	60.7	60.3	60.5
55,0°	83.8	80.9	75.3	69.2	65.6	65.1	65.4	66.8	67.0	65.4	61.2	57.6	57.6	60.5	59.3	58.5	58.3
56,0°	82.5	78.6	71.9	65.4	61.7	61.2	61.7	63.4	63.9	62.9	57.9	55.0	56.1	60.8	58.6	56.7	56.6
57,0°	80.4	75.7	68.5	62.0	58.1	57.9	58.1	60.0	60.7	59.8	55.0	53.2	54.7	61.3	58.1	55.4	54.7
58,0°	78.2	72.4	65.3	58.8	55.2	54.7	55.0	56.4	57.3	56.1	52.3	51.1	53.8	61.7	57.6	53.8	52.7
59,0°	75.8	69.5	62.2	56.1	52.7	52.0	52.3	53.3	53.8	52.5	49.9	49.4	53.5	61.0	56.4	52.1	50.3
60,0°	73.1	67.0	59.5	53.3	49.9	49.2	49.6	50.4	50.3	48.9	47.4	47.5	53.2	59.6	54.7	49.9	47.2
61,0°	70.2	64.4	57.4	51.3	47.9	47.2	47.2	47.7	47.4	46.0	45.3	46.0	52.7	58.1	52.7	47.0	44.0
62,0°	66.8	62.0	55.7	49.4	46.2	45.2	45.0	45.2	44.8	43.8	43.3	44.5	51.5	56.1	50.4	44.1	40.7
63,0°	62.4	58.5	53.0	47.5	44.3	42.9	42.4	42.6	42.1	41.4	41.4	42.6	49.4	53.5	48.4	41.6	38.0
64,0°	58.6	54.9	50.1	45.5	42.6	41.1	40.4	40.4	39.9	39.5	39.5	40.7	47.0	50.8	46.5	40.0	36.1
65,0°	55.6	51.6	46.7	42.9	40.6	39.4	38.3	38.3	37.7	37.8	37.5	38.7	43.8	47.9	44.1	38.7	34.4
66,0°	53.8	48.9	44.0	40.2	38.5	37.3	36.5	36.3	36.0	36.0	35.6	36.3	40.6	44.5	41.8	37.3	33.2
67,0°	52.5	47.0	41.8	38.2	36.6	35.6	34.8	34.6	34.3	34.1	33.9	34.3	37.5	41.1	39.5	36.1	32.2
68,0°	50.8	45.0	39.5	36.1	34.4	33.4	32.7	32.5	32.2	32.2	31.9	31.9	34.1	37.7	37.0	34.6	31.0
69,0°	49.2	43.5	38.0	34.4	32.7	31.7	30.8	30.8	30.7	30.5	30.2	29.8	31.2	34.6	34.6	33.2	30.0
70,0°	47.5	41.8	36.1	32.9	30.8	29.8	28.8	28.8	28.6	28.8	28.1	27.9	28.1	31.5	31.9	31.5	28.5
71,0°	45.7	39.7	34.6	31.0	29.5	28.1	27.3	26.9	26.9	26.9	26.4	25.7	25.9	28.1	29.5	29.5	27.1
72,0°	42.8	37.5	32.5	29.1	27.6	26.4	25.4	24.9	24.9	25.1	24.7	24.0	23.7	25.4	26.9	27.4	25.2
73,0°	39.4	34.4	30.2	27.3	25.7	24.7	23.5	22.8	22.8	23.0	22.8	22.0	21.3	22.5	23.9	24.7	23.2

Photometric test report

Family Streetlight 21 mini LED	Order number: 5XE2F43S08HB EAN: 4058352725771	LP number 59110_280
Table of values for luminous intensities		Maximum luminous intensity

siteco

C- planes	340,0°	342,5°	345,0°	347,5°	350,0°	352,5°	355,0°	357,5°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm								Luminous flux in lm/klm	
0,0°	240.3	240.3	240.3	240.3	240.3	240.3	240.3	240.3	0.4	0.4
2,5°	235.3	235.4	235.7	235.8	236.0	236.0	236.2	236.4	2.9	3.3
5,0°	226.5	226.0	226.1	225.8	226.1	225.6	226.0	226.0	5.9	9.1
7,5°	218.9	218.5	218.4	218.0	217.9	217.5	217.7	217.8	8.9	18.0
10,0°	209.1	209.3	209.4	209.4	209.4	209.3	209.6	209.8	11.9	29.9
12,5°	203.1	201.8	201.8	200.6	200.6	199.5	200.1	199.3	14.8	44.7
15,0°	187.1	185.2	184.4	182.5	182.0	180.5	180.6	180.0	17.5	62.2
17,5°	164.7	162.7	161.8	160.7	160.2	159.5	159.6	159.4	20.1	82.3
20,0°	150.1	148.1	147.7	146.2	146.2	145.0	145.5	144.8	22.6	105.0
22,5°	134.1	131.7	130.4	129.0	128.5	127.9	128.0	127.9	25.1	130.0
25,0°	122.5	123.4	124.1	124.7	125.1	125.1	125.4	125.6	27.6	157.6
27,5°	121.3	120.4	119.6	118.3	117.5	116.6	116.5	116.2	30.4	188.1
30,0°	112.3	110.3	108.9	107.5	106.5	105.3	105.0	104.5	33.5	221.5
32,5°	103.4	101.5	100.3	98.5	97.3	95.7	95.0	94.0	36.8	258.3
35,0°	97.5	95.4	93.0	90.7	88.3	86.1	84.4	83.2	40.2	298.5
37,5°	92.0	88.7	85.1	81.6	78.5	75.8	73.9	72.4	43.7	342.2
40,0°	84.9	80.4	76.9	74.1	72.3	70.9	69.7	69.0	47.5	389.7
42,5°	80.3	77.8	75.7	73.9	72.4	71.2	70.3	69.6	51.1	440.7
45,0°	77.0	74.8	72.9	71.6	70.7	70.0	69.7	69.4	37.3	478.1
46,0°	75.2	73.3	72.1	70.9	70.2	69.5	69.4	69.0	21.8	499.9
47,0°	73.3	71.9	70.7	70.0	69.4	69.2	69.0	68.8	22.0	521.9
48,0°	71.7	70.5	69.9	69.2	68.8	68.7	68.7	68.7	22.2	544.1
49,0°	70.0	69.2	68.8	68.3	68.2	68.0	68.2	68.0	22.3	566.4
50,0°	68.2	68.0	67.8	67.5	67.3	67.3	67.5	67.5	22.2	588.7
51,0°	66.5	66.6	66.6	66.5	66.5	66.3	66.6	66.6	22.1	610.7
52,0°	64.6	64.9	65.1	65.1	65.1	65.1	65.4	65.4	21.8	632.5
53,0°	62.7	63.2	63.6	63.6	63.7	63.6	63.7	63.7	21.4	654.0
54,0°	61.0	61.5	62.0	61.9	61.9	61.5	61.7	61.7	21.1	675.0
55,0°	58.8	59.3	59.8	59.6	59.3	59.0	59.1	59.0	20.7	695.7
56,0°	56.6	57.3	57.4	57.1	56.9	56.4	56.6	56.4	20.3	716.0
57,0°	54.4	54.7	55.0	54.5	54.5	53.8	54.2	54.0	20.0	736.0
58,0°	51.8	52.1	52.7	52.5	52.5	52.0	52.1	52.0	19.6	755.6
59,0°	49.1	49.2	50.4	50.3	50.4	49.9	50.1	50.1	19.1	774.8
60,0°	46.0	46.4	47.5	47.7	47.9	47.4	47.5	47.4	18.4	793.1
61,0°	42.9	43.3	44.5	44.8	45.0	44.5	44.6	44.6	17.5	810.6
62,0°	39.7	39.9	40.9	41.4	41.6	41.2	41.4	41.4	16.6	827.1
63,0°	36.5	36.5	37.1	37.5	37.5	37.3	37.5	37.3	15.7	842.8
64,0°	34.4	34.3	34.3	34.4	34.4	34.3	34.3	34.1	15.1	858.0
65,0°	32.7	32.0	32.2	31.9	32.2	31.7	31.9	31.5	14.7	872.6
66,0°	31.2	30.5	30.3	30.0	30.3	30.0	30.0	29.8	14.3	886.9
67,0°	29.7	28.8	28.6	28.3	28.6	28.3	28.3	28.3	13.8	900.7
68,0°	28.1	26.9	26.8	26.2	26.6	26.4	26.4	26.4	13.0	913.7
69,0°	26.6	25.4	25.1	24.7	24.7	24.7	24.9	24.7	12.3	926.0
70,0°	25.2	23.7	23.5	22.8	23.2	23.0	23.3	23.2	11.5	937.5
71,0°	23.7	22.0	21.6	21.1	21.3	21.3	21.5	21.5	10.7	948.2
72,0°	22.2	20.4	19.9	19.4	19.4	19.4	19.6	19.8	9.8	958.0
73,0°	20.4	18.7	18.1	17.6	17.4	17.4	17.7	17.9	8.7	966.7

Photometric test report

Family Streetlight 21 mini LED	Order number: 5XE2F43S08HB EAN: 4058352725771	LP number 59110_280
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0,0°	2,5°	5,0°	7,5°	10,0°	12,5°	15,0°	17,5°	20,0°	22,5°	25,0°	27,5°	30,0°	32,5°	35,0°	37,5°	40,0°
γ	Luminous intensity in cd/klm																
74,0°	16.4	16.4	16.7	16.7	17.0	17.6	18.7	19.8	21.5	23.5	26.1	26.8	25.4	23.2	22.3	22.0	22.8
75,0°	14.7	14.7	15.0	15.0	15.3	15.8	16.9	18.1	19.8	21.6	24.2	24.4	22.7	20.8	20.1	19.8	20.4
76,0°	12.8	12.8	13.3	13.1	13.6	13.8	15.0	16.0	18.1	19.8	21.8	21.1	19.4	18.2	17.7	17.4	17.9
77,0°	11.1	11.1	11.6	11.6	11.9	12.1	13.1	14.3	16.4	18.1	19.3	18.2	16.7	16.0	15.7	15.2	15.5
78,0°	9.5	9.5	10.1	9.7	10.2	10.4	11.4	12.4	14.7	15.8	16.7	15.0	14.5	13.8	13.6	12.8	13.1
79,0°	8.2	8.2	8.5	8.2	8.5	8.7	9.5	10.7	13.0	13.8	13.8	12.6	12.1	11.8	11.4	10.6	10.4
80,0°	6.6	6.6	7.0	6.8	7.0	7.2	7.8	8.9	10.6	11.2	11.4	10.6	10.2	9.9	9.4	8.7	8.5
81,0°	5.1	5.3	5.3	5.3	5.5	5.6	6.1	6.8	8.0	8.5	8.9	8.5	8.5	8.0	7.3	6.8	6.8
82,0°	4.1	4.4	4.6	4.6	4.9	4.6	4.8	4.9	5.6	6.1	6.6	6.5	6.5	5.8	5.6	5.3	5.5
83,0°	2.7	2.9	3.1	3.1	3.6	3.6	3.6	3.4	4.3	4.6	4.6	4.3	4.3	4.1	4.1	3.9	4.1
84,0°	1.5	1.5	1.7	1.7	1.9	2.2	2.2	2.4	3.4	3.4	2.9	2.6	2.7	2.7	2.9	2.7	2.9
85,0°	0.9	0.9	1.0	1.0	1.0	1.2	1.4	1.4	1.9	1.9	1.7	1.5	1.7	1.7	2.0	1.9	2.0
86,0°	0.5	0.5	0.5	0.5	0.7	0.7	0.7	0.7	1.0	0.9	1.0	0.9	1.0	1.2	1.4	1.2	1.4
87,0°	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.5	0.5	0.5	0.7	0.7	0.7	0.9	0.9	1.0
88,0°	0.2	0.2	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.5	0.5	0.5	0.5	0.7	0.7	0.7	0.7
89,0°	0.2	0.2	0.2	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.5	0.5	0.5	0.5	0.7	0.7	0.7
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Photometric test report

Family
Streetlight 21 mini LED

Order number: 5XE2F43S08HB
EAN: 4058352725771

LP number
59110_280

siteco

C- planes	42,5°	45,0°	47,5°	50,0°	52,5°	55,0°	57,5°	60,0°	62,5°	65,0°	67,5°	70,0°	72,5°	75,0°	77,5°	80,0°	82,5°
γ	Luminous intensity in cd/klm																
74,0°	23.0	24.2	25.6	28.1	32.0	37.8	42.6	44.6	41.9	38.5	31.5	29.5	26.9	28.1	29.0	32.5	42.1
75,0°	20.6	21.8	22.8	25.1	28.5	34.1	38.7	40.0	35.6	33.6	28.5	27.1	23.7	24.2	25.1	28.5	36.8
76,0°	18.1	19.1	19.9	21.5	24.5	29.8	33.7	34.1	30.7	30.2	26.1	24.5	21.0	20.8	21.8	25.2	32.5
77,0°	15.5	16.5	17.0	18.4	20.8	25.6	29.1	29.1	26.6	27.4	22.8	21.6	18.7	18.6	19.9	22.7	29.5
78,0°	12.8	14.0	14.3	15.7	17.2	20.6	21.8	22.7	21.5	22.8	18.2	18.4	17.0	16.7	18.2	20.3	26.1
79,0°	10.6	11.4	11.9	13.0	14.0	15.3	15.8	17.0	18.4	19.9	16.7	16.9	15.8	15.0	16.9	18.2	23.7
80,0°	8.7	9.4	9.9	10.4	11.2	11.9	12.6	14.1	15.8	17.2	15.7	15.3	14.7	13.3	15.5	17.2	21.5
81,0°	7.0	7.5	7.7	7.8	8.5	9.2	10.1	11.8	13.0	14.1	13.8	13.3	12.4	11.4	13.0	15.2	18.4
82,0°	5.5	5.8	6.0	6.3	6.8	7.2	7.8	9.2	9.9	10.9	11.6	10.4	9.4	9.7	10.9	13.0	15.3
83,0°	4.1	4.6	4.8	4.9	5.1	5.5	5.8	6.8	7.2	8.0	8.5	8.4	8.0	8.2	8.7	10.4	11.8
84,0°	2.9	3.2	3.4	3.6	3.7	3.9	4.1	4.6	4.8	5.5	5.8	6.5	6.3	6.3	6.3	7.3	7.8
85,0°	2.0	2.4	2.4	2.6	2.6	2.7	2.9	3.2	3.4	3.9	4.1	4.4	4.3	4.4	4.3	4.8	5.3
86,0°	1.4	1.5	1.5	1.7	1.7	1.9	1.9	2.2	2.2	2.7	2.9	3.2	2.9	2.9	2.7	3.2	3.1
87,0°	1.0	1.0	1.2	1.2	1.2	1.4	1.4	1.5	1.5	1.7	1.7	1.9	1.9	1.9	1.7	1.9	1.9
88,0°	0.9	0.9	0.9	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.2	1.2	1.2	1.2	1.2	1.2
89,0°	0.7	0.7	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	1.0	1.0	1.0
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Photometric test report

Family
Streetlight 21 mini LED

Order number: 5XE2F43S08HB
EAN: 4058352725771

LP number
59110_280

siteco

C- planes	85,0°	87,5°	90,0°	92,5°	95,0°	97,5°	100,0°	102,5°	105,0°	107,5°	110,0°	112,5°	115,0°	117,5°	120,0°	122,5°	125,0°
γ	Luminous intensity in cd/klm																
74,0°	80.3	173.3	287.3	343.0	385.8	435.1	491.6	485.7	462.5	420.1	341.5	214.5	137.2	103.3	84.7	66.5	47.7
75,0°	68.0	146.4	251.2	301.3	334.2	370.0	408.3	390.7	371.5	332.3	262.6	155.9	103.4	82.5	69.4	49.8	33.7
76,0°	57.8	117.4	207.2	248.5	275.5	294.8	317.8	293.8	278.1	247.3	188.6	106.7	75.2	63.7	52.1	33.2	27.3
77,0°	48.9	89.3	151.2	181.8	201.9	211.5	228.2	208.7	201.4	178.6	130.4	71.7	53.3	45.7	34.8	25.6	23.3
78,0°	42.8	66.5	102.9	119.6	135.5	132.7	151.5	135.8	138.0	120.0	90.7	49.9	37.3	29.3	24.9	20.8	19.8
79,0°	38.3	57.1	77.7	90.1	91.9	88.8	94.2	91.0	90.7	80.9	61.0	37.8	29.0	23.7	20.3	17.2	16.2
80,0°	34.6	52.5	70.9	80.9	77.7	70.7	67.5	64.2	62.0	54.5	43.1	29.0	23.5	19.3	16.4	14.5	13.6
81,0°	29.5	44.5	60.8	69.0	68.2	59.5	52.7	47.0	42.3	36.1	30.0	22.0	18.6	15.0	13.0	11.8	11.2
82,0°	23.5	35.1	47.4	52.7	52.1	47.0	41.2	34.8	30.3	24.7	21.5	17.0	14.5	11.9	10.6	9.5	9.0
83,0°	17.0	24.5	34.4	38.0	39.4	35.8	31.5	26.2	22.0	17.6	15.2	12.6	10.9	9.2	8.2	7.3	7.0
84,0°	10.7	14.7	19.3	19.9	22.2	20.8	19.6	17.0	15.0	11.6	10.1	8.5	7.8	6.5	6.0	5.3	5.1
85,0°	6.8	8.2	10.6	10.7	12.3	12.6	13.3	11.2	9.9	7.8	6.8	5.6	5.1	4.4	4.3	3.7	3.7
86,0°	4.1	3.9	5.5	4.8	6.0	5.6	7.5	5.6	6.0	4.8	4.4	3.6	3.4	2.7	2.7	2.4	2.4
87,0°	2.2	2.0	2.6	2.4	2.7	2.6	2.9	2.7	2.7	2.4	2.4	2.0	2.0	1.7	1.7	1.5	1.5
88,0°	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.0	1.0	1.0	1.0
89,0°	1.0	1.0	1.0	1.0	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.7	0.7	0.7
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Photometric test report

Family
Streetlight 21 mini LED

Order number: 5XE2F43S08HB
EAN: 4058352725771

LP number
59110_280


C- planes	127,5°	130,0°	132,5°	135,0°	137,5°	140,0°	142,5°	145,0°	147,5°	150,0°	152,5°	155,0°	157,5°	160,0°	162,5°	165,0°	167,5°
γ	Luminous intensity in cd/klm																
74,0°	37.8	35.6	34.3	34.3	30.0	25.9	23.9	23.9	23.3	22.7	20.8	19.8	18.9	18.4	17.6	17.0	16.2
75,0°	29.5	30.5	31.5	31.0	26.9	23.2	20.8	21.1	20.6	20.1	18.4	17.6	16.9	16.2	15.3	14.8	14.1
76,0°	25.7	27.1	28.1	27.3	23.9	20.4	18.2	18.2	18.1	17.4	16.0	15.3	14.5	14.0	13.1	12.8	12.1
77,0°	22.5	24.4	25.4	24.2	21.3	18.2	16.0	15.8	15.7	15.2	14.0	13.6	12.8	12.3	11.6	11.2	10.6
78,0°	19.1	21.0	21.8	21.1	18.4	16.2	14.1	13.8	13.1	13.1	11.9	11.9	10.7	10.4	9.9	9.7	9.2
79,0°	15.8	17.2	18.4	18.1	16.4	14.3	13.0	12.1	11.2	10.9	10.2	10.1	9.2	8.9	8.4	8.4	8.2
80,0°	13.3	14.0	15.2	15.3	14.3	12.8	12.1	10.7	9.7	9.2	8.7	8.5	7.8	7.3	7.0	7.0	7.0
81,0°	10.6	10.6	11.4	12.1	11.6	10.7	10.7	9.0	8.0	7.5	7.0	7.0	6.3	6.0	5.6	5.6	5.6
82,0°	8.5	8.2	8.2	9.0	9.0	8.9	8.2	7.2	6.6	6.3	5.6	5.5	4.9	4.8	4.4	4.4	4.3
83,0°	6.5	6.3	6.0	6.5	6.6	6.6	5.8	5.5	5.1	4.8	4.3	4.1	3.7	3.6	3.4	3.2	3.1
84,0°	4.8	4.4	4.3	4.3	4.3	4.4	3.9	3.9	3.6	3.2	2.9	2.7	2.6	2.6	2.4	2.2	2.0
85,0°	3.2	3.2	2.9	2.9	2.7	2.7	2.6	2.6	2.4	2.0	1.9	1.9	1.7	1.7	1.5	1.4	1.2
86,0°	2.0	2.0	1.9	1.9	1.7	1.7	1.5	1.5	1.4	1.2	1.0	1.2	0.9	0.9	0.9	0.9	0.7
87,0°	1.4	1.4	1.2	1.2	1.0	1.0	0.9	0.9	0.7	0.7	0.5	0.5	0.5	0.5	0.3	0.3	0.3
88,0°	0.9	0.9	0.9	0.9	0.7	0.7	0.7	0.5	0.5	0.5	0.3	0.3	0.3	0.3	0.3	0.3	0.3
89,0°	0.7	0.7	0.7	0.7	0.7	0.5	0.5	0.3	0.3	0.3	0.3	0.3	0.2	0.2	0.2	0.2	0.2
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Photometric test report

Family
Streetlight 21 mini LED

Order number: 5XE2F43S08HB
EAN: 4058352725771

LP number
59110_280

siteco

C- planes	170,0°	172,5°	175,0°	177,5°	180,0°	182,5°	185,0°	187,5°	190,0°	192,5°	195,0°	197,5°	200,0°	202,5°	205,0°	207,5°	210,0°
γ	Luminous intensity in cd/klm																
74,0°	16.0	15.7	15.7	15.2	14.8	14.5	14.5	14.1	14.5	14.5	15.2	15.3	15.8	16.4	17.0	17.0	17.9
75,0°	14.0	13.6	13.6	13.1	13.0	12.6	12.6	12.3	12.4	12.6	13.1	13.3	13.8	14.3	14.8	14.8	15.8
76,0°	11.9	11.8	11.8	11.4	11.2	10.9	10.9	10.6	10.7	10.7	11.2	11.4	11.9	12.3	12.8	12.8	14.0
77,0°	10.6	10.4	10.2	10.1	9.7	9.5	9.5	9.2	9.4	9.4	9.7	9.9	10.2	10.6	10.9	11.1	12.3
78,0°	9.2	9.0	9.2	8.9	8.7	8.5	8.5	8.0	8.2	8.0	8.4	8.2	8.9	8.9	9.2	9.4	10.6
79,0°	8.2	8.0	8.4	8.0	7.8	7.7	7.5	7.2	7.0	6.8	7.0	7.0	7.2	7.3	7.7	8.0	9.0
80,0°	7.2	6.8	7.0	6.5	6.3	6.1	6.3	6.0	6.1	5.8	5.8	5.8	6.0	6.1	6.5	6.6	7.5
81,0°	5.6	5.5	5.3	4.9	4.8	4.6	4.8	4.6	4.6	4.6	4.6	4.6	4.8	4.9	5.3	5.5	6.1
82,0°	4.4	4.1	3.9	3.7	3.6	3.6	3.6	3.6	3.4	3.4	3.6	3.7	3.7	3.9	4.3	4.4	4.9
83,0°	3.2	3.1	2.9	2.7	2.6	2.6	2.6	2.6	2.6	2.6	2.7	2.7	2.9	3.1	3.2	3.4	3.7
84,0°	2.0	2.0	2.0	1.7	1.7	1.7	1.7	1.5	1.7	1.7	1.9	1.9	2.0	2.0	2.2	2.4	2.6
85,0°	1.2	1.2	1.2	1.0	1.0	1.0	1.0	1.0	1.2	1.2	1.2	1.2	1.4	1.4	1.5	1.5	1.7
86,0°	0.7	0.7	0.7	0.5	0.5	0.5	0.7	0.7	0.7	0.7	0.7	0.7	0.9	0.9	0.9	0.9	1.0
87,0°	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.5	0.3	0.5	0.5	0.5	0.5	0.5
88,0°	0.3	0.3	0.2	0.2	0.2	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3
89,0°	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Photometric test report

Family
Streetlight 21 mini LED

Order number: 5XE2F43S08HB
EAN: 4058352725771

LP number
59110_280


C- planes	212,5°	215,0°	217,5°	220,0°	222,5°	225,0°	227,5°	230,0°	232,5°	235,0°	237,5°	240,0°	242,5°	245,0°	247,5°	250,0°	252,5°
γ	Luminous intensity in cd/klm																
74,0°	19.3	19.9	20.6	22.8	25.7	28.5	31.4	36.0	39.7	47.0	57.8	61.3	68.7	95.3	138.5	198.2	237.4
75,0°	17.2	17.9	18.2	19.9	22.2	24.7	26.6	27.6	29.3	34.1	45.3	51.8	57.1	77.2	110.8	158.0	188.1
76,0°	15.0	15.7	16.0	17.4	18.7	20.8	22.5	23.3	24.7	27.8	31.9	39.9	44.0	57.4	79.9	118.1	142.6
77,0°	13.1	13.8	14.1	15.3	16.2	17.6	19.1	19.9	20.6	23.0	25.4	29.3	34.6	45.2	61.3	89.6	112.0
78,0°	11.4	12.1	12.3	13.6	14.0	14.7	15.7	16.7	16.7	18.6	20.1	23.7	26.8	34.9	44.8	68.5	79.9
79,0°	9.9	10.4	10.7	11.6	11.9	12.1	12.8	13.3	13.5	14.7	15.8	17.9	20.4	25.6	33.2	46.4	54.2
80,0°	8.4	9.0	9.2	9.7	10.2	9.9	10.4	10.6	10.7	11.4	12.3	13.8	15.7	18.9	23.3	30.5	36.3
81,0°	7.0	7.3	7.5	7.8	8.0	7.7	7.8	8.0	8.0	8.5	9.0	10.2	11.4	13.5	15.8	20.1	20.8
82,0°	5.6	5.8	6.0	6.1	6.0	5.8	6.0	6.0	6.0	6.3	6.6	7.5	8.2	9.4	10.6	11.8	11.8
83,0°	4.1	4.4	4.4	4.4	4.3	4.3	4.3	4.4	4.4	4.6	4.8	5.3	5.6	6.3	6.6	7.2	7.0
84,0°	2.7	2.9	2.9	3.1	2.9	2.9	2.9	2.9	2.9	3.1	3.2	3.4	3.6	3.7	3.7	3.9	4.1
85,0°	1.7	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	2.0	2.0	2.2	2.2	2.4	2.4	2.6	2.4
86,0°	0.9	1.0	1.0	1.2	1.0	1.2	1.2	1.2	1.2	1.4	1.2	1.4	1.4	1.5	1.4	1.5	1.5
87,0°	0.5	0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.9	0.9	0.9	0.9	1.0	1.0	1.0	1.0
88,0°	0.5	0.3	0.5	0.5	0.5	0.5	0.5	0.5	0.7	0.7	0.7	0.7	0.9	0.9	0.9	0.9	1.0
89,0°	0.3	0.3	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.7	0.7	0.7	0.7	0.9	0.9
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Photometric test report

Family
Streetlight 21 mini LED

Order number: 5XE2F43S08HB
EAN: 4058352725771

LP number
59110_280

siteco

C- planes	255,0°	257,5°	260,0°	262,5°	265,0°	267,5°	270,0°	272,5°	275,0°	277,5°	280,0°	282,5°	285,0°	287,5°	290,0°	292,5°	295,0°
γ	Luminous intensity in cd/klm																
74,0°	265.2	273.7	272.8	245.6	227.0	205.2	187.4	153.0	120.5	89.1	71.7	58.3	52.7	47.4	44.5	41.6	39.9
75,0°	210.5	217.8	221.2	206.2	187.1	174.3	158.1	127.1	97.6	71.6	56.2	46.7	43.3	40.0	39.0	36.8	35.8
76,0°	163.1	166.1	169.2	152.7	140.8	130.0	119.1	93.0	70.7	51.6	42.4	35.8	34.9	33.2	33.2	31.4	30.7
77,0°	125.3	126.8	123.0	110.6	103.4	93.4	87.4	65.9	50.6	37.1	31.5	27.8	27.6	27.8	28.1	26.2	24.9
78,0°	91.9	82.6	82.6	70.4	65.3	57.6	55.6	38.5	30.8	22.8	21.8	19.4	21.8	22.3	23.3	21.0	20.1
79,0°	56.6	46.0	40.9	32.4	26.9	25.2	23.0	16.0	14.0	12.8	13.0	13.3	15.5	17.4	18.4	17.4	15.5
80,0°	34.3	28.5	25.2	19.1	15.2	12.3	12.1	9.9	8.9	8.7	9.4	9.7	11.6	13.8	14.5	14.1	12.4
81,0°	19.8	16.9	14.0	10.6	9.2	6.5	7.0	5.8	6.0	6.1	6.5	7.0	8.4	9.9	10.7	10.2	9.5
82,0°	11.1	9.5	8.4	6.3	5.8	4.3	4.4	4.1	4.4	4.4	4.9	5.3	6.1	6.8	7.5	7.3	7.2
83,0°	7.0	6.1	5.3	4.4	3.7	3.1	2.6	3.2	3.4	3.6	3.9	4.1	4.4	4.8	5.1	5.1	5.3
84,0°	4.1	3.7	3.2	3.1	2.6	2.4	1.9	2.6	2.6	2.7	2.9	3.1	3.2	3.2	3.4	3.2	3.2
85,0°	2.6	2.2	2.2	2.0	2.0	1.9	1.5	2.0	2.0	2.0	2.2	2.4	2.4	2.4	2.4	2.2	2.4
86,0°	1.5	1.4	1.5	1.4	1.5	1.4	1.4	1.5	1.5	1.5	1.7	1.7	1.7	1.7	1.7	1.7	1.7
87,0°	1.0	1.0	1.2	1.2	1.2	1.2	1.2	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.2	1.2
88,0°	1.0	1.0	1.0	1.0	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
89,0°	0.9	0.9	1.0	1.0	1.0	1.0	1.0	1.2	1.2	1.2	1.2	1.0	1.2	1.0	1.0	1.0	1.0
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Photometric test report

Family Streetlight 21 mini LED	Order number: 5XE2F43S08HB EAN: 4058352725771	LP number 59110_280 
---	--	---

C- planes	297,5°	300,0°	302,5°	305,0°	307,5°	310,0°	312,5°	315,0°	317,5°	320,0°	322,5°	325,0°	327,5°	330,0°	332,5°	335,0°	337,5°
γ	Luminous intensity in cd/klm																
74,0°	36.1	31.7	27.6	25.1	23.7	23.0	21.6	21.0	20.6	21.0	20.8	20.3	19.3	19.9	21.1	22.3	21.0
75,0°	32.5	28.8	25.2	22.8	21.5	21.0	19.8	19.3	18.6	18.9	18.9	18.4	17.2	17.7	18.6	19.8	18.7
76,0°	28.3	25.2	22.0	20.1	18.9	18.6	17.6	17.0	16.4	16.7	16.7	16.4	15.0	15.3	16.0	16.9	16.0
77,0°	23.9	21.3	19.1	17.2	16.2	16.2	15.3	15.0	14.5	14.8	14.8	14.5	13.3	13.1	13.6	14.3	13.5
78,0°	18.7	17.7	15.5	14.5	13.3	13.6	13.0	12.8	12.3	12.8	12.6	12.6	11.4	11.1	11.1	11.9	11.2
79,0°	14.7	13.8	12.3	11.4	10.7	11.1	10.6	10.4	10.2	10.6	10.7	10.6	9.7	9.2	9.2	9.5	9.4
80,0°	11.4	10.4	9.4	8.9	8.4	8.5	8.4	8.4	8.4	8.7	9.0	9.0	8.2	7.7	7.5	7.7	7.5
81,0°	8.9	8.0	7.2	6.6	6.3	6.5	6.3	6.3	6.3	6.6	7.0	7.0	6.5	6.1	6.0	5.6	5.5
82,0°	6.6	6.1	5.5	5.1	4.8	4.8	4.8	4.8	4.8	4.9	5.1	5.3	5.1	4.9	4.6	4.3	3.7
83,0°	4.8	4.4	4.1	3.7	3.6	3.6	3.6	3.6	3.4	3.6	3.6	3.7	3.7	3.7	3.4	3.2	2.7
84,0°	3.1	3.1	2.9	2.7	2.6	2.6	2.4	2.4	2.4	2.4	2.2	2.4	2.4	2.4	2.2	2.2	1.9
85,0°	2.2	2.2	2.0	1.9	1.9	1.9	1.7	1.7	1.5	1.5	1.5	1.5	1.5	1.5	1.4	1.4	1.2
86,0°	1.5	1.5	1.4	1.4	1.4	1.4	1.2	1.2	1.0	1.0	1.0	1.0	0.9	0.9	0.7	0.7	0.7
87,0°	1.2	1.2	1.2	1.0	1.0	1.0	0.9	0.9	0.9	0.9	0.7	0.7	0.7	0.7	0.5	0.5	0.5
88,0°	1.0	1.0	1.0	1.0	1.0	0.9	0.9	0.9	0.9	0.7	0.7	0.7	0.7	0.5	0.5	0.5	0.3
89,0°	1.0	1.0	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.7	0.7	0.7	0.7	0.5	0.5	0.5	0.3
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

C- planes	340,0°	342,5°	345,0°	347,5°	350,0°	352,5°	355,0°	357,5°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm								Luminous flux in lm/klm	
74,0°	18.9	17.2	16.5	15.8	15.7	15.7	16.0	16.2	7.5	974.2
75,0°	17.2	15.5	14.8	14.1	14.1	14.1	14.3	14.3	6.3	980.5
76,0°	15.2	13.8	13.0	12.3	12.3	12.3	12.6	12.4	5.0	985.5
77,0°	13.0	12.1	11.4	10.7	10.7	10.7	11.1	10.9	3.9	989.3
78,0°	10.9	10.1	9.7	9.0	9.2	9.0	9.5	9.2	2.9	992.2
79,0°	9.0	8.5	8.2	7.7	7.7	7.7	8.0	7.8	2.1	994.3
80,0°	7.2	6.6	6.6	6.1	6.1	6.1	6.6	6.5	1.6	995.9
81,0°	5.3	4.8	4.9	4.6	4.8	4.8	4.9	4.9	1.3	997.2
82,0°	3.6	3.6	3.4	3.4	4.1	4.1	4.3	4.3	0.9	998.1
83,0°	2.6	2.6	2.6	2.2	2.7	2.7	2.7	2.7	0.7	998.8
84,0°	1.7	1.7	1.7	1.4	1.5	1.5	1.5	1.4	0.5	999.3
85,0°	1.0	1.0	1.0	0.9	0.9	0.9	0.9	0.9	0.3	999.6
86,0°	0.7	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.2	999.7
87,0°	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.1	999.9
88,0°	0.3	0.3	0.3	0.3	0.3	0.2	0.2	0.2	0.1	999.9
89,0°	0.3	0.3	0.3	0.3	0.3	0.2	0.2	0.2	0.1	1000.0
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Streetlight 21 mini LED	Order number: 5XE2F43S08HB EAN: 4058352725771	LP number 59110_280
Dimming levels table		environmental temperature: 25°C
		siteco

Luminous flux [%]	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]start of lifetime	Power consumption [W]end of lifetime	Power consumption [W]average
100	254	254	8590	66.0	68.9	67.4
95	238	252	8160	61.7	64.5	63.1
90	223	249	7740	57.8	60.3	59.0
85	208	247	7305	53.8	56.3	55.0
80	193	244	6863	50.0	52.2	51.1
75	179	241	6433	46.4	48.4	47.4
70	165	238	5997	42.9	44.6	43.8
65	152	235	5583	39.6	41.2	40.4
60	139	232	5162	36.2	37.8	37.0
55	126	228	4729	33.0	34.4	33.7
50	113	224	4288	29.8	31.0	30.4
45	101	220	3872	26.8	27.9	27.4
40	89	216	3447	23.9	24.8	24.4
35	77	210	3013	20.9	21.8	21.4
30	65	204	2571	18.0	18.7	18.4
25	54	197	2160	15.3	15.8	15.6
20	42	188	1703	12.4	12.8	12.6
16	34	180	1393	10.5	10.8	10.6

Dimming levels table	environmental temperature: 5°C
----------------------	--------------------------------

Luminous flux [%]	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]start of lifetime	Power consumption [W]end of lifetime	Power consumption [W]average
100	254	254	8820	66.8	69.7	68.2
95	238	252	8366	62.5	65.3	63.9
90	223	249	7926	58.6	61.1	59.8
85	209	247	7502	54.8	57.3	56.0
80	194	244	7041	50.9	53.2	52.0
75	181	242	6629	47.5	49.6	48.6
70	167	239	6181	43.9	45.8	44.8
65	153	235	5722	40.3	42.1	41.2
60	140	232	5288	37.0	38.6	37.8
55	127	229	4844	33.8	35.2	34.5
50	115	225	4427	30.7	32.0	31.4
45	102	221	3968	27.5	28.6	28.0
40	90	216	3535	24.4	25.4	24.9
35	78	211	3093	21.5	22.3	21.9
30	66	205	2644	18.5	19.2	18.8
25	54	197	2188	15.5	16.1	15.8
20	43	189	1762	12.8	13.3	13.0
16	34	180	1409	10.7	11.0	10.8

Photometric test report

Family Streetlight 21 mini LED	Order number: 5XE2F43S08HB EAN: 4058352725771	LP number 59110_280
Dimming levels table		environmental temperature: 15°C
		sITeco

Luminous flux [%]	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]start of lifetime	Power consumption [W]end of lifetime	Power consumption [W]average
100	254	254	8720	66.4	69.3	67.8
95	238	252	8277	62.1	64.9	63.5
90	223	249	7846	58.2	60.7	59.4
85	208	247	7401	54.2	56.6	55.4
80	194	244	6978	50.6	52.8	51.7
75	180	241	6541	46.9	49.1	48.0
70	166	238	6099	43.3	45.2	44.2
65	153	235	5677	40.0	41.8	40.9
60	139	232	5216	36.5	38.1	37.3
55	127	229	4811	33.5	34.9	34.2
50	114	225	4363	30.3	31.5	30.9
45	101	220	3908	27.0	28.1	27.6
40	89	216	3478	24.0	24.9	24.4
35	77	210	3039	21.1	21.9	21.5
30	66	205	2630	18.4	19.1	18.8
25	54	197	2177	15.4	15.9	15.6
20	43	189	1754	12.7	13.2	13.0
16	34	180	1404	10.6	10.9	10.8

Photometric test report

Family Streetlight 21 mini LED	Order number: 5XE2F43S08HB EAN: 4058352725771	LP number 59110_280
Luminousfluxs table		siteco

Temperature °C	Luminous flux lm	Power consumption W
25.0	8590.0	66.0
5.0	8820.0	66.8
15.0	8720.0	66.4