

Photometric test report

Family
MUSHROOM LUMINAIRE LED

Order number: **5XA5235OF14H**
EAN: **4058352833339**

LP number
57120_32



Version post-top- or mounting to wall arm
Optic direct, symmetric wide distribution
C120005
Cover cover transparent, PMMA
Lamps LED 2700 K | CRI ≥ 70
Controlgear ECG SITECO iQ
Rated values Net luminous flux = 3000 lm
Power consumption = 21.8 W
Luminous efficacy = 137.6 lm/W

serial
documentation
24.02.2023

siteco

Luminous intensity in cd/klm


C180-0

C205-25

C210-30

C270-90

Imax: 401 cd/klm



Luminaire output ratios

Eta	100.0%
Eta 0° - 90°	97.4%
Eta 90° - 180°	2.6%

Luminous intensity class acc. to EN13201-2

Class:	G3
Imax 70°	366.2
Imax 80°	92.9
Imax 90°	11.9
Imax >90°	9.1
Imax >95°	8.3

Measurement conditions


DIN EN 13032 and DIN 5032

Photometric test report

Family MUSHROOM LUMINAIRE LED	Order number: 5XA5235OF14H EAN: 4058352833339	LP number 57120_32
--	--	-------------------------------------



Envelope curve in cd/klm **KMK 67.5°** **KMK 65°** **KMK 62.5°** **KMK 60°**



Photometric test report

Family MUSHROOM LUMINAIRE LED	Order number: 5XA5235OF14H EAN: 4058352833339	LP number 57120_32
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes	0° 180°	5°	10°	15°	20°	25°	30°	35°	40°	45°
		175° 185° 355°	170° 190° 350°	165° 195° 345°	160° 200° 340°	155° 205° 335°	150° 210° 330°	145° 215° 325°	140° 220° 320°	135° 225° 315°
Luminous intensity in cd/klm										
γ										
0,0°	26.9	26.9	26.9	26.9	26.9	26.9	26.9	26.9	26.9	26.9
2,5°	25.3	25.6	25.8	26.2	26.0	26.9	27.3	27.9	27.7	27.3
5,0°	37.9	38.2	38.8	38.6	38.4	37.9	37.7	38.1	38.5	39.5
7,5°	51.8	52.3	51.0	52.1	51.5	48.7	46.8	47.4	49.0	51.3
10,0°	62.2	62.3	63.7	66.4	69.8	70.7	71.1	72.3	71.6	70.4
12,5°	90.5	92.6	93.4	89.7	87.2	83.2	84.2	84.5	90.4	89.8
15,0°	89.9	101.2	103.2	104.3	102.5	112.4	120.5	115.8	118.4	112.5
17,5°	127.6	123.7	127.0	134.8	131.7	131.9	128.3	131.6	129.4	126.6
20,0°	152.3	150.9	149.7	151.7	149.4	141.9	131.8	124.5	123.8	118.1
22,5°	157.1	159.1	165.3	157.6	153.3	143.3	135.4	132.5	123.5	117.1
25,0°	159.6	152.0	158.6	149.9	152.2	149.3	145.8	138.6	124.4	115.9
27,5°	178.8	161.8	157.1	153.6	155.0	159.9	151.1	153.9	145.0	134.0
30,0°	204.8	179.3	197.8	179.9	169.4	163.8	148.3	140.2	142.5	147.0
32,5°	165.9	178.7	174.4	172.2	171.4	170.9	162.7	151.6	157.3	167.3
35,0°	208.5	216.0	210.4	200.0	189.3	181.9	174.8	164.6	163.3	167.0
37,5°	213.6	228.3	227.6	211.3	197.8	179.6	168.8	175.4	184.3	181.1
40,0°	226.9	244.3	235.1	220.1	211.0	196.5	180.1	184.7	195.4	201.2
42,5°	263.7	257.2	241.8	224.5	218.5	204.2	201.0	202.5	202.3	213.0
45,0°	273.3	272.5	263.5	241.7	228.7	203.3	205.7	220.2	223.9	220.2
47,5°	291.7	278.8	285.2	269.3	241.6	213.8	221.0	234.9	240.5	232.4
50,0°	297.4	298.3	308.8	291.1	266.5	227.9	254.7	255.7	245.8	234.4
52,5°	299.4	301.4	302.0	303.9	288.6	262.6	278.2	278.6	253.3	235.0
55,0°	303.7	321.4	318.2	320.1	319.5	300.0	300.6	291.2	265.1	239.5
57,5°	306.8	324.5	322.7	332.5	354.6	336.5	323.0	298.1	275.3	240.9
60,0°	282.7	302.4	321.1	334.7	380.0	365.2	332.2	312.2	286.8	239.2
62,5°	237.7	256.0	291.9	322.4	373.9	374.9	339.8	324.2	294.4	236.4
65,0°	189.6	221.3	257.9	273.5	341.5	393.8	366.4	334.5	288.2	235.8
67,5°	173.9	215.5	249.4	259.4	323.3	400.9	371.4	312.7	287.1	221.8
70,0°	196.1	224.3	258.1	273.0	300.6	366.2	344.0	295.3	256.8	203.8
72,5°	219.3	229.0	241.0	253.7	292.9	327.7	316.6	262.8	205.3	169.2
75,0°	175.7	183.5	207.7	221.0	264.4	272.0	262.5	196.3	145.4	124.9
77,5°	144.3	133.9	140.2	155.5	169.5	163.4	152.2	115.3	98.5	91.1
80,0°	74.0	69.8	74.4	92.9	86.6	85.0	91.9	83.7	74.9	58.4
82,5°	43.2	40.8	43.5	58.4	48.2	45.5	56.7	64.9	56.7	42.4
85,0°	20.8	21.1	22.9	28.4	27.5	30.8	37.8	41.7	33.1	27.9
87,5°	11.2	11.4	12.0	13.5	15.5	16.5	16.6	18.0	19.3	17.8
90,0°	10.0	10.2	10.5	11.2	11.4	11.7	11.9	11.8	11.2	10.8
92,5°	8.8	9.0	9.1	9.1	9.0	9.0	9.0	8.9	8.7	8.6
95,0°	8.6	8.6	8.7	8.5	8.4	8.3	8.2	7.9	7.9	7.7
97,5°	7.9	8.2	8.3	8.1	7.9	7.9	7.8	7.6	7.5	7.4
100,0°	7.5	7.7	7.8	7.8	7.7	7.5	7.5	7.3	7.1	7.0
102,5°	7.1	7.4	7.4	7.4	7.3	7.1	7.1	7.0	6.8	6.6
105,0°	6.9	7.0	7.1	7.0	7.0	6.7	6.7	6.7	6.6	6.4
107,5°	6.5	6.6	6.8	6.6	6.6	6.6	6.5	6.3	6.2	6.2
110,0°	6.1	6.2	6.4	6.3	6.2	6.2	6.1	6.0	6.0	5.8

Photometric test report

Family MUSHROOM LUMINAIRE LED	Order number: 5XA5235OF14H EAN: 4058352833339	LP number 57120_32
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes γ	50°	55°	60°	65°	70°	75°	80°	85°	90°	Phi-zone	Total Phi-zone
	130° 230° 310°	125° 235° 305°	120° 240° 300°	115° 245° 295°	110° 250° 290°	105° 255° 285°	100° 260° 280°	95° 265° 275°			
Luminous intensity in cd/klm										Luminous flux in lm/klm	
0,0°	26.9	26.9	26.9	26.9	26.9	26.9	26.9	26.9	26.9	0.0	0.0
2,5°	27.2	27.6	27.8	27.7	28.4	29.5	28.6	27.8	27.7	0.3	0.4
5,0°	39.8	39.9	39.6	38.9	38.2	38.0	38.8	39.0	38.9	0.9	1.3
7,5°	55.9	57.1	58.1	55.1	53.8	53.1	52.9	53.0	51.2	1.9	3.2
10,0°	73.9	76.7	75.5	73.7	74.5	78.6	78.8	79.3	80.1	3.4	6.6
12,5°	91.8	95.2	93.6	89.1	88.9	90.9	93.7	95.6	95.8	5.4	12.0
15,0°	110.2	111.7	111.4	110.5	112.7	113.0	114.0	116.4	119.6	7.9	19.8
17,5°	122.6	119.6	121.1	120.0	125.5	131.7	136.5	139.4	138.0	10.6	30.4
20,0°	115.9	123.3	126.3	127.9	130.4	133.5	135.8	138.9	142.9	12.6	43.0
22,5°	120.8	126.7	131.7	134.3	135.8	139.7	144.3	146.7	145.7	14.7	57.7
25,0°	118.2	126.4	133.8	136.7	142.4	147.9	155.0	156.7	158.0	16.5	74.2
27,5°	129.8	129.5	140.9	144.7	147.0	149.0	152.3	154.5	156.1	18.9	93.1
30,0°	143.0	138.9	147.5	155.7	158.4	155.7	154.3	151.6	149.6	21.7	114.8
32,5°	166.8	162.8	160.6	165.8	165.6	158.5	157.5	159.3	158.8	24.3	139.1
35,0°	176.3	179.8	169.7	170.4	173.7	166.1	163.6	164.8	164.5	28.1	167.2
37,5°	183.4	194.4	187.2	181.6	178.8	168.5	166.4	168.2	168.2	31.3	198.5
40,0°	197.3	201.4	199.4	186.8	180.6	169.6	169.0	171.0	172.0	34.7	233.1
42,5°	212.1	207.6	206.6	194.1	181.0	171.8	172.2	174.6	176.1	38.1	271.3
45,0°	221.4	214.9	209.3	200.7	182.3	174.5	175.2	177.6	178.3	41.6	312.8
47,5°	228.2	222.4	212.0	201.2	181.3	175.8	176.0	177.8	178.6	45.2	358.1
50,0°	234.0	226.2	212.4	198.2	178.7	176.1	176.8	179.6	180.4	49.0	407.1
52,5°	235.9	230.6	212.6	190.0	173.6	173.4	176.5	180.7	181.0	52.2	459.3
55,0°	236.2	230.0	205.0	178.3	162.6	164.2	169.8	176.7	178.8	55.4	514.7
57,5°	229.9	223.0	194.8	163.2	148.3	149.5	156.3	163.6	167.5	57.5	572.1
60,0°	217.8	206.6	177.8	147.2	131.5	127.4	135.3	144.9	148.2	57.7	629.9
62,5°	208.1	192.1	160.8	127.2	111.3	107.0	110.0	118.1	123.7	55.8	685.6
65,0°	199.0	176.2	143.7	107.6	89.5	85.7	85.6	89.9	91.1	52.9	738.5
67,5°	182.2	162.0	124.6	89.2	68.4	62.3	61.9	62.3	61.4	50.3	788.8
70,0°	165.3	144.3	105.8	74.7	53.5	41.7	40.9	41.5	41.6	47.4	836.1
72,5°	138.3	119.1	87.5	57.9	42.2	29.5	27.2	26.5	27.3	42.8	879.0
75,0°	117.2	105.9	77.5	45.1	27.8	22.5	20.3	19.7	19.6	35.5	914.4
77,5°	92.7	91.2	66.1	33.4	19.5	17.3	16.3	16.0	15.7	24.6	939.0
80,0°	50.5	51.2	34.1	17.1	14.0	13.2	13.1	13.0	12.8	14.5	953.5
82,5°	33.2	24.3	18.0	12.2	11.3	10.9	10.8	10.7	10.8	9.3	962.8
85,0°	21.8	17.1	14.0	10.6	9.8	9.5	9.3	9.1	9.0	5.9	968.7
87,5°	15.0	12.1	10.5	9.3	8.9	8.7	8.3	8.1	7.7	3.5	972.2
90,0°	10.2	9.8	9.0	8.6	8.3	7.8	7.4	7.3	7.3	2.7	974.9
92,5°	8.5	8.3	8.3	8.1	7.9	7.4	7.1	6.9	6.9	2.3	977.2
95,0°	7.5	7.5	7.1	7.0	6.8	6.6	6.6	6.5	6.5	2.1	979.3
97,5°	7.1	7.0	6.8	6.6	6.6	6.4	6.3	6.3	6.3	2.0	981.3
100,0°	6.7	6.7	6.6	6.4	6.2	6.2	6.1	6.1	6.1	1.9	983.1
102,5°	6.6	6.5	6.2	6.2	6.0	5.9	5.9	5.8	5.7	1.8	984.9
105,0°	6.2	6.2	6.1	5.8	5.8	5.8	5.7	5.6	5.5	1.7	986.6
107,5°	6.0	5.8	5.8	5.8	5.5	5.5	5.5	5.4	5.1	1.6	988.2
110,0°	5.7	5.7	5.6	5.5	5.5	5.4	5.3	5.2	4.7	1.5	989.7

Photometric test report

Family MUSHROOM LUMINAIRE LED	Order number: 5XA5235OF14H EAN: 4058352833339	LP number 57120_32
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes	0° 180°	5°	10°	15°	20°	25°	30°	35°	40°	45°
		175° 185° 355°	170° 190° 350°	165° 195° 345°	160° 200° 340°	155° 205° 335°	150° 210° 330°	145° 215° 325°	140° 220° 320°	135° 225° 315°
γ		Luminous intensity in cd/klm								
112,5°	5.7	6.0	6.0	6.1	5.9	5.8	5.7	5.7	5.7	5.6
115,0°	5.5	5.6	5.7	5.7	5.7	5.7	5.6	5.4	5.4	5.3
117,5°	5.1	5.3	5.3	5.3	5.3	5.3	5.3	5.1	5.1	5.0
120,0°	5.5	5.0	4.9	5.1	5.2	5.0	4.9	4.9	4.9	4.9
122,5°	4.7	4.7	4.9	4.8	4.8	4.8	4.7	4.8	4.6	4.5
125,0°	4.3	4.3	4.4	4.4	4.3	4.3	4.3	4.3	4.2	4.3
127,5°	3.7	3.7	3.7	3.7	3.8	3.7	3.7	3.7	3.6	3.7
130,0°	3.3	2.9	2.9	3.1	3.1	3.0	3.0	2.9	2.9	2.9
132,5°	2.4	2.3	2.3	2.2	2.2	2.2	2.2	2.2	2.3	2.2
135,0°	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	1.9
137,5°	2.0	1.9	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.8
140,0°	1.6	1.6	1.6	1.5	1.6	1.5	1.6	1.6	1.5	1.5
142,5°	1.4	1.5	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4
145,0°	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
147,5°	1.0	1.1	1.1	1.0	1.0	1.0	1.0	1.0	0.9	1.0
150,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

C-planes	50°	55°	60°	65°	70°	75°	80°	85°	90° 270°	Phi-zone	Total Phi-zone
	130° 230° 310°	125° 235° 305°	120° 240° 300°	115° 245° 295°	110° 250° 290°	105° 255° 285°	100° 260° 280°	95° 265° 275°			
γ		Luminous intensity in cd/klm								Luminous flux in lm/klm	
112,5°	5.6	5.5	5.4	5.3	5.2	5.2	5.1	5.0	4.1	1.4	991.1
115,0°	5.3	5.3	5.1	5.1	5.1	5.0	5.0	4.4	2.9	1.3	992.4
117,5°	5.0	4.9	4.9	4.9	4.8	4.9	4.8	4.0	2.4	1.2	993.6
120,0°	4.9	4.9	4.8	4.7	4.7	4.6	4.6	3.5	2.0	1.1	994.7
122,5°	4.5	4.5	4.5	4.5	4.5	4.5	4.4	3.2	2.0	1.0	995.8
125,0°	4.1	4.1	4.1	4.1	4.1	4.1	4.1	2.9	1.8	0.9	996.7
127,5°	3.7	3.6	3.6	3.5	3.6	3.6	3.3	2.4	1.6	0.8	997.5
130,0°	2.9	2.9	2.8	2.8	2.9	2.9	2.7	2.0	1.6	0.6	998.0
132,5°	2.2	2.2	2.2	2.2	2.2	2.2	2.0	1.6	1.4	0.4	998.5
135,0°	2.0	2.0	2.0	2.0	2.0	2.0	1.8	1.6	1.4	0.4	998.9
137,5°	1.7	1.8	1.6	1.6	1.6	1.6	1.6	1.4	1.2	0.3	999.2
140,0°	1.5	1.5	1.6	1.5	1.6	1.6	1.5	1.2	1.2	0.3	999.5
142,5°	1.3	1.3	1.2	1.3	1.2	1.2	1.2	1.2	1.2	0.2	999.7
145,0°	1.2	1.1	1.1	1.2	1.2	1.2	1.2	1.0	1.2	0.2	999.9
147,5°	0.9	1.0	0.9	1.0	1.1	1.0	1.0	1.0	1.0	0.2	1000.0
150,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family MUSHROOM LUMINAIRE LED	Order number: 5XA5235OF14H EAN: 4058352833339	LP number 57120_32
--	--	-------------------------------------

Dimming levels table	environmental temperature: 25°C	sITeco
-----------------------------	---------------------------------	---------------

Luminous flux [%]	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]start of lifetime	Power consumption [W]end of lifetime	Power consumption [W]average
100	254	254	3000	21.8	23.2	22.5
95	241	252	2846	20.6	21.9	21.2
90	229	250	2705	19.4	20.7	20.0
85	216	248	2551	18.3	19.4	18.8
80	203	246	2398	17.1	18.2	17.6
75	190	243	2244	15.9	16.9	16.4
70	178	241	2102	14.9	15.8	15.4
65	165	238	1949	13.8	14.7	14.2
60	152	235	1795	12.7	13.5	13.1
55	140	232	1654	11.7	12.4	12.0
50	127	229	1500	10.7	11.3	11.0
45	114	225	1346	9.6	10.1	9.8
40	102	221	1205	8.7	9.2	9.0
35	89	216	1051	7.7	8.1	7.9
30	76	210	898	6.8	7.1	7.0
25	63	203	744	5.8	6.1	5.9
20	51	195	602	5.0	5.2	5.1
15	39	185	461	4.0	4.3	4.2