



Photometric test report

Family DL® 50 mini LED	Order number: 5XA248V41F08LE EAN: 4058352803936	LP number 59397_25
	Version wire mounting Optic direct, symmetric wide distribution S080001 Cover toughened safety glass Lamps LED 4000 K CRI ≥ 70 Controlgear ECG SITECO iQ Rated values Net luminous flux = 10390 lm Power consumption = 64.1 W Luminous efficacy = 162.1 lm/W	serial documentation 03.04.2023



Luminous intensity in cd/klm
C180-0
C205-25
C210-30
C270-90
Imax: 466 cd/klm



Luminaire output ratios

Eta	100.0%
Eta 0° - 90°	100.0%
Eta 90° - 180°	0.0%

Luminous intensity class acc. to EN13201-2

Class:	G4
Imax 70°	442.5
Imax 80°	96.9
Imax 90°	0.0
Imax >90°	0.0
Imax >95°	0.0

Measurement conditions

DIN EN 13032 and DIN 5032


Photometric test report

Family
DL® 50 mini LED

Order number: 5XA248V41F08LE
EAN: 4058352803936

LP number
59397_25

Envelope curve in cd/klm **KMK 65°** **KMK 62,5°** **KMK 60°** **KMK 57,5°** **siteco**



Photometric test report

Family DL® 50 mini LED	Order number: 5XA248V41F08LE EAN: 4058352803936	LP number 59397_25
Table of values for luminous intensities		Maximum luminous intensity
siteco		

C-planes	0° 180°	5° 175°	10° 170°	15° 165°	20° 160°	25° 155°	30° 150°	35° 145°	40° 140°	45° 135°	50° 130°	55° 125°	60° 120°
γ	Luminous intensity in cd/klm												
0,0°	241.6	241.6	241.6	241.6	241.6	241.6	241.6	241.6	241.6	241.6	241.6	241.6	241.6
2,5°	241.2	241.1	240.8	242.5	241.9	241.7	242.2	243.7	244.6	244.6	245.9	244.8	246.3
5,0°	242.8	243.5	243.5	243.6	244.4	242.9	243.3	243.7	242.7	241.3	240.8	239.4	242.2
7,5°	238.1	241.5	243.8	244.8	248.4	246.0	245.9	244.9	245.5	244.8	241.7	245.5	246.9
10,0°	249.5	248.4	250.1	247.4	250.3	248.8	249.1	246.5	245.8	247.1	246.4	244.6	243.4
12,5°	252.1	255.3	255.2	253.1	253.2	253.6	253.2	254.8	257.0	257.2	252.3	246.4	244.3
15,0°	254.9	252.2	252.9	256.6	257.3	258.8	256.3	256.5	253.3	249.0	245.8	242.3	240.2
17,5°	256.6	254.4	257.8	262.8	262.4	261.5	260.8	252.4	248.2	245.7	244.3	234.9	234.4
20,0°	263.5	259.6	259.8	262.9	258.6	258.6	259.9	253.4	249.0	242.8	235.3	229.1	228.7
22,5°	259.6	265.4	266.3	270.8	266.6	259.3	254.2	252.9	248.2	240.5	232.0	228.8	222.0
25,0°	266.1	265.6	266.0	273.9	270.4	263.3	255.8	254.2	247.3	235.1	228.1	218.4	216.8
27,5°	272.3	270.3	274.3	276.4	274.1	268.4	257.4	249.0	240.3	236.6	223.0	218.7	218.2
30,0°	274.3	276.3	274.7	282.2	272.9	265.7	257.4	249.7	237.6	223.0	218.6	222.0	224.8
32,5°	279.1	285.8	282.4	280.8	281.9	267.8	258.2	247.3	233.5	226.8	228.8	232.6	233.7
35,0°	290.3	287.4	285.4	283.4	277.2	264.1	262.2	245.0	233.4	234.6	241.4	244.5	240.2
37,5°	294.9	294.0	287.3	285.9	280.9	267.1	257.6	245.8	242.3	249.7	256.4	254.6	247.1
40,0°	294.3	293.1	290.2	282.7	276.0	264.4	262.3	241.4	249.3	272.3	267.4	266.7	256.9
42,5°	296.2	293.5	290.6	284.0	276.9	270.4	252.9	247.0	267.5	290.3	283.1	270.2	258.2
45,0°	295.8	290.3	294.5	286.0	272.9	265.3	255.5	267.9	291.8	305.0	291.0	268.1	249.1
47,5°	295.0	292.6	292.3	282.5	272.5	269.0	263.4	291.0	314.5	315.2	288.5	252.7	225.7
50,0°	297.1	294.1	292.8	281.3	275.1	282.1	293.8	319.9	330.3	310.0	272.2	233.8	196.6
52,5°	304.1	305.1	291.7	276.2	281.1	312.1	328.9	347.0	330.8	289.8	246.6	198.1	157.6
55,0°	310.1	307.1	295.6	282.4	308.8	346.7	362.2	357.9	313.0	259.8	196.1	148.4	119.6
57,5°	318.6	313.3	295.2	291.2	351.0	393.0	390.4	359.4	276.7	189.0	135.9	100.1	78.7
60,0°	324.7	317.2	296.1	316.7	404.0	421.7	410.2	318.5	199.2	125.8	85.1	65.2	57.1
62,5°	324.4	319.8	306.1	358.3	437.3	452.6	381.6	231.6	126.1	79.6	56.8	48.4	45.3
65,0°	333.4	328.8	317.7	401.2	460.3	465.6	304.9	133.7	76.8	55.9	46.9	38.8	36.2
67,5°	373.8	358.7	357.8	443.3	463.4	378.1	169.4	74.3	53.7	46.6	40.0	32.3	30.7
70,0°	387.7	355.9	381.1	442.5	410.6	254.5	84.1	56.6	44.6	38.2	32.4	29.1	27.5
72,5°	352.6	313.3	374.2	387.2	312.4	127.0	60.6	45.2	34.7	31.0	27.0	22.4	21.2
75,0°	295.8	254.0	298.3	269.9	189.5	58.5	44.3	33.1	23.8	23.3	20.4	17.3	15.0
77,5°	213.1	166.1	166.9	135.4	86.6	37.0	26.6	19.3	16.2	16.9	14.8	13.2	12.8
80,0°	96.9	65.3	52.3	44.1	34.0	21.5	14.3	10.7	10.7	10.0	9.3	8.0	7.9
82,5°	18.6	14.2	11.4	7.8	7.3	5.9	4.4	4.3	4.9	5.0	4.9	4.0	4.1
85,0°	1.2	1.1	1.2	1.2	1.1	1.2	1.2	1.3	1.4	1.7	1.5	1.4	1.1
87,5°	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.2	0.2	0.2
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Photometric test report

Family DL® 50 mini LED	Order number: 5XA248V41F08LE EAN: 4058352803936	LP number 59397_25
Table of values for luminous intensities		Maximum luminous intensity
siteco		

C-planes	65° 115°	70° 110°	75° 105°	80° 100°	85° 95°	90°	185° 355°	190° 350°	195° 345°	200° 340°	205° 335°	210° 330°	215° 325°
γ	Luminous intensity in cd/klm												
0,0°	241.6	241.6	241.6	241.6	241.6	241.6	241.6	241.6	241.6	241.6	241.6	241.6	241.6
2,5°	245.8	247.0	246.8	247.4	246.5	248.2	241.1	240.8	242.5	241.9	241.7	242.2	243.7
5,0°	244.4	244.1	243.7	243.4	243.7	243.8	243.5	243.5	243.6	244.4	242.9	243.3	243.7
7,5°	246.6	247.7	246.9	245.7	247.0	245.5	241.5	243.8	244.8	248.4	246.0	245.9	244.9
10,0°	245.6	248.3	247.7	247.9	246.2	250.6	248.4	250.1	247.4	250.3	248.8	249.1	246.5
12,5°	243.9	244.4	242.6	238.4	240.2	240.7	255.3	255.2	253.1	253.2	253.6	253.2	254.8
15,0°	238.2	232.0	230.8	232.5	229.9	229.1	252.2	252.9	256.6	257.3	258.8	256.3	256.5
17,5°	231.3	225.1	223.8	224.2	226.4	225.9	254.4	257.8	262.8	262.4	261.5	260.8	252.4
20,0°	227.0	220.6	219.2	215.6	213.7	216.0	259.6	259.8	262.9	258.6	258.6	259.9	253.4
22,5°	218.8	212.2	207.8	207.9	206.6	202.9	265.4	266.3	270.8	266.6	259.3	254.2	252.9
25,0°	212.1	207.5	204.6	199.8	202.4	197.5	265.6	266.0	273.9	270.4	263.3	255.8	254.2
27,5°	211.2	212.3	210.7	211.8	207.1	205.8	270.3	274.3	276.4	274.1	268.4	257.4	249.0
30,0°	219.8	217.5	214.8	212.9	212.7	202.9	276.3	274.7	282.2	272.9	265.7	257.4	249.7
32,5°	229.5	224.0	219.5	217.8	213.2	217.3	285.8	282.4	280.8	281.9	267.8	258.2	247.3
35,0°	235.7	227.9	220.7	218.2	210.1	212.9	287.4	285.4	283.4	277.2	264.1	262.2	245.0
37,5°	237.8	229.2	218.5	211.9	208.8	199.7	294.0	287.3	285.9	280.9	267.1	257.6	245.8
40,0°	240.5	229.5	218.1	209.6	206.1	198.9	293.1	290.2	282.7	276.0	264.4	262.3	241.4
42,5°	238.5	224.4	210.4	205.3	196.4	189.0	293.5	290.6	284.0	276.9	270.4	252.9	247.0
45,0°	224.0	203.5	188.9	176.3	169.8	172.8	290.3	294.5	286.0	272.9	265.3	255.5	267.9
47,5°	198.1	177.6	164.7	153.5	143.3	143.4	292.6	292.3	282.5	272.5	269.0	263.4	291.0
50,0°	166.6	147.6	134.5	124.1	119.1	119.4	294.1	292.9	281.3	275.1	282.1	293.8	319.9
52,5°	132.7	117.0	103.6	95.9	88.3	87.7	305.1	291.7	276.2	281.1	312.1	328.9	347.0
55,0°	94.7	83.7	76.4	73.6	70.1	68.4	307.1	295.6	282.4	308.8	346.7	362.2	357.9
57,5°	64.8	61.9	61.2	58.4	60.1	61.8	313.3	295.2	291.2	351.0	393.0	390.4	359.4
60,0°	48.7	48.8	46.1	48.8	49.7	50.8	317.2	296.1	316.7	404.0	421.7	410.2	318.5
62,5°	41.2	40.9	40.8	41.7	41.1	39.0	319.8	306.1	358.3	437.3	452.6	381.6	231.6
65,0°	36.4	33.5	34.6	34.4	33.6	33.1	328.8	317.7	401.2	460.3	465.6	304.9	133.7
67,5°	32.2	30.0	28.9	29.5	27.9	27.6	358.7	357.8	443.3	463.4	378.1	169.4	74.3
70,0°	27.5	26.3	24.9	24.6	22.4	23.1	355.9	381.1	442.5	410.6	254.5	84.1	56.6
72,5°	20.6	20.3	19.8	18.7	18.1	17.2	313.3	374.2	387.2	312.4	127.0	60.6	45.2
75,0°	15.2	13.2	12.7	12.5	12.0	12.0	254.0	298.3	269.9	189.5	58.5	44.3	33.1
77,5°	11.0	8.8	7.7	7.4	7.1	7.0	166.1	166.9	135.4	86.6	37.0	26.6	19.3
80,0°	6.9	6.4	5.1	4.3	4.4	4.3	65.3	52.3	44.1	34.0	21.5	14.3	10.7
82,5°	3.5	3.5	2.6	2.3	2.1	2.1	14.2	11.4	7.8	7.3	5.9	4.4	4.3
85,0°	1.3	1.1	0.8	0.8	0.7	0.8	1.1	1.2	1.2	1.1	1.2	1.2	1.3
87,5°	0.2	0.2	0.2	0.1	0.1	0.1	0.3	0.3	0.3	0.3	0.3	0.3	0.3
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Photometric test report

Family DL® 50 mini LED	Order number: 5XA248V41F08LE EAN: 4058352803936	LP number 59397_25
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes	220° 320°	225° 315°	230° 310°	235° 305°	240° 300°	245° 295°	250° 290°	255° 285°	260° 280°	265° 275°	270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm											Luminous flux in lm/klm	
0,0°	241.6	241.6	241.6	241.6	241.6	241.6	241.6	241.6	241.6	241.6	241.6	0.4	0.4
2,5°	244.6	244.6	245.9	244.8	246.3	245.8	247.0	246.8	247.4	246.5	248.2	2.9	3.3
5,0°	242.7	241.3	240.8	239.4	242.2	244.4	244.1	243.7	243.4	243.7	243.8	5.8	9.1
7,5°	245.5	244.8	241.7	245.5	246.9	246.6	247.7	246.9	245.7	247.0	245.5	8.8	17.9
10,0°	245.8	247.1	246.4	244.6	243.4	245.6	248.3	247.7	247.9	246.2	250.6	11.8	29.6
12,5°	257.0	257.2	252.3	246.4	244.3	243.9	244.4	242.6	238.4	240.2	240.7	14.8	44.4
15,0°	253.3	249.0	245.8	242.3	240.2	238.2	232.0	230.8	232.5	229.9	229.1	17.4	61.9
17,5°	248.2	245.7	244.3	234.9	234.4	231.3	225.1	223.8	224.2	226.4	225.9	20.1	82.0
20,0°	249.0	242.8	235.3	229.1	228.7	227.0	220.6	219.2	215.6	213.7	216.0	22.6	104.6
22,5°	248.2	240.5	232.0	228.8	222.0	218.8	212.2	207.8	207.9	206.6	202.9	25.0	129.6
25,0°	247.3	235.1	228.1	218.4	216.8	212.1	207.5	204.6	199.8	202.4	197.5	27.4	157.0
27,5°	240.3	236.6	223.0	218.7	218.2	211.2	212.3	210.7	211.8	207.1	205.8	30.2	187.2
30,0°	237.6	223.0	218.6	222.0	224.8	219.8	217.5	214.8	212.9	212.7	202.9	32.9	220.1
32,5°	233.5	226.8	228.8	232.6	233.7	229.5	224.0	219.5	217.8	213.2	217.3	36.1	256.2
35,0°	233.4	234.6	241.4	244.5	240.2	235.7	227.9	220.7	218.2	210.1	212.9	39.0	295.2
37,5°	242.3	249.7	256.4	254.6	247.1	237.8	229.2	218.5	211.9	208.8	199.7	41.9	337.1
40,0°	249.3	272.3	267.4	266.7	256.9	240.5	229.5	218.1	209.6	206.1	198.9	44.8	381.9
42,5°	267.5	290.3	283.1	270.2	258.2	238.5	224.4	210.4	205.3	196.4	189.0	47.4	429.2
45,0°	291.8	305.0	291.0	268.1	249.1	224.0	203.5	188.9	176.3	169.8	172.8	48.8	478.1
47,5°	314.5	315.2	288.5	252.7	225.7	198.1	177.6	164.7	153.5	143.3	143.4	49.6	527.7
50,0°	330.3	310.0	272.2	233.8	196.6	166.6	147.6	134.5	124.1	119.1	119.4	50.0	577.6
52,5°	330.8	289.8	246.6	198.1	157.6	132.7	117.0	103.6	95.9	88.3	87.7	49.5	627.1
55,0°	313.0	259.8	196.1	148.4	119.6	94.7	83.7	76.4	73.6	70.1	68.4	48.5	675.6
57,5°	276.7	189.0	135.9	100.1	78.7	64.8	61.9	61.2	58.4	60.1	61.8	47.1	722.8
60,0°	199.2	125.8	85.1	65.2	57.1	48.7	48.8	46.1	48.8	49.7	50.8	45.5	768.2
62,5°	126.1	79.6	56.8	48.4	45.3	41.2	40.9	40.8	41.7	41.1	39.0	43.6	811.9
65,0°	76.8	55.9	46.9	38.8	36.2	36.4	33.5	34.6	34.4	33.6	33.1	41.7	853.6
67,5°	53.7	46.6	40.0	32.3	30.7	32.2	30.0	28.9	29.5	27.9	27.6	39.4	892.9
70,0°	44.6	38.2	32.4	29.1	27.5	27.5	26.3	24.9	24.6	22.4	23.1	35.6	928.5
72,5°	34.7	31.0	27.0	22.4	21.2	20.6	20.3	19.8	18.7	18.1	17.2	29.6	958.2
75,0°	23.8	23.3	20.4	17.3	15.0	15.2	13.2	12.7	12.5	12.0	12.0	21.6	979.7
77,5°	16.2	16.9	14.8	13.2	12.8	11.0	8.8	7.7	7.4	7.1	7.0	12.8	992.6
80,0°	10.7	10.0	9.3	8.0	7.9	6.9	6.4	5.1	4.3	4.4	4.3	5.5	998.1
82,5°	4.9	5.0	4.9	4.0	4.1	3.5	3.5	2.6	2.3	2.1	2.1	1.5	999.6
85,0°	1.4	1.7	1.5	1.4	1.1	1.3	1.1	0.8	0.8	0.7	0.8	0.3	999.9
87,5°	0.3	0.3	0.2	0.2	0.2	0.2	0.2	0.2	0.1	0.1	0.1	0.1	1000.0
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family DL® 50 mini LED	Order number: 5XA248V41F08LE EAN: 4058352803936	LP number 59397_25
----------------------------------	--	------------------------------

Dimming levels table	environmental temperature: 25°C	siteco
-----------------------------	---------------------------------	---------------

Luminous flux [%]	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]start of lifetime	Power consumption [W]end of lifetime	Power consumption [W]average
100	254	254	10390	64.1	66.9	65.5
95	241	252	9858	60.1	62.7	61.4
90	229	250	9367	56.5	59.0	57.8
85	216	248	8836	52.8	55.1	54.0
80	203	246	8304	49.2	51.3	50.2
75	190	243	7772	45.6	47.5	46.6
70	178	241	7281	42.4	44.2	43.3
65	165	238	6749	39.0	40.7	39.8
60	152	235	6218	35.7	37.1	36.4
55	140	232	5727	32.7	34.0	33.4
50	127	229	5195	29.5	30.7	30.1
45	114	225	4663	26.5	27.5	27.0
40	102	221	4172	23.6	24.6	24.1
35	89	216	3641	20.6	21.4	21.0
30	76	210	3109	17.7	18.4	18.0
25	63	203	2577	15.0	15.5	15.2
20	51	195	2086	12.5	12.9	12.7
15	38	184	1554	9.8	10.1	10.0
11	28	173	1145	7.8	7.9	7.8