

Photometric test report

Family
Silica® 21

Order number: **51MX31DB49SB**
EAN: **4058352886793**

LP number
59281_82



Version Suspended luminaire, reflector, black, direct-/indirect distribution, narrow distribution, $UGR \leq 16$ ($L65 \leq 3000 \text{ cd/m}^2$)

Lamps LED 4000 K | CRI ≥ 80

Controlgear ECG-DALI

Rated values Net luminous flux = 9120 lm
Power consumption = 54.8 W
Luminous efficacy = 166.4 lm/W

serial
documentation
02.08.2023


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 959 cd/klm



Classifications

DIN 5040 C 7 2
CIE N1=86 N2=99 N3=100
N4=59 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 59.0%
 ϕ_o 41.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Silica® 21	Order number: 51MX31DB49SB EAN: 4058352886793	LP number 59281_82
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	959.4	959.4	959.4	959.4	959.4	959.4	959.4	5.7	5.7
5°	912.2	913.2	911.7	911.4	911.5	911.7	910.3	43.6	49.3
10°	754.6	755.9	762.5	767.9	766.9	758.5	757.5	72.5	121.8
15°	578.2	581.5	588.5	595.2	592.8	584.9	581.1	83.3	205.1
20°	450.2	447.9	438.1	432.3	432.3	433.7	435.2	82.1	287.1
25°	337.4	332.5	314.5	302.7	311.9	319.4	319.2	73.7	360.8
30°	251.3	246.8	227.0	216.4	227.8	237.2	231.6	63.8	424.6
35°	181.9	180.8	165.4	156.1	165.0	174.0	165.2	53.2	477.8
40°	124.1	124.5	116.4	111.0	116.6	120.7	113.9	41.6	519.4
45°	77.3	77.7	75.1	73.6	76.6	76.5	72.7	29.4	548.8
50°	44.9	46.1	46.4	46.4	47.6	45.7	43.0	19.3	568.1
55°	25.0	26.0	27.2	27.9	28.2	25.7	24.0	11.9	580.0
60°	7.9	9.6	14.5	15.8	15.1	10.6	8.6	5.8	585.9
65°	2.5	3.1	4.5	8.1	4.9	3.1	2.7	2.2	588.0
70°	1.0	1.1	0.9	1.6	1.1	1.3	1.3	0.6	588.6
75°	0.2	0.3	0.3	0.3	0.3	0.3	0.3	0.2	588.8
80°	0.0	0.1	0.1	0.1	0.1	0.1	0.1	0.0	588.8
85°	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.2	589.1
90°	4.7	4.6	4.9	4.8	2.9	1.0	0.4	1.9	590.9
95°	22.0	22.5	24.1	22.8	14.6	7.5	3.9	9.5	600.4
100°	39.3	40.4	40.8	35.7	24.0	13.5	8.9	16.1	616.5
105°	56.4	57.6	56.5	48.2	33.0	20.5	15.0	22.2	638.7
110°	75.8	76.1	71.3	59.4	42.3	27.6	21.4	27.9	666.6
115°	92.7	91.8	84.7	69.7	51.3	34.9	28.6	32.5	699.2
120°	106.6	104.9	95.6	78.0	59.7	42.0	35.6	35.7	734.9
125°	115.7	112.5	102.2	85.6	66.8	48.7	43.0	37.1	771.9
130°	118.9	116.2	105.4	90.1	72.2	55.6	50.5	36.7	808.6
135°	118.7	116.2	106.6	93.2	76.5	62.0	57.9	35.1	843.7
140°	116.7	115.0	106.9	95.4	80.1	68.1	65.7	32.7	876.4
145°	114.8	113.6	106.8	96.6	83.5	73.7	72.0	29.7	906.1
150°	112.1	111.6	105.6	96.5	86.2	79.2	77.7	26.2	932.3
155°	109.0	108.7	103.0	96.1	88.3	84.0	82.9	22.2	954.6
160°	104.7	104.4	99.9	95.3	90.2	87.8	87.5	17.9	972.5
165°	100.1	99.5	97.2	94.2	92.0	90.8	90.9	13.5	985.9
170°	96.6	96.1	95.5	94.2	93.3	93.1	93.2	9.0	994.9
175°	94.6	94.5	94.0	93.8	93.8	93.9	93.9	4.5	999.4
180°	94.1	94.1	94.1	94.1	94.1	94.1	94.1	0.6	1000.0

Photometric test report

Family Silica® 21		Order number: 51MX31DB49SB EAN: 4058352886793							LP number 59281_82	
UGR-Table		Standard room							siteco	
Reflection factor of ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5
Reflection factor of walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3
Reflection factor of floor		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		View crosswise (C0)					View endwise (C90)			
x	y									
2H	2H	14.3	15.1	15.1	15.9	17.0	14.2	15.0	15.0	15.8
	3H	14.0	14.7	14.9	15.6	16.7	13.9	14.6	14.8	15.5
	4H	13.8	14.5	14.7	15.4	16.5	13.8	14.5	14.7	15.3
	6H	13.7	14.3	14.6	15.2	16.3	13.6	14.2	14.5	15.1
	8H	13.6	14.1	14.5	15.0	16.2	13.5	14.0	14.4	14.9
	12H	13.5	14.0	14.4	14.9	16.1	13.4	13.9	14.4	14.8
4H	2H	14.0	14.7	14.9	15.6	16.7	13.9	14.5	14.8	15.4
	3H	13.7	14.3	14.7	15.2	16.4	13.6	14.2	14.5	15.1
	4H	13.6	14.1	14.5	15.0	16.2	13.5	14.0	14.4	14.9
	6H	13.4	13.8	14.4	14.8	16.0	13.3	13.7	14.3	14.7
	8H	13.3	13.7	14.3	14.6	15.9	13.2	13.6	14.2	14.6
	12H	13.2	13.5	14.2	14.5	15.7	13.1	13.5	14.1	14.4
8H	4H	13.3	13.7	14.3	14.7	15.9	13.2	13.6	14.2	14.5
	6H	13.2	13.5	14.2	14.5	15.7	13.0	13.3	14.0	14.3
	8H	13.1	13.4	14.1	14.3	15.6	13.0	13.3	14.0	14.2
	12H	13.0	13.2	14.0	14.2	15.5	12.9	13.1	13.9	14.1
12H	4H	13.2	13.6	14.2	14.5	15.8	13.1	13.4	14.1	14.4
	6H	13.1	13.3	14.1	14.3	15.6	13.0	13.2	14.0	14.2
	8H	13.0	13.2	14.0	14.2	15.5	12.9	13.1	13.9	14.1

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 1470 B = 49	
C-planes	γ	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°
			Luminance in cd/m²				
45° 50° 55° 60°	γ	13833.7	13904.5	13449.7	13183.4	13716.1	13704.6
		8851.1	9078.4	9131.6	9147.6	9383.9	9001.6
		5513.1	5735.8	5999.8	6164.7	6224.3	5678.4
		2000.5	2427.9	3682.7	3989.6	3827.8	2677.6
65° 70° 75° 80°	γ	734.3	920.1	1347.0	2421.0	1466.2	931.4
		377.2	400.6	337.2	584.5	411.7	463.1
		95.4	134.5	133.1	170.2	165.8	159.0
		30.6	40.8	40.8	51.0	66.4	75.8
85°	γ	616.0	600.0	584.0	550.6	537.5	530.2

Photometric test report

Family
Silica® 21

Order number: 51MX31DB49SB
EAN: 4058352886793

LP number
59281_82

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Silica® 21	Order number: 51MX31DB49SB EAN: 4058352886793	LP number 59281_82
Dimming levels table environmental temperature: 25°C		siteco

Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]
100	254	254	9120	54.8
95	241	252	8678	52.1
90	227	250	8199	49.1
85	214	248	7751	46.3
80	201	245	7299	43.7
75	188	243	6845	40.9
70	175	240	6388	38.2
65	162	238	5929	35.5
60	149	234	5467	32.7
55	136	231	5001	30.1
50	124	228	4569	27.6
45	111	224	4100	24.9
40	99	219	3663	22.4
35	86	214	3187	19.8
30	74	209	2746	17.3
25	61	202	2264	14.6
20	49	194	1818	12.1
15	37	183	1371	9.7
10	25	169	922	7.3
5	13	145	471	5.1
2	6	117	207	4.2