

Photometric test report

Family
Silica® 21



Order number: **51MX33DC3DSB**
EAN: **4058352893586**

LP number
59331_96

serial
documentation
02.08.2023

Version

Suspended luminaire, with homogeneous illumination, prismatic cover, direct-/ indirect distribution, extremely wide distribution, $UGR \leq 16$ ($L65 \leq 3000 \text{ cd/m}^2$)

Lamps

LED 3000 K | CRI ≥ 80

Controlgear

ECG-DALI

Rated values

Net luminous flux = 14780 lm

Power consumption = 99.5 W

Luminous efficacy = 148.5 lm/W


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 353 cd/klm



Classifications

DIN 5040 C 6 2
CIE N1=78 N2=96 N3=99
N4=55 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 55.4%
 ϕ_o 44.6%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Silica® 21	Order number: 51MX33DC3DSB EAN: 4058352893586	LP number 59331_96
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	349.9	349.9	349.9	349.9	349.9	349.9	349.9	2.1	2.1
5°	352.7	353.3	353.1	353.3	352.9	352.0	351.1	16.9	18.9
10°	340.4	339.5	339.7	341.6	345.2	345.5	345.7	32.6	51.5
15°	335.2	334.1	331.5	331.4	333.4	336.4	336.2	47.3	98.9
20°	323.4	322.7	318.7	319.6	318.0	320.3	324.7	60.1	159.0
25°	303.6	304.4	302.2	302.2	302.6	302.3	307.6	70.2	229.2
30°	283.2	283.0	279.5	280.9	281.3	280.3	282.2	77.1	306.3
35°	244.1	243.6	241.2	242.6	243.2	242.2	242.9	76.3	382.6
40°	179.9	179.6	180.9	182.1	183.5	183.3	184.4	64.1	446.7
45°	110.1	109.9	111.2	112.6	113.8	115.2	117.5	43.7	490.4
50°	51.7	59.9	67.3	61.6	55.5	66.0	73.6	26.1	516.5
55°	21.0	28.2	26.7	30.5	23.0	31.8	29.6	12.4	528.9
60°	14.1	14.7	15.5	14.4	14.4	15.4	16.1	7.1	536.0
65°	11.6	11.5	12.0	11.7	12.2	12.2	12.1	5.9	541.9
70°	8.4	8.6	8.9	8.9	9.1	9.2	9.2	4.6	546.5
75°	5.8	6.1	6.7	6.4	6.5	6.9	6.6	3.4	549.9
80°	3.5	3.8	4.1	4.5	4.2	4.7	4.7	2.3	552.2
85°	1.8	1.8	1.8	2.1	2.2	2.5	2.7	1.2	553.3
90°	5.2	5.0	5.3	5.2	3.1	1.1	0.4	2.0	555.4
95°	23.9	24.4	26.2	24.8	15.9	8.2	4.2	10.3	565.7
100°	42.8	43.9	44.3	38.8	26.0	14.7	9.7	17.5	583.2
105°	61.3	62.6	61.4	52.4	35.9	22.2	16.3	24.1	607.3
110°	82.4	82.7	77.5	64.5	46.0	30.0	23.3	30.4	637.7
115°	100.7	99.8	92.0	75.7	55.8	37.9	31.1	35.4	673.0
120°	115.9	114.0	103.9	84.8	64.9	45.6	38.7	38.8	711.8
125°	125.7	122.3	111.1	93.1	72.6	52.9	46.8	40.3	752.1
130°	129.2	126.3	114.5	98.0	78.5	60.4	54.8	39.9	792.0
135°	129.0	126.3	115.8	101.3	83.2	67.4	62.9	38.1	830.1
140°	126.9	124.9	116.2	103.6	87.1	74.0	71.4	35.5	865.6
145°	124.8	123.4	116.1	105.0	90.7	80.2	78.2	32.3	897.9
150°	121.9	121.3	114.8	104.9	93.7	86.1	84.5	28.5	926.4
155°	118.5	118.2	111.9	104.4	96.0	91.3	90.1	24.2	950.6
160°	113.8	113.5	108.5	103.6	98.0	95.4	95.1	19.5	970.1
165°	108.8	108.2	105.6	102.3	100.0	98.6	98.8	14.6	984.7
170°	105.0	104.5	103.8	102.4	101.4	101.2	101.3	9.8	994.5
175°	102.8	102.7	102.1	101.9	102.0	102.0	102.0	4.9	999.4
180°	102.2	102.2	102.2	102.2	102.2	102.2	102.2	0.6	1000.0

Photometric test report

Family Silica® 21		Order number: 51MX33DC3DSB EAN: 4058352893586							LP number 59331_96	
UGR-Table		Standard room							siteco	
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		View crosswise (C0)					View endwise (C90)			
x	y									
2H	2H	15.4	16.3	16.3	17.2	18.3	15.6	16.5	16.5	17.4
	3H	15.3	16.1	16.2	17.0	18.1	15.6	16.3	16.5	17.2
	4H	15.3	16.0	16.2	16.9	18.1	15.6	16.3	16.5	17.2
	6H	15.2	15.8	16.1	16.8	18.0	15.5	16.2	16.5	17.1
	8H	15.1	15.7	16.1	16.7	17.9	15.4	16.0	16.4	17.0
	12H	15.0	15.6	16.0	16.5	17.8	15.5	16.0	16.4	16.9
4H	2H	15.2	15.9	16.1	16.8	17.9	15.3	16.0	16.2	16.9
	3H	15.2	15.7	16.1	16.7	17.9	15.4	15.9	16.3	16.9
	4H	15.2	15.7	16.1	16.6	17.9	15.4	15.9	16.4	16.9
	6H	15.2	15.6	16.1	16.6	17.8	15.5	15.9	16.4	16.9
	8H	15.1	15.5	16.1	16.5	17.8	15.5	15.9	16.5	16.9
	12H	15.0	15.4	16.1	16.4	17.7	15.5	15.8	16.5	16.8
8H	4H	15.0	15.4	16.0	16.4	17.7	15.2	15.6	16.2	16.6
	6H	15.1	15.5	16.1	16.5	17.7	15.4	15.7	16.4	16.7
	8H	15.1	15.4	16.1	16.4	17.7	15.5	15.8	16.5	16.8
	12H	15.1	15.3	16.1	16.3	17.7	15.5	15.8	16.6	16.8
12H	4H	15.0	15.3	16.0	16.3	17.6	15.1	15.5	16.2	16.5
	6H	15.1	15.3	16.1	16.3	17.6	15.3	15.6	16.3	16.6
	8H	15.1	15.3	16.1	16.3	17.7	15.4	15.7	16.4	16.7

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 3000 B = 50	
C-planes	γ	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°
			Luminance in cd/m²				
45° 50° 55° 60°	γ	15342.7	15309.5	15501.5	15684.2	15853.9	16056.6
		7923.4	9179.4	10322.9	9447.5	8514.1	10111.8
		3602.6	4852.8	4584.0	5236.6	3955.1	5461.3
		2788.1	2893.3	3058.5	2835.0	2845.4	3026.2
65° 70° 75° 80° 85°	γ	2708.7	2687.5	2795.5	2726.9	2842.6	2838.4
		2423.4	2468.7	2568.6	2568.6	2609.0	2638.9
		2225.2	2309.7	2545.4	2430.8	2486.8	2613.9
		2009.8	2129.0	2348.0	2555.7	2370.7	2644.8
85°	γ	1985.2	1997.7	2073.4	2396.8	2520.0	2873.8

Photometric test report

Family
Silica® 21

Order number: **51MX33DC3DSB**
EAN: **4058352893586**

LP number
59331_96

Luminance values in cd/m²

γ 65°

γ 70°


γ 75°

γ 80°

γ 85°

sit

eco



Photometric test report

Family Silica® 21	Order number: 51MX33DC3DSB EAN: 4058352893586	LP number 59331_96
Dimming levels table		environmental temperature: 25°C

siteco

Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]
100	254	254	14780	99.5
95	241	252	14064	95.0
90	227	250	13286	89.6
85	214	248	12561	84.3
80	201	245	11830	79.4
75	188	243	11095	74.7
70	175	240	10356	69.8
65	162	238	9607	64.4
60	149	234	8857	59.5
55	136	231	8103	54.9
50	124	228	7403	50.0
45	111	224	6640	45.4
40	99	219	5933	40.9
35	86	214	5161	36.0
30	74	209	4447	31.6
25	61	202	3670	26.4
20	49	194	2944	21.8
15	37	183	2220	17.2
10	25	169	1492	12.5
5	13	145	761	7.7
2	6	117	333	4.3