

Photometric test report

Family
Licross® 21 Recessed

Order number: 52TL12CN475G
EAN: 4058352890714

LP number
59101_307



Version cover frosted, wide distribution, high visual comfort
Lamps LED 4000 K | CRI ≥ 80
Controlgear ECG-Multilumen CLOi
Rated values Net luminous flux = 7990 lm
Power consumption = 42.6 W
Luminous efficacy = 187.6 lm/W

serial
documentation
17.08.2023


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 671 cd/klm



Classifications

DIN 5040 A 6 0
CIE N1=72 N2=92 N3=99
N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 100.0%
 ϕ_o 0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Licross® 21 Recessed	Order number: 52TL12CN475G EAN: 4058352890714	LP number 59101_307
Table of values for luminous intensities		Maximum luminous intensity

siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	668.4	668.4	668.4	668.4	668.4	668.4	668.4	4.0	4.0
5°	667.5	664.4	657.4	655.8	655.7	654.2	654.4	31.4	35.4
10°	670.7	665.0	649.1	636.1	625.3	618.7	618.1	60.9	96.3
15°	666.2	657.2	632.9	612.0	594.0	578.5	575.5	87.4	183.7
20°	644.4	632.9	606.9	585.4	554.6	522.7	512.3	108.8	292.5
25°	604.1	590.6	566.7	541.2	494.5	444.9	427.0	121.8	414.2
30°	532.4	517.7	496.3	466.1	413.9	359.9	340.6	122.9	537.1
35°	425.0	409.7	387.0	361.9	325.4	286.0	271.1	111.0	648.1
40°	313.4	295.8	270.7	255.1	246.8	229.4	218.8	91.8	739.9
45°	219.2	200.3	175.7	171.1	181.8	184.7	175.5	71.8	811.7
50°	149.7	132.6	112.6	116.3	133.0	145.6	134.9	54.8	866.5
55°	102.7	89.1	74.7	81.5	98.1	107.9	98.1	41.3	907.7
60°	72.4	62.1	51.3	58.3	71.8	76.5	71.0	31.0	938.7
65°	52.1	44.3	35.9	41.6	51.4	54.2	52.1	23.1	961.9
70°	37.6	31.7	24.7	29.1	35.6	38.4	38.3	16.9	978.8
75°	26.0	21.3	16.2	19.0	22.9	25.9	26.8	11.6	990.4
80°	16.1	12.5	9.2	10.4	12.6	14.8	15.7	6.8	997.3
85°	7.0	5.4	3.8	4.1	4.8	5.7	5.8	2.7	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Licross® 21 Recessed		Order number: 52TL12CN475G EAN: 4058352890714							LP number 59101_307	
UGR-Table		Standard room							siteco	
Reflection factor of ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5
Reflection factor of walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3
Reflection factor of floor		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		View crosswise (C0)					View endwise (C90)			
x	y									
2H	2H	21.0	22.4	21.3	22.7	23.0	20.9	22.3	21.3	22.6
	3H	21.6	22.8	21.9	23.2	23.5	21.7	23.0	22.1	23.3
	4H	21.8	23.0	22.2	23.4	23.7	22.0	23.2	22.4	23.6
	6H	22.1	23.2	22.5	23.5	23.9	22.3	23.4	22.7	23.7
	8H	22.3	23.2	22.7	23.6	24.0	22.4	23.4	22.9	23.8
	12H	22.3	23.2	22.8	23.6	24.0	22.5	23.4	22.9	23.8
4H	2H	21.1	22.3	21.5	22.7	23.0	21.1	22.3	21.5	22.6
	3H	21.8	22.8	22.2	23.2	23.6	22.1	23.0	22.5	23.4
	4H	22.1	23.0	22.6	23.4	23.9	22.5	23.4	22.9	23.8
	6H	22.5	23.2	22.9	23.6	24.1	22.9	23.6	23.3	24.0
	8H	22.6	23.3	23.1	23.7	24.2	23.0	23.7	23.5	24.1
	12H	22.7	23.3	23.2	23.8	24.3	23.1	23.7	23.6	24.1
8H	4H	22.2	22.9	22.7	23.3	23.8	22.6	23.2	23.0	23.7
	6H	22.6	23.1	23.1	23.6	24.1	23.0	23.5	23.5	24.0
	8H	22.7	23.2	23.2	23.7	24.2	23.2	23.6	23.7	24.1
	12H	22.9	23.3	23.4	23.8	24.3	23.3	23.7	23.8	24.2
12H	4H	22.2	22.8	22.7	23.3	23.8	22.6	23.1	23.1	23.6
	6H	22.6	23.1	23.1	23.5	24.1	23.0	23.5	23.5	24.0
	8H	22.8	23.2	23.3	23.7	24.2	23.2	23.6	23.7	24.1

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 1500 B = 58	
C-planes	γ	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°
			Luminance in cd/m²				
45° 50° 55° 60°	γ	28472.3	26021.2	22816.4	22227.0	23612.1	23988.8
		21386.4	18941.5	16089.4	16617.4	19001.8	20805.4
		16438.5	14270.5	11963.6	13053.2	15704.1	17284.3
		13295.0	11412.5	9424.2	10716.5	13182.0	14053.4
65° 70° 75° 80° 85°	γ	11322.3	9636.6	7811.9	9045.3	11179.9	11768.4
		10089.6	8507.5	6633.5	7801.6	9550.2	10311.4
		9225.5	7557.0	5760.1	6734.1	8129.7	9176.1
		8509.2	6633.7	4880.5	5524.2	6678.2	7853.3
85°	γ	7379.3	5683.8	4013.7	4327.7	5087.4	5957.8

Photometric test report

Family
Licross® 21 Recessed

Order number: 52TL12CN475G
EAN: 4058352890714

LP number
59101_307

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Licross® 21 Recessed	Order number: 52TL12CN475G EAN: 4058352890714	LP number 59101_307
Multilumen Table environmental temperature: 25°C		

DIP-Step	Switch Setting			Luminous flux [lm]	Power consumption [W]	Power consumption [W]	Power consumption [W]
	1	2	3			end of lifetime	average
1	A	C	E	7990	42.6	50.8	46.7
2	A	C	F	7530	40.0	47.8	43.9
3	A	D	E	7000	37.0	43.9	40.4
4	A	D	F	6540	34.6	41.4	38.0
5	B	C	E	5990	31.6	37.5	34.6
6	B	C	F	5520	29.0	34.6	31.8
7	B	D	E	5040	26.5	31.6	29.0
8	B	D	F	4480	23.6	27.8	25.7