

Photometric test report

Family
Licross® 21 Protected

Order number: 52TD12MN4A5G
EAN: 4058352902899

LP number
58524_262



Version prismatic cover, frosted, wide distribution
Lamps LED 4000 K | CRI ≥ 80
Controlgear ECG Multilumen
Rated values Net luminous flux = 10750 lm
 Power consumption = 60.5 W
 Luminous efficacy = 177.7 lm/W

serial
documentation
24.08.2023


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 631 cd/klm



Classifications

DIN 5040 A 5 1
 CIE N1=73 N2=92 N3=98
 N4=99 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 98.6%
 ϕ_o 1.4%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Licross® 21 Protected	Order number: 52TD12MN4A5G EAN: 4058352902899	LP number 58524_262
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	615.0	615.0	615.0	615.0	615.0	615.0	615.0	3.7	3.7
5°	616.1	614.1	609.7	611.1	612.9	611.9	612.2	29.3	32.9
10°	616.9	615.1	606.4	602.8	600.3	597.0	596.6	57.6	90.5
15°	620.9	617.8	600.9	587.5	576.7	568.6	566.8	83.8	174.3
20°	630.8	623.5	591.7	561.2	536.7	520.1	515.5	106.4	280.7
25°	629.8	620.7	576.3	523.2	476.9	445.6	435.5	122.6	403.3
30°	570.2	568.9	534.3	469.6	398.0	348.4	331.9	126.5	529.9
35°	447.2	456.9	450.2	394.1	307.5	246.5	227.0	114.9	644.8
40°	317.0	331.0	344.1	303.2	220.2	163.1	146.0	93.6	738.3
45°	213.9	226.3	244.1	214.7	147.7	105.6	94.0	70.6	808.9
50°	143.1	152.0	166.9	144.8	97.7	70.8	64.1	51.5	860.4
55°	96.6	102.1	111.9	95.1	64.8	49.7	46.3	37.0	897.4
60°	67.0	69.6	74.2	63.4	44.8	36.0	34.5	26.8	924.2
65°	49.0	49.5	50.0	42.8	32.0	26.6	25.7	19.7	943.9
70°	37.9	37.0	34.4	29.4	23.3	19.5	18.8	14.8	958.7
75°	30.5	28.7	24.6	20.4	16.6	13.6	12.7	11.1	969.8
80°	24.8	22.7	18.1	14.1	11.2	8.8	7.6	8.2	978.0
85°	19.7	17.8	13.4	9.8	7.1	4.8	3.4	5.9	983.8
90°	14.9	13.4	9.7	6.4	4.0	1.9	0.4	3.9	987.8
95°	12.2	11.1	8.2	5.4	3.1	1.2	0.3	3.2	991.0
100°	10.0	9.2	6.9	4.5	2.4	0.7	0.3	2.6	993.6
105°	8.2	7.6	5.7	3.6	1.7	0.4	0.3	2.1	995.6
110°	6.8	6.2	4.6	2.7	1.1	0.3	0.3	1.6	997.2
115°	5.5	5.0	3.7	2.0	0.7	0.4	0.4	1.2	998.4
120°	4.3	3.8	2.7	1.4	0.6	0.5	0.5	0.9	999.3
125°	3.1	2.7	1.8	0.9	0.6	0.6	0.6	0.6	1000.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0


Photometric test report

Family Licross® 21 Protected			Order number: 52TD12MN4A5G EAN: 4058352902899							LP number 58524_262	
UGR-Table			Standard room							siteco	
Reflection factor of ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Reflection factor of walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reflection factor of floor		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	21.5	23.0	21.9	23.3	23.6	18.3	19.7	18.6	20.0	20.3
	3H	21.9	23.2	22.3	23.5	23.9	18.6	19.9	19.0	20.2	20.6
	4H	22.2	23.3	22.6	23.7	24.1	18.8	20.0	19.2	20.3	20.7
	6H	22.5	23.5	22.9	23.9	24.3	18.9	20.0	19.3	20.4	20.8
	8H	22.7	23.6	23.1	24.0	24.4	19.0	20.0	19.4	20.4	20.8
	12H	22.9	23.7	23.3	24.1	24.5	19.0	20.0	19.4	20.3	20.8
4H	2H	21.6	22.8	22.0	23.1	23.5	18.8	20.0	19.2	20.3	20.7
	3H	22.1	23.1	22.6	23.5	23.9	19.3	20.2	19.7	20.6	21.0
	4H	22.5	23.3	22.9	23.8	24.2	19.5	20.4	19.9	20.8	21.2
	6H	22.9	23.6	23.3	24.1	24.5	19.7	20.4	20.1	20.9	21.3
	8H	23.1	23.8	23.6	24.2	24.7	19.7	20.5	20.2	20.9	21.4
	12H	23.4	24.0	23.9	24.4	24.9	19.8	20.4	20.3	20.9	21.4
8H	4H	22.5	23.2	22.9	23.6	24.1	19.7	20.4	20.2	20.8	21.3
	6H	23.0	23.5	23.5	24.0	24.5	20.0	20.6	20.5	21.0	21.5
	8H	23.3	23.8	23.8	24.3	24.8	20.1	20.6	20.6	21.1	21.6
	12H	23.7	24.1	24.2	24.6	25.1	20.2	20.6	20.7	21.1	21.7
12H	4H	22.5	23.1	23.0	23.5	24.0	19.8	20.4	20.3	20.8	21.3
	6H	23.0	23.5	23.5	24.0	24.5	20.1	20.6	20.6	21.1	21.6
	8H	23.3	23.7	23.8	24.2	24.8	20.3	20.7	20.8	21.2	21.7

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 1480 B = 78	H(C0) = 13 H(C90) = 0	H(C180) = 13 H(C270) = 0
C-planes	γ	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
			Luminance in cd/m²					
45°		24148.9	25665.5	28091.2	25291.3	17952.2	13334.2	12384.0
50°		17291.2	18476.7	20635.7	18399.0	12876.1	9751.9	9280.4
55°		12662.6	13472.8	15058.3	13215.1	9402.3	7595.2	7518.1
60°		9689.0	10135.2	11058.9	9803.1	7283.7	6245.2	6418.2
65°		7960.8	8113.7	8405.4	7520.3	5976.8	5373.6	5662.7
70°		7079.3	6991.8	6715.7	6052.4	5152.5	4754.7	5108.1
75°		6767.8	6455.9	5742.5	5102.5	4549.4	4216.9	4586.3
80°		6841.7	6368.5	5343.9	4533.8	4093.5	3782.5	4077.2
85°		7233.5	6684.0	5420.5	4445.4	3911.0	3457.1	3681.9

Photometric test report

Family Licross® 21 Protected	Order number: 52TD12MN4A5G EAN: 4058352902899	LP number 58524_262
Luminance values in cd/m²		siteco
		γ 65° γ 70° γ 75° γ 80° γ 85°



Photometric test report

Family Licross® 21 Protected	Order number: 52TD12MN4A5G EAN: 4058352902899	LP number 58524_262
Multilumen Table	environmental temperature: 25°C	siteco

DIP-Step	Switch Setting			Luminous flux [lm]	Power consumption [W]
	1	2	3		
1	A	C	E	10750	60.5
2	A	C	F	9860	56.1
3	A	D	E	9380	53.1
4	A	D	F	8880	50.0
5	B	C	E	8380	47.0
6	B	C	F	7880	43.9
7	B	D	E	7370	41.0
8	B	D	F	6930	38.4