

Photometric test report

Family
Licross® 21 Recessed

Order number: 52TE1EMN4E5S
EAN: 4058352890257

LP number
59263_179



Version cover frosted, elliptical narrow distribution
Lamps LED 4000 K | CRI ≥ 80
Controlgear ECG Multilumen
Rated values Net luminous flux = 14710 lm
 Power consumption = 83.1 W
 Luminous efficacy = 177 lm/W

serial
documentation
24.08.2023


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 1670 cd/klm



Classifications

DIN 5040 A 7 0
 CIE N1=85 N2=95 N3=99
 N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 100.0%
 ϕ_o 0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Licross® 21 Recessed	Order number: 52TE1EMN4E5S EAN: 4058352890257	LP number 59263_179
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	1669.5	1669.5	1669.5	1669.5	1669.5	1669.5	1669.5	10.0	10.0
5°	1493.3	1495.6	1516.6	1565.9	1616.3	1649.8	1662.9	75.0	85.0
10°	1088.5	1106.7	1175.0	1303.4	1460.6	1586.1	1636.2	126.8	211.8
15°	678.3	712.7	825.0	1006.5	1239.9	1474.8	1578.7	151.0	362.9
20°	362.1	388.9	492.0	707.6	980.6	1275.8	1432.9	148.2	511.0
25°	217.8	231.1	285.8	436.7	705.9	972.9	1137.5	127.8	638.8
30°	151.3	158.5	185.3	264.1	455.8	646.3	761.7	99.0	737.8
35°	95.4	107.0	131.3	171.8	268.4	391.1	463.8	70.7	808.5
40°	57.7	64.5	93.9	120.6	157.9	239.7	291.4	50.0	858.5
45°	43.5	45.9	58.2	86.3	99.5	145.4	176.9	35.2	893.7
50°	37.7	39.0	42.8	61.0	68.3	89.3	109.1	26.2	919.9
55°	34.6	35.0	36.7	43.5	50.5	59.6	73.7	20.9	940.8
60°	30.2	31.1	32.8	34.2	38.6	42.0	53.5	17.5	958.3
65°	23.9	25.4	29.1	28.1	30.1	30.8	41.3	14.6	972.8
70°	17.0	18.4	22.5	23.3	23.4	22.7	30.8	11.5	984.3
75°	10.9	12.0	16.2	17.9	17.4	15.7	20.7	8.4	992.7
80°	6.2	6.7	9.0	10.7	11.0	9.3	11.6	5.0	997.7
85°	3.1	3.3	4.2	5.0	4.8	3.9	4.2	2.3	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Licross® 21 Recessed		Order number: 52TE1EMN4E5S EAN: 4058352890257							LP number 59263_179	
UGR-Table		Standard room							siteco	
Reflection factor of ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5
Reflection factor of walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3
Reflection factor of floor		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		View crosswise (C0)					View endwise (C90)			
x	y									
2H	2H	16.5	17.7	16.8	18.0	18.4	21.5	22.7	21.9	23.0
	3H	17.7	18.8	18.1	19.1	19.4	22.1	23.1	22.5	23.5
	4H	18.0	19.1	18.4	19.4	19.8	22.4	23.3	22.8	23.7
	6H	18.2	19.2	18.7	19.6	20.0	22.6	23.4	23.0	23.8
	8H	18.4	19.2	18.9	19.6	20.0	22.7	23.5	23.1	23.8
	12H	18.5	19.3	18.9	19.6	20.1	22.8	23.4	23.2	23.8
4H	2H	17.3	18.3	17.7	18.6	19.0	21.5	22.5	21.9	22.9
	3H	18.7	19.6	19.2	20.0	20.4	22.2	23.0	22.6	23.4
	4H	19.2	20.0	19.7	20.4	20.8	22.6	23.3	23.0	23.7
	6H	19.5	20.2	20.0	20.6	21.1	22.9	23.5	23.3	23.9
	8H	19.7	20.2	20.1	20.7	21.2	23.0	23.5	23.5	24.0
	12H	19.7	20.2	20.2	20.7	21.2	23.1	23.5	23.6	24.0
8H	4H	19.7	20.3	20.2	20.7	21.2	22.7	23.2	23.1	23.7
	6H	20.2	20.6	20.7	21.1	21.6	23.1	23.5	23.6	24.0
	8H	20.3	20.7	20.8	21.2	21.7	23.2	23.6	23.7	24.1
	12H	20.4	20.8	21.0	21.3	21.8	23.3	23.6	23.8	24.1
12H	4H	19.8	20.2	20.3	20.7	21.2	22.7	23.2	23.1	23.6
	6H	20.3	20.7	20.8	21.1	21.7	23.1	23.5	23.6	24.0
	8H	20.5	20.8	21.0	21.3	21.9	23.2	23.6	23.8	24.1

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 1500 B = 58	
C-planes	γ	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°
			Luminance in cd/m²				
45°		10398.9	10969.4	13905.1	20630.4	23800.2	34767.4
50°		9927.0	10253.4	11257.4	16054.8	17968.7	23497.6
55°		10188.3	10311.8	10824.4	12815.7	14891.5	17576.7
60°		10197.6	10532.7	11096.8	11574.2	13050.6	14196.3
65°		9573.1	10151.6	11649.1	11245.8	12054.4	12314.0
70°		8392.7	9077.9	11112.7	11529.4	11566.0	11205.6
75°		7092.6	7845.2	10579.2	11715.2	11376.8	10283.2
80°		5992.1	6479.9	8769.1	10376.7	10681.4	9043.7
85°		6062.4	6466.0	8227.5	9752.3	9342.9	7554.3

Photometric test report

Family
Licross® 21 Recessed

Order number: 52TE1EMN4E5S
EAN: 4058352890257

LP number
59263_179

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Licross® 21 Recessed	Order number: 52TE1EMN4E5S EAN: 4058352890257	LP number 59263_179
Multilumen Table	environmental temperature: 25°C	siteco

DIP-Step	Switch Setting			Luminous flux [lm]	Power consumption [W]
	1	2	3		
1	A	C	E	14710	83.1
2	A	C	F	13820	77.5
3	A	D	E	12770	71.1
4	A	D	F	11850	65.4
5	B	C	E	10840	59.4
6	B	C	F	9880	53.9
7	B	D	E	8850	47.9
8	B	D	F	7870	42.4