



# Photometric test report

<b>Family</b> <b>DL 11 iQ</b>	<b>Order number: 5XA5565BF14H000022</b> <b>EAN: 4058352955727</b>	<b>LP number</b> <b>59428_42</b>
	<b>Version</b> post-top- or mounting to wall arm <b>Optic</b> direct, asymmetric extremely wide distribution P100012 <b>Cover</b> cover transparent, PMMA <b>Lamps</b> LED 2200 K   CRI ≥ 70 <b>Controlgear</b> ECG SITECO iQ <b>Rated values</b> Net luminous flux = 1530 lm Power consumption = 12.9 W Luminous efficacy = 118.6 lm/W	<b>serial documentation</b> <b>13.09.2023</b>



**Luminous intensity in cd/klm** C180-0 C190-10 C195-15 C270-90 **Imax: 832 cd/klm**



**Luminaire output ratios**

Eta	100.0%
Eta 0° - 90°	94.5%
Eta 90° - 180°	5.5%

**Luminous intensity class acc. to EN13201-2**

Class:	---
Imax 70°	832.2
Imax 80°	279.9
Imax 90°	35.4
Imax >90°	18.0
Imax >95°	13.5


**Measurement conditions**

DIN EN 13032 and DIN 5032

**Photometric test report**

<b>Family</b> DL 11 iQ	<b>Order number: 5XA5565BF14H000022</b> <b>EAN: 4058352955727</b>	<b>LP number</b> 59428_42
---------------------------	--	------------------------------

**Envelope curve in cd/klm**      **KMK 70°**    **KMK 67.5°**    **KMK 65°**    **KMK 62.5°**      **siteco**



## Photometric test report

<b>Family</b> DL 11 iQ	<b>Order number: 5XA5565BF14H000022</b> <b>EAN: 4058352955727</b>	<b>LP number</b> 59428_42
---------------------------	--	------------------------------



### Table of values for luminous intensities Maximum luminous intensity

C-planes	0° 180°	5° 175°	10° 170°	15° 165°	20° 160°	25° 155°	30° 150°	35° 145°	40° 140°	45° 135°	50° 130°	55° 125°	60° 120°
$\gamma$	Luminous intensity in cd/klm												
0,0°	6.9	6.9	6.9	6.9	6.9	6.9	6.9	6.9	6.9	6.9	6.9	6.9	6.9
2,5°	6.9	6.9	6.9	6.7	6.6	6.6	6.8	7.0	7.2	7.2	7.2	7.2	7.5
5,0°	9.8	9.8	9.6	9.6	9.7	9.8	9.9	10.2	10.6	11.1	11.2	11.3	11.5
7,5°	27.5	30.8	35.7	40.7	44.7	47.5	49.9	51.8	53.0	53.0	51.7	50.3	49.1
10,0°	114.3	123.5	128.7	134.8	139.6	143.2	143.9	145.2	148.5	149.5	147.2	146.8	148.8
12,5°	141.8	144.4	152.5	166.5	175.1	180.9	189.2	196.3	206.2	214.1	229.9	248.2	266.0
15,0°	195.8	198.5	215.6	223.5	236.2	250.8	266.4	281.8	304.0	315.4	329.0	341.0	347.8
17,5°	234.3	251.9	278.2	304.0	324.8	336.2	349.0	358.5	368.7	373.5	378.9	373.4	365.9
20,0°	272.1	303.7	334.2	349.6	364.3	368.1	368.5	364.0	370.4	377.2	381.0	380.6	375.7
22,5°	300.7	331.2	351.7	361.5	366.7	374.9	385.3	377.9	374.5	376.2	378.3	376.8	370.3
25,0°	315.0	334.9	348.4	359.7	362.6	362.3	367.0	368.8	367.6	361.6	363.8	368.1	357.5
27,5°	305.9	332.5	354.2	365.1	375.8	374.3	367.3	368.4	364.9	358.6	350.9	349.5	339.9
30,0°	336.2	352.4	359.2	367.8	369.6	373.2	374.6	365.1	356.7	352.9	340.3	334.6	321.6
32,5°	334.0	351.9	361.7	363.0	362.7	356.6	352.5	347.1	331.7	326.4	319.9	312.7	298.7
35,0°	327.6	346.7	359.6	368.0	371.3	372.3	362.7	360.0	341.6	322.6	308.2	291.9	272.9
37,5°	358.1	378.6	387.0	389.4	381.9	376.0	369.5	351.0	331.7	310.7	292.4	272.2	252.2
40,0°	362.2	386.0	393.8	389.1	383.3	369.5	358.9	340.7	317.3	293.8	269.5	247.5	226.8
42,5°	370.8	401.3	413.1	411.4	406.8	390.4	371.3	344.1	312.0	281.0	251.5	221.6	205.2
45,0°	387.3	409.6	433.8	429.3	405.7	380.2	361.1	331.1	292.5	263.7	234.8	207.5	193.5
47,5°	388.9	405.2	431.8	435.1	419.1	377.7	343.3	304.6	267.4	235.5	206.9	186.1	171.4
50,0°	407.3	429.3	445.3	465.1	451.7	393.5	338.7	289.2	246.1	215.9	183.9	168.4	157.3
52,5°	413.6	448.4	447.6	472.9	458.5	416.1	349.9	284.9	236.5	200.0	166.7	155.7	144.1
55,0°	436.8	472.9	470.1	487.6	458.4	428.6	360.3	290.9	236.5	189.8	158.8	151.8	128.4
57,5°	451.1	498.1	517.9	531.8	506.1	437.4	354.1	290.1	232.2	190.1	161.2	150.2	118.0
60,0°	491.1	536.4	585.5	588.0	561.2	465.4	362.5	299.9	247.6	197.6	163.2	142.1	116.3
62,5°	498.2	565.0	605.4	600.6	573.0	474.7	371.0	306.4	250.8	198.5	159.8	130.5	103.6
65,0°	537.2	635.1	653.9	603.6	548.0	459.1	377.0	306.3	244.6	197.0	149.4	115.3	85.1
67,5°	578.8	693.6	713.2	669.7	548.1	437.2	360.2	298.0	249.5	193.6	135.8	94.9	60.1
70,0°	666.8	766.2	832.2	706.0	514.5	387.5	296.6	252.4	227.8	190.7	132.2	84.5	48.1
72,5°	666.2	755.8	767.7	584.6	387.5	247.1	197.0	183.8	185.2	180.0	125.4	72.2	39.0
75,0°	603.5	656.1	563.3	341.2	213.7	157.3	137.9	120.3	123.5	128.0	92.9	55.3	29.0
77,5°	469.2	448.0	332.2	232.5	169.1	134.2	115.0	104.4	88.4	69.6	48.2	32.0	23.4
80,0°	279.9	234.8	188.4	184.6	145.7	96.6	85.6	87.0	60.7	46.1	34.6	24.7	19.4
82,5°	117.8	106.9	120.4	123.5	100.0	74.5	74.5	62.4	33.5	23.8	21.1	20.3	17.2
85,0°	52.7	58.8	72.4	91.3	83.5	60.2	54.4	41.0	23.7	17.9	15.6	15.2	15.1
87,5°	23.3	30.8	45.8	57.4	45.7	36.0	30.4	23.7	17.9	15.2	14.4	14.2	14.0
90,0°	16.5	21.6	31.6	35.4	24.5	19.0	18.7	15.9	14.5	14.1	13.8	13.7	13.5
92,5°	13.4	14.8	18.0	16.5	15.7	14.4	14.1	13.8	13.7	13.5	13.5	13.5	13.4
95,0°	12.6	13.0	13.3	13.6	13.5	13.5	13.5	13.4	13.3	13.3	13.2	13.1	13.0
97,5°	12.5	12.9	13.0	13.3	13.5	13.5	13.5	13.3	13.3	13.3	13.2	13.1	13.0
100,0°	12.4	12.9	13.0	13.3	13.3	13.5	13.5	13.3	13.3	13.3	13.3	13.1	13.0
102,5°	12.4	12.8	13.0	13.2	13.3	13.4	13.4	13.3	13.3	13.2	13.2	13.0	13.0
105,0°	12.4	12.7	13.0	13.1	13.1	13.2	13.2	13.2	13.1	13.2	13.0	13.0	13.0
107,5°	12.2	12.5	12.8	13.0	13.1	13.1	13.0	13.0	13.0	13.0	13.0	13.0	13.0
110,0°	12.0	12.4	12.6	12.8	12.8	12.9	12.8	12.9	12.9	12.9	12.7	12.7	12.7
112,5°	11.9	12.2	12.5	12.6	12.6	12.8	12.8	12.6	12.6	12.6	12.6	12.6	12.6

# Photometric test report

<b>Family</b> DL 11 iQ	<b>Order number: 5XA5565BF14H000022</b> <b>EAN: 4058352955727</b>	<b>LP number</b> 59428_42
---------------------------	--	------------------------------



## Table of values for luminous intensities Maximum luminous intensity

C-planes	65° 115°	70° 110°	75° 105°	80° 100°	85° 95°	90°	185° 355°	190° 350°	195° 345°	200° 340°	205° 335°	210° 330°	215° 325°
$\gamma$	Luminous intensity in cd/klm												
0,0°	6.9	6.9	6.9	6.9	6.9	6.9	6.9	6.9	6.9	6.9	6.9	6.9	6.9
2,5°	7.8	7.9	7.9	8.1	8.1	8.1	6.8	6.8	6.7	6.7	6.7	6.9	7.1
5,0°	11.5	11.3	11.2	11.0	10.7	10.6	9.9	10.0	9.7	9.0	8.3	7.9	7.6
7,5°	47.4	44.9	43.3	41.9	41.1	40.9	23.3	19.2	15.6	12.4	10.1	8.5	7.6
10,0°	152.1	153.9	155.0	157.1	158.2	158.9	103.1	91.6	78.7	64.8	50.4	36.5	25.9
12,5°	278.3	286.7	294.9	299.5	302.2	301.3	128.3	115.6	105.7	94.0	87.6	83.9	77.8
15,0°	361.3	362.0	352.3	342.3	332.5	327.7	185.4	166.3	163.0	149.7	135.1	120.2	101.7
17,5°	367.7	362.4	356.5	351.5	347.7	346.2	217.7	191.3	173.4	152.2	133.8	118.7	102.1
20,0°	373.2	372.0	363.7	355.4	354.7	356.1	248.8	225.6	203.9	181.9	151.4	129.9	108.6
22,5°	371.3	367.0	354.7	349.5	351.6	353.1	281.1	247.5	220.5	191.2	151.7	124.0	105.2
25,0°	353.9	349.5	339.0	335.3	338.6	341.1	292.2	266.0	230.3	195.6	158.6	125.5	104.1
27,5°	333.3	324.1	315.6	314.4	319.0	321.2	286.3	263.9	233.6	190.8	156.8	124.8	92.7
30,0°	307.7	295.9	289.6	290.8	295.9	297.3	313.1	282.2	240.3	188.7	153.2	116.9	77.3
32,5°	285.0	275.5	272.2	273.5	277.2	278.1	313.7	297.9	245.8	191.7	150.6	100.1	70.3
35,0°	259.4	254.7	255.2	257.8	259.9	260.1	306.1	281.1	230.5	183.9	140.9	92.6	69.8
37,5°	239.3	236.8	236.0	235.1	235.2	233.9	339.4	310.1	248.2	197.6	138.4	91.7	62.5
40,0°	217.4	215.5	211.6	208.5	206.5	205.9	342.8	306.9	245.9	189.7	128.4	86.8	53.2
42,5°	195.0	190.1	183.5	176.5	168.9	165.7	350.6	299.8	226.1	161.8	111.5	72.8	51.9
45,0°	181.5	169.1	156.6	145.7	136.2	131.7	371.0	313.3	230.2	143.3	92.8	61.0	54.6
47,5°	156.5	143.1	129.8	116.4	107.2	103.8	368.2	292.5	205.8	119.9	75.3	56.0	51.9
50,0°	140.7	124.3	108.7	94.7	85.1	81.6	367.1	275.7	178.1	101.9	62.9	53.2	50.0
52,5°	125.8	104.6	90.4	76.9	68.5	64.9	351.5	253.3	155.7	86.0	57.9	51.2	48.8
55,0°	107.9	88.1	75.2	61.0	54.4	52.6	362.3	250.7	145.3	79.6	56.9	49.7	47.6
57,5°	93.9	78.1	63.9	48.8	44.8	44.4	377.9	255.1	144.6	81.1	58.0	50.9	50.8
60,0°	90.8	64.7	49.4	40.1	38.6	38.5	387.6	245.6	138.3	79.9	58.2	53.3	53.0
62,5°	83.5	55.5	39.6	35.1	34.5	34.5	389.8	224.4	119.9	73.8	57.3	56.1	55.7
65,0°	60.3	43.0	32.9	31.0	30.9	30.8	412.3	224.0	109.6	69.7	59.8	60.1	59.8
67,5°	42.8	32.3	28.8	27.8	27.9	28.0	402.0	216.8	123.0	72.1	62.3	65.6	60.7
70,0°	34.2	27.7	25.7	25.3	25.5	25.6	417.3	207.0	133.3	81.0	69.7	68.5	61.7
72,5°	26.4	23.3	23.1	23.2	23.4	23.5	428.9	230.1	114.2	68.0	70.8	71.4	67.3
75,0°	21.3	21.0	21.2	21.2	21.1	21.2	448.1	242.7	92.2	64.1	67.5	66.1	60.6
77,5°	21.0	19.8	19.3	18.9	18.4	18.0	353.4	202.9	81.0	56.2	59.8	55.0	49.3
80,0°	18.6	18.1	17.4	16.8	16.3	16.1	257.2	196.9	114.0	54.7	53.3	45.8	35.2
82,5°	16.6	16.1	15.5	15.1	15.0	14.9	163.2	116.3	73.0	45.7	41.4	34.8	27.5
85,0°	15.0	14.8	14.4	14.2	14.1	14.1	61.4	61.1	49.9	40.2	30.8	26.4	23.5
87,5°	13.8	13.8	13.7	13.5	13.5	13.3	17.9	26.8	27.3	24.0	22.9	22.3	22.4
90,0°	13.5	13.4	13.3	13.2	13.0	12.8	14.8	15.1	16.7	17.3	18.4	18.3	18.4
92,5°	13.3	13.1	13.0	12.9	12.9	12.8	12.5	12.3	12.9	13.2	12.8	11.6	10.2
95,0°	13.0	13.0	13.0	12.9	12.8	12.8	12.2	11.7	11.1	10.6	10.1	9.4	8.8
97,5°	13.0	13.0	13.0	13.0	13.0	13.0	12.1	11.7	11.1	10.4	9.9	9.4	8.7
100,0°	13.1	13.0	13.0	13.1	13.0	13.1	12.0	11.7	11.1	10.5	9.9	9.4	8.8
102,5°	13.1	13.0	13.0	13.1	13.1	13.1	12.0	11.6	11.1	10.5	10.0	9.4	8.8
105,0°	13.0	13.0	13.0	13.0	13.0	13.0	12.0	11.6	11.1	10.4	9.9	9.4	8.8
107,5°	13.0	13.0	12.9	12.9	12.8	12.8	11.9	11.3	10.9	10.4	9.8	9.3	8.7
110,0°	12.8	12.8	12.8	12.8	12.8	12.8	11.7	11.3	10.8	10.3	9.8	9.2	8.7
112,5°	12.6	12.6	12.5	12.5	12.4	12.4	11.5	11.2	10.7	10.3	9.8	9.1	8.7

## Photometric test report

Family <b>DL 11 iQ</b>	Order number: <b>5XA5565BF14H000022</b> EAN: <b>4058352955727</b>	LP number <b>59428_42</b>
<b>Table of values for luminous intensities</b>		<b>Maximum luminous intensity</b>
		<b>siteco</b>

C-planes	220° 320°	225° 315°	230° 310°	235° 305°	240° 300°	245° 295°	250° 290°	255° 285°	260° 280°	265° 275°	270°	Phi-zone	Total Phi-zone
$\gamma$	Luminous intensity in cd/klm											Luminous flux in lm/klm	
0,0°	6.9	6.9	6.9	6.9	6.9	6.9	6.9	6.9	6.9	6.9	6.9	0.0	0.0
2,5°	7.1	7.2	7.6	8.0	8.3	8.2	7.7	7.5	7.5	7.4	7.3	0.1	0.1
5,0°	7.4	7.4	7.1	6.7	6.2	6.1	6.0	5.8	5.7	5.6	5.4	0.2	0.3
7,5°	6.8	6.4	6.2	6.0	6.1	6.1	6.0	5.9	5.8	5.8	5.8	1.0	1.3
10,0°	17.8	13.1	10.4	9.0	8.0	7.1	6.6	6.4	6.1	5.9	5.8	4.2	5.5
12,5°	68.7	55.8	43.0	30.1	20.0	14.1	10.5	8.3	7.2	6.6	6.4	8.4	13.9
15,0°	87.3	77.4	73.0	66.8	57.1	45.5	35.5	28.2	23.3	19.9	18.9	13.7	27.6
17,5°	88.8	77.7	70.9	64.8	60.2	55.5	50.2	47.2	52.0	54.9	54.6	18.3	46.0
20,0°	92.9	80.5	72.9	66.6	62.0	61.8	55.9	48.5	57.0	64.6	65.4	22.3	68.2
22,5°	89.4	72.0	61.6	56.7	57.0	59.4	55.3	44.7	50.9	56.2	56.8	25.2	93.4
25,0°	80.1	58.2	51.7	50.9	52.5	54.1	50.6	40.9	44.3	48.8	49.5	27.2	120.6
27,5°	67.3	51.9	48.0	47.6	48.7	49.7	47.0	37.7	39.7	43.4	44.1	28.9	149.6
30,0°	60.1	49.7	45.8	45.3	45.9	45.9	43.3	35.6	36.6	39.0	39.8	30.7	180.3
32,5°	57.5	46.8	43.9	43.8	43.8	43.0	40.4	34.0	33.7	35.6	36.1	31.7	212.0
35,0°	50.4	43.4	42.8	42.2	41.5	40.6	38.1	32.7	31.5	32.8	33.3	32.9	244.9
37,5°	46.5	43.7	41.5	40.8	40.1	38.5	35.6	30.6	29.2	30.2	30.4	34.9	279.8
40,0°	46.0	44.9	43.4	41.2	38.7	36.8	33.7	28.8	26.8	27.3	27.4	35.4	315.3
42,5°	47.0	45.1	43.7	41.4	39.2	36.2	31.9	27.2	24.7	25.1	25.1	36.1	351.4
45,0°	50.5	47.0	45.2	42.5	39.4	35.7	31.7	26.9	23.7	23.3	23.3	36.8	388.2
47,5°	50.4	50.9	50.2	46.3	41.2	36.2	31.1	26.9	23.8	22.4	21.8	36.1	424.3
50,0°	49.3	49.8	49.8	47.1	41.7	35.7	30.3	26.4	24.2	24.8	25.7	36.6	460.9
52,5°	48.7	48.6	47.7	43.6	38.2	33.5	29.2	26.5	26.0	25.8	25.8	36.7	497.6
55,0°	47.1	46.9	45.6	41.6	37.7	33.2	27.2	24.2	22.3	20.7	20.4	37.6	535.2
57,5°	49.1	47.7	47.0	42.1	35.8	29.6	24.4	21.0	19.3	18.2	18.2	39.5	574.7
60,0°	50.1	44.7	41.3	36.6	31.4	26.9	22.7	19.6	17.8	16.9	16.9	42.2	616.9
62,5°	52.3	44.0	38.6	34.3	29.6	25.3	21.5	18.6	16.9	16.0	16.0	43.1	660.0
65,0°	54.1	43.3	35.7	31.5	27.4	23.6	20.0	17.4	15.8	15.0	15.0	44.2	704.3
67,5°	53.8	42.7	33.1	28.5	24.8	21.7	18.6	16.2	14.7	13.8	13.6	45.6	749.9
70,0°	56.0	43.2	30.6	25.6	22.4	19.8	17.2	15.0	13.6	12.8	12.4	46.9	796.8
72,5°	58.5	45.2	28.8	23.1	20.3	17.9	15.7	13.8	12.5	11.5	11.1	42.3	839.1
75,0°	53.7	41.2	26.4	21.3	18.5	16.1	14.0	12.5	11.1	10.2	9.9	33.9	873.0
77,5°	37.7	28.4	22.9	19.4	16.8	14.7	12.8	11.4	10.1	9.1	8.8	25.4	898.4
80,0°	26.3	23.4	20.4	17.6	15.3	13.4	11.8	10.5	9.2	8.3	8.0	18.8	917.2
82,5°	23.3	22.2	18.1	15.6	13.7	12.3	11.1	9.5	8.3	7.5	7.4	12.3	929.5
85,0°	23.4	21.3	15.7	13.3	12.0	10.8	9.7	8.4	7.5	6.9	6.7	8.4	937.9
87,5°	23.7	18.6	13.5	11.2	10.1	9.1	8.1	7.3	6.7	6.2	6.1	5.5	943.4
90,0°	18.6	13.7	10.6	9.1	8.0	7.1	6.7	6.1	5.7	5.3	5.1	4.1	947.5
92,5°	9.0	8.0	7.3	6.6	5.9	5.5	5.1	4.7	4.4	4.3	4.1	3.1	950.6
95,0°	8.2	7.6	6.9	6.4	6.0	5.5	5.1	4.8	4.5	4.3	4.1	2.9	953.5
97,5°	8.1	7.6	6.9	6.4	5.9	5.5	5.1	4.8	4.5	4.3	4.1	2.8	956.3
100,0°	8.2	7.6	6.9	6.4	6.0	5.5	5.1	4.8	4.5	4.3	4.1	2.8	959.1
102,5°	8.2	7.6	7.1	6.5	6.0	5.6	5.2	4.8	4.5	4.4	4.1	2.8	962.0
105,0°	8.2	7.6	7.0	6.4	6.0	5.6	5.2	4.8	4.5	4.3	4.1	2.8	964.7
107,5°	8.1	7.6	7.1	6.5	6.0	5.6	5.1	4.8	4.6	4.5	4.2	2.7	967.4
110,0°	8.1	7.5	7.0	6.5	6.0	5.6	5.3	4.9	4.6	4.5	4.2	2.6	970.1
112,5°	8.1	7.5	7.1	6.4	6.0	5.6	5.3	5.0	4.7	4.6	4.4	2.6	972.6

## Photometric test report

<b>Family</b> DL 11 iQ	<b>Order number: 5XA5565BF14H000022</b> <b>EAN: 4058352955727</b>	<b>LP number</b> 59428_42
<b>Table of values for luminous intensities</b>		<b>Maximum luminous intensity</b>
		<b>siteco</b>

C-planes	0° 180°	5° 175°	10° 170°	15° 165°	20° 160°	25° 155°	30° 150°	35° 145°	40° 140°	45° 135°	50° 130°	55° 125°	60° 120°
$\gamma$	Luminous intensity in cd/klm												
115,0°	11.9	12.0	12.3	12.4	12.5	12.6	12.5	12.6	12.5	12.6	12.6	12.5	12.4
117,5°	11.6	11.9	12.0	12.3	12.3	12.3	12.3	12.3	12.3	12.3	12.3	12.3	12.3
120,0°	11.4	11.6	11.9	11.9	12.0	12.1	12.1	12.0	12.0	12.0	12.0	11.9	11.9
122,5°	11.1	11.3	11.5	11.6	11.6	11.6	11.6	11.6	11.6	11.6	11.7	11.7	11.7
125,0°	10.8	10.9	11.1	11.3	11.3	11.3	11.3	11.3	11.3	11.3	11.3	11.3	11.3
127,5°	10.4	10.6	10.8	10.9	10.9	10.9	10.9	10.9	10.9	11.0	11.0	10.9	10.9
130,0°	9.9	10.1	10.3	10.5	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6
132,5°	9.5	9.6	9.8	9.9	10.0	10.1	10.2	10.3	10.2	10.3	10.3	10.3	10.3
135,0°	8.9	9.1	9.4	9.5	9.6	9.7	9.8	9.8	9.8	9.9	9.8	9.9	9.9
137,5°	8.5	8.7	8.9	9.0	9.1	9.3	9.3	9.4	9.4	9.5	9.5	9.5	9.6
140,0°	8.0	8.2	8.4	8.5	8.7	8.7	8.8	9.0	9.1	9.1	9.1	9.1	9.1
142,5°	7.7	7.8	8.1	8.1	8.4	8.4	8.4	8.5	8.6	8.7	8.7	8.7	8.7
145,0°	7.2	7.4	7.6	7.7	7.8	7.9	8.1	8.1	8.1	8.4	8.4	8.4	8.4
147,5°	6.7	6.9	7.1	7.2	7.4	7.4	7.5	7.7	7.7	7.7	7.7	7.8	7.9
150,0°	5.9	6.1	6.3	6.4	6.6	6.7	6.7	6.9	7.1	7.1	7.1	7.1	7.1
152,5°	5.0	5.2	5.4	5.4	5.6	5.7	5.8	5.9	6.1	6.1	6.1	6.1	6.1
155,0°	3.9	3.9	4.1	4.2	4.3	4.4	4.5	4.6	4.7	4.8	4.8	4.8	4.9
157,5°	2.7	2.9	2.9	3.1	3.2	3.2	3.3	3.4	3.4	3.5	3.5	3.5	3.6
160,0°	2.0	2.0	2.1	2.2	2.2	2.3	2.3	2.4	2.4	2.4	2.4	2.4	2.4
162,5°	1.7	1.7	1.7	1.7	1.9	1.9	1.9	2.0	2.0	2.0	2.0	2.0	2.0
165,0°	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.9	2.0	1.8	1.9	2.0
167,5°	1.4	1.4	1.5	1.5	1.6	1.7	1.7	1.7	1.9	1.8	1.8	1.8	1.9
170,0°	1.3	1.3	1.3	1.3	1.3	1.4	1.4	1.3	1.3	1.5	1.5	1.4	1.4
172,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

## Photometric test report

Family DL 11 iQ	Order number: 5XA5565BF14H000022 EAN: 4058352955727	LP number 59428_42
Table of values for luminous intensities		Maximum luminous intensity
		<b>siteco</b>

C-planes	65° 115°	70° 110°	75° 105°	80° 100°	85° 95°	90°	185° 355°	190° 350°	195° 345°	200° 340°	205° 335°	210° 330°	215° 325°
$\gamma$	Luminous intensity in cd/klm												
115,0°	12.5	12.5	12.4	12.4	12.4	12.4	11.5	11.1	10.6	10.2	9.7	9.1	8.7
117,5°	12.3	12.2	12.1	12.1	12.1	12.1	11.3	10.9	10.5	10.1	9.7	9.1	8.6
120,0°	12.1	12.0	12.0	12.0	12.1	12.1	11.1	10.8	10.4	9.9	9.5	9.1	8.5
122,5°	11.7	11.8	11.7	11.8	11.8	11.8	10.8	10.4	10.1	9.8	9.4	8.9	8.4
125,0°	11.3	11.3	11.3	11.4	11.4	11.4	10.5	10.2	9.8	9.5	9.2	8.7	8.2
127,5°	11.0	11.0	11.0	11.1	11.0	11.1	10.1	9.9	9.5	9.2	8.9	8.5	8.1
130,0°	10.7	10.7	10.6	10.7	10.7	10.7	9.7	9.5	9.2	8.8	8.5	8.2	7.8
132,5°	10.3	10.3	10.2	10.3	10.3	10.3	9.2	8.9	8.7	8.4	8.2	7.8	7.4
135,0°	10.0	10.0	9.9	9.8	9.9	9.8	8.7	8.5	8.2	8.0	7.7	7.4	7.0
137,5°	9.6	9.6	9.5	9.5	9.5	9.4	8.2	8.0	7.8	7.5	7.3	7.0	6.8
140,0°	9.2	9.2	9.1	9.1	9.1	9.1	7.8	7.6	7.4	7.1	7.0	6.7	6.4
142,5°	8.7	8.7	8.7	8.7	8.7	8.7	7.5	7.2	7.0	6.8	6.6	6.4	6.1
145,0°	8.5	8.4	8.4	8.4	8.4	8.4	7.1	6.8	6.6	6.4	6.1	6.0	5.8
147,5°	8.1	8.1	8.1	8.1	8.1	8.1	6.5	6.4	6.1	5.9	5.7	5.6	5.4
150,0°	7.3	7.4	7.4	7.4	7.4	7.4	5.7	5.7	5.4	5.2	5.0	4.9	4.7
152,5°	6.4	6.3	6.4	6.4	6.4	6.4	4.8	4.7	4.5	4.3	4.2	4.1	3.9
155,0°	5.0	5.0	5.0	5.0	5.0	5.0	3.7	3.6	3.5	3.2	3.1	3.1	2.9
157,5°	3.7	3.7	3.7	3.7	3.7	3.7	2.7	2.6	2.5	2.4	2.4	2.4	2.2
160,0°	2.4	2.4	2.4	2.4	2.4	2.4	2.0	2.0	1.9	1.8	1.9	1.8	1.7
162,5°	2.0	2.0	2.0	2.0	2.0	2.0	1.7	1.7	1.7	1.7	1.7	1.7	1.7
165,0°	1.9	1.7	1.7	1.7	1.7	1.7	1.6	1.7	1.6	1.5	1.6	1.4	1.3
167,5°	1.9	1.8	1.7	1.7	1.7	1.7	1.4	1.4	1.4	1.3	1.4	1.4	1.3
170,0°	1.6	1.5	1.4	1.5	1.6	1.5	1.3	1.3	1.3	1.3	1.3	1.3	1.3
172,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

## Photometric test report

Family DL 11 iQ	Order number: 5XA5565BF14H000022 EAN: 4058352955727	LP number 59428_42
Table of values for luminous intensities		Maximum luminous intensity
		<b>sITeco</b>

C-planes	220° 320°	225° 315°	230° 310°	235° 305°	240° 300°	245° 295°	250° 290°	255° 285°	260° 280°	265° 275°	270°	Phi-zone	Total Phi-zone
$\gamma$	Luminous intensity in cd/klm											Luminous flux in lm/klm	
115,0°	8.1	7.6	7.1	6.5	6.0	5.6	5.3	5.0	4.8	4.6	4.4	2.5	975.1
117,5°	8.1	7.5	7.0	6.5	6.1	5.6	5.3	5.0	4.8	4.7	4.5	2.4	977.6
120,0°	7.9	7.5	7.0	6.5	6.1	5.7	5.4	5.1	4.8	4.7	4.5	2.3	979.9
122,5°	7.9	7.3	6.8	6.5	6.1	5.7	5.4	5.1	4.8	4.7	4.5	2.2	982.1
125,0°	7.8	7.3	6.8	6.4	6.1	5.7	5.4	5.1	4.9	4.8	4.6	2.1	984.2
127,5°	7.6	7.2	6.8	6.4	6.0	5.7	5.4	5.1	4.9	4.8	4.7	2.0	986.2
130,0°	7.5	7.1	6.7	6.3	5.9	5.6	5.4	5.1	4.9	4.8	4.7	1.9	988.0
132,5°	7.1	6.7	6.3	6.0	5.8	5.5	5.1	4.9	4.7	4.7	4.6	1.7	989.8
135,0°	6.7	6.4	6.0	5.7	5.5	5.3	5.0	4.8	4.7	4.5	4.4	1.6	991.3
137,5°	6.5	6.1	5.8	5.6	5.3	5.1	4.9	4.7	4.6	4.5	4.4	1.4	992.8
140,0°	6.1	5.9	5.6	5.4	5.1	5.0	4.8	4.6	4.4	4.4	4.4	1.3	994.1
142,5°	6.0	5.7	5.5	5.2	5.0	4.8	4.7	4.5	4.4	4.3	4.4	1.2	995.3
145,0°	5.7	5.4	5.2	5.0	5.0	4.7	4.6	4.4	4.3	4.2	4.3	1.1	996.3
147,5°	5.3	5.1	4.8	4.7	4.5	4.3	4.2	4.1	4.0	4.0	4.0	0.9	997.3
150,0°	4.5	4.4	4.2	4.0	3.9	3.7	3.6	3.4	3.4	3.4	3.4	0.8	998.1
152,5°	3.7	3.6	3.5	3.2	3.1	3.0	3.0	2.8	2.7	2.7	2.7	0.6	998.7
155,0°	2.9	2.7	2.6	2.4	2.4	2.4	2.4	2.4	2.4	2.3	2.2	0.4	999.1
157,5°	2.2	2.1	2.0	2.0	2.0	2.0	2.0	1.9	2.0	2.0	2.0	0.3	999.4
160,0°	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	0.2	999.6
162,5°	1.7	1.6	1.6	1.4	1.4	1.3	1.4	1.4	1.5	1.5	1.5	0.1	999.7
165,0°	1.4	1.5	1.4	1.3	1.3	1.3	1.4	1.4	1.5	1.5	1.5	0.1	999.8
167,5°	1.3	1.3	1.3	1.4	1.5	1.4	1.4	1.4	1.3	1.3	1.3	0.1	999.9
170,0°	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	0.1	1000.0
172,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
177,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

## Photometric test report

Family DL 11 iQ	Order number: 5XA5565BF14H000022 EAN: 4058352955727	LP number 59428_42
--------------------	--	-----------------------

Dimming levels table	environmental temperature: 25°C	siteco
----------------------	---------------------------------	--------

Luminous flux [%]	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]start of lifetime	Power consumption [W]end of lifetime	Power consumption [W]average
100	254	254	1530	12.9	13.3	13.1
95	241	252	1452	12.2	12.6	12.4
90	229	250	1379	11.5	11.9	11.7
85	216	248	1301	10.7	11.1	10.9
80	203	246	1223	10.1	10.5	10.3
75	190	243	1144	9.4	9.8	9.6
70	178	241	1072	8.9	9.1	9.0
65	165	238	994	8.2	8.4	8.3
60	152	235	916	7.6	7.8	7.7
55	140	232	843	7.0	7.2	7.1
50	127	229	765	6.4	6.6	6.5
45	114	225	687	5.8	6.0	5.9
40	102	221	614	5.3	5.4	5.4
35	89	216	536	4.8	4.9	4.8
30	76	210	458	4.3	4.3	4.3
25	63	203	379	3.7	3.8	3.8
24	60	201	361	3.5	3.7	3.6