

Photometric test report

Family
CITY-LIGHT PLUS LED

Order number: 5XA5275EV14H000022
EAN: 4069025025777

LP number
57130_77

serial
documentation
11.10.2023

siteco



Version post-top- or mounting to wall arm, Smart Interface up

Optic direct, symmetric wide distribution S120011

Cover cover transparent, PMMA

Lamps LED 3000 K | CRI ≥ 70

Controlgear EVG SITECO iQ - Smart Interface

Rated values Net luminous flux = 1460 lm
Power consumption = 10.7 W
Luminous efficacy = 136.5 lm/W

Luminous intensity in cd/klm


C180-0

C205-25

C210-30

C270-90

Imax: 814 cd/klm



Luminaire output ratios

Eta	100.0%
Eta 0° - 90°	97.4%
Eta 90° - 180°	2.6%

Luminous intensity class acc. to EN13201-2

Class:	G1
Imax 70°	727.6
Imax 80°	157.2
Imax 90°	13.4
Imax >90°	12.4
Imax >95°	10.3

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family
CITY-LIGHT PLUS LED

Order number: **5XA5275EV14H000022**
EAN: **4069025025777**

LP number
57130_77

Envelope curve in cd/klm


KMK 67.5°

KMK 65°

KMK 62.5°

KMK 60°

siteco



Photometric test report

Family CITY-LIGHT PLUS LED	Order number: 5XA5275EV14H000022 EAN: 4069025025777	LP number 57130_77
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes	0° 180°	5° 175°	10° 170°	15° 165°	20° 160°	25° 155°	30° 150°	35° 145°	40° 140°	45° 135°	50° 130°	55° 125°	60° 120°
γ	Luminous intensity in cd/klm												
0,0°	7.2	7.2	7.2	7.2	7.2	7.2	7.2	7.2	7.2	7.2	7.2	7.2	7.2
2,5°	6.9	6.9	6.9	6.9	7.2	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6
5,0°	7.9	8.2	8.2	8.9	9.3	10.0	10.0	10.3	10.6	11.0	11.7	12.7	13.4
7,5°	16.5	19.2	20.3	19.6	17.8	15.8	14.4	14.1	15.8	18.2	21.3	25.7	29.5
10,0°	24.7	23.7	24.7	26.8	24.4	21.6	17.5	17.2	24.7	36.0	45.3	49.8	46.7
12,5°	47.4	52.5	58.0	59.7	67.3	63.2	52.5	49.1	59.4	67.6	70.0	71.0	72.4
15,0°	65.2	66.6	67.6	70.4	78.9	71.7	59.7	52.2	64.9	85.5	107.4	108.5	116.4
17,5°	96.8	107.8	123.9	109.1	107.4	110.9	112.9	105.7	93.7	105.4	136.9	149.6	150.0
20,0°	116.7	112.2	152.0	127.7	143.1	136.3	134.2	126.3	103.3	122.9	157.9	160.3	174.0
22,5°	158.6	162.3	185.7	176.1	163.7	156.5	155.1	143.1	115.7	129.1	172.6	182.9	206.6
25,0°	152.0	153.1	177.8	189.8	186.0	174.4	179.9	182.3	123.6	144.2	182.6	188.1	226.2
27,5°	178.1	167.5	188.8	190.8	181.9	170.2	193.6	207.0	127.0	163.4	205.2	200.4	242.7
30,0°	191.9	196.0	216.9	229.6	216.6	205.6	203.9	213.8	137.3	186.0	244.4	224.1	256.7
32,5°	210.1	204.2	226.9	244.4	241.6	226.2	237.5	245.8	151.4	216.9	281.8	263.6	281.8
35,0°	238.2	229.6	243.0	254.7	237.2	235.8	282.8	290.0	164.1	229.3	310.3	300.7	313.4
37,5°	268.1	268.1	281.4	290.0	273.2	254.0	286.3	289.0	173.3	260.5	327.4	339.8	352.8
40,0°	277.7	278.0	282.1	307.2	303.4	297.6	316.8	312.3	188.1	297.6	353.9	356.6	384.4
42,5°	303.8	285.2	313.4	313.0	320.2	318.5	361.4	339.5	204.2	326.1	399.5	384.8	401.9
45,0°	314.4	305.1	341.2	341.5	345.6	335.0	377.2	370.3	221.4	339.5	427.3	407.8	412.6
47,5°	328.1	318.2	397.1	396.1	400.5	369.3	411.5	390.9	240.9	358.3	445.5	428.0	418.1
50,0°	327.1	339.5	435.6	440.0	452.4	422.5	477.1	435.2	255.0	363.5	447.9	432.8	415.6
52,5°	341.2	348.4	457.5	468.8	511.1	488.8	546.1	465.8	273.6	354.6	452.4	445.2	411.2
55,0°	348.0	370.3	458.2	509.7	574.6	582.1	613.0	491.2	296.9	347.3	442.8	446.5	399.9
57,5°	349.4	394.4	486.7	579.4	663.8	667.6	671.7	485.7	311.3	340.1	439.0	446.9	384.1
60,0°	312.7	393.7	522.0	628.8	712.9	727.3	697.4	486.7	311.0	315.1	416.0	417.7	356.3
62,5°	260.5	360.0	510.7	633.6	724.9	753.7	700.5	482.9	331.9	299.3	395.7	390.6	323.0
65,0°	219.7	314.4	453.4	556.0	667.6	781.9	746.9	465.8	326.4	280.8	371.4	360.0	287.6
67,5°	202.8	306.8	446.5	513.5	639.1	814.1	702.2	434.5	327.1	262.2	341.2	328.5	244.0
70,0°	227.9	334.0	444.5	502.5	606.5	727.6	627.8	370.0	293.5	220.7	302.0	290.0	202.8
72,5°	243.0	353.5	427.0	486.7	580.4	652.1	537.5	327.8	258.1	176.1	246.1	235.8	163.0
75,0°	191.2	298.6	370.0	416.7	509.7	538.5	441.0	228.6	168.5	86.5	181.9	193.2	141.1
77,5°	145.5	211.1	248.8	284.5	321.9	316.8	277.7	150.0	80.3	70.0	153.1	175.7	125.6
80,0°	81.7	93.0	127.7	154.5	157.2	148.3	145.2	68.0	48.7	52.2	79.3	87.9	55.3
82,5°	47.7	52.9	63.2	81.3	74.8	60.4	73.8	40.5	52.2	35.7	35.0	27.5	20.3
85,0°	22.7	24.4	29.9	31.9	25.7	28.5	33.6	18.5	27.5	19.9	14.8	15.4	15.1
87,5°	17.2	16.1	17.5	18.2	16.8	18.5	19.2	15.1	15.4	14.4	11.3	13.0	13.0
90,0°	11.7	11.3	12.7	13.4	13.0	12.7	12.4	11.7	10.3	8.9	9.6	11.0	11.7
92,5°	10.6	10.6	11.7	12.4	12.0	11.7	11.7	11.0	9.3	8.6	8.6	10.3	11.0
95,0°	10.0	10.0	10.6	11.3	11.0	10.6	10.3	10.0	8.9	7.9	8.2	9.6	10.3
97,5°	9.3	9.3	10.0	10.3	10.0	9.6	9.6	8.9	8.2	7.6	7.6	8.9	9.6
100,0°	8.6	8.6	9.3	9.3	9.3	8.9	8.9	8.6	7.9	7.2	7.2	8.2	8.9
102,5°	7.9	8.2	8.6	8.6	8.6	8.2	8.2	7.9	7.2	6.9	6.9	7.9	8.2
105,0°	7.6	7.9	7.9	8.2	7.9	7.6	7.6	7.2	6.9	6.9	6.9	7.6	7.6
107,5°	7.2	7.2	7.6	7.6	7.2	7.2	7.2	6.9	6.5	6.2	6.2	6.9	7.6
110,0°	6.5	6.9	7.2	6.9	6.9	6.5	6.5	6.2	6.2	6.2	6.2	6.2	6.9
112,5°	6.2	6.2	6.5	6.5	6.2	6.2	6.2	5.8	5.8	5.8	5.8	6.2	6.9

Photometric test report

Family CITY-LIGHT PLUS LED	Order number: 5XA5275EV14H000022 EAN: 4069025025777	LP number 57130_77
Table of values for luminous intensities		Maximum luminous intensity

siteco

C-planes	65° 115°	70° 110°	75° 105°	80° 100°	85° 95°	90°	185° 355°	190° 350°	195° 345°	200° 340°	205° 335°	210° 330°	215° 325°
γ	Luminous intensity in cd/klm												
0,0°	7.2	7.2	7.2	7.2	7.2	7.2	7.2	7.2	7.2	7.2	7.2	7.2	7.2
2,5°	7.9	8.2	8.2	7.9	8.2	8.2	6.9	6.9	6.9	6.9	7.2	6.9	7.6
5,0°	13.7	14.1	13.7	14.1	13.7	13.7	7.9	7.9	7.9	7.9	7.6	7.6	7.6
7,5°	30.2	33.0	35.7	38.1	37.1	35.7	13.7	12.0	10.6	9.6	8.9	8.6	8.6
10,0°	40.8	45.0	58.3	59.0	54.2	50.8	26.4	29.2	27.8	23.0	17.8	13.4	11.0
12,5°	77.6	83.7	100.6	104.3	105.4	107.1	38.8	34.7	25.4	23.7	24.4	27.1	27.5
15,0°	127.7	106.7	99.5	125.3	133.5	131.8	64.2	60.8	55.9	66.9	57.0	49.4	47.4
17,5°	148.3	157.5	167.2	190.5	196.3	211.4	87.9	86.8	96.1	71.0	64.9	65.2	59.0
20,0°	190.5	194.3	199.8	209.7	232.7	236.8	117.7	113.6	100.9	85.5	60.4	62.1	58.7
22,5°	221.7	228.2	239.2	254.7	261.5	263.6	140.4	122.5	119.4	108.8	83.4	75.9	55.3
25,0°	252.3	255.7	255.7	258.1	263.3	265.0	135.2	130.8	127.3	115.7	92.7	74.1	55.9
27,5°	267.4	267.7	268.1	274.9	277.3	277.3	170.6	140.7	121.8	117.7	91.0	81.3	62.5
30,0°	296.2	294.1	288.3	288.3	291.1	293.8	176.8	157.9	136.6	123.9	100.6	80.0	58.3
32,5°	315.4	316.1	305.5	303.4	305.1	304.8	196.3	173.0	148.3	127.0	102.3	89.6	71.7
35,0°	338.4	340.8	327.8	318.5	321.9	327.4	212.5	177.1	152.0	133.5	101.3	96.8	86.8
37,5°	364.9	361.4	338.8	335.3	341.2	343.9	239.2	189.5	157.5	136.6	98.2	88.9	88.9
40,0°	381.0	366.2	350.1	348.4	352.5	355.6	249.5	201.5	165.4	133.2	91.6	85.8	90.3
42,5°	396.4	375.5	355.2	356.6	361.1	363.8	285.2	215.2	176.8	129.1	81.3	84.1	89.6
45,0°	411.5	382.7	361.1	362.8	366.6	369.3	304.8	231.0	174.4	117.7	74.1	83.4	89.6
47,5°	413.2	375.8	360.7	364.5	369.3	371.4	315.1	237.2	175.7	98.5	65.6	79.3	84.4
50,0°	399.5	365.9	355.9	361.1	367.6	370.0	309.9	239.2	168.9	84.4	61.4	76.2	77.9
52,5°	378.6	344.6	342.5	353.2	361.4	363.1	315.4	236.1	166.5	70.0	62.1	71.7	71.7
55,0°	351.8	319.5	321.6	334.3	347.3	352.2	309.9	233.4	151.4	68.6	61.1	69.3	66.2
57,5°	320.9	285.9	291.4	306.5	323.0	329.5	295.2	204.6	121.2	62.8	59.4	65.9	60.4
60,0°	290.7	250.9	248.5	266.7	286.9	294.5	239.6	165.1	94.4	61.8	53.9	62.1	53.9
62,5°	250.9	212.1	202.5	214.5	234.1	246.4	188.8	127.3	69.0	57.7	51.1	55.3	46.7
65,0°	211.1	170.6	159.3	163.0	173.7	181.9	153.1	99.2	65.2	56.6	49.8	52.5	40.8
67,5°	168.2	126.0	114.3	116.7	120.5	120.1	140.4	91.3	72.1	60.4	50.8	48.1	36.0
70,0°	138.3	97.8	76.9	73.8	76.5	76.9	155.8	99.2	79.3	62.1	49.8	45.3	31.9
72,5°	108.5	73.8	47.4	44.3	44.3	46.0	147.9	94.4	73.8	59.4	51.5	46.7	28.8
75,0°	86.5	54.2	35.4	31.2	29.9	29.5	99.5	72.8	60.8	50.5	48.4	45.3	28.5
77,5°	63.5	31.6	26.4	23.7	22.7	22.7	77.9	58.3	51.8	44.6	43.2	39.8	26.8
80,0°	32.3	20.6	19.9	19.2	18.5	18.5	55.3	47.0	44.6	39.5	35.7	33.0	24.7
82,5°	16.8	15.8	15.4	15.8	15.8	15.8	37.8	35.4	34.3	30.9	28.8	26.4	20.6
85,0°	14.1	13.7	14.1	14.1	13.7	13.7	22.0	24.0	26.8	27.1	24.0	21.6	18.9
87,5°	13.0	13.0	13.0	13.0	13.0	13.0	17.8	18.9	19.9	18.9	17.2	16.5	15.1
90,0°	11.7	11.7	11.7	11.7	11.7	11.7	12.0	12.0	11.7	11.3	11.0	10.6	10.0
92,5°	11.0	11.0	11.3	11.3	11.0	11.0	11.0	10.6	10.6	10.0	10.0	9.3	8.9
95,0°	10.3	10.3	10.6	10.3	10.3	10.3	10.0	10.0	9.3	9.3	8.6	8.2	7.9
97,5°	9.6	9.6	9.6	10.0	9.6	9.6	9.3	8.9	8.6	8.2	7.9	7.6	7.2
100,0°	8.9	9.3	9.6	9.3	8.9	8.9	8.6	8.2	7.9	7.9	7.2	6.9	6.5
102,5°	8.9	8.9	8.9	8.9	8.9	8.9	7.9	7.9	7.6	7.2	6.9	6.5	6.2
105,0°	8.2	8.2	8.2	8.2	8.2	8.2	7.2	7.2	6.9	6.5	6.2	6.2	5.8
107,5°	7.6	7.6	8.2	8.2	7.9	7.6	6.9	6.9	6.5	6.2	5.8	5.5	5.1
110,0°	7.6	7.6	7.6	7.6	7.6	6.9	6.5	6.2	6.2	5.8	5.5	5.1	4.8
112,5°	6.9	6.9	7.6	7.6	7.2	6.2	6.2	5.8	5.5	5.5	5.1	4.8	4.8

Photometric test report

Family CITY-LIGHT PLUS LED	Order number: 5XA5275EV14H000022 EAN: 4069025025777	LP number 57130_77
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes	220° 320°	225° 315°	230° 310°	235° 305°	240° 300°	245° 295°	250° 290°	255° 285°	260° 280°	265° 275°	270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm											Luminous flux in lm/klm	
0,0°	7.2	7.2	7.2	7.2	7.2	7.2	7.2	7.2	7.2	7.2	7.2	0.0	0.0
2,5°	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.2	7.2	7.6	0.1	0.1
5,0°	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.2	7.2	7.6	0.2	0.3
7,5°	8.2	8.2	8.2	8.2	8.2	8.2	8.2	7.6	7.6	7.2	7.6	0.6	0.9
10,0°	9.6	9.3	8.9	8.9	8.9	8.9	8.2	7.9	7.6	7.2	7.6	1.2	2.1
12,5°	23.3	17.5	12.0	10.0	9.3	9.3	8.6	7.9	7.2	7.2	7.6	2.7	4.8
15,0°	34.0	34.3	29.9	26.1	17.2	11.3	10.3	8.9	7.9	7.6	7.6	4.5	9.3
17,5°	42.6	32.3	25.1	22.3	20.9	20.3	15.1	14.1	13.0	9.3	8.9	7.4	16.7
20,0°	45.6	36.0	28.8	26.4	27.8	17.5	12.4	16.5	23.3	25.7	26.8	9.9	26.5
22,5°	41.2	31.2	26.8	26.8	26.8	20.9	15.8	24.4	26.1	22.3	22.7	12.9	39.4
25,0°	39.1	29.9	25.7	23.7	25.1	21.6	18.5	26.8	30.5	32.6	33.0	15.1	54.5
27,5°	42.2	33.3	26.8	27.8	28.8	25.7	25.7	28.8	27.1	29.2	30.9	17.6	72.1
30,0°	43.6	38.8	33.3	30.9	27.8	25.7	27.8	33.0	29.9	28.8	28.8	20.9	93.1
32,5°	62.5	54.2	40.5	34.7	31.6	29.2	27.1	31.2	28.5	27.5	28.1	24.6	117.7
35,0°	83.4	70.4	57.3	50.5	43.9	36.0	27.8	35.0	31.2	27.8	28.1	28.7	146.4
37,5°	87.5	76.5	65.6	59.0	48.7	37.4	32.6	41.9	38.1	34.3	34.3	33.0	179.4
40,0°	87.2	75.9	65.6	60.1	50.8	39.5	35.0	47.4	46.3	43.2	43.9	36.8	216.2
42,5°	87.9	75.9	66.2	62.8	53.2	42.6	37.1	48.4	47.4	44.6	45.3	40.9	257.1
45,0°	88.2	76.9	67.6	63.5	53.9	43.2	37.4	47.4	46.7	42.9	44.6	44.5	301.7
47,5°	87.2	77.2	67.3	63.8	52.9	43.2	36.7	45.6	45.3	41.5	42.6	48.3	350.0
50,0°	81.3	74.1	65.2	63.2	51.1	41.9	35.7	42.6	42.6	38.1	40.5	51.6	401.6
52,5°	77.6	72.8	64.2	62.1	49.8	40.2	34.3	39.1	38.8	35.0	36.4	54.7	456.3
55,0°	72.4	70.4	62.8	59.4	47.7	36.7	31.9	36.0	35.4	30.9	33.6	57.3	513.7
57,5°	67.6	67.6	61.4	56.6	46.0	34.7	29.9	33.0	31.9	27.8	29.5	59.4	573.1
60,0°	59.7	61.4	57.3	55.3	45.0	33.3	27.5	29.5	29.2	24.4	26.8	59.1	632.1
62,5°	53.5	55.6	52.9	58.3	47.0	37.8	25.7	27.5	26.4	22.0	22.7	56.9	689.0
65,0°	47.7	52.5	49.4	58.0	50.8	40.5	25.1	25.4	24.4	19.6	22.0	53.3	742.3
67,5°	43.9	49.8	50.8	58.0	51.8	43.9	24.0	23.7	22.0	17.8	18.5	50.4	792.7
70,0°	40.5	43.6	48.7	54.6	49.8	39.1	25.7	22.0	19.9	16.1	17.8	46.8	839.5
72,5°	35.0	40.5	44.6	51.5	48.4	34.3	27.5	20.9	17.5	14.4	15.8	42.7	882.2
75,0°	32.6	37.4	37.1	41.9	35.4	24.7	22.7	18.5	15.4	12.4	13.7	34.6	916.8
77,5°	27.5	29.5	27.8	31.6	23.0	18.5	16.1	15.8	13.4	11.0	11.7	24.6	941.3
80,0°	22.7	19.6	17.5	21.6	18.2	18.2	15.4	14.1	11.0	9.3	9.6	14.0	955.4
82,5°	17.8	14.8	13.4	15.8	15.1	16.1	14.1	12.7	10.0	8.6	8.2	8.4	963.7
85,0°	14.1	11.3	9.6	12.4	12.4	13.4	11.7	11.0	8.6	7.2	7.6	5.0	968.8
87,5°	11.7	9.3	7.9	10.0	10.3	10.6	9.6	9.6	7.6	6.9	6.9	3.8	972.6
90,0°	8.2	6.2	5.5	8.2	8.6	8.2	7.9	7.9	6.5	5.5	5.5	2.8	975.4
92,5°	7.6	5.8	4.8	6.9	6.9	6.9	6.5	6.5	5.1	4.8	4.8	2.5	977.9
95,0°	6.5	5.1	4.5	5.5	5.8	5.8	5.5	5.5	4.8	4.5	4.1	2.3	980.2
97,5°	6.2	4.8	4.1	4.8	5.5	5.1	4.8	4.8	4.5	4.1	4.1	2.1	982.4
100,0°	5.8	4.8	4.1	4.8	4.8	4.8	4.8	4.8	4.1	4.1	4.1	2.0	984.3
102,5°	5.5	4.8	4.1	4.8	4.8	4.1	4.1	4.1	4.1	3.8	4.1	1.8	986.2
105,0°	5.1	4.5	4.1	4.1	4.1	4.1	4.1	4.1	4.1	3.4	3.4	1.7	987.9
107,5°	4.8	4.1	3.8	3.8	4.1	3.8	3.8	3.8	3.4	3.4	3.4	1.6	989.5
110,0°	4.8	4.1	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4	1.5	990.9
112,5°	4.1	4.1	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.1	2.7	1.4	992.3

Photometric test report

Family CITY-LIGHT PLUS LED	Order number: 5XA5275EV14H000022 EAN: 4069025025777	LP number 57130_77
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	5° 175°	10° 170°	15° 165°	20° 160°	25° 155°	30° 150°	35° 145°	40° 140°	45° 135°	50° 130°	55° 125°	60° 120°
γ	Luminous intensity in cd/klm												
115,0°	5.8	6.2	6.2	6.2	5.8	5.8	5.5	5.5	5.5	5.5	5.8	6.2	6.2
117,5°	5.5	5.5	5.8	5.8	5.5	5.5	5.5	5.1	5.5	5.5	5.5	5.5	6.2
120,0°	4.8	5.1	5.5	5.5	5.1	5.1	4.8	4.8	5.1	5.1	5.5	5.5	5.5
122,5°	4.8	4.8	5.1	5.1	4.8	4.5	4.8	4.8	4.8	4.8	4.8	4.8	5.5
125,0°	4.1	3.8	4.1	3.8	3.8	3.8	3.8	3.8	3.8	4.1	4.1	4.1	4.1
127,5°	2.7	2.7	3.1	3.1	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7
130,0°	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	1.7	1.7	2.1	2.1
132,5°	2.1	2.1	2.1	1.7	1.7	1.7	1.7	1.4	1.4	1.4	1.4	1.4	1.4
135,0°	1.4	1.7	1.7	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4
137,5°	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4
140,0°	1.4	1.4	1.4	1.4	1.0	1.0	0.7	0.7	0.7	0.7	0.7	0.7	0.7
142,5°	1.4	1.4	1.0	1.0	1.0	0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.7
145,0°	1.4	1.4	1.0	1.0	1.0	1.0	0.7	0.7	0.7	0.7	0.7	0.7	0.7
147,5°	1.0	1.0	1.0	1.0	1.0	1.0	0.7	0.7	0.7	0.7	0.7	0.7	0.7
150,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Photometric test report

Family CITY-LIGHT PLUS LED	Order number: 5XA5275EV14H000022 EAN: 4069025025777	LP number 57130_77 sit eco
---	--	--

C- planes	65° 115°	70° 110°	75° 105°	80° 100°	85° 95°	90°	185° 355°	190° 350°	195° 345°	200° 340°	205° 335°	210° 330°	215° 325°
γ	Luminous intensity in cd/klm												
115,0°	6.9	6.9	6.9	6.9	6.5	4.1	5.8	5.5	5.1	5.1	4.8	4.8	4.5
117,5°	6.2	6.5	6.9	6.9	5.5	2.1	5.1	4.8	4.8	4.8	4.8	4.5	4.1
120,0°	6.2	6.2	6.2	6.2	4.8	2.1	4.8	4.8	4.8	4.5	4.1	4.1	4.1
122,5°	5.5	5.5	5.5	6.2	4.1	2.1	4.5	4.5	4.1	4.1	4.1	3.8	3.4
125,0°	4.1	4.8	4.8	4.8	3.1	1.4	3.8	3.8	3.4	3.4	3.4	3.1	3.1
127,5°	2.7	2.7	3.1	2.7	2.1	1.4	2.7	2.7	2.7	2.7	2.7	2.7	2.4
130,0°	2.1	2.1	2.1	2.1	1.4	0.7	2.1	2.1	2.1	2.1	2.1	2.1	2.1
132,5°	1.4	1.4	1.4	1.4	1.4	0.7	2.1	2.1	2.1	2.1	2.1	2.1	2.1
135,0°	1.4	1.4	1.4	1.4	1.0	0.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7
137,5°	1.4	1.4	1.4	1.0	0.7	0.7	1.4	1.4	1.4	1.4	1.4	1.7	1.4
140,0°	0.7	0.7	0.7	0.7	0.7	0.7	1.4	1.4	1.4	1.4	1.4	1.4	1.4
142,5°	0.7	0.7	0.7	0.7	0.7	0.7	1.4	1.4	1.4	1.4	1.4	1.4	1.4
145,0°	0.7	0.7	0.7	0.7	0.7	0.7	1.4	1.4	1.4	1.4	1.4	1.4	1.4
147,5°	0.7	0.7	0.7	0.7	0.7	0.7	1.0	1.4	1.4	1.4	1.4	1.4	1.4
150,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

C- planes	220° 320°	225° 315°	230° 310°	235° 305°	240° 300°	245° 295°	250° 290°	255° 285°	260° 280°	265° 275°	270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm											Luminous flux in lm/klm	
115,0°	4.1	4.1	3.4	3.1	3.4	2.7	2.7	3.1	2.7	2.7	2.7	1.3	993.6
117,5°	4.1	3.4	3.4	3.1	2.7	2.7	2.7	2.7	2.7	2.7	2.7	1.1	994.7
120,0°	4.1	3.4	3.4	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	1.1	995.8
122,5°	3.4	3.4	3.4	2.7	2.7	2.4	2.4	2.7	2.7	2.4	2.1	1.0	996.7
125,0°	2.7	2.7	2.7	2.4	2.1	2.1	2.1	2.1	2.1	2.1	2.1	0.8	997.5
127,5°	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	0.5	998.0
130,0°	2.1	2.1	2.1	2.1	1.7	1.7	2.1	1.7	1.7	1.4	1.4	0.4	998.4
132,5°	2.1	1.7	2.1	2.1	1.4	1.4	1.4	1.4	1.7	1.4	1.4	0.3	998.8
135,0°	1.7	1.7	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	0.3	999.1
137,5°	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	0.2	999.3
140,0°	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	0.2	999.5
142,5°	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	0.2	999.7
145,0°	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	0.2	999.9
147,5°	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.0	1.4	1.4	0.2	1000.0
150,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family CITY-LIGHT PLUS LED	Order number: 5XA5275EV14H000022 EAN: 4069025025777	LP number 57130_77
Dimming levels table environmental temperature: 25°C		

Luminous flux [%]	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]start of lifetime	Power consumption [W]end of lifetime	Power consumption [W]average
100	254	254	1460	10.7	11.1	10.9
95	241	252	1385	10.1	10.4	10.2
90	229	250	1316	9.6	9.9	9.8
85	216	248	1242	9.0	9.3	9.2
80	203	246	1167	8.5	8.8	8.6
75	190	243	1092	7.9	8.2	8.0
70	178	241	1023	7.5	7.7	7.6
65	165	238	948	6.9	7.2	7.0
60	152	235	874	6.6	6.7	6.6
55	140	232	805	6.1	6.3	6.2
50	127	229	730	5.6	5.8	5.7
45	114	225	655	5.2	5.3	5.2
40	102	221	586	4.7	4.8	4.8
35	89	216	512	4.2	4.4	4.3
30	76	210	437	3.8	3.9	3.8
25	63	203	362	3.3	3.4	3.4
20	51	195	293	2.7	2.8	2.8
17	42	188	241	2.2	2.3	2.2