

Photometric test report

Family
Apollon® 31

Order number: 51MP12W72442
EAN: 4058352926390

LP number
59516_10

serial
documentation
11.12.2023

siteco

Version recessed luminaire for lay-in mounting, square
M600, wide distribution, UGR≤19
($L_{65} \leq 3000 \text{ cd/m}^2$)

Lamps LED 4000 K | CRI ≥ 80

Controlgear ECG


Rated values Net luminous flux = 4000 lm
Power consumption = 27.5 W
Luminous efficacy = 145.5 lm/W

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 456 cd/klm



Classifications

DIN 5040 A 5 0
CIE N1=61 N2=87 N3=97
N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 100.0%
 ϕ_o 0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Apollon® 31	Order number: 51MP12W72442 EAN: 4058352926390	LP number 59516_10
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0°	15° 345°	30° 330°	45° 315°	60° 300°	75° 285°	90° 270°
γ	Luminous intensity in cd/klm						
0°	455.9	455.9	455.9	455.9	455.9	455.9	455.9
5°	454.0	453.9	453.9	453.9	453.9	453.9	453.9
10°	448.0	448.0	448.0	448.1	448.1	448.1	448.1
15°	438.4	438.3	438.4	438.5	438.5	438.6	438.5
20°	425.5	425.3	425.3	425.5	425.7	425.7	425.5
25°	408.8	408.7	408.7	408.8	409.0	409.1	408.9
30°	386.3	386.6	386.8	387.0	387.1	387.3	387.6
35°	356.0	357.3	358.0	358.0	357.9	358.4	359.6
40°	308.0	312.5	314.7	314.8	313.9	315.4	319.3
45°	237.4	240.4	242.0	242.0	242.8	245.2	249.3
50°	157.6	168.1	171.3	167.4	163.5	168.2	181.5
55°	95.3	119.8	128.0	119.9	107.7	114.5	140.2
60°	69.0	89.0	96.4	91.3	79.3	83.2	102.9
65°	59.5	68.4	72.7	72.3	65.8	66.0	72.9
70°	49.1	51.9	54.5	56.9	54.9	52.5	49.7
75°	38.5	40.5	42.0	43.2	41.8	40.0	37.8
80°	30.1	29.9	29.5	28.8	29.4	30.3	31.5
85°	16.8	15.8	15.0	14.4	15.2	15.6	15.7
90°	0.6	0.6	0.5	0.3	0.3	0.3	0.3
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0

office	industry	traffic	retail	public	sports
--------	----------	---------	--------	--------	--------

Photometric test report

Family Apollon® 31	Order number: 51MP12W72442 EAN: 4058352926390	LP number 59516_10
Table of values for luminous intensities Maximum luminous intensity		sitEco

C- planes	105° 255°	120° 240°	135° 225°	150° 210°	165° 195°	180°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm						Luminous flux in lm/klm	
0°	455.9	455.9	455.9	455.9	455.9	455.9	2.7	2.7
5°	453.9	453.9	453.9	453.9	453.9	454.0	21.7	24.4
10°	448.1	448.1	448.1	448.0	448.0	448.0	42.6	67.1
15°	438.6	438.5	438.5	438.4	438.3	438.4	62.2	129.3
20°	425.7	425.7	425.5	425.3	425.3	425.5	79.8	209.0
25°	409.1	409.0	408.8	408.7	408.7	408.8	94.7	303.7
30°	387.3	387.1	387.0	386.8	386.6	386.3	106.1	409.8
35°	358.4	357.9	358.0	358.0	357.3	356.0	112.5	522.3
40°	315.4	313.9	314.8	314.7	312.5	308.0	110.7	633.0
45°	245.2	242.8	242.0	242.0	240.4	237.4	94.0	727.0
50°	168.2	163.5	167.4	171.3	168.1	157.6	70.5	797.6
55°	114.5	107.7	119.9	128.0	119.8	95.3	53.0	850.5
60°	83.2	79.3	91.3	96.4	89.0	69.0	41.5	892.1
65°	66.0	65.8	72.3	72.7	68.4	59.5	34.1	926.1
70°	52.5	54.9	56.9	54.5	51.9	49.1	27.5	953.6
75°	40.0	41.8	43.2	42.0	40.5	38.5	21.7	975.3
80°	30.3	29.4	28.8	29.5	29.9	30.1	16.1	991.4
85°	15.6	15.2	14.4	15.0	15.8	16.8	8.4	999.8
90°	0.3	0.3	0.3	0.5	0.6	0.6	0.2	1000.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Apollon® 31			Order number: 51MP12W72442 EAN: 4058352926390							LP number 59516_10	
UGR-Table			Standard room							siteco	
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	15.4	16.9	15.7	17.2	17.6	15.5	17.0	15.8	17.3	17.6
	3H	16.3	17.6	16.6	18.0	18.3	16.4	17.7	16.7	18.1	18.4
	4H	16.7	18.0	17.1	18.4	18.8	16.8	18.1	17.2	18.5	18.8
	6H	17.3	18.5	17.7	18.8	19.2	17.3	18.5	17.8	18.9	19.3
	8H	17.5	18.7	18.0	19.0	19.4	17.6	18.8	18.0	19.1	19.5
	12H	17.8	18.8	18.2	19.2	19.6	17.9	18.9	18.3	19.3	19.7
4H	2H	15.8	17.1	16.2	17.5	17.8	15.9	17.2	16.3	17.5	17.9
	3H	16.9	18.0	17.4	18.4	18.8	17.0	18.1	17.4	18.5	18.9
	4H	17.6	18.6	18.0	19.0	19.4	17.6	18.6	18.1	19.0	19.5
	6H	18.3	19.1	18.8	19.6	20.0	18.4	19.2	18.8	19.6	20.1
	8H	18.6	19.4	19.1	19.9	20.3	18.7	19.5	19.2	19.9	20.4
	12H	18.9	19.6	19.4	20.1	20.6	19.0	19.7	19.5	20.1	20.6
8H	4H	17.9	18.7	18.4	19.1	19.6	18.0	18.7	18.4	19.2	19.7
	6H	18.8	19.4	19.3	19.9	20.4	18.8	19.5	19.3	20.0	20.5
	8H	19.2	19.8	19.7	20.3	20.8	19.3	19.9	19.8	20.3	20.9
	12H	19.6	20.1	20.2	20.6	21.2	19.7	20.1	20.2	20.6	21.2
12H	4H	18.0	18.7	18.5	19.1	19.6	18.0	18.7	18.5	19.2	19.7
	6H	18.9	19.5	19.4	19.9	20.5	19.0	19.5	19.5	20.0	20.5
	8H	19.4	19.9	19.9	20.4	20.9	19.4	19.9	20.0	20.4	21.0

Luminance table				Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:			L = 555 B = 555				
C-planes	0°	15° 345°	30° 330°	45° 315°	60° 300°	75° 285°	90° 270°	105° 255°	120° 240°	135° 225°	150° 210°	165° 195°	180°
γ	Luminance in cd/m²												
45°	4359.0	4415.3	4443.9	4444.8	4459.3	4503.7	4578.0	4503.7	4459.3	4444.8	4443.9	4415.3	4359.0
50°	3184.2	3395.0	3460.7	3381.3	3302.2	3397.6	3667.6	3397.6	3302.2	3381.3	3460.7	3395.0	3184.2
55°	2158.3	2713.1	2898.8	2715.6	2438.5	2591.2	3173.8	2591.2	2438.5	2715.6	2898.8	2713.1	2158.3
60°	1790.9	2310.4	2503.5	2370.2	2060.6	2161.6	2673.3	2161.6	2060.6	2370.2	2503.5	2310.4	1790.9
65°	1828.1	2102.5	2233.2	2220.2	2020.8	2027.8	2241.4	2027.8	2020.8	2220.2	2233.2	2102.5	1828.1
70°	1862.5	1970.6	2069.9	2160.6	2085.8	1994.1	1885.4	1994.1	2085.8	2160.6	2069.9	1970.6	1862.5
75°	1933.6	2029.7	2108.1	2168.8	2098.2	2006.9	1895.0	2006.9	2098.2	2168.8	2108.1	2029.7	1933.6
80°	2249.6	2239.4	2207.3	2153.2	2196.9	2263.6	2353.1	2263.6	2196.9	2153.2	2207.3	2239.4	2249.6
85°	2506.1	2360.7	2241.2	2147.6	2257.3	2322.7	2343.9	2322.7	2257.3	2147.6	2241.2	2360.7	2506.1

Photometric test report

Family
Apollon® 31

Order number: 51MP12W72442
EAN: 4058352926390

LP number
59516_10

Luminance values in cd/m²

γ 65°

γ 70°

γ 75°

γ 80°

γ 85°

siteco

