

Photometric test report

Family
DL 11 iQ

Order number: 5XA5565JF108000022
EAN: 4058352955963

LP number
59374_102

serial
documentation
01.02.2024



Version luminaire insert LED, Siteco® metallic grey (DB 702S), post-top- or mounting to wall arm
Optic symmetric, wide distribution (PL1.2s)
Cover cover transparent, PMMA
Lamps LED 3000 K | CRI ≥ 70
Controlgear ECG SITECO iQ
Rated values Net luminous flux = 2850 lm
Power consumption = 19.3 W
Luminous efficacy = 147.7 lm/W

siteco

Luminous intensity in cd/klm


C180-0

C200-20

C205-25

C270-90

Imax: 392 cd/klm



Luminaire output ratios

Eta	100.0%
Eta 0° - 90°	98.8%
Eta 90° - 180°	1.2%

Luminous intensity class acc. to EN13201-2

Class:	G3
Imax 70°	349.4
Imax 80°	94.8
Imax 90°	7.3
Imax >90°	4.7
Imax >95°	3.7

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family DL 11 iQ	Order number: 5XA5565JF108000022 EAN: 4058352955963	LP number 59374_102
----------------------------------	--	--------------------------------------

Envelope curve in cd/klm

KMK 62.5°


KMK 60°

KMK 57.5°

KMK 55°

sit

eco



Photometric test report

Family DL 11 iQ	Order number: 5XA5565JF108000022 EAN: 4058352955963	LP number 59374_102
Table of values for luminous intensities		Maximum luminous intensity



C- planes	0° 180°	5° 175° 185° 355°	10° 170° 190° 350°	15° 165° 195° 345°	20° 160° 200° 340°	25° 155° 205° 335°	30° 150° 210° 330°	35° 145° 215° 325°	40° 140° 220° 320°	45° 135° 225° 315°
γ	Luminous intensity in cd/klm									
0,0°	23.6	23.6	23.6	23.6	23.6	23.6	23.6	23.6	23.6	23.6
2,5°	22.9	23.0	23.2	23.3	23.7	24.6	25.1	25.3	25.2	25.7
5,0°	35.6	36.2	36.9	36.6	36.3	34.7	33.9	34.1	34.8	35.5
7,5°	48.3	49.0	49.5	50.5	49.2	48.1	48.0	48.8	51.7	54.3
10,0°	66.5	66.9	67.0	68.8	64.8	66.0	68.2	70.7	71.3	72.9
12,5°	88.4	88.1	91.9	87.8	85.1	82.5	80.9	81.8	85.0	86.3
15,0°	113.5	107.0	98.9	100.9	107.3	114.3	124.6	125.3	115.7	109.5
17,5°	141.2	129.6	129.5	133.9	132.9	129.3	126.3	121.7	119.5	122.0
20,0°	145.5	137.7	144.7	139.3	134.5	135.3	126.6	117.4	117.1	118.2
22,5°	168.0	153.1	152.8	137.0	133.1	128.7	123.4	117.8	114.8	114.8
25,0°	169.9	155.6	165.6	149.2	147.1	137.4	122.4	116.5	115.6	116.3
27,5°	182.4	171.3	176.2	153.2	156.2	152.6	142.2	133.1	129.5	129.6
30,0°	198.1	195.0	201.7	170.4	163.9	150.8	140.3	135.4	137.4	138.7
32,5°	193.5	187.3	189.2	164.6	167.1	164.5	152.9	155.5	164.5	168.1
35,0°	244.5	244.0	233.3	209.9	189.5	173.0	164.3	163.1	167.2	176.8
37,5°	246.4	246.6	230.3	216.2	202.5	184.1	172.9	176.6	185.5	187.8
40,0°	250.1	260.3	240.9	222.5	206.3	190.5	191.4	195.1	198.7	204.7
42,5°	262.1	272.3	240.4	228.1	215.6	204.2	204.1	209.6	214.3	218.8
45,0°	276.2	290.7	253.0	237.8	224.3	214.5	214.1	225.2	230.0	229.0
47,5°	291.2	301.3	262.8	252.3	230.7	228.9	234.0	243.9	239.4	234.4
50,0°	304.5	319.7	284.8	273.0	243.8	249.0	255.4	256.4	248.6	238.5
52,5°	308.7	331.8	301.5	306.8	272.8	275.1	276.4	276.1	260.5	246.7
55,0°	315.9	348.4	314.5	333.0	310.0	303.4	311.5	289.1	279.9	248.4
57,5°	315.0	357.1	333.9	358.0	346.2	336.4	327.4	306.9	281.8	244.6
60,0°	295.8	350.4	338.8	365.6	380.4	359.1	336.9	318.2	283.7	235.6
62,5°	277.7	325.7	323.4	350.6	391.7	382.5	349.4	327.4	285.2	230.2
65,0°	242.1	282.0	311.6	354.9	387.6	389.5	359.1	319.7	277.8	226.3
67,5°	226.1	250.0	288.7	340.2	380.7	366.6	352.9	311.3	265.3	212.8
70,0°	230.4	255.8	286.0	330.1	349.4	336.0	325.4	280.4	236.5	197.4
72,5°	207.7	244.8	259.3	308.5	326.1	307.1	263.7	238.8	199.2	156.6
75,0°	145.9	192.5	220.7	265.0	265.2	253.9	198.0	173.3	130.6	110.7
77,5°	89.1	112.5	145.2	177.4	178.6	150.7	120.4	102.7	89.2	79.0
80,0°	53.1	65.3	84.2	92.8	94.8	81.7	78.7	79.3	64.1	48.7
82,5°	31.4	35.9	41.0	45.8	49.6	44.1	52.1	59.6	48.9	33.7
85,0°	16.6	17.3	18.3	19.8	22.3	24.4	33.3	36.7	30.3	22.8
87,5°	7.1	7.2	7.7	8.4	10.1	11.7	13.3	13.5	12.8	12.0
90,0°	5.8	5.8	5.9	6.1	6.7	7.3	7.1	6.6	6.3	6.1
92,5°	4.7	4.6	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7
95,0°	4.1	4.1	4.1	4.1	4.1	4.0	4.0	3.9	3.9	3.8
97,5°	3.7	3.7	3.7	3.7	3.7	3.6	3.5	3.5	3.5	3.3
100,0°	3.4	3.3	3.3	3.3	3.3	3.2	3.2	3.1	3.1	3.0
102,5°	3.0	3.0	3.1	3.1	3.0	2.9	2.8	2.8	2.8	2.7
105,0°	2.8	2.8	2.8	2.8	2.7	2.6	2.6	2.6	2.6	2.5
107,5°	2.6	2.6	2.6	2.6	2.5	2.5	2.4	2.4	2.4	2.4
110,0°	2.4	2.4	2.4	2.4	2.4	2.3	2.2	2.2	2.2	2.2

Photometric test report

Family DL 11 iQ	Order number: 5XA5565JF108000022 EAN: 4058352955963	LP number 59374_102
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	50° 130° 230° 310°	55° 125° 235° 305°	60° 120° 240° 300°	65° 115° 245° 295°	70° 110° 250° 290°	75° 105° 255° 285°	80° 100° 260° 280°	85° 95° 265° 275°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm								Luminous flux in lm/klm		
0,0°	23.6	23.6	23.6	23.6	23.6	23.6	23.6	23.6	23.6	0.0	0.0
2,5°	26.5	26.9	26.4	26.0	26.4	26.6	26.1	26.0	25.9	0.3	0.3
5,0°	36.1	37.0	36.7	36.6	36.8	36.3	36.6	36.7	37.1	0.9	1.2
7,5°	57.0	58.1	57.6	56.0	54.9	52.1	51.0	51.0	50.4	1.9	3.1
10,0°	75.0	76.8	76.6	74.2	74.6	76.2	80.2	80.9	81.3	3.5	6.5
12,5°	89.5	95.6	97.4	96.7	96.5	95.8	94.6	97.2	96.5	5.4	11.9
15,0°	111.6	113.1	115.3	115.1	116.1	116.3	116.7	121.1	124.7	8.1	19.9
17,5°	120.7	121.2	117.9	120.7	128.0	136.7	142.2	145.0	148.4	10.6	30.6
20,0°	120.6	121.3	125.0	127.7	133.5	138.4	141.0	143.2	145.2	12.3	42.9
22,5°	118.2	123.5	127.5	130.6	135.1	142.5	147.5	149.3	149.2	14.0	56.9
25,0°	119.1	123.7	130.1	134.8	141.9	149.3	154.9	154.2	154.3	16.1	73.0
27,5°	132.9	135.6	140.9	144.9	147.3	151.1	153.9	156.4	157.3	18.8	91.8
30,0°	142.1	147.0	151.6	158.1	162.2	161.4	158.5	154.7	153.7	21.7	113.5
32,5°	167.5	171.7	172.7	176.4	169.2	162.0	163.3	164.5	165.5	24.9	138.4
35,0°	181.3	179.7	182.2	182.1	179.4	175.4	173.1	172.4	173.2	29.3	167.7
37,5°	193.6	193.0	196.8	197.1	193.0	181.9	177.8	179.7	182.4	32.7	200.4
40,0°	205.6	202.7	203.5	203.1	198.8	186.1	183.9	186.5	190.5	36.2	236.6
42,5°	217.0	212.0	210.8	210.3	200.7	187.6	188.1	192.4	194.0	39.7	276.3
45,0°	229.2	218.4	217.8	216.6	201.0	189.8	193.1	195.4	195.4	43.2	319.5
47,5°	234.3	226.7	224.5	222.1	202.0	192.7	196.0	197.8	196.6	46.8	366.3
50,0°	234.4	228.6	224.8	223.3	202.2	193.6	196.7	199.6	199.5	50.5	416.8
52,5°	236.3	230.1	218.7	215.7	200.7	195.2	197.2	201.6	202.4	54.4	471.1
55,0°	231.2	222.9	200.7	198.8	192.0	188.7	192.8	200.2	203.3	57.7	528.8
57,5°	218.6	207.2	187.1	181.5	172.8	169.5	177.4	187.8	192.2	59.7	588.5
60,0°	204.8	187.1	168.8	161.4	152.2	139.7	150.9	165.0	169.5	59.8	648.3
62,5°	195.2	171.1	150.0	132.2	127.4	114.6	119.6	128.5	136.5	58.2	706.5
65,0°	186.6	158.4	130.9	107.2	96.5	85.1	89.2	93.9	92.1	55.5	762.1
67,5°	178.8	145.5	112.6	88.6	71.4	55.9	58.4	59.3	58.1	51.8	813.9
70,0°	163.9	128.8	97.1	72.8	52.2	35.6	31.6	32.9	35.2	47.9	861.7
72,5°	130.0	104.4	83.9	59.5	35.4	22.9	19.2	18.6	19.3	42.0	903.7
75,0°	104.6	96.5	77.3	46.6	20.3	15.9	13.9	13.5	13.5	33.5	937.2
77,5°	78.3	73.6	61.7	25.9	13.1	11.6	10.9	10.6	10.3	22.2	959.4
80,0°	41.6	32.1	29.4	12.2	9.2	8.8	8.6	8.3	8.2	13.1	972.5
82,5°	23.7	17.5	12.5	7.9	7.0	6.9	6.7	6.6	6.6	7.8	980.3
85,0°	15.7	11.9	8.8	6.4	5.9	5.6	5.4	5.3	5.3	4.6	984.9
87,5°	9.7	7.4	6.3	5.5	5.2	4.9	4.6	4.4	4.4	2.3	987.2
90,0°	5.8	5.4	5.2	4.9	4.7	4.4	4.0	3.9	3.9	1.5	988.7
92,5°	4.6	4.5	4.6	4.5	4.3	4.0	3.8	3.6	3.5	1.2	989.9
95,0°	3.7	3.6	3.6	3.5	3.3	3.3	3.3	3.2	3.2	1.0	990.9
97,5°	3.3	3.2	3.1	3.0	3.0	3.0	2.9	2.8	2.8	0.9	991.8
100,0°	3.0	2.9	2.8	2.8	2.8	2.6	2.6	2.6	2.6	0.8	992.6
102,5°	2.6	2.6	2.6	2.6	2.5	2.4	2.4	2.4	2.4	0.7	993.4
105,0°	2.5	2.4	2.4	2.4	2.4	2.2	2.2	2.2	2.2	0.7	994.0
107,5°	2.3	2.2	2.2	2.2	2.1	2.1	2.1	2.0	2.0	0.6	994.6
110,0°	2.2	2.2	2.1	2.0	2.0	2.0	2.0	2.0	2.0	0.6	995.2

Photometric test report

Family DL 11 iQ	Order number: 5XA5565JF108000022 EAN: 4058352955963	LP number 59374_102
Table of values for luminous intensities		Maximum luminous intensity

sitEco

C- planes	0° 180°	5° 175° 185° 355°	10° 170° 190° 350°	15° 165° 195° 345°	20° 160° 200° 340°	25° 155° 205° 335°	30° 150° 210° 330°	35° 145° 215° 325°	40° 140° 220° 320°	45° 135° 225° 315°
γ	Luminous intensity in cd/klm									
112,5°	2.3	2.3	2.2	2.2	2.2	2.2	2.1	2.1	2.1	2.0
115,0°	2.2	2.2	2.2	2.2	2.2	2.1	2.0	2.0	2.0	2.0
117,5°	2.2	2.1	2.1	2.1	2.0	2.0	2.0	2.0	2.0	1.9
120,0°	2.0	2.0	2.0	2.0	2.0	2.0	2.0	1.9	1.9	1.9
122,5°	2.0	2.0	2.0	2.0	1.9	1.9	1.9	1.8	1.8	1.8
125,0°	1.9	1.9	1.9	1.9	1.8	1.8	1.8	1.8	1.8	1.7
127,5°	1.8	1.8	1.8	1.8	1.7	1.7	1.7	1.6	1.6	1.6
130,0°	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5
132,5°	1.5	1.5	1.5	1.4	1.4	1.4	1.4	1.4	1.4	1.3
135,0°	1.3	1.4	1.3	1.4	1.3	1.3	1.3	1.4	1.4	1.3
137,5°	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.2	1.2
140,0°	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1
142,5°	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1
145,0°	0.9	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
147,5°	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9
150,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Photometric test report

Family DL 11 iQ	Order number: 5XA5565JF108000022 EAN: 4058352955963	LP number 59374_102
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	50° 130° 230° 310°	55° 125° 235° 305°	60° 120° 240° 300°	65° 115° 245° 295°	70° 110° 250° 290°	75° 105° 255° 285°	80° 100° 260° 280°	85° 95° 265° 275°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm									Luminous flux in lm/klm	
112,5°	2.0	2.0	2.0	2.0	2.0	2.0	1.9	1.9	1.9	0.5	995.7
115,0°	2.0	2.0	2.0	2.0	1.9	1.8	1.8	1.8	1.8	0.5	996.2
117,5°	2.0	1.9	1.9	1.8	1.8	1.8	1.8	1.8	1.8	0.5	996.7
120,0°	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.8	0.4	997.1
122,5°	1.8	1.8	1.8	1.7	1.7	1.7	1.7	1.6	1.5	0.4	997.6
125,0°	1.7	1.7	1.6	1.6	1.5	1.5	1.5	1.5	1.5	0.4	997.9
127,5°	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	0.3	998.3
130,0°	1.5	1.5	1.4	1.4	1.4	1.4	1.4	1.3	1.3	0.3	998.6
132,5°	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	0.3	998.9
135,0°	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.2	1.2	0.3	999.1
137,5°	1.2	1.2	1.2	1.2	1.1	1.1	1.1	1.1	1.1	0.2	999.3
140,0°	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	0.2	999.5
142,5°	1.1	1.1	1.1	1.1	1.0	1.0	1.0	1.0	1.0	0.2	999.7
145,0°	1.0	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.1	999.9
147,5°	0.8	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.1	1000.0
150,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
152,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
157,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
162,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
167,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
172,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
177,5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family DL 11 iQ	Order number: 5XA5565JF108000022 EAN: 4058352955963	LP number 59374_102
Dimming levels table		environmental temperature: 25°C
		siteco

Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W] start of lifetime	Power consumption [W] end of lifetime	Power consumption [W] average
100	254	254	2850	19.3	20.6	20.0
95	241	252	2704	18.3	19.4	18.8
90	229	250	2569	17.3	18.4	17.8
85	216	248	2424	16.3	17.3	16.8
80	203	246	2278	15.2	16.2	15.7
75	190	243	2132	14.2	15.1	14.6
70	178	241	1997	13.3	14.1	13.7
65	165	238	1851	12.4	13.2	12.8
60	152	235	1706	11.4	12.1	11.8
55	140	232	1571	10.5	11.2	10.8
50	127	229	1425	9.6	10.1	9.8
45	114	225	1279	8.7	9.2	9.0
40	102	221	1144	7.9	8.3	8.1
35	89	216	999	7.1	7.4	7.2
30	76	210	853	6.2	6.5	6.4
25	63	203	707	5.4	5.6	5.5
20	51	195	572	4.6	4.8	4.7
17	44	190	494	4.1	4.3	4.2