

Photometric test report

Family
Licross® 21 Performance

Order number: 52TD16CN445G
EAN: 4058352903025

LP number
58520_391



Version cover frosted, direct-/ indirect distribution,
UGR≤19 (L65≤3000cd/m²)
Lamps LED 4000 K | CRI ≥ 80
Controlgear ECG-Multilumen CLOi
Rated values Net luminous flux = 4500 lm
Power consumption = 24.1 W
Luminous efficacy = 186.7 lm/W

serial
documentation
20.02.2024


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 452 cd/klm



Classifications

DIN 5040 B 5 1
CIE N1=65 N2=88 N3=96
N4=79 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 79.3%
 ϕ_o 20.7%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Licross® 21 Performance	Order number: 52TD16CN445G EAN: 4058352903025	LP number 58520_391
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	427.7	427.7	427.7	427.7	427.7	427.7	427.7	2.6	2.6
5°	424.4	422.4	420.2	422.1	424.3	424.4	424.8	20.2	22.8
10°	414.9	412.5	408.9	409.5	411.2	411.6	412.2	39.1	61.9
15°	410.8	406.7	398.1	393.2	390.9	389.7	390.1	56.3	118.2
20°	424.3	415.5	394.5	375.8	364.0	357.7	356.8	71.8	190.0
25°	451.7	439.9	403.9	360.3	329.2	311.6	307.2	85.9	275.8
30°	429.5	430.9	412.5	347.4	284.5	251.0	241.5	94.2	370.0
35°	325.6	344.5	379.3	329.0	231.5	183.8	171.0	89.9	460.0
40°	224.9	238.5	293.1	289.7	177.2	125.7	113.8	76.0	535.9
45°	176.4	174.8	199.5	224.7	128.0	84.3	75.7	60.6	596.5
50°	156.0	144.3	136.6	154.2	90.2	58.9	53.2	48.2	644.7
55°	139.0	122.9	98.4	99.7	63.9	43.4	39.8	38.7	683.4
60°	113.7	99.1	72.2	64.7	46.3	33.0	30.8	30.7	714.1
65°	79.7	70.2	51.6	43.8	34.5	25.6	24.0	23.0	737.1
70°	47.7	43.4	35.6	31.1	26.2	19.7	18.2	16.2	753.3
75°	33.9	31.2	26.1	23.2	19.9	14.4	12.7	12.2	765.5
80°	33.7	30.7	23.7	18.2	15.1	9.9	7.5	10.6	776.1
85°	39.3	35.6	26.3	17.2	11.4	6.2	3.2	10.7	786.9
90°	50.4	45.6	32.3	18.9	10.0	3.9	0.6	12.4	799.3
95°	71.3	63.5	42.3	22.5	11.4	4.6	1.0	16.4	815.7
100°	97.9	84.6	52.5	26.5	12.9	5.3	1.6	20.8	836.6
105°	120.7	101.7	62.6	30.2	14.2	6.1	2.4	24.4	860.9
110°	134.6	112.6	69.4	33.2	15.3	6.7	2.9	26.3	887.2
115°	137.8	115.5	72.0	34.6	16.0	7.2	3.2	26.1	913.3
120°	129.6	108.9	68.7	33.6	15.7	7.4	3.5	23.8	937.1
125°	109.1	92.2	59.5	30.3	14.7	7.4	3.7	19.5	956.6
130°	83.4	71.0	47.4	25.5	13.2	7.2	3.7	14.5	971.2
135°	58.6	50.3	35.1	20.5	11.4	6.8	3.7	10.0	981.2
140°	39.2	34.3	25.3	16.3	9.8	6.3	3.7	6.7	987.9
145°	26.6	23.8	18.6	13.0	8.2	5.4	3.7	4.4	992.3
150°	18.7	17.2	14.2	10.0	6.9	5.0	3.7	2.9	995.2
155°	13.8	12.8	10.8	7.8	6.8	4.4	3.6	2.0	997.2
160°	10.2	9.8	7.9	6.8	5.6	4.6	3.5	1.3	998.5
165°	8.2	7.8	6.5	5.6	5.0	4.1	3.7	0.8	999.3
170°	6.4	5.6	4.7	4.7	5.0	4.1	3.9	0.5	999.8
175°	4.2	3.7	4.1	4.1	4.1	4.2	4.2	0.2	1000.0
180°	3.7	3.7	3.7	3.7	3.7	3.7	3.7	0.0	1000.0

Photometric test report

Family Licross® 21 Performance	Order number: 52TD16CN445G EAN: 4058352903025	LP number 58520_391
-----------------------------------	--	------------------------

UGR-Table		Standard room							siteco		
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	16.3	17.6	16.9	18.1	18.8	12.5	13.8	13.1	14.3	15.0
	3H	16.9	18.0	17.5	18.6	19.3	12.9	14.0	13.5	14.6	15.3
	4H	17.1	18.1	17.7	18.7	19.4	13.1	14.2	13.7	14.8	15.5
	6H	17.3	18.2	18.0	18.9	19.6	13.3	14.2	13.9	14.8	15.6
	8H	17.6	18.4	18.3	19.0	19.8	13.2	14.1	13.9	14.8	15.5
	12H	17.9	18.6	18.6	19.3	20.1	13.3	14.1	13.9	14.8	15.5
4H	2H	16.3	17.4	16.9	18.0	18.7	13.0	14.0	13.6	14.6	15.3
	3H	17.0	17.8	17.6	18.5	19.3	13.5	14.4	14.2	15.0	15.8
	4H	17.2	18.0	17.9	18.7	19.5	13.8	14.6	14.5	15.3	16.1
	6H	17.7	18.3	18.4	19.0	19.9	14.0	14.7	14.7	15.4	16.2
	8H	18.0	18.6	18.7	19.3	20.2	14.1	14.7	14.8	15.4	16.3
	12H	18.5	19.0	19.3	19.8	20.7	14.1	14.7	14.9	15.4	16.3
8H	4H	17.2	17.8	17.9	18.5	19.4	14.0	14.6	14.7	15.3	16.1
	6H	17.8	18.3	18.5	19.0	19.9	14.4	14.8	15.1	15.6	16.5
	8H	18.3	18.7	19.0	19.5	20.3	14.5	15.0	15.3	15.7	16.6
	12H	19.0	19.4	19.8	20.2	21.1	14.6	15.0	15.4	15.8	16.7
12H	4H	17.1	17.7	17.9	18.4	19.3	14.0	14.5	14.8	15.2	16.1
	6H	17.7	18.2	18.5	18.9	19.8	14.5	14.9	15.2	15.6	16.6
	8H	18.3	18.7	19.1	19.4	20.4	14.7	15.1	15.5	15.8	16.8

Luminance table		Max. for $\gamma \geq 65^\circ$			Photometric dimensions in mm:	L = 1480 B = 115	H(C0) = 36 H(C90) = 0	H(C180) = 36 H(C270) = 0
C- planes	γ	0°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
		Luminance in cd/m²						
	45°	5023.8	5018.4	5868.8	6879.2	4139.9	2916.3	2828.9
	50°	4673.3	4361.9	4245.2	5019.1	3127.8	2210.6	2187.0
	55°	4427.7	3957.5	3270.4	3492.8	2407.2	1793.0	1833.6
	60°	3898.2	3440.1	2596.9	2473.4	1928.0	1532.5	1628.5
	65°	2985.1	2662.3	2040.1	1858.2	1618.1	1365.9	1503.6
	70°	1981.6	1832.2	1577.3	1497.1	1413.8	1244.8	1409.5
	75°	1599.3	1496.2	1325.8	1297.9	1285.1	1132.2	1298.5
	80°	1850.5	1723.3	1422.0	1227.1	1220.0	1034.8	1143.0
	85°	2602.2	2426.8	1945.7	1478.4	1236.9	978.2	973.2

Photometric test report

Family
Licross® 21 Performance

Order number: 52TD16CN445G
EAN: 4058352903025

LP number
58520_391

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Licross® 21 Performance	Order number: 52TD16CN445G EAN: 4058352903025	LP number 58520_391
Multilumen Table	environmental temperature: 25°C	siteco

DIP-Step	Switch Setting			Luminous flux [lm]	Power consumption [W]	Power consumption [W]	Power consumption [W]
	1	2	3			end of lifetime	average
1	A	C	E	4500	24.1	28.2	26.2
2	A	C	F	4420	23.7	27.9	25.8
3	A	D	E	4340	23.2	27.4	25.3
4	A	D	F	4270	22.8	27.0	24.9
5	B	C	E	4180	22.3	26.2	24.2
6	B	C	F	4100	22.0	25.7	23.8