

Photometric test report

Family
Batten 41



Order number: 51LP327KM20AE
EAN: 4058352704998

Version

Lamps

Controlgear

Setting

Rated values

diffuser optic, frosted, polycarbonate,
adjustable color temperature: 3000K | 4000K |
5000K, extremely wide distribution

LED 4000 K | CRI ≥ 80

ECG


factory setting: colour temperature 4000K

Net luminous flux = 2000 lm
Power consumption = 16.0 W
Luminous efficacy = 125 lm/W

LP number
59484_8

serial
documentation
26.08.2024

siteco



Classifications		Luminaire light output ratios	
DIN 5040	B 3 1	η_{LB}	100.0%
CIE	N1=37 N2=66 N3=87	ϕ_u	86.8%
	N4=87 N5=100	ϕ_o	13.2%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Batten 41	Order number: 51LP327KM20AE EAN: 4058352704998	LP number 59484_8
Table of values for luminous intensities		Maximum luminous intensity

sITeco

C- planes	0°	15°	30°	45°	60°	75°	90°	105°	120°	135°	150°	165°	180°
γ	Luminous intensity in cd/klm												
0°	229.9	229.9	229.9	229.9	229.9	229.9	229.9	229.9	229.9	229.9	229.9	229.9	229.9
5°	229.9	229.9	229.8	229.6	229.4	229.8	230.2	229.8	229.4	229.6	229.8	229.9	229.9
10°	229.7	229.0	228.3	227.9	227.4	227.5	227.7	227.5	227.4	227.9	228.3	229.0	229.7
15°	227.6	227.6	227.7	225.6	223.6	222.8	222.0	222.8	223.6	225.6	227.7	227.6	227.6
20°	224.1	223.7	223.2	219.8	216.4	214.9	213.5	214.9	216.4	219.8	223.2	223.7	224.1
25°	217.8	217.7	217.6	213.6	209.6	206.7	203.8	206.7	209.6	213.6	217.6	217.7	217.8
30°	210.2	209.6	209.0	204.6	200.1	195.9	191.6	195.9	200.1	204.6	209.0	209.6	210.2
35°	201.7	201.5	201.4	197.3	193.2	185.2	177.3	185.2	193.2	197.3	201.4	201.5	201.7
40°	194.4	193.3	192.2	186.6	181.1	174.2	167.4	174.2	181.1	186.6	192.2	193.3	194.4
45°	189.5	186.3	183.2	175.8	168.3	160.1	151.8	160.1	168.3	175.8	183.2	186.3	189.5
50°	180.8	176.0	171.3	163.0	154.7	144.8	134.9	144.8	154.7	163.0	171.3	176.0	180.8
55°	171.6	169.3	167.0	153.6	140.2	128.8	117.4	128.8	140.2	153.6	167.0	169.3	171.6
60°	161.2	158.5	155.9	141.2	126.5	113.7	101.0	113.7	126.5	141.2	155.9	158.5	161.2
65°	150.0	146.9	143.9	127.9	111.9	97.5	83.1	97.5	111.9	127.9	143.9	146.9	150.0
70°	136.1	133.4	130.6	113.2	95.8	80.9	66.0	80.9	95.8	113.2	130.6	133.4	136.1
75°	122.4	119.6	116.9	98.8	80.7	64.7	48.8	64.7	80.7	98.8	116.9	119.6	122.4
80°	108.6	105.2	101.9	83.8	65.8	49.0	32.1	49.0	65.8	83.8	101.9	105.2	108.6
85°	94.0	91.1	88.1	70.0	51.8	34.6	17.5	34.6	51.8	70.0	88.1	91.1	94.0
90°	81.7	79.1	76.5	59.1	41.8	24.8	7.9	24.8	41.8	59.1	76.5	79.1	81.7
95°	74.4	70.8	67.2	52.2	37.2	21.1	4.9	21.1	37.2	52.2	67.2	70.8	74.4
100°	65.8	61.9	57.9	42.8	27.7	15.7	3.6	15.7	27.7	42.8	57.9	61.9	65.8
105°	62.2	58.3	54.5	40.5	26.6	14.5	2.4	14.5	26.6	40.5	54.5	58.3	62.2
110°	56.6	53.8	51.1	39.2	27.4	14.5	1.6	14.5	27.4	39.2	51.1	53.8	56.6
115°	52.8	50.1	47.3	36.0	24.7	13.2	1.6	13.2	24.7	36.0	47.3	50.1	52.8
120°	48.4	46.4	44.3	33.2	22.1	11.8	1.6	11.8	22.1	33.2	44.3	46.4	48.4
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Photometric test report

Family Batten 41	Order number: 51LP327KM20AE EAN: 4058352704998	LP number 59484_8
Table of values for luminous intensities		Maximum luminous intensity

siteco

C-planes	195°	210°	225°	240°	255°	270°	285°	300°	315°	330°	345°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm											Luminous flux in lm/klm	
0°	229.9	229.9	229.9	229.9	229.9	229.9	229.9	229.9	229.9	229.9	229.9	1.4	1.4
5°	229.9	229.8	229.6	229.4	229.8	230.2	229.8	229.4	229.6	229.8	229.9	11.0	12.4
10°	229.0	228.3	227.9	227.4	227.5	227.7	227.5	227.4	227.9	228.3	229.0	21.7	34.1
15°	227.6	227.7	225.6	223.6	222.8	222.0	222.8	223.6	225.6	227.7	227.6	32.0	66.0
20°	223.7	223.2	219.8	216.4	214.9	213.5	214.9	216.4	219.8	223.2	223.7	41.1	107.2
25°	217.7	217.6	213.6	209.6	206.7	203.8	206.7	209.6	213.6	217.6	217.7	49.3	156.4
30°	209.6	209.0	204.6	200.1	195.9	191.6	195.9	200.1	204.6	209.0	209.6	55.7	212.2
35°	201.5	201.4	197.3	193.2	185.2	177.3	185.2	193.2	197.3	201.4	201.5	61.2	273.4
40°	193.3	192.2	186.6	181.1	174.2	167.4	174.2	181.1	186.6	192.2	193.3	65.1	338.5
45°	186.3	183.2	175.8	168.3	160.1	151.8	160.1	168.3	175.8	183.2	186.3	67.5	405.9
50°	176.0	171.3	163.0	154.7	144.8	134.9	144.8	154.7	163.0	171.3	176.0	67.7	473.6
55°	169.3	167.0	153.6	140.2	128.8	117.4	128.8	140.2	153.6	167.0	169.3	67.6	541.2
60°	158.5	155.9	141.2	126.5	113.7	101.0	113.7	126.5	141.2	155.9	158.5	65.4	606.7
65°	146.9	143.9	127.9	111.9	97.5	83.1	97.5	111.9	127.9	143.9	146.9	61.6	668.3
70°	133.4	130.6	113.2	95.8	80.9	66.0	80.9	95.8	113.2	130.6	133.4	56.2	724.5
75°	119.6	116.9	98.8	80.7	64.7	48.8	64.7	80.7	98.8	116.9	119.6	50.0	774.5
80°	105.2	101.9	83.8	65.8	49.0	32.1	49.0	65.8	83.8	101.9	105.2	42.8	817.3
85°	91.1	88.1	70.0	51.8	34.6	17.5	34.6	51.8	70.0	88.1	91.1	35.6	853.0
90°	79.1	76.5	59.1	41.8	24.8	7.9	24.8	41.8	59.1	76.5	79.1	29.8	882.8
95°	70.8	67.2	52.2	37.2	21.1	4.9	21.1	37.2	52.2	67.2	70.8	26.2	909.0
100°	61.9	57.9	42.8	27.7	15.7	3.6	15.7	27.7	42.8	57.9	61.9	21.6	930.6
105°	58.3	54.5	40.5	26.6	14.5	2.4	14.5	26.6	40.5	54.5	58.3	20.0	950.6
110°	53.8	51.1	39.2	27.4	14.5	1.6	14.5	27.4	39.2	51.1	53.8	18.5	969.1
115°	50.1	47.3	36.0	24.7	13.2	1.6	13.2	24.7	36.0	47.3	50.1	16.4	985.5
120°	46.4	44.3	33.2	22.1	11.8	1.6	11.8	22.1	33.2	44.3	46.4	14.5	1000.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Batten 41			Order number: 51LP327KM20AE EAN: 4058352704998							LP number 59484_8	
UGR-Table			Standard room							siteco	
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	20.2	21.9	20.7	22.3	22.8	19.9	21.6	20.3	22.0	22.4
	3H	22.3	23.9	22.8	24.3	24.8	21.6	23.2	22.1	23.6	24.1
	4H	23.3	24.7	23.8	25.2	25.7	22.3	23.8	22.8	24.2	24.7
	6H	24.2	25.5	24.7	26.0	26.6	22.9	24.2	23.4	24.7	25.3
	8H	24.7	25.9	25.2	26.4	27.0	23.1	24.4	23.6	24.9	25.5
	12H	25.0	26.1	25.6	26.7	27.3	23.2	24.4	23.8	25.0	25.6
4H	2H	21.0	22.4	21.5	22.9	23.4	20.7	22.1	21.2	22.6	23.1
	3H	23.3	24.5	23.8	25.0	25.6	22.6	23.8	23.1	24.3	24.9
	4H	24.4	25.5	25.0	26.1	26.7	23.4	24.6	24.0	25.1	25.7
	6H	25.4	26.4	26.0	27.0	27.7	24.1	25.1	24.7	25.7	26.3
	8H	26.0	26.9	26.6	27.5	28.2	24.5	25.4	25.1	26.0	26.6
	12H	26.4	27.2	27.1	27.9	28.6	24.6	25.5	25.2	26.1	26.8
8H	4H	24.8	25.7	25.4	26.3	27.0	23.9	24.8	24.5	25.4	26.1
	6H	26.1	26.9	26.7	27.5	28.2	24.9	25.6	25.5	26.3	27.0
	8H	26.7	27.4	27.4	28.1	28.8	25.3	26.0	25.9	26.6	27.3
	12H	27.3	27.9	28.0	28.6	29.4	25.6	26.2	26.2	26.8	27.6
12H	4H	24.8	25.6	25.4	26.2	26.9	24.0	24.8	24.6	25.4	26.1
	6H	26.2	26.8	26.8	27.5	28.2	25.0	25.7	25.7	26.3	27.1
	8H	26.9	27.5	27.5	28.1	28.9	25.5	26.1	26.2	26.7	27.5

Luminance table		Max. for $\gamma \geq 65^\circ$				Photometric dimensions in mm:		L = 1175 B = 25		H(C0) = 18 H(C90) = 0		H(C180) = 18 H(C270) = 0	
C-planes	0°	30°	60°	90°	120°	150°	180°	210°	240°	270°	300°	330°	
γ	Luminance in cd/m²												
45°	10607.0	10862.5	11919.0	14611.5	11919.0	10862.5	10607.0	10862.5	11919.0	14611.5	11919.0	10862.5	
50°	10306.7	10407.6	11464.6	14285.4	11464.6	10407.6	10306.7	10407.6	11464.6	14285.4	11464.6	10407.6	
55°	10040.2	10487.6	10987.3	13938.1	10987.3	10487.6	10040.2	10487.6	10987.3	13938.1	10987.3	10487.6	
60°	9767.4	10206.2	10607.7	13754.6	10607.7	10206.2	9767.4	10206.2	10607.7	13754.6	10607.7	10206.2	
65°	9496.2	9920.6	10169.4	13383.0	10169.4	9920.6	9496.2	9920.6	10169.4	13383.0	10169.4	9920.6	
70°	9096.8	9584.0	9589.8	13142.2	9589.8	9584.0	9096.8	9584.0	9589.8	13142.2	9589.8	9584.0	
75°	8734.2	9239.2	9056.8	12831.8	9056.8	9239.2	8734.2	9239.2	9056.8	12831.8	9056.8	9239.2	
80°	8373.1	8804.0	8487.1	12598.9	8487.1	8804.0	8373.1	8804.0	8487.1	12598.9	8487.1	8804.0	
85°	7953.0	8471.8	7912.4	13637.2	7912.4	8471.8	7953.0	8471.8	7912.4	13637.2	7912.4	8471.8	

Photometric test report

Family
Batten 41

Order number: 51LP327KM20AE
EAN: 4058352704998

LP number
59484_8

Luminance values in cd/m²

γ 65°

γ 70°

γ 75°

γ 80°

γ 85°

siteco

