

Photometric test report

Family
Batten 41

Order number: **51LP327KM20AN**
EAN: **4058352705070**

LP number
59484_6



Version diffuser optic, frosted, polycarbonate,
adjustable color temperature: 3000K | 4000K |
5000K, extremely wide distribution

Lamps LED 4000 K | CRI ≥ 80

Controlgear ECG

Setting factory setting: colour temperature 4000K

Rated values Net luminous flux = 2000 lm
Power consumption = 16.0 W
Luminous efficacy = 125 lm/W

serial
documentation
26.08.2024


sitEco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 230 cd/klm



Classifications

DIN 5040 B 3 1
CIE N1=37 N2=66 N3=87
N4=87 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 86.8%
 ϕ_o 13.2%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Batten 41	Order number: 51LP327KM20AN EAN: 4058352705070	LP number 59484_6
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes	0°	15°	30°	45°	60°	75°	90°	105°	120°	135°	150°	165°	180°
γ	Luminous intensity in cd/klm												
0°	229.9	229.9	229.9	229.9	229.9	229.9	229.9	229.9	229.9	229.9	229.9	229.9	229.9
5°	229.9	229.9	229.8	229.6	229.4	229.8	230.2	229.8	229.4	229.6	229.8	229.9	229.9
10°	229.7	229.0	228.3	227.9	227.4	227.5	227.7	227.5	227.4	227.9	228.3	229.0	229.7
15°	227.6	227.6	227.7	225.6	223.6	222.8	222.0	222.8	223.6	225.6	227.7	227.6	227.6
20°	224.1	223.7	223.2	219.8	216.4	214.9	213.5	214.9	216.4	219.8	223.2	223.7	224.1
25°	217.8	217.7	217.6	213.6	209.6	206.7	203.8	206.7	209.6	213.6	217.6	217.7	217.8
30°	210.2	209.6	209.0	204.6	200.1	195.9	191.6	195.9	200.1	204.6	209.0	209.6	210.2
35°	201.7	201.5	201.4	197.3	193.2	185.2	177.3	185.2	193.2	197.3	201.4	201.5	201.7
40°	194.4	193.3	192.2	186.6	181.1	174.2	167.4	174.2	181.1	186.6	192.2	193.3	194.4
45°	189.5	186.3	183.2	175.8	168.3	160.1	151.8	160.1	168.3	175.8	183.2	186.3	189.5
50°	180.8	176.0	171.3	163.0	154.7	144.8	134.9	144.8	154.7	163.0	171.3	176.0	180.8
55°	171.6	169.3	167.0	153.6	140.2	128.8	117.4	128.8	140.2	153.6	167.0	169.3	171.6
60°	161.2	158.5	155.9	141.2	126.5	113.7	101.0	113.7	126.5	141.2	155.9	158.5	161.2
65°	150.0	146.9	143.9	127.9	111.9	97.5	83.1	97.5	111.9	127.9	143.9	146.9	150.0
70°	136.1	133.4	130.6	113.2	95.8	80.9	66.0	80.9	95.8	113.2	130.6	133.4	136.1
75°	122.4	119.6	116.9	98.8	80.7	64.7	48.8	64.7	80.7	98.8	116.9	119.6	122.4
80°	108.6	105.2	101.9	83.8	65.8	49.0	32.1	49.0	65.8	83.8	101.9	105.2	108.6
85°	94.0	91.1	88.1	70.0	51.8	34.6	17.5	34.6	51.8	70.0	88.1	91.1	94.0
90°	81.7	79.1	76.5	59.1	41.8	24.8	7.9	24.8	41.8	59.1	76.5	79.1	81.7
95°	74.4	70.8	67.2	52.2	37.2	21.1	4.9	21.1	37.2	52.2	67.2	70.8	74.4
100°	65.8	61.9	57.9	42.8	27.7	15.7	3.6	15.7	27.7	42.8	57.9	61.9	65.8
105°	62.2	58.3	54.5	40.5	26.6	14.5	2.4	14.5	26.6	40.5	54.5	58.3	62.2
110°	56.6	53.8	51.1	39.2	27.4	14.5	1.6	14.5	27.4	39.2	51.1	53.8	56.6
115°	52.8	50.1	47.3	36.0	24.7	13.2	1.6	13.2	24.7	36.0	47.3	50.1	52.8
120°	48.4	46.4	44.3	33.2	22.1	11.8	1.6	11.8	22.1	33.2	44.3	46.4	48.4
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Photometric test report

Family Batten 41	Order number: 51LP327KM20AN EAN: 4058352705070	LP number 59484_6
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes	195°	210°	225°	240°	255°	270°	285°	300°	315°	330°	345°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm											Luminous flux in lm/klm	
0°	229.9	229.9	229.9	229.9	229.9	229.9	229.9	229.9	229.9	229.9	229.9	1.4	1.4
5°	229.9	229.8	229.6	229.4	229.8	230.2	229.8	229.4	229.6	229.8	229.9	11.0	12.4
10°	229.0	228.3	227.9	227.4	227.5	227.7	227.5	227.4	227.9	228.3	229.0	21.7	34.1
15°	227.6	227.7	225.6	223.6	222.8	222.0	222.8	223.6	225.6	227.7	227.6	32.0	66.0
20°	223.7	223.2	219.8	216.4	214.9	213.5	214.9	216.4	219.8	223.2	223.7	41.1	107.2
25°	217.7	217.6	213.6	209.6	206.7	203.8	206.7	209.6	213.6	217.6	217.7	49.3	156.4
30°	209.6	209.0	204.6	200.1	195.9	191.6	195.9	200.1	204.6	209.0	209.6	55.7	212.2
35°	201.5	201.4	197.3	193.2	185.2	177.3	185.2	193.2	197.3	201.4	201.5	61.2	273.4
40°	193.3	192.2	186.6	181.1	174.2	167.4	174.2	181.1	186.6	192.2	193.3	65.1	338.5
45°	186.3	183.2	175.8	168.3	160.1	151.8	160.1	168.3	175.8	183.2	186.3	67.5	405.9
50°	176.0	171.3	163.0	154.7	144.8	134.9	144.8	154.7	163.0	171.3	176.0	67.7	473.6
55°	169.3	167.0	153.6	140.2	128.8	117.4	128.8	140.2	153.6	167.0	169.3	67.6	541.2
60°	158.5	155.9	141.2	126.5	113.7	101.0	113.7	126.5	141.2	155.9	158.5	65.4	606.7
65°	146.9	143.9	127.9	111.9	97.5	83.1	97.5	111.9	127.9	143.9	146.9	61.6	668.3
70°	133.4	130.6	113.2	95.8	80.9	66.0	80.9	95.8	113.2	130.6	133.4	56.2	724.5
75°	119.6	116.9	98.8	80.7	64.7	48.8	64.7	80.7	98.8	116.9	119.6	50.0	774.5
80°	105.2	101.9	83.8	65.8	49.0	32.1	49.0	65.8	83.8	101.9	105.2	42.8	817.3
85°	91.1	88.1	70.0	51.8	34.6	17.5	34.6	51.8	70.0	88.1	91.1	35.6	853.0
90°	79.1	76.5	59.1	41.8	24.8	7.9	24.8	41.8	59.1	76.5	79.1	29.8	882.8
95°	70.8	67.2	52.2	37.2	21.1	4.9	21.1	37.2	52.2	67.2	70.8	26.2	909.0
100°	61.9	57.9	42.8	27.7	15.7	3.6	15.7	27.7	42.8	57.9	61.9	21.6	930.6
105°	58.3	54.5	40.5	26.6	14.5	2.4	14.5	26.6	40.5	54.5	58.3	20.0	950.6
110°	53.8	51.1	39.2	27.4	14.5	1.6	14.5	27.4	39.2	51.1	53.8	18.5	969.1
115°	50.1	47.3	36.0	24.7	13.2	1.6	13.2	24.7	36.0	47.3	50.1	16.4	985.5
120°	46.4	44.3	33.2	22.1	11.8	1.6	11.8	22.1	33.2	44.3	46.4	14.5	1000.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Batten 41	Order number: 51LP327KM20AN EAN: 4058352705070	LP number 59484_6
-----------------------------------	---	------------------------------------

UGR-Table	Standard room	siteco
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	20.2	21.9	20.7	22.3	22.8	19.9	21.6	20.3	22.0	22.4
	3H	22.3	23.9	22.8	24.3	24.8	21.6	23.2	22.1	23.6	24.1
	4H	23.3	24.7	23.8	25.2	25.7	22.3	23.8	22.8	24.2	24.7
	6H	24.2	25.5	24.7	26.0	26.6	22.9	24.2	23.4	24.7	25.3
	8H	24.7	25.9	25.2	26.4	27.0	23.1	24.4	23.6	24.9	25.5
	12H	25.0	26.1	25.6	26.7	27.3	23.2	24.4	23.8	25.0	25.6
4H	2H	21.0	22.4	21.5	22.9	23.4	20.7	22.1	21.2	22.6	23.1
	3H	23.3	24.5	23.8	25.0	25.6	22.6	23.8	23.1	24.3	24.9
	4H	24.4	25.5	25.0	26.1	26.7	23.4	24.6	24.0	25.1	25.7
	6H	25.4	26.4	26.0	27.0	27.7	24.1	25.1	24.7	25.7	26.3
	8H	26.0	26.9	26.6	27.5	28.2	24.5	25.4	25.1	26.0	26.6
	12H	26.4	27.2	27.1	27.9	28.6	24.6	25.5	25.2	26.1	26.8
8H	4H	24.8	25.7	25.4	26.3	27.0	23.9	24.8	24.5	25.4	26.1
	6H	26.1	26.9	26.7	27.5	28.2	24.9	25.6	25.5	26.3	27.0
	8H	26.7	27.4	27.4	28.1	28.8	25.3	26.0	25.9	26.6	27.3
	12H	27.3	27.9	28.0	28.6	29.4	25.6	26.2	26.2	26.8	27.6
12H	4H	24.8	25.6	25.4	26.2	26.9	24.0	24.8	24.6	25.4	26.1
	6H	26.2	26.8	26.8	27.5	28.2	25.0	25.7	25.7	26.3	27.1
	8H	26.9	27.5	27.5	28.1	28.9	25.5	26.1	26.2	26.7	27.5

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 1175	H(C0) = 18	H(C180) = 18
			B = 25	H(C90) = 0	H(C270) = 0

C-planes	0°	30°	60°	90°	120°	150°	180°	210°	240°	270°	300°	330°
γ	Luminance in cd/m²											
45°	10607.0	10862.5	11919.0	14611.5	11919.0	10862.5	10607.0	10862.5	11919.0	14611.5	11919.0	10862.5
50°	10306.7	10407.6	11464.6	14285.4	11464.6	10407.6	10306.7	10407.6	11464.6	14285.4	11464.6	10407.6
55°	10040.2	10487.6	10987.3	13938.1	10987.3	10487.6	10040.2	10487.6	10987.3	13938.1	10987.3	10487.6
60°	9767.4	10206.2	10607.7	13754.6	10607.7	10206.2	9767.4	10206.2	10607.7	13754.6	10607.7	10206.2
65°	9496.2	9920.6	10169.4	13383.0	10169.4	9920.6	9496.2	9920.6	10169.4	13383.0	10169.4	9920.6
70°	9096.8	9584.0	9589.8	13142.2	9589.8	9584.0	9096.8	9584.0	9589.8	13142.2	9589.8	9584.0
75°	8734.2	9239.2	9056.8	12831.8	9056.8	9239.2	8734.2	9239.2	9056.8	12831.8	9056.8	9239.2
80°	8373.1	8804.0	8487.1	12598.9	8487.1	8804.0	8373.1	8804.0	8487.1	12598.9	8487.1	8804.0
85°	7953.0	8471.8	7912.4	13637.2	7912.4	8471.8	7953.0	8471.8	7912.4	13637.2	7912.4	8471.8

Photometric test report

Family Batten 41	Order number: 51LP327KM20AN EAN: 4058352705070	LP number 59484_6
-----------------------------------	---	------------------------------------

Luminance values in cd/m²

γ 65°
 γ 70°
 γ 75°
 γ 80°
 γ 85°

