

Photometric test report

Family
Modario® 31



Order number: 53BM8117U4GXC2
EAN: 4069025227089

Version

Lamps

Controlgear

Rated values

diffuser optic, frosted, narrow distribution

LED 4000 K | CRI ≥ 80


ECG

Net luminous flux = 16360 lm
Power consumption = 90.4 W
Luminous efficacy = 181 lm/W

LP number
59593_42

serial
documentation
30.08.2024

siteco



Classifications		Luminaire light output ratios	
DIN 5040	A 4 1	η_{LB}	100.0%
CIE	N1=50 N2=78 N3=94	ϕ_u	90.4%
	N4=90 N5=100	ϕ_o	9.6%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Modario® 31	Order number: 53BM8117U4GXC2 EAN: 4069025227089	LP number 59593_42
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	450.4	450.4	450.4	450.4	450.4	450.4	450.4	2.7	2.7
5°	434.8	434.4	434.2	439.8	445.7	448.7	450.2	21.1	23.8
10°	387.7	390.2	396.4	411.2	428.2	439.8	444.6	39.4	63.1
15°	329.8	334.4	345.9	370.2	400.2	424.7	434.9	53.4	116.5
20°	278.9	283.9	296.1	324.2	364.7	403.3	420.8	63.2	179.7
25°	239.6	243.9	253.6	279.8	325.0	376.1	401.3	69.5	249.1
30°	209.6	212.8	219.1	240.3	283.9	343.6	376.3	72.7	321.9
35°	186.9	188.8	191.5	205.8	243.8	306.6	344.9	73.5	395.4
40°	173.0	173.1	171.1	177.5	207.0	267.1	308.1	72.6	468.0
45°	169.1	166.9	158.6	155.4	174.1	225.8	265.4	70.9	538.9
50°	171.8	167.4	153.3	140.0	146.6	186.3	219.9	69.2	608.2
55°	169.0	164.3	148.2	128.3	123.8	150.1	175.1	66.4	674.5
60°	152.5	148.9	135.5	115.0	103.6	117.6	133.2	60.4	734.9
65°	126.3	124.1	114.5	97.6	84.4	89.2	96.9	51.5	786.4
70°	99.0	97.7	90.6	78.2	65.9	64.8	67.1	41.2	827.6
75°	76.1	75.0	69.7	60.3	49.1	44.1	43.1	31.6	859.2
80°	57.7	56.8	53.2	44.9	34.6	27.3	24.1	23.2	882.4
85°	43.5	42.6	39.5	32.5	22.9	14.7	10.1	16.3	898.6
90°	33.0	32.1	28.8	22.5	14.4	6.3	0.8	11.1	909.7
95°	29.9	28.9	25.8	20.4	13.4	6.1	0.9	10.0	919.7
100°	28.7	27.7	24.5	19.6	13.4	6.3	0.9	9.6	929.3
105°	27.4	26.4	23.6	19.5	13.7	6.7	0.8	9.2	938.4
110°	26.5	25.4	23.3	19.7	14.2	7.2	0.7	8.9	947.3
115°	26.1	25.1	23.5	20.2	14.6	6.8	0.8	8.6	955.9
120°	26.2	25.3	23.9	20.5	14.8	6.4	0.8	8.3	964.2
125°	26.5	25.6	24.0	20.4	14.4	6.3	0.8	7.8	972.0
130°	26.5	25.4	23.5	19.6	12.9	6.2	0.9	7.1	979.0
135°	25.6	24.4	22.2	18.2	10.9	5.6	1.1	6.1	985.2
140°	23.7	22.4	20.1	15.4	9.4	4.6	1.1	4.9	990.1
145°	21.0	19.8	17.0	12.1	7.6	3.5	1.3	3.7	993.8
150°	16.9	15.5	12.9	9.4	6.3	2.5	1.3	2.5	996.4
155°	12.6	11.7	10.1	7.4	5.2	1.9	1.4	1.7	998.0
160°	9.9	9.3	7.5	5.7	3.8	1.6	1.4	1.0	999.1
165°	7.7	7.3	5.1	4.1	2.4	1.5	1.4	0.6	999.7
170°	4.8	3.7	2.7	2.3	1.6	1.5	1.5	0.2	999.9
175°	1.6	1.5	1.5	1.5	1.5	1.5	1.5	0.1	1000.0
180°	1.5	1.5	1.5	1.5	1.5	1.5	1.5	0.0	1000.0

Photometric test report

Family Modario® 31			Order number: 53BM8117U4GXC2 EAN: 4069025227089							LP number 59593_42	
UGR-Table			Standard room							siteco	
Reflection factor of ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Reflection factor of walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reflection factor of floor		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	22.1	23.8	22.5	24.1	24.4	22.6	24.3	23.0	24.6	24.9
	3H	23.9	25.4	24.3	25.7	26.1	23.8	25.4	24.2	25.7	26.0
	4H	24.6	26.0	25.0	26.3	26.7	24.3	25.7	24.7	26.1	26.4
	6H	25.1	26.5	25.6	26.8	27.2	24.6	25.9	25.0	26.3	26.7
	8H	25.4	26.7	25.9	27.0	27.4	24.8	26.0	25.2	26.4	26.8
	12H	25.7	26.8	26.1	27.2	27.6	24.8	26.0	25.3	26.4	26.8
4H	2H	22.7	24.1	23.1	24.5	24.9	23.1	24.5	23.5	24.9	25.2
	3H	24.7	25.9	25.1	26.3	26.7	24.5	25.7	24.9	26.1	26.5
	4H	25.5	26.6	25.9	27.0	27.4	25.0	26.1	25.5	26.5	27.0
	6H	26.2	27.2	26.7	27.6	28.1	25.4	26.4	25.9	26.8	27.3
	8H	26.6	27.5	27.0	27.9	28.4	25.6	26.5	26.1	26.9	27.4
	12H	26.9	27.7	27.4	28.1	28.6	25.7	26.5	26.2	27.0	27.5
8H	4H	25.8	26.7	26.2	27.1	27.6	25.4	26.2	25.8	26.7	27.1
	6H	26.7	27.4	27.2	27.9	28.4	25.9	26.6	26.4	27.1	27.6
	8H	27.1	27.8	27.6	28.3	28.8	26.1	26.8	26.6	27.2	27.8
	12H	27.6	28.1	28.1	28.6	29.2	26.3	26.8	26.8	27.3	27.9
12H	4H	25.8	26.6	26.3	27.1	27.6	25.4	26.2	25.9	26.7	27.2
	6H	26.8	27.4	27.3	27.9	28.4	26.0	26.7	26.5	27.1	27.7
	8H	27.3	27.8	27.8	28.3	28.9	26.3	26.8	26.8	27.3	27.9

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 2392 B = 75	H(C0) = 25 H(C90) = 0	H(C180) = 25 H(C270) = 0
C-planes	γ	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
			Luminance in cd/m²					
45°		16353.5	16277.2	15872.0	16222.3	19242.2	26811.2	34223.4
50°		17439.7	17166.6	16178.9	15507.2	17348.7	23971.0	31196.1
55°		18201.8	17895.4	16689.1	15255.5	15903.3	21245.9	27834.5
60°		17627.7	17439.8	16472.2	14896.3	14663.0	18653.0	24300.2
65°		15890.4	15843.1	15255.4	13990.2	13421.7	16241.1	20913.5
70°		13783.5	13819.6	13466.5	12656.9	12049.7	13963.3	17901.5
75°		11942.8	12008.1	11825.5	11299.0	10662.5	11766.4	15172.6
80°		10490.7	10557.9	10589.2	10084.6	9341.7	9642.6	12632.2
85°		9458.2	9527.4	9622.7	9195.7	8233.3	7759.0	10521.8

Photometric test report

Family
Modario® 31

Order number: 53BM8117U4GXC2
EAN: 4069025227089

LP number
59593_42

Luminance values in cd/m²

γ 65°

γ 70°

γ 75°

γ 80°

γ 85°

siteco

