

Photometric test report

Family
Lunis 21



Order number: 51DB16MD91C
EAN: 4069025013262

Version

Lamps

Controlgear

Setting

Rated values

recessed luminaire, cover opal, PMMA, diffuse beam, adjustable color temperature: 3000K | 4000K | 6500K

LED 6500 K | CRI ≥ 80

ECG Multilumen


individual position: DIP-Step=1, colour temperature 6500K

Net luminous flux = 1730 lm
Power consumption = 12.2 W
Luminous efficacy = 141.8 lm/W

LP number
59574_34

serial
documentation
27.09.2024

siteco



Classifications		Luminaire light output ratios	
DIN 5040	A 4 0	η_{LB}	100.0%
CIE	N1=50 N2=80 N3=96	ϕ_u	100.0%
	N4=100 N5=100	ϕ_o	0.0%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Lunis 21	Order number: 51DB16MD91C EAN: 4069025013262	LP number 59574_34
Table of values for luminous intensities		Maximum luminous intensity

siteco

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm Luminous flux in lm/klm		
0°	388.6	0.1	0.1
1°	388.5	0.7	0.8
2°	388.2	1.5	2.3
3°	387.7	2.2	4.5
4°	387.0	3.0	7.5
5°	386.1	3.7	11.2
6°	385.0	4.4	15.6
7°	383.7	5.1	20.7
8°	382.2	5.8	26.6
9°	380.5	6.5	33.1
10°	378.7	7.2	40.3
11°	376.6	7.9	48.2
12°	374.4	8.5	56.7
13°	372.0	9.2	65.9
14°	369.4	9.8	75.7
15°	366.7	10.4	86.1
16°	363.6	11.0	97.1
17°	360.6	11.6	108.7
18°	357.5	12.1	120.8
19°	353.9	12.6	133.4
20°	350.6	13.1	146.6
21°	347.0	13.6	160.2
22°	343.1	14.1	174.3
23°	339.3	14.5	188.8
24°	335.2	14.9	203.8
25°	331.0	15.3	219.1
26°	326.9	15.7	234.8
27°	322.3	16.0	250.9
28°	317.9	16.4	267.2
29°	313.5	16.7	283.9
30°	308.6	16.9	300.8
31°	304.0	17.2	318.0
32°	299.1	17.4	335.4
33°	294.2	17.6	353.0
34°	289.4	17.7	370.7
35°	284.0	17.9	388.6
36°	279.1	18.0	406.6
37°	274.0	18.1	424.6
38°	268.5	18.1	442.8
39°	263.3	18.2	460.9
40°	257.8	18.2	479.1
41°	252.6	18.2	497.3
42°	247.3	18.1	515.4
43°	241.7	18.1	533.5
44°	236.3	18.0	551.5
45°	230.5	17.9	569.4
46°	225.0	17.7	587.1

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm Luminous flux in lm/klm		
47°	219.7	17.6	604.8
48°	213.7	17.4	622.2
49°	208.2	17.2	639.4
50°	202.8	17.0	656.4
51°	196.8	16.8	673.2
52°	191.2	16.5	689.7
53°	185.4	16.2	706.0
54°	179.7	15.9	721.9
55°	174.1	15.6	737.5
56°	168.1	15.3	752.8
57°	162.4	14.9	767.8
58°	156.7	14.6	782.3
59°	150.8	14.2	796.5
60°	145.1	13.8	810.3
61°	139.2	13.4	823.7
62°	133.5	12.9	836.6
63°	127.9	12.5	849.1
64°	121.9	12.0	861.1
65°	116.3	11.6	872.6
66°	110.7	11.1	883.7
67°	104.9	10.6	894.3
68°	99.4	10.1	904.4
69°	93.7	9.6	914.0
70°	88.2	9.1	923.1
71°	82.8	8.6	931.7
72°	77.2	8.1	939.8
73°	72.1	7.6	947.3
74°	66.7	7.0	954.3
75°	61.3	6.5	960.8
76°	56.5	6.0	966.8
77°	51.1	5.5	972.3
78°	46.1	4.9	977.3
79°	41.4	4.5	981.7
80°	36.4	3.9	985.6
81°	31.8	3.4	989.1
82°	27.0	2.9	992.0
83°	22.3	2.4	994.4
84°	17.9	2.0	996.4
85°	13.4	1.5	997.9
86°	9.3	1.0	998.9
87°	5.5	0.6	999.5
88°	2.7	0.3	999.8
89°	1.6	0.2	1000.0
90°	0.9	0.1	1000.0

Photometric test report

Family Lunis 21			Order number: 51DB16MD91C EAN: 4069025013262							LP number 59574_34	
UGR-Table			Standard room							siteco	
Reflection factor of ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Reflection factor of walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reflection factor of floor		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	24.8	26.5	25.1	26.8	27.1	24.8	26.5	25.1	26.8	27.1
	3H	26.3	27.8	26.7	28.1	28.5	26.3	27.8	26.7	28.1	28.5
	4H	26.9	28.3	27.3	28.7	29.1	26.9	28.3	27.3	28.7	29.1
	6H	27.4	28.7	27.8	29.0	29.4	27.4	28.7	27.8	29.0	29.4
	8H	27.6	28.8	28.0	29.2	29.6	27.6	28.8	28.0	29.2	29.6
	12H	27.6	28.8	28.1	29.2	29.6	27.6	28.8	28.1	29.2	29.6
4H	2H	25.5	26.9	25.9	27.3	27.6	25.5	26.9	25.9	27.3	27.6
	3H	27.2	28.4	27.6	28.8	29.2	27.2	28.4	27.6	28.8	29.2
	4H	27.9	29.0	28.4	29.4	29.9	27.9	29.0	28.4	29.4	29.9
	6H	28.5	29.5	29.0	29.9	30.3	28.5	29.5	29.0	29.9	30.3
	8H	28.7	29.6	29.2	30.0	30.5	28.7	29.6	29.2	30.0	30.5
	12H	28.8	29.6	29.3	30.1	30.6	28.8	29.6	29.3	30.1	30.6
8H	4H	28.3	29.1	28.7	29.6	30.0	28.3	29.1	28.7	29.6	30.0
	6H	29.0	29.7	29.4	30.1	30.6	29.0	29.7	29.4	30.1	30.6
	8H	29.2	29.8	29.7	30.3	30.8	29.2	29.8	29.7	30.3	30.8
	12H	29.4	29.9	29.9	30.4	31.0	29.4	29.9	29.9	30.4	31.0
12H	4H	28.3	29.1	28.8	29.5	30.0	28.3	29.1	28.8	29.5	30.0
	6H	29.0	29.7	29.5	30.1	30.7	29.0	29.7	29.5	30.1	30.7
	8H	29.3	29.9	29.8	30.4	30.9	29.3	29.9	29.8	30.4	30.9

Luminance table		Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	D = 135
C-planes		0°		
γ	Luminance in cd/m²			
45°	39400.9			
50°	38135.9			
55°	36676.8			
60°	35084.5			
65°	33248.1			
70°	31168.8			
75°	28626.0			
80°	25305.0			
85°	18553.1			

Photometric test report

Family
Lunis 21

Order number: 51DB16MD91C
EAN: 4069025013262

LP number
59574_34

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Lunis 21	Order number: 51DB16MD91C EAN: 4069025013262	LP number 59574_34
Multilumen Table	environmental temperature: 25°C	siteco

DIP-Step	Switch Setting				Luminous flux [lm]	Power consumption [W]
	1	2	3	4		
7	OFF	ON	ON	ON	3020	21.7
6	OFF	ON	ON	OFF	2820	20.3
5	OFF	ON	OFF	ON	2690	19.2
4	OFF	ON	OFF	OFF	2500	17.7
3	OFF	OFF	ON	ON	2190	15.5
2	OFF	OFF	ON	OFF	1950	13.7
1	OFF	OFF	OFF	ON	1730	12.2
0	OFF	OFF	OFF	OFF	1490	10.5