

Photometric test report

Family
Monsun® 11




Order number: 51FE107P680S
EAN: 4069025242372

Version
prismatic diffuser, opal, PMMA, wide distribution
Lamps
LED 6500 K | CRI ≥ 80
Controlgear
ECG
Rated values
Net luminous flux = 7900 lm
Power consumption = 41.8 W
Luminous efficacy = 189 lm/W

LP number
58939_145

serial
documentation
20.08.2024

siteco



Classifications		Luminaire light output ratios	
DIN 5040	A 4 1	η_{LB}	100.0%
CIE	N1=47 N2=77 N3=93	ϕ_u	94.2%
	N4=94 N5=100	ϕ_o	5.8%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Monsun® 11	Order number: 51FE107P680S EAN: 4069025242372	LP number 58939_145
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	340.1	340.1	340.1	340.1	340.1	340.1	340.1	2.0	2.0
5°	339.4	338.3	336.5	337.9	339.5	339.4	339.8	16.2	18.2
10°	333.5	333.0	331.2	332.8	334.6	334.7	335.0	31.7	49.9
15°	324.2	324.2	322.5	324.2	326.1	326.4	326.9	46.1	96.0
20°	311.0	311.6	310.1	311.9	314.1	314.7	315.3	58.6	154.6
25°	294.4	295.4	294.1	296.0	298.4	299.4	300.2	68.7	223.4
30°	275.2	276.6	275.1	276.8	279.4	280.7	281.6	76.1	299.5
35°	253.9	255.2	253.8	254.9	257.1	258.4	259.7	80.5	380.0
40°	231.8	232.9	231.3	231.1	232.5	233.8	235.1	81.9	461.9
45°	209.4	209.9	207.8	205.9	206.1	206.6	208.2	80.4	542.4
50°	187.2	187.1	184.8	181.3	179.3	178.3	179.7	76.6	619.0
55°	165.5	164.8	162.1	157.0	153.1	150.2	150.9	70.7	689.7
60°	143.9	142.9	139.5	133.7	127.9	123.2	122.7	63.3	753.0
65°	123.6	122.5	117.8	111.0	104.2	97.9	96.0	54.9	808.0
70°	104.7	103.3	97.1	89.4	81.7	74.3	71.0	45.8	853.8
75°	86.1	84.4	77.8	69.2	60.2	52.2	47.8	36.3	890.0
80°	68.0	66.1	60.2	50.5	40.7	32.1	26.9	26.7	916.7
85°	51.8	50.0	44.6	35.3	24.7	15.7	10.1	18.3	935.0
90°	40.8	39.2	34.4	26.0	15.9	6.9	1.8	13.1	948.2
95°	34.8	33.5	29.7	22.7	13.6	5.1	1.6	11.2	959.3
100°	29.9	28.8	25.4	19.2	11.3	3.7	1.4	9.4	968.7
105°	25.7	24.7	21.4	16.1	8.8	2.4	1.2	7.7	976.4
110°	22.1	20.9	18.0	13.0	6.6	1.4	1.1	6.1	982.5
115°	19.0	17.8	15.0	10.4	4.7	1.2	1.1	4.9	987.4
120°	16.0	14.8	12.2	7.9	3.1	1.2	1.0	3.8	991.2
125°	13.0	11.9	9.4	5.6	1.7	1.1	0.9	2.7	993.9
130°	10.1	9.1	6.9	3.7	1.4	1.1	1.0	1.9	995.9
135°	7.3	6.5	4.6	2.1	1.4	1.1	1.1	1.3	997.1
140°	4.8	4.1	2.7	1.7	1.4	1.1	1.1	0.8	998.0
145°	2.6	2.3	1.9	1.7	1.4	1.2	1.2	0.5	998.5
150°	2.0	2.0	1.9	1.6	1.3	1.3	1.3	0.4	998.9
155°	1.9	1.9	1.7	1.6	1.4	1.4	1.4	0.4	999.3
160°	1.7	1.7	1.6	1.4	1.4	1.4	1.4	0.3	999.6
165°	1.4	1.4	1.4	1.4	1.4	1.4	1.4	0.2	999.8
170°	1.3	1.4	1.4	1.4	1.4	1.4	1.4	0.1	999.9
175°	1.4	1.4	1.4	1.4	1.4	1.4	1.4	0.1	1000.0
180°	1.4	1.4	1.4	1.4	1.4	1.4	1.4	0.0	1000.0

Photometric test report

Family Monsun® 11			Order number: 51FE107P680S EAN: 4069025242372							LP number 58939_145	
UGR-Table			Standard room							siteco	
Reflection factor of ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Reflection factor of walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reflection factor of floor		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	21.0	22.7	21.4	23.0	23.3	21.0	22.7	21.3	23.0	23.3
	3H	22.7	24.3	23.1	24.6	25.0	22.4	23.9	22.7	24.2	24.6
	4H	23.6	25.0	24.0	25.4	25.7	22.9	24.3	23.3	24.7	25.1
	6H	24.3	25.7	24.7	26.0	26.4	23.2	24.6	23.7	25.0	25.4
	8H	24.7	25.9	25.1	26.3	26.7	23.4	24.7	23.8	25.0	25.4
	12H	25.0	26.2	25.4	26.6	27.0	23.4	24.6	23.9	25.0	25.5
4H	2H	21.7	23.2	22.1	23.5	23.9	21.7	23.1	22.1	23.5	23.9
	3H	23.6	24.9	24.1	25.3	25.7	23.3	24.5	23.7	24.9	25.3
	4H	24.6	25.7	25.0	26.1	26.6	23.9	25.0	24.3	25.4	25.9
	6H	25.5	26.5	26.0	26.9	27.4	24.4	25.4	24.8	25.8	26.3
	8H	25.9	26.8	26.4	27.3	27.8	24.5	25.4	25.0	25.9	26.4
	12H	26.3	27.2	26.8	27.6	28.1	24.6	25.5	25.1	25.9	26.4
8H	4H	24.9	25.8	25.4	26.3	26.7	24.3	25.2	24.8	25.7	26.1
	6H	26.0	26.8	26.5	27.2	27.7	24.9	25.7	25.4	26.2	26.7
	8H	26.5	27.2	27.0	27.7	28.2	25.1	25.8	25.6	26.3	26.8
	12H	27.1	27.7	27.6	28.2	28.7	25.3	25.9	25.8	26.4	26.9
12H	4H	25.0	25.8	25.4	26.2	26.7	24.4	25.2	24.9	25.7	26.2
	6H	26.1	26.8	26.6	27.2	27.8	25.1	25.8	25.6	26.2	26.7
	8H	26.7	27.3	27.2	27.8	28.3	25.4	25.9	25.9	26.4	27.0

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 1590 B = 87	H(C0) = 21 H(C90) = 21	H(C180) = 21 H(C270) = 21
C-planes	γ	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
			Luminance in cd/m²					
45° 50° 55° 60°	γ	13621.9	13706.3	13806.6	14095.3	14703.6	15518.0	16594.5
		12919.4	12967.3	13064.3	13263.6	13765.2	14538.5	15718.1
		12250.8	12265.0	12340.1	12437.4	12825.1	13500.9	14743.9
		11589.9	11580.1	11600.3	11637.1	11892.6	12450.7	13704.6
65° 70° 75° 80°	γ	11008.9	10982.4	10889.5	10820.4	10972.3	11392.3	12616.0
		10510.0	10450.6	10179.4	9987.2	10004.9	10277.6	11446.6
		9989.9	9895.6	9515.9	9129.9	8903.5	8995.3	10056.3
		9438.6	9281.9	8901.5	8215.3	7643.1	7388.8	8223.7
85°	γ	9036.4	8845.1	8431.5	7571.1	6435.6	5514.4	5743.3

Photometric test report

Family
Monsun® 11

Order number: 51FE107P680S
EAN: 4069025242372

LP number
58939_145

Luminance values in cd/m²

γ 65°

γ 70°

γ 75°

γ 80°

γ 85°

siteco

