

Photometric test report

Family
Lunis 41



Order number: 51DR10MDHBB
EAN: 4069025152084

Version

Lamps

Controlgear

Setting

Rated values

recessed luminaire, diffuse cover, extremely wide distribution, adjustable color temperature: 4000 K | 6500 K

LED 6500 K | CRI ≥ 80

ECG


individual position: colour temperature 6500K

Net luminous flux = 1600 lm
Power consumption = 12.5 W
Luminous efficacy = 128 lm/W

LP number
59234_12

serial
documentation
16.01.2025

siteco



Classifications		Luminaire light output ratios	
DIN 5040	A 4 0	η_{LB}	100.0%
CIE	N1=49 N2=80 N3=96	ϕ_u	100.0%
	N4=100 N5=100	ϕ_o	0.0%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Lunis 41	Order number: 51DR10MDHBB EAN: 4069025152084	LP number 59234_12
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0°	368.6	368.6	368.6	368.6	368.6	368.6	368.6	2.2	2.2
5°	367.2	366.8	366.3	365.8	365.5	365.3	365.0	17.5	19.7
10°	362.1	361.4	360.8	360.1	359.5	358.9	358.3	34.3	54.0
15°	354.2	353.1	351.9	350.8	350.1	349.3	348.6	49.8	103.8
20°	342.9	341.5	340.1	338.8	337.8	336.9	336.0	63.6	167.3
25°	327.9	326.3	324.6	323.0	321.8	320.6	319.4	74.9	242.3
30°	310.7	308.8	306.8	304.8	303.5	302.2	300.8	83.7	325.9
35°	290.5	288.3	286.2	284.0	282.5	281.0	279.5	89.4	415.4
40°	267.0	264.6	262.3	260.0	258.4	256.8	255.2	91.8	507.2
45°	242.2	239.7	237.3	234.8	233.0	231.3	229.5	91.2	598.4
50°	215.7	213.2	210.6	208.1	206.2	204.3	202.4	87.6	686.0
55°	186.3	184.1	181.9	179.7	177.4	175.1	172.8	80.7	766.6
60°	157.1	154.5	151.9	149.2	146.6	144.0	141.4	70.8	837.5
65°	128.1	125.1	122.0	118.9	116.8	114.6	112.5	59.4	896.9
70°	96.9	93.9	90.9	87.9	85.9	83.8	81.7	45.6	942.5
75°	66.8	64.2	61.7	59.2	57.0	54.7	52.5	31.5	974.0
80°	40.0	39.6	39.2	38.8	35.1	31.4	27.8	19.6	993.6
85°	16.1	14.5	12.9	11.3	10.3	9.3	8.3	6.4	1000.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
95°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
100°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
105°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
110°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
115°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
120°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
125°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
130°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
135°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
140°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
145°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
150°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
155°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
160°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
165°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
170°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
175°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0
180°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Lunis 41			Order number: 51DR10MDHBB EAN: 4069025152084							LP number 59234_12	
UGR-Table			Standard room							sitemco	
Reflection factor of ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Reflection factor of walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reflection factor of floor		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	25.4	27.1	25.8	27.4	27.7	25.0	26.7	25.4	27.0	27.3
	3H	27.0	28.5	27.4	28.8	29.2	26.4	28.0	26.8	28.3	28.6
	4H	27.6	29.0	28.0	29.4	29.7	26.9	28.4	27.3	28.7	29.1
	6H	28.1	29.4	28.5	29.8	30.2	27.3	28.6	27.7	28.9	29.3
	8H	28.3	29.5	28.7	29.9	30.3	27.4	28.6	27.8	29.0	29.4
	12H	28.4	29.5	28.8	29.9	30.3	27.4	28.6	27.8	29.0	29.4
4H	2H	26.1	27.5	26.5	27.9	28.2	25.8	27.2	26.2	27.6	27.9
	3H	27.8	29.0	28.3	29.4	29.8	27.4	28.6	27.8	29.0	29.4
	4H	28.6	29.7	29.0	30.1	30.5	28.0	29.1	28.4	29.5	29.9
	6H	29.2	30.1	29.6	30.5	31.0	28.4	29.4	28.9	29.8	30.2
	8H	29.4	30.2	29.8	30.7	31.2	28.5	29.4	29.0	29.8	30.3
	12H	29.5	30.3	30.0	30.7	31.2	28.6	29.4	29.1	29.8	30.3
8H	4H	28.8	29.7	29.3	30.2	30.6	28.3	29.2	28.8	29.6	30.1
	6H	29.6	30.3	30.1	30.8	31.3	28.9	29.6	29.4	30.1	30.6
	8H	29.8	30.5	30.3	31.0	31.5	29.1	29.7	29.6	30.2	30.7
	12H	30.0	30.6	30.6	31.1	31.6	29.2	29.7	29.7	30.2	30.7
12H	4H	28.9	29.7	29.4	30.1	30.6	28.4	29.2	28.9	29.6	30.1
	6H	29.7	30.3	30.2	30.8	31.3	29.0	29.6	29.5	30.1	30.6
	8H	29.9	30.5	30.5	31.0	31.5	29.2	29.7	29.7	30.2	30.8

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		D = 125	
C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
γ	Luminance in cd/m²						
45°	44659.7	44205.7	43751.9	43297.8	42970.1	42642.7	42315.0
50°	43753.7	43238.9	42724.3	42209.5	41823.1	41437.1	41050.9
55°	42352.4	41850.7	41348.6	40846.7	40321.9	39796.8	39271.9
60°	40960.6	40278.7	39597.4	38915.5	38233.9	37552.0	36870.3
65°	39534.3	38579.1	37623.7	36668.6	36018.5	35368.5	34718.5
70°	36921.2	35789.0	34656.9	33525.1	32731.4	31938.1	31144.8
75°	33638.8	32359.8	31081.8	29803.3	28690.5	27578.7	26465.9
80°	30014.3	29709.5	29403.9	29099.0	26354.8	23611.3	20867.0
85°	24033.8	21679.2	19326.0	16971.4	15453.1	13934.7	12414.8

Photometric test report

Family
Lunis 41

Order number: 51DR10MDHBB
EAN: 4069025152084

LP number
59234_12

Luminance values in cd/m²

γ 65°

γ 70°

γ 75°

γ 80°

γ 85°

siteco

