



Photometric test report

Family Highbay 11	Order number: 51HN11DA4KDA EAN: 4069025358134	LP number 59711_184
	Version	primary light control with lens, PMMA, housing, white, narrow distribution
	Lamps	LED 4000 K CRI ≥ 80
	Controlgear	ECG-DALI
	Setting	DC mode (central or group accumulator) initial emergency light level
Rated values	Net luminous flux = 3650 lm Power consumption = 18.3 W Luminous efficacy = 199.5 lm/W	serial documentation 14.02.2025
		

Luminous intensity in cd/klm **C180-0** **C270-90** **Imax: 2679 cd/klm**



Classifications	
DIN 5040	A 7 0
CIE	N1=85 N2=97 N3=100 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
 DIN EN 13032 and DIN 5032

Photometric test report

Family Highbay 11	Order number: 51HN11DA4KDA EAN: 4069025358134	LP number 59711_184
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm							Luminous flux in lm/klm		
0,0°	2678.6	2678.6	2678.6	2678.6	2678.6	2678.6	2678.6	4.0	4.0
2,5°	2608.0	2619.4	2619.4	2616.5	2617.6	2616.2	2606.1	31.3	35.3
5,0°	2420.1	2415.7	2414.1	2408.4	2406.6	2402.3	2391.7	57.6	92.8
7,5°	2113.4	2116.1	2112.3	2103.0	2097.6	2090.5	2079.6	75.2	168.1
10,0°	1780.1	1768.7	1762.7	1751.6	1743.6	1735.2	1724.7	83.4	251.5
12,5°	1410.1	1409.3	1404.7	1395.9	1388.1	1380.5	1373.1	82.8	334.3
15,0°	1106.5	1097.8	1095.0	1089.4	1083.1	1078.4	1073.9	77.3	411.5
17,5°	830.1	840.2	835.5	831.1	826.6	824.9	824.1	68.5	480.0
20,0°	671.1	661.9	651.8	643.2	639.9	639.4	641.0	60.8	540.8
22,5°	531.9	530.5	514.2	498.9	497.0	496.6	496.8	53.4	594.2
25,0°	450.6	441.3	420.6	401.3	399.0	395.8	392.4	47.9	642.1
27,5°	370.8	368.7	351.4	331.7	326.8	321.1	316.0	43.1	685.2
30,0°	320.4	312.1	300.8	284.1	278.0	270.2	264.7	39.7	724.9
32,5°	271.0	266.8	259.0	245.6	238.0	229.0	224.7	36.5	761.4
35,0°	235.8	228.9	222.7	210.5	201.6	193.0	191.7	33.3	794.7
37,5°	204.4	197.8	191.5	181.1	172.0	164.3	162.4	30.3	825.0
40,0°	176.7	170.7	163.1	154.3	146.1	138.3	135.6	27.3	852.2
42,5°	147.6	145.5	138.6	130.6	123.2	115.8	113.3	24.2	876.4
45,0°	126.0	121.8	116.3	109.0	102.0	95.3	93.2	21.1	897.6
47,5°	103.2	101.5	97.1	90.9	84.6	78.4	76.7	18.3	915.9
50,0°	85.9	82.9	79.4	74.6	69.1	63.7	61.9	15.5	931.4
52,5°	69.0	67.2	64.5	61.0	56.2	51.6	49.7	13.0	944.4
55,0°	55.6	54.1	52.2	49.5	45.7	41.7	40.0	10.9	955.3
57,5°	43.6	43.1	41.8	39.8	37.0	33.6	32.2	9.0	964.3
60,0°	33.2	33.3	33.9	32.4	30.5	27.5	26.1	7.4	971.7
62,5°	25.9	26.0	27.0	26.2	25.1	22.4	21.3	6.1	977.8
65,0°	21.6	21.2	21.7	21.3	20.9	18.8	17.7	5.1	982.9
67,5°	17.0	17.1	17.8	17.0	17.3	15.6	14.8	4.3	987.2
70,0°	13.5	13.4	14.4	13.6	14.1	13.0	12.4	3.5	990.7
72,5°	11.0	10.8	10.9	10.9	11.0	10.7	10.6	2.8	993.5
75,0°	9.0	8.4	8.4	8.3	8.6	9.0	8.9	2.3	995.8
77,5°	6.6	6.4	6.2	6.2	6.6	7.3	7.4	1.8	997.5
80,0°	4.4	4.2	4.1	4.2	4.7	5.7	5.8	1.3	998.8
82,5°	2.0	2.1	2.2	2.4	3.0	3.9	4.1	0.8	999.6
85,0°	0.8	0.8	0.8	1.0	1.5	2.2	2.4	0.4	999.9
87,5°	0.3	0.3	0.3	0.3	0.3	0.4	0.5	0.1	1000.0
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Highbay 11	Order number: 51HN11DA4KDA EAN: 4069025358134	LP number 59711_184
----------------------	--------------------------------------------------	------------------------

UGR-Table	Standard room	siteco								
-----------	---------------	--------	--	--	--	--	--	--	--	--

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	14.0	15.2	14.3	15.5	15.8	12.8	14.0	13.2	14.3	14.6
	3H	14.2	15.2	14.6	15.6	15.9	13.1	14.1	13.5	14.5	14.8
	4H	14.3	15.2	14.7	15.6	16.0	13.2	14.2	13.6	14.5	14.9
	6H	14.4	15.2	14.8	15.6	15.9	13.4	14.2	13.8	14.6	15.0
	8H	14.4	15.1	14.8	15.5	15.9	13.5	14.2	13.9	14.6	15.0
	12H	14.4	15.0	14.8	15.4	15.8	13.5	14.2	13.9	14.6	15.0
4H	2H	14.0	15.0	14.4	15.3	15.7	13.0	13.9	13.4	14.3	14.7
	3H	14.4	15.1	14.8	15.5	16.0	13.4	14.2	13.8	14.6	15.0
	4H	14.5	15.2	14.9	15.6	16.0	13.6	14.3	14.0	14.7	15.1
	6H	14.6	15.1	15.0	15.6	16.0	13.8	14.4	14.2	14.8	15.3
	8H	14.5	15.1	15.0	15.5	16.0	13.9	14.4	14.3	14.8	15.3
	12H	14.5	15.0	15.0	15.4	15.9	13.9	14.4	14.4	14.8	15.3
8H	4H	14.5	15.0	14.9	15.4	15.9	13.6	14.1	14.1	14.6	15.1
	6H	14.5	15.0	15.0	15.4	16.0	13.8	14.3	14.3	14.7	15.3
	8H	14.5	14.9	15.0	15.4	15.9	13.9	14.3	14.4	14.8	15.3
	12H	14.5	14.8	15.0	15.3	15.9	14.0	14.3	14.5	14.8	15.4
12H	4H	14.4	14.9	14.9	15.3	15.8	13.6	14.0	14.1	14.5	15.0
	6H	14.5	14.9	15.0	15.4	15.9	13.8	14.2	14.3	14.7	15.2
	8H	14.5	14.8	15.0	15.3	15.9	13.9	14.2	14.4	14.7	15.3

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 426 B = 264
-----------------	---------------------------------	-------------------------------	--------------------

C-planes	γ	Luminance in cd/m ²								
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°		
45,0°		5782.6	5589.6	5337.8	5003.9	4681.7	4375.4	4277.5		
50,0°		4335.0	4184.1	4006.9	3769.0	3486.4	3214.1	3123.2		
55,0°		3145.5	3060.4	2954.3	2800.9	2585.1	2359.6	2264.8		
60,0°		2158.2	2160.5	2200.7	2102.6	1977.5	1784.2	1695.1		
65,0°		1657.0	1629.0	1666.0	1639.0	1604.4	1441.8	1362.9		
70,0°		1283.8	1268.3	1362.5	1286.7	1335.3	1229.3	1174.9		
75,0°		1125.4	1056.2	1058.6	1044.3	1077.4	1123.4	1121.4		
80,0°		821.1	790.6	764.8	778.6	870.0	1056.5	1078.0		
85,0°		303.9	300.1	313.9	354.9	544.8	802.1	909.0		

Photometric test report

Family Highbay 11	Order number: 51HN11DA4KDA EAN: 4069025358134	LP number 59711_184
-----------------------------	----------------------------------------------------------------	-------------------------------



Luminance values in cd/m²

γ 65°
 γ 70°
 γ 75°
 γ 80°
 γ 85°

