



Photometric test report

Family Highbay 11	Order number: 51HN32DA4KDA EAN: 4069025431110	LP number 59710_186
	Version primary light control with lens, PMMA, housing, black, wide distribution Lamps LED 4000 K CRI ≥ 80 Controlgear ECG-DALI Setting DC mode (central or group accumulator) initial emergency light level Rated values Net luminous flux = 3650 lm Power consumption = 18.3 W Luminous efficacy = 199.5 lm/W	serial documentation 14.02.2025



Luminous intensity in cd/klm C180-0 C270-90 **Imax: 772 cd/klm**



Classifications	
DIN 5040	A 6 0
CIE	N1=88 N2=98 N3=100 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Highbay 11	Order number: 51HN32DA4KDA EAN: 4069025431110	LP number 59710_186
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm							Luminous flux in lm/klm		
0,0°	643.6	643.6	643.6	643.6	643.6	643.6	643.6	1.0	1.0
2,5°	644.5	645.1	645.0	644.3	644.2	643.7	641.7	7.7	8.7
5,0°	651.5	652.3	650.7	647.5	645.3	643.2	640.4	15.5	24.1
7,5°	669.6	669.1	664.2	657.2	651.2	645.8	641.3	23.5	47.6
10,0°	693.4	691.0	681.5	670.0	659.9	651.2	645.8	31.9	79.6
12,5°	711.8	709.4	700.3	685.9	671.9	660.7	654.0	40.7	120.2
15,0°	721.3	721.7	717.1	704.9	689.4	675.9	667.7	49.7	169.9
17,5°	743.8	740.8	737.9	726.5	708.9	693.0	684.2	59.4	229.3
20,0°	761.9	761.9	759.6	745.2	724.0	705.6	696.8	69.2	298.5
22,5°	772.0	771.2	770.0	754.7	731.1	710.8	702.6	78.2	376.7
25,0°	758.1	756.6	756.3	743.6	722.7	703.3	695.6	85.1	461.8
27,5°	706.7	709.5	709.5	700.0	685.7	672.3	667.0	87.8	549.7
30,0°	640.4	635.6	633.7	626.6	621.7	614.1	609.9	85.8	635.5
32,5°	530.6	537.6	535.6	526.2	530.2	524.1	520.8	78.1	713.6
35,0°	428.2	426.4	425.9	411.9	420.8	414.2	411.4	66.0	779.6
37,5°	322.5	323.4	327.0	311.0	319.4	310.8	308.2	53.0	832.6
40,0°	236.1	234.0	241.6	230.8	230.9	219.8	218.4	40.7	873.3
42,5°	162.3	165.3	172.9	171.1	161.7	151.3	150.8	30.2	903.5
45,0°	117.3	114.9	119.4	122.5	109.3	102.6	102.3	21.9	925.4
47,5°	80.5	81.4	82.8	85.5	75.2	71.4	70.8	15.9	941.3
50,0°	59.4	58.0	58.0	59.0	52.9	50.5	49.6	11.7	953.0
52,5°	43.3	42.8	42.8	43.0	39.3	37.2	36.6	8.9	961.8
55,0°	33.3	32.4	32.9	33.7	30.5	28.7	28.3	7.1	968.9
57,5°	25.9	25.4	25.9	26.8	24.5	22.9	22.9	5.8	974.7
60,0°	20.9	20.2	21.2	21.8	20.4	18.9	19.2	4.9	979.5
62,5°	16.9	16.2	17.4	18.0	17.2	15.9	16.4	4.1	983.6
65,0°	14.9	13.6	14.4	15.1	14.8	13.6	14.4	3.6	987.2
67,5°	12.3	11.4	12.5	12.4	13.0	11.7	12.6	3.1	990.3
70,0°	10.4	9.5	10.5	10.1	11.1	10.1	11.0	2.7	993.0
72,5°	8.2	7.7	7.9	8.2	8.7	8.6	9.5	2.2	995.2
75,0°	6.5	6.0	6.0	6.4	6.6	7.1	7.9	1.7	996.9
77,5°	4.5	4.3	4.4	4.7	5.1	5.6	6.3	1.3	998.2
80,0°	2.9	2.7	2.9	3.1	3.5	4.1	4.7	0.9	999.1
82,5°	1.3	1.4	1.6	1.8	2.2	2.7	3.3	0.5	999.7
85,0°	0.6	0.6	0.6	0.7	1.0	1.4	1.8	0.3	999.9
87,5°	0.3	0.3	0.3	0.3	0.3	0.4	0.5	0.1	1000.0
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Highbay 11	Order number: 51HN32DA4KDA EAN: 4069025431110	LP number 59710_186
----------------------	--	------------------------

UGR-Table	Standard room	siteco	
-----------	---------------	--------	--

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	15.0	16.3	15.4	16.6	16.9	14.7	16.0	15.1	16.3	16.6
	3H	15.0	16.1	15.4	16.5	16.8	14.7	15.9	15.1	16.2	16.6
	4H	15.0	16.0	15.4	16.4	16.8	14.8	15.8	15.2	16.2	16.5
	6H	15.0	15.9	15.4	16.3	16.7	14.8	15.7	15.2	16.1	16.5
	8H	15.1	15.8	15.5	16.2	16.6	14.9	15.7	15.3	16.1	16.5
	12H	15.0	15.8	15.5	16.1	16.6	14.9	15.6	15.3	16.0	16.4
4H	2H	14.9	15.9	15.3	16.3	16.7	14.6	15.7	15.0	16.0	16.4
	3H	14.9	15.8	15.4	16.2	16.6	14.7	15.5	15.1	15.9	16.4
	4H	14.9	15.7	15.4	16.1	16.6	14.7	15.5	15.2	15.9	16.4
	6H	14.9	15.6	15.4	16.0	16.5	14.8	15.4	15.2	15.9	16.3
	8H	14.9	15.5	15.4	15.9	16.4	14.8	15.4	15.3	15.8	16.3
	12H	14.9	15.4	15.4	15.8	16.3	14.8	15.3	15.3	15.8	16.3
8H	4H	14.9	15.5	15.4	15.9	16.4	14.7	15.3	15.2	15.7	16.2
	6H	14.9	15.3	15.3	15.8	16.3	14.7	15.2	15.2	15.7	16.2
	8H	14.8	15.2	15.3	15.7	16.3	14.7	15.2	15.2	15.6	16.2
	12H	14.8	15.1	15.3	15.6	16.2	14.8	15.1	15.3	15.6	16.1
12H	4H	14.9	15.4	15.4	15.8	16.3	14.7	15.2	15.2	15.6	16.1
	6H	14.9	15.2	15.4	15.7	16.2	14.7	15.1	15.2	15.6	16.1
	8H	14.8	15.1	15.3	15.6	16.2	14.7	15.1	15.3	15.6	16.1

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 426 B = 264
-----------------	---------------------------------	-------------------------------	--------------------

C-planes	γ	Luminance in cd/m ²							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
45,0°		5385.0	5272.9	5481.1	5621.5	5015.2	4708.8	4694.9	
50,0°		3000.3	2929.4	2926.3	2978.6	2672.8	2548.4	2504.7	
55,0°		1885.5	1835.1	1861.3	1904.0	1727.2	1623.6	1604.1	
60,0°		1356.2	1309.2	1375.6	1416.8	1326.6	1228.5	1244.1	
65,0°		1144.3	1041.0	1109.5	1157.4	1133.3	1048.1	1107.3	
70,0°		983.6	897.4	992.7	960.4	1053.6	959.1	1047.4	
75,0°		810.6	750.7	748.7	800.8	832.0	890.6	992.8	
80,0°		547.2	510.6	540.3	583.7	658.8	774.9	883.3	
85,0°		218.6	217.5	224.5	262.9	388.8	518.0	671.0	

Photometric test report

Family
Highbay 11

Order number: 51HN32DA4KDA
EAN: 4069025431110

LP number
59710_186

Luminance values in cd/m²

γ 65°
 γ 70°
 γ 75°
 γ 80°
 γ 85°

