

## Photometric test report

**Family**  
**Highbay 11**

**Order number: 51HN32DB4VDA**  
**EAN: 4069025438348**

**LP number**  
**59710\_226**

**serial**  
**documentation**  
**14.02.2025**

**sit**eco



**Version** primary light control with lens, PMMA, housing, black, wide distribution

**Lamps** LED 4000 K | CRI ≥ 80

**Controlgear** ECG-DALI

**Setting** DC mode (central or group accumulator) initial emergency light level


**Rated values** Net luminous flux = 9070 lm  
Power consumption = 44.6 W  
Luminous efficacy = 203.4 lm/W

**Luminous intensity in cd/klm**

**C180-0**

**C270-90**

**Imax: 772 cd/klm**



### Classifications

DIN 5040 A 6 0  
CIE N1=88 N2=98 N3=100  
N4=100 N5=100

### Luminaire light output ratios

$\eta_{LB}$  100.0%  
 $\phi_u$  100.0%  
 $\phi_o$  0.0%

### Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

|                                          |                                                  |                            |
|------------------------------------------|--------------------------------------------------|----------------------------|
| Family<br>Highbay 11                     | Order number: 51HN32DB4VDA<br>EAN: 4069025438348 | LP number<br>59710_226     |
| Table of values for luminous intensities |                                                  | Maximum luminous intensity |
|                                          |                                                  | siteco                     |

| C-<br>planes | 0°<br>180°                   | 15°<br>165°<br>195°<br>345° | 30°<br>150°<br>210°<br>330° | 45°<br>135°<br>225°<br>315° | 60°<br>120°<br>240°<br>300° | 75°<br>105°<br>255°<br>285° | 90°<br>270° | Phi-zone                | Total<br>Phi-zone |
|--------------|------------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|-------------|-------------------------|-------------------|
| γ            | Luminous intensity in cd/klm |                             |                             |                             |                             |                             |             | Luminous flux in lm/klm |                   |
| 0,0°         | 643.6                        | 643.6                       | 643.6                       | 643.6                       | 643.6                       | 643.6                       | 643.6       | 1.0                     | 1.0               |
| 2,5°         | 644.5                        | 645.1                       | 645.0                       | 644.3                       | 644.2                       | 643.7                       | 641.7       | 7.7                     | 8.7               |
| 5,0°         | 651.5                        | 652.3                       | 650.7                       | 647.5                       | 645.3                       | 643.2                       | 640.4       | 15.5                    | 24.1              |
| 7,5°         | 669.6                        | 669.1                       | 664.2                       | 657.2                       | 651.2                       | 645.8                       | 641.3       | 23.5                    | 47.6              |
| 10,0°        | 693.4                        | 691.0                       | 681.5                       | 670.0                       | 659.9                       | 651.2                       | 645.8       | 31.9                    | 79.6              |
| 12,5°        | 711.8                        | 709.4                       | 700.3                       | 685.9                       | 671.9                       | 660.7                       | 654.0       | 40.7                    | 120.2             |
| 15,0°        | 721.3                        | 721.7                       | 717.1                       | 704.9                       | 689.4                       | 675.9                       | 667.7       | 49.7                    | 169.9             |
| 17,5°        | 743.8                        | 740.8                       | 737.9                       | 726.5                       | 708.9                       | 693.0                       | 684.2       | 59.4                    | 229.3             |
| 20,0°        | 761.9                        | 761.9                       | 759.6                       | 745.2                       | 724.0                       | 705.6                       | 696.8       | 69.2                    | 298.5             |
| 22,5°        | 772.0                        | 771.2                       | 770.0                       | 754.7                       | 731.1                       | 710.8                       | 702.6       | 78.2                    | 376.7             |
| 25,0°        | 758.1                        | 756.6                       | 756.3                       | 743.6                       | 722.7                       | 703.3                       | 695.6       | 85.1                    | 461.8             |
| 27,5°        | 706.7                        | 709.5                       | 709.5                       | 700.0                       | 685.7                       | 672.3                       | 667.0       | 87.8                    | 549.7             |
| 30,0°        | 640.4                        | 635.6                       | 633.7                       | 626.6                       | 621.7                       | 614.1                       | 609.9       | 85.8                    | 635.5             |
| 32,5°        | 530.6                        | 537.6                       | 535.6                       | 526.2                       | 530.2                       | 524.1                       | 520.8       | 78.1                    | 713.6             |
| 35,0°        | 428.2                        | 426.4                       | 425.9                       | 411.9                       | 420.8                       | 414.2                       | 411.4       | 66.0                    | 779.6             |
| 37,5°        | 322.5                        | 323.4                       | 327.0                       | 311.0                       | 319.4                       | 310.8                       | 308.2       | 53.0                    | 832.6             |
| 40,0°        | 236.1                        | 234.0                       | 241.6                       | 230.8                       | 230.9                       | 219.8                       | 218.4       | 40.7                    | 873.3             |
| 42,5°        | 162.3                        | 165.3                       | 172.9                       | 171.1                       | 161.7                       | 151.3                       | 150.8       | 30.2                    | 903.5             |
| 45,0°        | 117.3                        | 114.9                       | 119.4                       | 122.5                       | 109.3                       | 102.6                       | 102.3       | 21.9                    | 925.4             |
| 47,5°        | 80.5                         | 81.4                        | 82.8                        | 85.5                        | 75.2                        | 71.4                        | 70.8        | 15.9                    | 941.3             |
| 50,0°        | 59.4                         | 58.0                        | 58.0                        | 59.0                        | 52.9                        | 50.5                        | 49.6        | 11.7                    | 953.0             |
| 52,5°        | 43.3                         | 42.8                        | 42.8                        | 43.0                        | 39.3                        | 37.2                        | 36.6        | 8.9                     | 961.8             |
| 55,0°        | 33.3                         | 32.4                        | 32.9                        | 33.7                        | 30.5                        | 28.7                        | 28.3        | 7.1                     | 968.9             |
| 57,5°        | 25.9                         | 25.4                        | 25.9                        | 26.8                        | 24.5                        | 22.9                        | 22.9        | 5.8                     | 974.7             |
| 60,0°        | 20.9                         | 20.2                        | 21.2                        | 21.8                        | 20.4                        | 18.9                        | 19.2        | 4.9                     | 979.5             |
| 62,5°        | 16.9                         | 16.2                        | 17.4                        | 18.0                        | 17.2                        | 15.9                        | 16.4        | 4.1                     | 983.6             |
| 65,0°        | 14.9                         | 13.6                        | 14.4                        | 15.1                        | 14.8                        | 13.6                        | 14.4        | 3.6                     | 987.2             |
| 67,5°        | 12.3                         | 11.4                        | 12.5                        | 12.4                        | 13.0                        | 11.7                        | 12.6        | 3.1                     | 990.3             |
| 70,0°        | 10.4                         | 9.5                         | 10.5                        | 10.1                        | 11.1                        | 10.1                        | 11.0        | 2.7                     | 993.0             |
| 72,5°        | 8.2                          | 7.7                         | 7.9                         | 8.2                         | 8.7                         | 8.6                         | 9.5         | 2.2                     | 995.2             |
| 75,0°        | 6.5                          | 6.0                         | 6.0                         | 6.4                         | 6.6                         | 7.1                         | 7.9         | 1.7                     | 996.9             |
| 77,5°        | 4.5                          | 4.3                         | 4.4                         | 4.7                         | 5.1                         | 5.6                         | 6.3         | 1.3                     | 998.2             |
| 80,0°        | 2.9                          | 2.7                         | 2.9                         | 3.1                         | 3.5                         | 4.1                         | 4.7         | 0.9                     | 999.1             |
| 82,5°        | 1.3                          | 1.4                         | 1.6                         | 1.8                         | 2.2                         | 2.7                         | 3.3         | 0.5                     | 999.7             |
| 85,0°        | 0.6                          | 0.6                         | 0.6                         | 0.7                         | 1.0                         | 1.4                         | 1.8         | 0.3                     | 999.9             |
| 87,5°        | 0.3                          | 0.3                         | 0.3                         | 0.3                         | 0.3                         | 0.4                         | 0.5         | 0.1                     | 1000.0            |
| 90,0°        | 0.0                          | 0.0                         | 0.0                         | 0.0                         | 0.0                         | 0.0                         | 0.0         | 0.0                     | 1000.0            |

Photometric test report

|                              |     |                                                  |      |      |      |      |                    |      |                        |      |
|------------------------------|-----|--------------------------------------------------|------|------|------|------|--------------------|------|------------------------|------|
| Family<br>Highbay 11         |     | Order number: 51HN32DB4VDA<br>EAN: 4069025438348 |      |      |      |      |                    |      | LP number<br>59710_226 |      |
| UGR-Table                    |     | Standard room                                    |      |      |      |      |                    |      | siteco                 |      |
| Reflection factor of ceiling |     | 0.7                                              | 0.7  | 0.5  | 0.5  | 0.3  | 0.7                | 0.7  | 0.5                    | 0.5  |
| Reflection factor of walls   |     | 0.5                                              | 0.3  | 0.5  | 0.3  | 0.3  | 0.5                | 0.3  | 0.5                    | 0.3  |
| Reflection factor of floor   |     | 0.2                                              | 0.2  | 0.2  | 0.2  | 0.2  | 0.2                | 0.2  | 0.2                    | 0.2  |
| Room dimensions              |     | View crosswise (C0)                              |      |      |      |      | View endwise (C90) |      |                        |      |
| 2H                           | x   |                                                  |      |      |      |      |                    |      |                        |      |
|                              | y   |                                                  |      |      |      |      |                    |      |                        |      |
|                              | 2H  | 15.8                                             | 17.1 | 16.1 | 17.4 | 17.7 | 15.5               | 16.8 | 15.8                   | 17.1 |
|                              | 3H  | 15.8                                             | 16.9 | 16.2 | 17.2 | 17.6 | 15.5               | 16.6 | 15.9                   | 17.0 |
|                              | 4H  | 15.8                                             | 16.8 | 16.2 | 17.2 | 17.5 | 15.5               | 16.6 | 15.9                   | 16.9 |
|                              | 6H  | 15.7                                             | 16.7 | 16.1 | 17.0 | 17.4 | 15.5               | 16.5 | 15.9                   | 16.8 |
| 4H                           | 8H  | 15.8                                             | 16.6 | 16.2 | 17.0 | 17.4 | 15.6               | 16.4 | 16.1                   | 16.8 |
|                              | 12H | 15.8                                             | 16.5 | 16.2 | 16.9 | 17.3 | 15.6               | 16.4 | 16.1                   | 16.7 |
|                              | 2H  | 15.7                                             | 16.7 | 16.1 | 17.1 | 17.4 | 15.4               | 16.4 | 15.8                   | 16.8 |
|                              | 3H  | 15.7                                             | 16.6 | 16.1 | 16.9 | 17.4 | 15.4               | 16.3 | 15.9                   | 16.7 |
|                              | 4H  | 15.7                                             | 16.5 | 16.1 | 16.9 | 17.3 | 15.5               | 16.3 | 15.9                   | 16.7 |
|                              | 6H  | 15.7                                             | 16.3 | 16.1 | 16.8 | 17.2 | 15.5               | 16.2 | 16.0                   | 16.6 |
| 8H                           | 8H  | 15.6                                             | 16.2 | 16.1 | 16.7 | 17.2 | 15.5               | 16.1 | 16.0                   | 16.6 |
|                              | 12H | 15.7                                             | 16.1 | 16.2 | 16.6 | 17.1 | 15.6               | 16.1 | 16.1                   | 16.5 |
|                              | 4H  | 15.6                                             | 16.2 | 16.1 | 16.7 | 17.1 | 15.4               | 16.0 | 15.9                   | 16.5 |
|                              | 6H  | 15.6                                             | 16.1 | 16.1 | 16.6 | 17.1 | 15.5               | 16.0 | 16.0                   | 16.4 |
|                              | 8H  | 15.6                                             | 16.0 | 16.1 | 16.5 | 17.0 | 15.5               | 15.9 | 16.0                   | 16.4 |
|                              | 12H | 15.6                                             | 15.9 | 16.1 | 16.4 | 16.9 | 15.5               | 15.8 | 16.1                   | 16.4 |
| 12H                          | 4H  | 15.6                                             | 16.1 | 16.1 | 16.6 | 17.1 | 15.4               | 15.9 | 15.9                   | 16.4 |
|                              | 6H  | 15.6                                             | 16.0 | 16.1 | 16.5 | 17.0 | 15.5               | 15.9 | 16.0                   | 16.3 |
|                              | 8H  | 15.6                                             | 15.9 | 16.1 | 16.4 | 16.9 | 15.5               | 15.8 | 16.0                   | 16.3 |
|                              | 2H  | 15.8                                             | 17.1 | 16.1 | 17.4 | 17.7 | 15.5               | 16.8 | 15.8                   | 17.1 |
|                              | 3H  | 15.8                                             | 16.9 | 16.2 | 17.2 | 17.6 | 15.5               | 16.6 | 15.9                   | 17.0 |
|                              | 4H  | 15.8                                             | 16.8 | 16.2 | 17.2 | 17.5 | 15.5               | 16.6 | 15.9                   | 16.9 |

| Luminance table |                    | Max. for $\gamma \geq 65^\circ$ |                             | Photometric dimensions in mm: |                             | L = 852<br>B = 264          |             |
|-----------------|--------------------|---------------------------------|-----------------------------|-------------------------------|-----------------------------|-----------------------------|-------------|
| C-planes        | 0°<br>180°         | 15°<br>165°<br>195°<br>345°     | 30°<br>150°<br>210°<br>330° | 45°<br>135°<br>225°<br>315°   | 60°<br>120°<br>240°<br>300° | 75°<br>105°<br>255°<br>285° | 90°<br>270° |
| $\gamma$        | Luminance in cd/m² |                                 |                             |                               |                             |                             |             |
| 45,0°           | 6690.7             | 6551.3                          | 6810.0                      | 6984.6                        | 6231.2                      | 5850.5                      | 5833.3      |
| 50,0°           | 3727.8             | 3639.6                          | 3635.8                      | 3700.7                        | 3320.8                      | 3166.3                      | 3112.0      |
| 55,0°           | 2342.7             | 2280.1                          | 2312.6                      | 2365.7                        | 2146.0                      | 2017.3                      | 1993.0      |
| 60,0°           | 1685.0             | 1626.6                          | 1709.1                      | 1760.4                        | 1648.2                      | 1526.3                      | 1545.8      |
| 65,0°           | 1421.8             | 1293.3                          | 1378.6                      | 1438.0                        | 1408.1                      | 1302.2                      | 1375.8      |
| 70,0°           | 1222.0             | 1115.0                          | 1233.3                      | 1193.3                        | 1309.0                      | 1191.6                      | 1301.4      |
| 75,0°           | 1007.1             | 932.8                           | 930.3                       | 994.9                         | 1033.7                      | 1106.5                      | 1233.5      |
| 80,0°           | 679.9              | 634.4                           | 671.3                       | 725.2                         | 818.6                       | 962.8                       | 1097.5      |
| 85,0°           | 271.6              | 270.2                           | 279.0                       | 326.6                         | 483.0                       | 643.6                       | 833.7       |

Photometric test report

Family  
Highbay 11

Order number: 51HN32DB4VDA  
EAN: 4069025438348

LP number  
59710\_226

Luminance values in cd/m²

γ 65°

γ 70°

γ 75°

γ 80°

γ 85°

siteco

