

Photometric test report

Family
Highbay 11

Order number: 51HN31DB4QDA
EAN: 4069025256430

LP number
59711_158

serial
documentation
14.02.2025

siteco



Version primary light control with lens, PMMA, housing, black, narrow distribution

Lamps LED 4000 K | CRI ≥ 80

Controlgear ECG-DALI

Setting AC-mode


Rated values Net luminous flux = 36000 lm
Power consumption = 177.7 W
Luminous efficacy = 202.6 lm/W

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 2679 cd/klm



Classifications

DIN 5040 A 7 0
CIE N1=85 N2=97 N3=100
N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 100.0%
 ϕ_o 0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Highbay 11	Order number: 51HN31DB4QDA EAN: 4069025256430	LP number 59711_158
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0,0°	2678.6	2678.6	2678.6	2678.6	2678.6	2678.6	2678.6	4.0	4.0
2,5°	2608.0	2619.4	2619.4	2616.5	2617.6	2616.2	2606.1	31.3	35.3
5,0°	2420.1	2415.7	2414.1	2408.4	2406.6	2402.3	2391.7	57.6	92.8
7,5°	2113.4	2116.1	2112.3	2103.0	2097.6	2090.5	2079.6	75.2	168.1
10,0°	1780.1	1768.7	1762.7	1751.6	1743.6	1735.2	1724.7	83.4	251.5
12,5°	1410.1	1409.3	1404.7	1395.9	1388.1	1380.5	1373.1	82.8	334.3
15,0°	1106.5	1097.8	1095.0	1089.4	1083.1	1078.4	1073.9	77.3	411.5
17,5°	830.1	840.2	835.5	831.1	826.6	824.9	824.1	68.5	480.0
20,0°	671.1	661.9	651.8	643.2	639.9	639.4	641.0	60.8	540.8
22,5°	531.9	530.5	514.2	498.9	497.0	496.6	496.8	53.4	594.2
25,0°	450.6	441.3	420.6	401.3	399.0	395.8	392.4	47.9	642.1
27,5°	370.8	368.7	351.4	331.7	326.8	321.1	316.0	43.1	685.2
30,0°	320.4	312.1	300.8	284.1	278.0	270.2	264.7	39.7	724.9
32,5°	271.0	266.8	259.0	245.6	238.0	229.0	224.7	36.5	761.4
35,0°	235.8	228.9	222.7	210.5	201.6	193.0	191.7	33.3	794.7
37,5°	204.4	197.8	191.5	181.1	172.0	164.3	162.4	30.3	825.0
40,0°	176.7	170.7	163.1	154.3	146.1	138.3	135.6	27.3	852.2
42,5°	147.6	145.5	138.6	130.6	123.2	115.8	113.3	24.2	876.4
45,0°	126.0	121.8	116.3	109.0	102.0	95.3	93.2	21.1	897.6
47,5°	103.2	101.5	97.1	90.9	84.6	78.4	76.7	18.3	915.9
50,0°	85.9	82.9	79.4	74.6	69.1	63.7	61.9	15.5	931.4
52,5°	69.0	67.2	64.5	61.0	56.2	51.6	49.7	13.0	944.4
55,0°	55.6	54.1	52.2	49.5	45.7	41.7	40.0	10.9	955.3
57,5°	43.6	43.1	41.8	39.8	37.0	33.6	32.2	9.0	964.3
60,0°	33.2	33.3	33.9	32.4	30.5	27.5	26.1	7.4	971.7
62,5°	25.9	26.0	27.0	26.2	25.1	22.4	21.3	6.1	977.8
65,0°	21.6	21.2	21.7	21.3	20.9	18.8	17.7	5.1	982.9
67,5°	17.0	17.1	17.8	17.0	17.3	15.6	14.8	4.3	987.2
70,0°	13.5	13.4	14.4	13.6	14.1	13.0	12.4	3.5	990.7
72,5°	11.0	10.8	10.9	10.9	11.0	10.7	10.6	2.8	993.5
75,0°	9.0	8.4	8.4	8.3	8.6	9.0	8.9	2.3	995.8
77,5°	6.6	6.4	6.2	6.2	6.6	7.3	7.4	1.8	997.5
80,0°	4.4	4.2	4.1	4.2	4.7	5.7	5.8	1.3	998.8
82,5°	2.0	2.1	2.2	2.4	3.0	3.9	4.1	0.8	999.6
85,0°	0.8	0.8	0.8	1.0	1.5	2.2	2.4	0.4	999.9
87,5°	0.3	0.3	0.3	0.3	0.3	0.4	0.5	0.1	1000.0
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Highbay 11		Order number: 51HN31DB4QDA EAN: 4069025256430							LP number 59711_158	
UGR-Table		Standard room							siteco	
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		View crosswise (C0)					View endwise (C90)			
x	y									
2H	2H	19.5	20.7	19.9	21.0	21.3	18.3	19.5	18.7	19.8
	3H	19.8	20.8	20.1	21.1	21.5	18.6	19.7	19.0	20.0
	4H	19.8	20.8	20.2	21.1	21.5	18.8	19.7	19.2	20.1
	6H	19.9	20.7	20.3	21.1	21.5	18.9	19.7	19.3	20.1
	8H	20.0	20.7	20.4	21.0	21.5	19.0	19.7	19.4	20.1
	12H	19.9	20.6	20.3	21.0	21.4	19.0	19.7	19.5	20.1
4H	2H	19.6	20.5	20.0	20.9	21.3	18.5	19.5	18.9	19.8
	3H	19.9	20.7	20.3	21.1	21.5	18.9	19.7	19.4	20.1
	4H	20.0	20.7	20.5	21.1	21.6	19.1	19.8	19.6	20.2
	6H	20.1	20.7	20.6	21.1	21.6	19.3	19.9	19.8	20.3
	8H	20.1	20.6	20.6	21.1	21.5	19.4	19.9	19.9	20.4
	12H	20.1	20.5	20.6	21.0	21.5	19.5	19.9	20.0	20.4
8H	4H	20.0	20.5	20.5	21.0	21.5	19.2	19.7	19.6	20.1
	6H	20.1	20.5	20.6	21.0	21.5	19.4	19.8	19.9	20.3
	8H	20.1	20.4	20.6	20.9	21.5	19.5	19.8	20.0	20.3
	12H	20.0	20.3	20.6	20.9	21.4	19.6	19.9	20.1	20.4
12H	4H	20.0	20.4	20.5	20.9	21.4	19.1	19.6	19.6	20.0
	6H	20.1	20.4	20.6	20.9	21.4	19.4	19.7	19.9	20.2
	8H	20.1	20.4	20.6	20.9	21.4	19.5	19.8	20.0	20.3

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 852 B = 264	
C-planes	γ	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°
			Luminance in cd/m²				
45,0°	50,0°	55,0°	60,0°				
65,0°	70,0°	75,0°	80,0°	85,0°			
85,0°							

Photometric test report

Family
Highbay 11

Order number: 51HN31DB4QDA
EAN: 4069025256430

LP number
59711_158

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Highbay 11	Order number: 51HN31DB4QDA EAN: 4069025256430	LP number 59711_158
Dimming levels table		environmental temperature: 25°C
		siteco

Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]
100	254	254	36000	177.7
95	241	252	34258	168.3
90	227	250	32370	158.2
85	214	248	30612	149.0
80	201	245	28833	139.6
75	188	243	27050	130.5
70	175	240	25256	121.2
65	162	238	23457	112.2
60	149	234	21641	103.1
55	136	231	19822	94.1
50	123	227	17982	85.1
45	111	224	16268	76.9
40	98	219	14402	68.0
35	86	214	12670	59.9
30	73	208	10780	51.0
25	61	202	9014	43.0
20	49	194	7241	35.1
15	37	183	5454	27.2
10	25	169	3653	19.3
5	13	145	1834	11.1
1	4	102	463	4.8