

Photometric test report

Family
Highbay 11

Order number: 51HN11DB4MDA3S
EAN: 4069025363350

LP number
59711_282

serial
documentation
24.02.2025

siteco



Version primary light control with lens, PMMA, housing, white, narrow distribution

Lamps LED 4000 K | CRI ≥ 80

Controlgear ECG-DALI

Setting AC-mode


Rated values Net luminous flux = 30000 lm
Power consumption = 150.3 W
Luminous efficacy = 199.6 lm/W

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 2679 cd/klm



Classifications

DIN 5040 A 7 0
CIE N1=85 N2=97 N3=100
N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 100.0%
 ϕ_o 0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Highbay 11	Order number: 51HN11DB4MDA3S EAN: 4069025363350	LP number 59711_282
Table of values for luminous intensities		Maximum luminous intensity

siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0,0°	2678.6	2678.6	2678.6	2678.6	2678.6	2678.6	2678.6	4.0	4.0
2,5°	2608.0	2619.4	2619.4	2616.5	2617.6	2616.2	2606.1	31.3	35.3
5,0°	2420.1	2415.7	2414.1	2408.4	2406.6	2402.3	2391.7	57.6	92.8
7,5°	2113.4	2116.1	2112.3	2103.0	2097.6	2090.5	2079.6	75.2	168.1
10,0°	1780.1	1768.7	1762.7	1751.6	1743.6	1735.2	1724.7	83.4	251.5
12,5°	1410.1	1409.3	1404.7	1395.9	1388.1	1380.5	1373.1	82.8	334.3
15,0°	1106.5	1097.8	1095.0	1089.4	1083.1	1078.4	1073.9	77.3	411.5
17,5°	830.1	840.2	835.5	831.1	826.6	824.9	824.1	68.5	480.0
20,0°	671.1	661.9	651.8	643.2	639.9	639.4	641.0	60.8	540.8
22,5°	531.9	530.5	514.2	498.9	497.0	496.6	496.8	53.4	594.2
25,0°	450.6	441.3	420.6	401.3	399.0	395.8	392.4	47.9	642.1
27,5°	370.8	368.7	351.4	331.7	326.8	321.1	316.0	43.1	685.2
30,0°	320.4	312.1	300.8	284.1	278.0	270.2	264.7	39.7	724.9
32,5°	271.0	266.8	259.0	245.6	238.0	229.0	224.7	36.5	761.4
35,0°	235.8	228.9	222.7	210.5	201.6	193.0	191.7	33.3	794.7
37,5°	204.4	197.8	191.5	181.1	172.0	164.3	162.4	30.3	825.0
40,0°	176.7	170.7	163.1	154.3	146.1	138.3	135.6	27.3	852.2
42,5°	147.6	145.5	138.6	130.6	123.2	115.8	113.3	24.2	876.4
45,0°	126.0	121.8	116.3	109.0	102.0	95.3	93.2	21.1	897.6
47,5°	103.2	101.5	97.1	90.9	84.6	78.4	76.7	18.3	915.9
50,0°	85.9	82.9	79.4	74.6	69.1	63.7	61.9	15.5	931.4
52,5°	69.0	67.2	64.5	61.0	56.2	51.6	49.7	13.0	944.4
55,0°	55.6	54.1	52.2	49.5	45.7	41.7	40.0	10.9	955.3
57,5°	43.6	43.1	41.8	39.8	37.0	33.6	32.2	9.0	964.3
60,0°	33.2	33.3	33.9	32.4	30.5	27.5	26.1	7.4	971.7
62,5°	25.9	26.0	27.0	26.2	25.1	22.4	21.3	6.1	977.8
65,0°	21.6	21.2	21.7	21.3	20.9	18.8	17.7	5.1	982.9
67,5°	17.0	17.1	17.8	17.0	17.3	15.6	14.8	4.3	987.2
70,0°	13.5	13.4	14.4	13.6	14.1	13.0	12.4	3.5	990.7
72,5°	11.0	10.8	10.9	10.9	11.0	10.7	10.6	2.8	993.5
75,0°	9.0	8.4	8.4	8.3	8.6	9.0	8.9	2.3	995.8
77,5°	6.6	6.4	6.2	6.2	6.6	7.3	7.4	1.8	997.5
80,0°	4.4	4.2	4.1	4.2	4.7	5.7	5.8	1.3	998.8
82,5°	2.0	2.1	2.2	2.4	3.0	3.9	4.1	0.8	999.6
85,0°	0.8	0.8	0.8	1.0	1.5	2.2	2.4	0.4	999.9
87,5°	0.3	0.3	0.3	0.3	0.3	0.4	0.5	0.1	1000.0
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Highbay 11		Order number: 51HN11DB4MDA3S EAN: 4069025363350							LP number 59711_282	
UGR-Table		Standard room							siteco	
Reflection factor of ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5
Reflection factor of walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3
Reflection factor of floor		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		View crosswise (C0)					View endwise (C90)			
2H	x									
	y									
	2H	18.9	20.1	19.3	20.4	20.7	17.7	18.9	18.1	19.2
	3H	19.1	20.2	19.5	20.5	20.9	18.0	19.0	18.4	19.4
	4H	19.2	20.1	19.6	20.5	20.9	18.1	19.1	18.5	19.4
	6H	19.3	20.1	19.7	20.5	20.9	18.3	19.1	18.7	19.5
4H	8H	19.3	20.0	19.7	20.4	20.8	18.4	19.1	18.8	19.5
	12H	19.3	19.9	19.7	20.3	20.7	18.4	19.1	18.8	19.5
	2H	19.0	19.9	19.4	20.3	20.6	17.9	18.8	18.3	19.2
	3H	19.3	20.1	19.7	20.4	20.9	18.3	19.1	18.7	19.5
	4H	19.4	20.1	19.8	20.5	20.9	18.5	19.2	18.9	19.6
	6H	19.5	20.0	19.9	20.5	20.9	18.7	19.3	19.2	19.7
8H	8H	19.5	20.0	19.9	20.4	20.9	18.8	19.3	19.2	19.7
	12H	19.4	19.9	19.9	20.3	20.8	18.8	19.3	19.3	19.7
	4H	19.4	19.9	19.9	20.3	20.8	18.5	19.0	19.0	19.5
	6H	19.5	19.9	20.0	20.4	20.9	18.8	19.2	19.3	19.6
	8H	19.4	19.8	19.9	20.3	20.8	18.8	19.2	19.4	19.7
	12H	19.4	19.7	19.9	20.2	20.8	18.9	19.2	19.4	19.7
12H	4H	19.4	19.8	19.9	20.3	20.8	18.5	18.9	19.0	19.4
	6H	19.4	19.8	20.0	20.3	20.8	18.7	19.1	19.3	19.6
	8H	19.4	19.7	19.9	20.2	20.8	18.8	19.1	19.4	19.6
	2H	18.9	20.1	19.3	20.4	20.7	17.7	18.9	18.1	19.2
	3H	19.1	20.2	19.5	20.5	20.9	18.0	19.0	18.4	19.4
	4H	19.2	20.1	19.6	20.5	20.9	18.1	19.1	18.5	19.4

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 852 B = 264	
C-planes	γ	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°
			Luminance in cd/m²				
45,0°	50,0°	23764.1	22970.8	21936.0	20564.0	19239.8	17981.2
		17815.2	17195.0	16466.7	15489.0	14327.6	13208.8
55,0°	60,0°	12926.8	12576.8	12141.1	11510.4	10623.8	9697.1
		8869.2	8878.8	9044.0	8640.6	8126.9	7332.2
65,0°	70,0°	6809.6	6694.7	6846.5	6735.7	6593.4	5925.3
		5275.8	5212.3	5599.5	5287.9	5487.6	5052.0
75,0°	80,0°	4625.0	4340.6	4350.4	4291.6	4427.7	4616.8
		3374.2	3249.0	3143.0	3199.8	3575.4	4342.0
85,0°		1248.7	1233.4	1290.1	1458.4	2238.9	3296.3
							3735.5

Photometric test report

Family
Highbay 11

Order number: 51HN11DB4MDA3S
EAN: 4069025363350

LP number
59711_282

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Highbay 11	Order number: 51HN11DB4MDA3S EAN: 4069025363350	LP number 59711_282
Dimming levels table environmental temperature: 25°C		

Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]
100	254	254	30000	150.3
95	241	252	28538	142.5
90	227	250	26952	134.2
85	214	248	25476	126.5
80	201	245	23987	118.8
75	188	243	22496	111.3
70	175	240	20989	103.7
65	162	238	19482	96.1
60	149	234	17966	88.6
55	137	231	16558	81.7
50	124	228	15025	74.3
45	111	224	13477	66.8
40	99	219	12044	60.1
35	86	214	10478	52.7
30	74	209	9026	46.0
25	62	202	7560	39.3
20	49	194	5966	32.3
15	37	183	4482	25.6
10	25	169	2992	19.1
5	13	145	1488	12.2
2	5	110	482	7.7