

Photometric test report

Family
Highbay 11

Order number: 51HN12DB4MDA3C
EAN: 4069025363534

LP number
59710_311

serial
documentation
24.02.2025

siteco




Version primary light control with lens, PMMA, housing, white, wide distribution
Lamps LED 4000 K | CRI ≥ 80
Controlgear ECG-DALI
Setting emergency light operation: 3 h
Rated values Net luminous flux = 940 lm
Power consumption = 6.0 W
Luminous efficacy = 156.7 lm/W

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 772 cd/klm



Classifications

DIN 5040 A 6 0
CIE N1=88 N2=98 N3=100
N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 100.0%
 ϕ_o 0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Highbay 11	Order number: 51HN12DB4MDA3C EAN: 4069025363534	LP number 59710_311
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0,0°	643.6	643.6	643.6	643.6	643.6	643.6	643.6	1.0	1.0
2,5°	644.5	645.1	645.0	644.3	644.2	643.7	641.7	7.7	8.7
5,0°	651.5	652.3	650.7	647.5	645.3	643.2	640.4	15.5	24.1
7,5°	669.6	669.1	664.2	657.2	651.2	645.8	641.3	23.5	47.6
10,0°	693.4	691.0	681.5	670.0	659.9	651.2	645.8	31.9	79.6
12,5°	711.8	709.4	700.3	685.9	671.9	660.7	654.0	40.7	120.2
15,0°	721.3	721.7	717.1	704.9	689.4	675.9	667.7	49.7	169.9
17,5°	743.8	740.8	737.9	726.5	708.9	693.0	684.2	59.4	229.3
20,0°	761.9	761.9	759.6	745.2	724.0	705.6	696.8	69.2	298.5
22,5°	772.0	771.2	770.0	754.7	731.1	710.8	702.6	78.2	376.7
25,0°	758.1	756.6	756.3	743.6	722.7	703.3	695.6	85.1	461.8
27,5°	706.7	709.5	709.5	700.0	685.7	672.3	667.0	87.8	549.7
30,0°	640.4	635.6	633.7	626.6	621.7	614.1	609.9	85.8	635.5
32,5°	530.6	537.6	535.6	526.2	530.2	524.1	520.8	78.1	713.6
35,0°	428.2	426.4	425.9	411.9	420.8	414.2	411.4	66.0	779.6
37,5°	322.5	323.4	327.0	311.0	319.4	310.8	308.2	53.0	832.6
40,0°	236.1	234.0	241.6	230.8	230.9	219.8	218.4	40.7	873.3
42,5°	162.3	165.3	172.9	171.1	161.7	151.3	150.8	30.2	903.5
45,0°	117.3	114.9	119.4	122.5	109.3	102.6	102.3	21.9	925.4
47,5°	80.5	81.4	82.8	85.5	75.2	71.4	70.8	15.9	941.3
50,0°	59.4	58.0	58.0	59.0	52.9	50.5	49.6	11.7	953.0
52,5°	43.3	42.8	42.8	43.0	39.3	37.2	36.6	8.9	961.8
55,0°	33.3	32.4	32.9	33.7	30.5	28.7	28.3	7.1	968.9
57,5°	25.9	25.4	25.9	26.8	24.5	22.9	22.9	5.8	974.7
60,0°	20.9	20.2	21.2	21.8	20.4	18.9	19.2	4.9	979.5
62,5°	16.9	16.2	17.4	18.0	17.2	15.9	16.4	4.1	983.6
65,0°	14.9	13.6	14.4	15.1	14.8	13.6	14.4	3.6	987.2
67,5°	12.3	11.4	12.5	12.4	13.0	11.7	12.6	3.1	990.3
70,0°	10.4	9.5	10.5	10.1	11.1	10.1	11.0	2.7	993.0
72,5°	8.2	7.7	7.9	8.2	8.7	8.6	9.5	2.2	995.2
75,0°	6.5	6.0	6.0	6.4	6.6	7.1	7.9	1.7	996.9
77,5°	4.5	4.3	4.4	4.7	5.1	5.6	6.3	1.3	998.2
80,0°	2.9	2.7	2.9	3.1	3.5	4.1	4.7	0.9	999.1
82,5°	1.3	1.4	1.6	1.8	2.2	2.7	3.3	0.5	999.7
85,0°	0.6	0.6	0.6	0.7	1.0	1.4	1.8	0.3	999.9
87,5°	0.3	0.3	0.3	0.3	0.3	0.4	0.5	0.1	1000.0
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Highbay 11	Order number: 51HN12DB4MDA3C EAN: 4069025363534	LP number 59710_311
----------------------	--	------------------------

UGR-Table		Standard room							siTeco		
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	7.9	9.2	8.3	9.5	9.8	7.6	8.9	8.0	9.2	9.5
	3H	7.9	9.0	8.3	9.4	9.7	7.6	8.7	8.0	9.1	9.4
	4H	7.9	8.9	8.3	9.3	9.7	7.6	8.7	8.0	9.0	9.4
	6H	7.9	8.8	8.3	9.2	9.6	7.7	8.6	8.1	9.0	9.4
	8H	7.9	8.7	8.4	9.1	9.5	7.8	8.6	8.2	8.9	9.3
	12H	7.9	8.6	8.3	9.0	9.4	7.7	8.5	8.2	8.9	9.3
4H	2H	7.8	8.8	8.2	9.2	9.6	7.5	8.5	7.9	8.9	9.3
	3H	7.8	8.7	8.2	9.1	9.5	7.6	8.4	8.0	8.8	9.2
	4H	7.8	8.6	8.3	9.0	9.4	7.6	8.4	8.1	8.8	9.2
	6H	7.8	8.4	8.3	8.9	9.4	7.7	8.3	8.1	8.7	9.2
	8H	7.8	8.4	8.3	8.8	9.3	7.7	8.3	8.1	8.7	9.2
	12H	7.8	8.3	8.3	8.7	9.2	7.7	8.2	8.2	8.6	9.1
8H	4H	7.8	8.3	8.2	8.8	9.3	7.6	8.1	8.0	8.6	9.1
	6H	7.7	8.2	8.2	8.7	9.2	7.6	8.1	8.1	8.6	9.1
	8H	7.7	8.1	8.2	8.6	9.1	7.6	8.0	8.1	8.5	9.1
	12H	7.7	8.0	8.2	8.5	9.1	7.7	8.0	8.2	8.5	9.0
12H	4H	7.8	8.2	8.3	8.7	9.2	7.6	8.0	8.1	8.5	9.0
	6H	7.7	8.1	8.2	8.6	9.1	7.6	8.0	8.1	8.5	9.0
	8H	7.7	8.0	8.2	8.5	9.1	7.6	7.9	8.1	8.4	9.0

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 852 B = 264	
C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
γ	Luminance in cd/m²						
45,0°	693.4	679.0	705.8	723.9	645.8	606.3	604.6
50,0°	386.3	377.2	376.8	383.5	344.2	328.2	322.5
55,0°	242.8	236.3	239.7	245.2	222.4	209.1	206.6
60,0°	174.6	168.6	177.1	182.4	170.8	158.2	160.2
65,0°	147.4	134.0	142.9	149.0	145.9	135.0	142.6
70,0°	126.6	115.6	127.8	123.7	135.7	123.5	134.9
75,0°	104.4	96.7	96.4	103.1	107.1	114.7	127.8
80,0°	70.5	65.7	69.6	75.2	84.8	99.8	113.7
85,0°	28.1	28.0	28.9	33.9	50.1	66.7	86.4

Photometric test report

Family
Highbay 11

Order number: 51HN12DB4MDA3C
EAN: 4069025363534

LP number
59710_311

Luminance values in cd/m²

γ 65°

γ 70°

γ 75°

γ 80°

γ 85°

siteco

