

Photometric test report

Family
Highbay 21

Order number: 52HN12DA4FLA
EAN: 4069025284181


LP number
59723_74



Versionprimary light control with lens, PMMA, housing, white, for Licross® rail, wide distribution
LampsLED 4000 K | CRI ≥ 80
ControlgearECG-DALI
Rated valuesNet luminous flux = 14000 lm
Power consumption = 72.1 W
Luminous efficacy = 194.2 lm/W

serial
documentation
27.02.2025

sITeco



Classifications		Luminaire light output ratios	
DIN 5040	A 7 0	η_{LB}	100.0%
CIE	N1=90 N2=98 N3=100	ϕ_u	100.0%
	N4=100 N5=100	ϕ_o	0.0%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Highbay 21	Order number: 52HN12DA4FLA EAN: 4069025284181	LP number 59723_74
Table of values for luminous intensities		Maximum luminous intensity

siteco

C- planes	0,0° 180,0°	7,5° 172,5° 187,5° 352,5°	15,0° 165,0° 195,0° 345,0°	22,5° 157,5° 202,5° 337,5°	30,0° 150,0° 210,0° 330,0°	37,5° 142,5° 217,5° 322,5°	45,0° 135,0° 225,0° 315,0°
		Luminous intensity in cd/klm					
γ							
0,0°	791.0	791.0	791.0	791.0	791.0	791.0	791.0
2,5°	794.7	794.4	795.0	795.0	794.2	792.8	792.0
5,0°	809.1	811.4	809.6	807.9	804.8	800.8	797.1
7,5°	839.0	837.9	835.9	831.3	824.9	817.3	810.1
10,0°	873.0	873.9	866.7	857.6	846.5	834.6	825.0
12,5°	902.2	899.8	892.6	881.8	868.2	853.9	842.5
15,0°	912.4	911.0	905.2	895.6	883.1	869.5	858.7
17,5°	919.8	918.2	913.1	904.4	892.7	879.7	870.3
20,0°	913.1	910.4	906.8	900.7	891.6	880.0	870.9
22,5°	873.0	875.7	872.3	868.8	863.2	854.7	847.2
25,0°	810.1	803.4	805.6	804.0	800.6	794.9	789.9
27,5°	697.5	704.9	702.5	701.8	699.9	697.0	693.3
30,0°	593.2	587.4	585.8	584.9	582.5	580.2	578.9
32,5°	456.1	464.3	462.1	462.0	458.3	454.5	453.6
35,0°	347.7	343.4	342.9	343.5	340.5	335.4	333.2
37,5°	248.6	249.1	246.7	247.3	245.8	241.7	237.9
40,0°	174.7	169.8	171.0	172.0	172.0	169.5	166.1
42,5°	115.9	118.7	117.3	118.1	118.9	118.2	116.5
45,0°	82.2	79.8	80.4	81.1	81.3	81.6	80.9
47,5°	56.5	57.6	57.2	57.7	57.6	57.9	57.5
50,0°	42.4	41.3	41.7	42.1	42.1	42.1	42.0
52,5°	32.0	31.8	31.7	32.2	32.5	32.7	32.7
55,0°	25.6	24.9	25.0	25.6	26.1	26.6	26.9
57,5°	20.6	20.3	20.3	20.8	21.4	22.1	22.4
60,0°	17.2	16.8	16.6	17.2	18.2	18.6	18.9
62,5°	14.5	14.3	13.9	14.3	15.3	15.8	16.0
65,0°	13.1	12.5	12.0	12.2	13.0	13.5	13.7
67,5°	11.1	10.9	10.3	10.4	11.4	11.4	11.5
70,0°	9.4	9.0	8.7	8.7	9.6	9.3	9.5
72,5°	7.6	7.5	7.3	7.2	7.3	7.4	7.8
75,0°	5.9	5.7	5.6	5.7	5.6	5.7	6.1
77,5°	4.1	4.1	4.1	4.2	4.1	4.2	4.5
80,0°	2.6	2.5	2.5	2.7	2.7	2.8	2.9
82,5°	1.1	1.2	1.2	1.3	1.5	1.5	1.7
85,0°	0.5	0.5	0.5	0.5	0.5	0.5	0.6
87,5°	0.2	0.3	0.3	0.3	0.3	0.3	0.3

Photometric test report

Family Highbay 21	Order number: 52HN12DA4FLA EAN: 4069025284181	LP number 59723_74
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	52,5° 127,5° 232,5° 307,5°	60,0° 120,0° 240,0° 300,0°	67,5° 112,5° 247,5° 292,5°	75,0° 105,0° 255,0° 285,0°	82,5° 97,5° 262,5° 277,5°	90,0° 270,0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm						Luminous flux in lm/klm	
0,0°	791.0	791.0	791.0	791.0	791.0	791.0	1.2	1.2
2,5°	791.3	790.7	790.0	789.4	788.0	786.7	9.5	10.7
5,0°	794.2	790.9	788.1	786.0	783.2	781.9	19.1	29.7
7,5°	803.7	797.3	791.2	786.8	782.5	780.9	29.0	58.7
10,0°	816.7	808.7	801.4	796.1	791.2	788.9	39.5	98.2
12,5°	833.0	825.3	818.6	813.6	808.7	806.6	50.4	148.6
15,0°	850.7	844.9	836.9	832.9	831.6	829.0	61.4	210.0
17,5°	864.2	859.8	856.6	853.6	849.6	847.0	72.4	282.5
20,0°	864.8	860.1	856.9	853.9	850.4	848.0	82.3	364.7
22,5°	841.4	836.7	833.2	829.7	826.8	824.5	89.2	453.9
25,0°	786.0	782.5	779.1	775.6	772.9	771.0	91.6	545.4
27,5°	691.2	689.6	687.4	684.8	682.7	681.4	87.8	633.3
30,0°	578.6	579.1	578.3	576.4	575.3	574.3	79.6	712.9
32,5°	454.5	456.7	457.0	455.4	454.6	454.3	67.4	780.2
35,0°	335.0	337.7	338.0	336.6	336.0	336.2	53.3	833.5
37,5°	239.3	241.4	241.0	239.6	239.1	239.2	40.5	874.0
40,0°	166.2	166.4	164.7	163.3	162.9	163.0	29.6	903.6
42,5°	115.3	113.5	111.1	110.0	109.8	109.7	21.3	924.9
45,0°	79.0	76.9	75.1	74.3	74.0	73.9	15.2	940.1
47,5°	56.0	54.4	53.1	52.3	51.9	51.7	11.2	951.3
50,0°	40.9	39.8	38.8	38.0	37.5	37.4	8.5	959.8
52,5°	31.8	30.8	29.9	29.1	28.8	28.7	6.8	966.6
55,0°	25.9	25.0	24.2	23.4	23.2	23.3	5.6	972.3
57,5°	21.7	20.8	20.1	19.5	19.4	19.6	4.8	977.0
60,0°	18.6	18.0	17.1	16.6	16.8	17.1	4.2	981.2
62,5°	16.0	15.6	14.7	14.4	14.7	15.1	3.6	984.8
65,0°	14.0	13.6	12.8	12.7	13.1	13.5	3.2	988.1
67,5°	12.0	12.1	11.2	11.1	11.6	12.1	2.9	991.0
70,0°	9.8	10.4	9.7	9.7	10.2	10.6	2.5	993.4
72,5°	7.8	8.3	8.3	8.3	8.8	9.1	2.1	995.5
75,0°	6.2	6.3	6.8	6.9	7.3	7.6	1.6	997.1
77,5°	4.6	4.9	5.3	5.5	5.8	6.0	1.3	998.4
80,0°	3.1	3.4	3.7	4.0	4.2	4.4	0.9	999.2
82,5°	1.8	2.1	2.4	2.6	2.8	2.9	0.5	999.7
85,0°	0.7	1.0	1.2	1.3	1.6	1.6	0.2	1000.0
87,5°	0.3	0.3	0.3	0.3	0.4	0.4	0.1	1000.0

Photometric test report

Family Highbay 21			Order number: 52HN12DA4FLA EAN: 4069025284181						LP number 59723_74		
UGR-Table			Standard room						siteco		
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	18.1	19.4	18.5	19.7	20.0	17.9	19.2	18.3	19.5	19.8
	3H	18.2	19.2	18.5	19.6	19.9	18.0	19.1	18.4	19.4	19.8
	4H	18.2	19.2	18.6	19.5	19.9	18.1	19.1	18.5	19.4	19.8
	6H	18.1	19.0	18.6	19.4	19.8	18.1	19.0	18.5	19.4	19.8
	8H	18.2	19.0	18.7	19.4	19.8	18.2	19.0	18.7	19.4	19.8
	12H	18.2	18.9	18.6	19.3	19.7	18.2	18.9	18.7	19.3	19.7
4H	2H	18.0	19.0	18.4	19.4	19.7	17.9	18.8	18.2	19.2	19.6
	3H	18.1	18.9	18.5	19.3	19.7	18.0	18.8	18.4	19.2	19.6
	4H	18.1	18.9	18.6	19.3	19.7	18.1	18.8	18.5	19.2	19.7
	6H	18.1	18.7	18.6	19.2	19.7	18.2	18.8	18.6	19.2	19.7
	8H	18.1	18.7	18.6	19.1	19.6	18.2	18.7	18.7	19.2	19.7
	12H	18.1	18.6	18.6	19.0	19.5	18.3	18.7	18.8	19.1	19.6
8H	4H	18.1	18.6	18.6	19.1	19.6	18.0	18.6	18.5	19.0	19.5
	6H	18.1	18.5	18.6	19.0	19.5	18.1	18.6	18.6	19.1	19.6
	8H	18.0	18.4	18.6	18.9	19.5	18.2	18.6	18.7	19.1	19.6
	12H	18.0	18.3	18.6	18.8	19.4	18.2	18.5	18.7	19.0	19.6
12H	4H	18.1	18.5	18.6	19.0	19.5	18.1	18.5	18.6	19.0	19.5
	6H	18.1	18.4	18.6	18.9	19.5	18.2	18.5	18.7	19.0	19.5
	8H	18.1	18.3	18.6	18.9	19.4	18.2	18.5	18.7	19.0	19.5

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:				L = 426 B = 264		
C-planes	0,0° 180,0°	10,0° 170,0° 190,0° 350,0°	20,0° 160,0° 200,0° 340,0°	30,0° 150,0° 210,0° 330,0°	40,0° 140,0° 220,0° 320,0°	50,0° 130,0° 230,0° 310,0°	60,0° 120,0° 240,0° 300,0°	70,0° 110,0° 250,0° 290,0°	80,0° 100,0° 260,0° 280,0°	90,0° 270,0°
		Luminance in cd/m²								
γ										
45,0°	14476.2	14028.1	14239.0	14318.1	14347.6	14028.5	13530.1	13159.9	13037.9	13002.0
50,0°	8212.1	7985.8	8135.3	8154.0	8152.9	7998.3	7711.1	7454.8	7292.0	7234.9
55,0°	5559.9	5397.2	5517.3	5658.2	5810.2	5698.9	5416.9	5190.6	5049.2	5066.4
60,0°	4277.5	4154.2	4224.2	4522.3	4664.4	4656.7	4485.9	4211.2	4162.2	4249.4
65,0°	3848.9	3625.2	3547.5	3839.5	4016.1	4130.7	4014.5	3744.9	3813.7	3984.1
70,0°	3435.5	3244.6	3139.3	3477.3	3401.2	3528.9	3775.8	3513.7	3653.1	3872.3
75,0°	2825.2	2727.3	2739.9	2712.2	2795.6	2954.8	3045.5	3316.6	3445.0	3655.4
80,0°	1842.4	1783.4	1897.5	1968.5	2001.4	2187.7	2435.9	2754.9	2960.8	3134.9
85,0°	719.9	701.8	713.5	717.0	784.0	988.2	1392.6	1734.1	2126.4	2318.1

Photometric test report

Family
Highbay 21

Order number: 52HN12DA4FLA
EAN: 4069025284181

LP number
59723_74

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Highbay 21	Order number: 52HN12DA4FLA EAN: 4069025284181	LP number 59723_74
Dimming levels table		environmental temperature: 25°C

siteco

Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]
100	----	----	----	----
100	253	254	13946	71.8
95	241	252	13303	68.3
90	228	250	12606	64.7
85	215	248	11901	61.0
80	202	246	11197	57.4
75	189	243	10494	53.5
70	176	241	9782	49.9
65	164	238	9126	46.6
60	151	235	8413	42.9
55	138	232	7695	39.3
50	125	228	6976	35.7
45	113	224	6313	32.4
40	100	220	5591	28.8
35	88	215	4919	25.5
30	75	209	4192	22.0
25	63	203	3520	18.7
20	50	194	2785	15.1
15	38	184	2109	11.9
10	25	169	1374	8.4
5	13	145	690	4.9
2	5	110	235	2.5