

Photometric test report

Family
Highbay 11

Order number: 51HN12DA4LMA
EAN: 4069025379184

LP number
59710_337

serial
documentation
05.03.2025

siteco

Version primary light control with lens, PMMA, housing, white, for Modario® rail, wide distribution

Lamps LED 4000 K | CRI ≥ 80

Controlgear ECG-DALI

Rated values Net luminous flux = 26500 lm
Power consumption = 137.7 W
Luminous efficacy = 192.4 lm/W




Luminous intensity in cd/klm

C180-0

C270-90

Imax: 772 cd/klm



Classifications

DIN 5040 A 6 0
CIE N1=88 N2=98 N3=100
N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 100.0%
 ϕ_o 0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Highbay 11	Order number: 51HN12DA4LMA EAN: 4069025379184	LP number 59710_337
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0,0°	643.6	643.6	643.6	643.6	643.6	643.6	643.6	1.0	1.0
2,5°	644.5	645.1	645.0	644.3	644.2	643.7	641.7	7.7	8.7
5,0°	651.5	652.3	650.7	647.5	645.3	643.2	640.4	15.5	24.1
7,5°	669.6	669.1	664.2	657.2	651.2	645.8	641.3	23.5	47.6
10,0°	693.4	691.0	681.5	670.0	659.9	651.2	645.8	31.9	79.6
12,5°	711.8	709.4	700.3	685.9	671.9	660.7	654.0	40.7	120.2
15,0°	721.3	721.7	717.1	704.9	689.4	675.9	667.7	49.7	169.9
17,5°	743.8	740.8	737.9	726.5	708.9	693.0	684.2	59.4	229.3
20,0°	761.9	761.9	759.6	745.2	724.0	705.6	696.8	69.2	298.5
22,5°	772.0	771.2	770.0	754.7	731.1	710.8	702.6	78.2	376.7
25,0°	758.1	756.6	756.3	743.6	722.7	703.3	695.6	85.1	461.8
27,5°	706.7	709.5	709.5	700.0	685.7	672.3	667.0	87.8	549.7
30,0°	640.4	635.6	633.7	626.6	621.7	614.1	609.9	85.8	635.5
32,5°	530.6	537.6	535.6	526.2	530.2	524.1	520.8	78.1	713.6
35,0°	428.2	426.4	425.9	411.9	420.8	414.2	411.4	66.0	779.6
37,5°	322.5	323.4	327.0	311.0	319.4	310.8	308.2	53.0	832.6
40,0°	236.1	234.0	241.6	230.8	230.9	219.8	218.4	40.7	873.3
42,5°	162.3	165.3	172.9	171.1	161.7	151.3	150.8	30.2	903.5
45,0°	117.3	114.9	119.4	122.5	109.3	102.6	102.3	21.9	925.4
47,5°	80.5	81.4	82.8	85.5	75.2	71.4	70.8	15.9	941.3
50,0°	59.4	58.0	58.0	59.0	52.9	50.5	49.6	11.7	953.0
52,5°	43.3	42.8	42.8	43.0	39.3	37.2	36.6	8.9	961.8
55,0°	33.3	32.4	32.9	33.7	30.5	28.7	28.3	7.1	968.9
57,5°	25.9	25.4	25.9	26.8	24.5	22.9	22.9	5.8	974.7
60,0°	20.9	20.2	21.2	21.8	20.4	18.9	19.2	4.9	979.5
62,5°	16.9	16.2	17.4	18.0	17.2	15.9	16.4	4.1	983.6
65,0°	14.9	13.6	14.4	15.1	14.8	13.6	14.4	3.6	987.2
67,5°	12.3	11.4	12.5	12.4	13.0	11.7	12.6	3.1	990.3
70,0°	10.4	9.5	10.5	10.1	11.1	10.1	11.0	2.7	993.0
72,5°	8.2	7.7	7.9	8.2	8.7	8.6	9.5	2.2	995.2
75,0°	6.5	6.0	6.0	6.4	6.6	7.1	7.9	1.7	996.9
77,5°	4.5	4.3	4.4	4.7	5.1	5.6	6.3	1.3	998.2
80,0°	2.9	2.7	2.9	3.1	3.5	4.1	4.7	0.9	999.1
82,5°	1.3	1.4	1.6	1.8	2.2	2.7	3.3	0.5	999.7
85,0°	0.6	0.6	0.6	0.7	1.0	1.4	1.8	0.3	999.9
87,5°	0.3	0.3	0.3	0.3	0.3	0.4	0.5	0.1	1000.0
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Highbay 11			Order number: 51HN12DA4LMA EAN: 4069025379184							LP number 59710_337	
UGR-Table			Standard room							siteco	
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	21.9	23.2	22.3	23.5	23.8	21.6	22.9	22.0	23.2	23.5
	3H	21.9	23.0	22.3	23.4	23.7	21.6	22.8	22.0	23.1	23.4
	4H	21.9	22.9	22.3	23.3	23.7	21.6	22.7	22.0	23.0	23.4
	6H	21.9	22.8	22.3	23.2	23.6	21.7	22.6	22.1	23.0	23.4
	8H	21.9	22.7	22.4	23.1	23.5	21.8	22.6	22.2	22.9	23.4
	12H	21.9	22.6	22.3	23.0	23.5	21.8	22.5	22.2	22.9	23.3
4H	2H	21.8	22.8	22.2	23.2	23.6	21.5	22.5	21.9	22.9	23.3
	3H	21.8	22.7	22.3	23.1	23.5	21.6	22.4	22.0	22.8	23.2
	4H	21.8	22.6	22.3	23.0	23.4	21.6	22.4	22.1	22.8	23.2
	6H	21.8	22.5	22.3	22.9	23.4	21.7	22.3	22.1	22.8	23.2
	8H	21.8	22.4	22.3	22.8	23.3	21.7	22.3	22.2	22.7	23.2
	12H	21.8	22.3	22.3	22.7	23.2	21.7	22.2	22.2	22.7	23.2
8H	4H	21.8	22.3	22.2	22.8	23.3	21.6	22.1	22.0	22.6	23.1
	6H	21.7	22.2	22.2	22.7	23.2	21.6	22.1	22.1	22.6	23.1
	8H	21.7	22.1	22.2	22.6	23.1	21.6	22.0	22.1	22.5	23.1
	12H	21.7	22.0	22.2	22.5	23.1	21.7	22.0	22.2	22.5	23.0
12H	4H	21.8	22.2	22.3	22.7	23.2	21.6	22.0	22.1	22.5	23.0
	6H	21.7	22.1	22.3	22.6	23.1	21.6	22.0	22.1	22.5	23.0
	8H	21.7	22.0	22.2	22.5	23.1	21.6	21.9	22.2	22.5	23.0

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 426 B = 264	
C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
γ	Luminance in cd/m²						
45,0°	39096.5	38282.4	39794.0	40814.0	36411.6	34187.0	34086.4
50,0°	21783.1	21268.0	21245.7	21625.1	19405.1	18502.2	18184.8
55,0°	13689.4	13323.4	13513.6	13823.8	12540.0	11787.8	11646.1
60,0°	9846.1	9504.9	9987.0	10286.7	9631.2	8919.1	9032.7
65,0°	8308.1	7557.6	8055.5	8402.8	8228.3	7609.4	8039.3
70,0°	7140.9	6515.3	7207.0	6972.7	7649.3	6963.1	7604.5
75,0°	5884.9	5450.6	5436.0	5813.9	6040.6	6465.7	7207.7
80,0°	3973.1	3707.2	3922.9	4237.7	4783.2	5625.9	6412.9
85,0°	1587.0	1578.9	1630.2	1908.7	2822.5	3760.7	4871.8

Photometric test report

Family
Highbay 11

Order number: 51HN12DA4LMA
EAN: 4069025379184

LP number
59710_337

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Highbay 11	Order number: 51HN12DA4LMA EAN: 4069025379184	LP number 59710_337
Dimming levels table		environmental temperature: 25°C



Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]
100	254	254	26500	137.7
95	240	252	25140	129.7
90	227	250	23873	122.3
85	213	248	22501	114.5
80	200	245	21220	107.2
75	186	243	19826	99.4
70	173	240	18520	92.4
65	160	237	17202	85.3
60	147	234	15879	78.3
55	134	231	14540	71.3
50	122	227	13295	64.8
45	109	223	11932	57.9
40	96	218	10562	51.0
35	84	213	9279	44.6
30	72	208	7987	38.4
25	60	201	6678	32.2
20	47	192	5250	25.5
15	36	182	4023	20.0
10	24	168	2675	13.8
5	12	142	1308	7.4
2	5	110	503	3.7