

Photometric test report

Family
Highbay 11

Order number: 51HN12DA4KLA02
EAN: 4069025421043

LP number
59710_367

serial
documentation
19.03.2025



Version primary light control with lens, PMMA, housing, white, for Licross® rail, wide distribution, with Node BT

Lamps LED 4000 K | CRI ≥ 80

Controlgear ECG-DALI

Rated values
Net luminous flux = 23000 lm
Power consumption = 117.7 W
Luminous efficacy = 195.4 lm/W


siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 772 cd/klm



Classifications

DIN 5040 A 6 0
CIE N1=88 N2=98 N3=100
N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 100.0%
 ϕ_o 0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Highbay 11	Order number: 51HN12DA4KLA02 EAN: 4069025421043	LP number 59710_367
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0,0°	643.6	643.6	643.6	643.6	643.6	643.6	643.6	1.0	1.0
2,5°	644.5	645.1	645.0	644.3	644.2	643.7	641.7	7.7	8.7
5,0°	651.5	652.3	650.7	647.5	645.3	643.2	640.4	15.5	24.1
7,5°	669.6	669.1	664.2	657.2	651.2	645.8	641.3	23.5	47.6
10,0°	693.4	691.0	681.5	670.0	659.9	651.2	645.8	31.9	79.6
12,5°	711.8	709.4	700.3	685.9	671.9	660.7	654.0	40.7	120.2
15,0°	721.3	721.7	717.1	704.9	689.4	675.9	667.7	49.7	169.9
17,5°	743.8	740.8	737.9	726.5	708.9	693.0	684.2	59.4	229.3
20,0°	761.9	761.9	759.6	745.2	724.0	705.6	696.8	69.2	298.5
22,5°	772.0	771.2	770.0	754.7	731.1	710.8	702.6	78.2	376.7
25,0°	758.1	756.6	756.3	743.6	722.7	703.3	695.6	85.1	461.8
27,5°	706.7	709.5	709.5	700.0	685.7	672.3	667.0	87.8	549.7
30,0°	640.4	635.6	633.7	626.6	621.7	614.1	609.9	85.8	635.5
32,5°	530.6	537.6	535.6	526.2	530.2	524.1	520.8	78.1	713.6
35,0°	428.2	426.4	425.9	411.9	420.8	414.2	411.4	66.0	779.6
37,5°	322.5	323.4	327.0	311.0	319.4	310.8	308.2	53.0	832.6
40,0°	236.1	234.0	241.6	230.8	230.9	219.8	218.4	40.7	873.3
42,5°	162.3	165.3	172.9	171.1	161.7	151.3	150.8	30.2	903.5
45,0°	117.3	114.9	119.4	122.5	109.3	102.6	102.3	21.9	925.4
47,5°	80.5	81.4	82.8	85.5	75.2	71.4	70.8	15.9	941.3
50,0°	59.4	58.0	58.0	59.0	52.9	50.5	49.6	11.7	953.0
52,5°	43.3	42.8	42.8	43.0	39.3	37.2	36.6	8.9	961.8
55,0°	33.3	32.4	32.9	33.7	30.5	28.7	28.3	7.1	968.9
57,5°	25.9	25.4	25.9	26.8	24.5	22.9	22.9	5.8	974.7
60,0°	20.9	20.2	21.2	21.8	20.4	18.9	19.2	4.9	979.5
62,5°	16.9	16.2	17.4	18.0	17.2	15.9	16.4	4.1	983.6
65,0°	14.9	13.6	14.4	15.1	14.8	13.6	14.4	3.6	987.2
67,5°	12.3	11.4	12.5	12.4	13.0	11.7	12.6	3.1	990.3
70,0°	10.4	9.5	10.5	10.1	11.1	10.1	11.0	2.7	993.0
72,5°	8.2	7.7	7.9	8.2	8.7	8.6	9.5	2.2	995.2
75,0°	6.5	6.0	6.0	6.4	6.6	7.1	7.9	1.7	996.9
77,5°	4.5	4.3	4.4	4.7	5.1	5.6	6.3	1.3	998.2
80,0°	2.9	2.7	2.9	3.1	3.5	4.1	4.7	0.9	999.1
82,5°	1.3	1.4	1.6	1.8	2.2	2.7	3.3	0.5	999.7
85,0°	0.6	0.6	0.6	0.7	1.0	1.4	1.8	0.3	999.9
87,5°	0.3	0.3	0.3	0.3	0.3	0.4	0.5	0.1	1000.0
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Highbay 11			Order number: 51HN12DA4KLA02 EAN: 4069025421043							LP number 59710_367	
UGR-Table			Standard room							siteco	
Reflection factor of ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Reflection factor of walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reflection factor of floor		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	21.4	22.7	21.8	23.0	23.3	21.1	22.4	21.5	22.7	23.0
	3H	21.4	22.5	21.8	22.9	23.2	21.1	22.3	21.5	22.6	23.0
	4H	21.4	22.4	21.8	22.8	23.2	21.2	22.2	21.6	22.6	22.9
	6H	21.4	22.3	21.8	22.7	23.1	21.2	22.1	21.6	22.5	22.9
	8H	21.4	22.2	21.9	22.6	23.0	21.3	22.1	21.7	22.5	22.9
	12H	21.4	22.1	21.9	22.5	23.0	21.3	22.0	21.7	22.4	22.8
4H	2H	21.3	22.3	21.7	22.7	23.1	21.0	22.1	21.4	22.4	22.8
	3H	21.3	22.2	21.8	22.6	23.0	21.1	21.9	21.5	22.3	22.8
	4H	21.3	22.1	21.8	22.5	23.0	21.1	21.9	21.6	22.3	22.7
	6H	21.3	22.0	21.8	22.4	22.9	21.2	21.8	21.6	22.3	22.7
	8H	21.3	21.9	21.8	22.3	22.8	21.2	21.8	21.7	22.2	22.7
	12H	21.3	21.8	21.8	22.2	22.7	21.2	21.7	21.7	22.2	22.7
8H	4H	21.3	21.9	21.7	22.3	22.8	21.1	21.7	21.5	22.1	22.6
	6H	21.2	21.7	21.7	22.2	22.7	21.1	21.6	21.6	22.1	22.6
	8H	21.2	21.6	21.7	22.1	22.6	21.1	21.6	21.6	22.0	22.6
	12H	21.2	21.5	21.7	22.0	22.6	21.2	21.5	21.7	22.0	22.5
12H	4H	21.3	21.8	21.8	22.2	22.7	21.1	21.5	21.6	22.0	22.5
	6H	21.3	21.6	21.8	22.1	22.6	21.1	21.5	21.6	22.0	22.5
	8H	21.2	21.5	21.7	22.0	22.6	21.1	21.5	21.7	22.0	22.5

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 426 B = 264	
C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
γ	Luminance in cd/m²						
45,0°	33932.8	33226.2	34538.2	35423.5	31602.6	29671.7	29584.4
50,0°	18906.1	18459.1	18439.7	18768.9	16842.2	16058.5	15783.0
55,0°	11881.4	11563.7	11728.8	11998.0	10883.8	10230.9	10107.9
60,0°	8545.7	8249.5	8667.9	8928.1	8359.1	7741.1	7839.7
65,0°	7210.8	6559.4	6991.6	7293.0	7141.6	6604.4	6977.5
70,0°	6197.7	5654.8	6255.1	6051.8	6639.0	6043.4	6600.1
75,0°	5107.6	4730.7	4718.1	5046.0	5242.7	5611.8	6255.7
80,0°	3448.4	3217.5	3404.8	3678.0	4151.5	4882.8	5565.9
85,0°	1377.4	1370.3	1414.9	1656.6	2449.7	3264.0	4228.4

Photometric test report

Family
Highbay 11

Order number: 51HN12DA4KLA02
EAN: 4069025421043

LP number
59710_367

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Highbay 11	Order number: 51HN12DA4KLA02 EAN: 4069025421043	LP number 59710_367
Dimming levels table		environmental temperature: 25°C
		siteco

Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]
100	254	254	23000	117.7
95	240	252	21817	111.0
90	227	250	20712	104.9
85	213	248	19510	98.3
80	200	245	18390	92.1
75	187	243	17257	86.1
70	174	240	16121	80.0
65	161	237	14975	74.0
60	148	234	13820	68.1
55	135	231	12656	62.1
50	122	227	11484	56.1
45	110	223	10395	50.6
40	97	219	9201	44.8
35	85	214	8092	39.4
30	72	208	6876	33.6
25	60	201	5747	28.3
20	48	193	4608	23.1
15	36	182	3453	17.9
10	24	168	2290	12.5
5	12	142	1112	7.0
2	6	117	520	4.3