

Photometric test report

Family Highbay 11	Order number: 51HN11DB3MMA EAN: 4069025424273	LP number 59711_378
	Version	primary light control with lens, PMMA, housing, white, for Modario® rail, narrow distribution
	Lamps	LED 3000 K CRI ≥ 80
	Controlgear	ECG-DALI
	Rated values	Net luminous flux = 28480 lm Power consumption = 146.3 W Luminous efficacy = 194.7 lm/W
		serial documentation 09.04.2025
		



Classifications		Luminaire light output ratios	
DIN 5040	A 7 0	η_{LB}	100.0%
CIE	N1=85 N2=97 N3=100	ϕ_u	100.0%
	N4=100 N5=100	ϕ_o	0.0%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Highbay 11	Order number: 51HN11DB3MMA EAN: 4069025424273	LP number 59711_378
Table of values for luminous intensities		Maximum luminous intensity

siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0,0°	2678.6	2678.6	2678.6	2678.6	2678.6	2678.6	2678.6	4.0	4.0
2,5°	2608.0	2619.4	2619.4	2616.5	2617.6	2616.2	2606.1	31.3	35.3
5,0°	2420.1	2415.7	2414.1	2408.4	2406.6	2402.3	2391.7	57.6	92.8
7,5°	2113.4	2116.1	2112.3	2103.0	2097.6	2090.5	2079.6	75.2	168.1
10,0°	1780.1	1768.7	1762.7	1751.6	1743.6	1735.2	1724.7	83.4	251.5
12,5°	1410.1	1409.3	1404.7	1395.9	1388.1	1380.5	1373.1	82.8	334.3
15,0°	1106.5	1097.8	1095.0	1089.4	1083.1	1078.4	1073.9	77.3	411.5
17,5°	830.1	840.2	835.5	831.1	826.6	824.9	824.1	68.5	480.0
20,0°	671.1	661.9	651.8	643.2	639.9	639.4	641.0	60.8	540.8
22,5°	531.9	530.5	514.2	498.9	497.0	496.6	496.8	53.4	594.2
25,0°	450.6	441.3	420.6	401.3	399.0	395.8	392.4	47.9	642.1
27,5°	370.8	368.7	351.4	331.7	326.8	321.1	316.0	43.1	685.2
30,0°	320.4	312.1	300.8	284.1	278.0	270.2	264.7	39.7	724.9
32,5°	271.0	266.8	259.0	245.6	238.0	229.0	224.7	36.5	761.4
35,0°	235.8	228.9	222.7	210.5	201.6	193.0	191.7	33.3	794.7
37,5°	204.4	197.8	191.5	181.1	172.0	164.3	162.4	30.3	825.0
40,0°	176.7	170.7	163.1	154.3	146.1	138.3	135.6	27.3	852.2
42,5°	147.6	145.5	138.6	130.6	123.2	115.8	113.3	24.2	876.4
45,0°	126.0	121.8	116.3	109.0	102.0	95.3	93.2	21.1	897.6
47,5°	103.2	101.5	97.1	90.9	84.6	78.4	76.7	18.3	915.9
50,0°	85.9	82.9	79.4	74.6	69.1	63.7	61.9	15.5	931.4
52,5°	69.0	67.2	64.5	61.0	56.2	51.6	49.7	13.0	944.4
55,0°	55.6	54.1	52.2	49.5	45.7	41.7	40.0	10.9	955.3
57,5°	43.6	43.1	41.8	39.8	37.0	33.6	32.2	9.0	964.3
60,0°	33.2	33.3	33.9	32.4	30.5	27.5	26.1	7.4	971.7
62,5°	25.9	26.0	27.0	26.2	25.1	22.4	21.3	6.1	977.8
65,0°	21.6	21.2	21.7	21.3	20.9	18.8	17.7	5.1	982.9
67,5°	17.0	17.1	17.8	17.0	17.3	15.6	14.8	4.3	987.2
70,0°	13.5	13.4	14.4	13.6	14.1	13.0	12.4	3.5	990.7
72,5°	11.0	10.8	10.9	10.9	11.0	10.7	10.6	2.8	993.5
75,0°	9.0	8.4	8.4	8.3	8.6	9.0	8.9	2.3	995.8
77,5°	6.6	6.4	6.2	6.2	6.6	7.3	7.4	1.8	997.5
80,0°	4.4	4.2	4.1	4.2	4.7	5.7	5.8	1.3	998.8
82,5°	2.0	2.1	2.2	2.4	3.0	3.9	4.1	0.8	999.6
85,0°	0.8	0.8	0.8	1.0	1.5	2.2	2.4	0.4	999.9
87,5°	0.3	0.3	0.3	0.3	0.3	0.4	0.5	0.1	1000.0
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Highbay 11	Order number: 51HN11DB3MMA EAN: 4069025424273	LP number 59711_378
UGR-Table	Standard room	siteco

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	18.7	19.9	19.1	20.2	20.5	17.5	18.7	17.9	19.0	19.3
	3H	19.0	20.0	19.3	20.3	20.7	17.8	18.8	18.2	19.2	19.5
	4H	19.0	20.0	19.4	20.3	20.7	18.0	18.9	18.3	19.3	19.6
	6H	19.1	19.9	19.5	20.3	20.7	18.1	18.9	18.5	19.3	19.7
	8H	19.1	19.8	19.6	20.2	20.6	18.2	18.9	18.6	19.3	19.7
	12H	19.1	19.8	19.5	20.1	20.6	18.2	18.9	18.6	19.3	19.7
4H	2H	18.8	19.7	19.2	20.1	20.4	17.7	18.7	18.1	19.0	19.4
	3H	19.1	19.9	19.5	20.3	20.7	18.1	18.9	18.6	19.3	19.7
	4H	19.2	19.9	19.7	20.3	20.8	18.3	19.0	18.8	19.4	19.9
	6H	19.3	19.9	19.7	20.3	20.8	18.5	19.1	19.0	19.5	20.0
	8H	19.3	19.8	19.8	20.2	20.7	18.6	19.1	19.1	19.6	20.0
	12H	19.3	19.7	19.8	20.2	20.7	18.6	19.1	19.1	19.5	20.0
8H	4H	19.2	19.7	19.7	20.2	20.6	18.3	18.8	18.8	19.3	19.8
	6H	19.3	19.7	19.8	20.2	20.7	18.6	19.0	19.1	19.5	20.0
	8H	19.3	19.6	19.8	20.1	20.7	18.7	19.0	19.2	19.5	20.1
	12H	19.2	19.5	19.8	20.0	20.6	18.7	19.0	19.3	19.5	20.1
12H	4H	19.2	19.6	19.7	20.1	20.6	18.3	18.8	18.8	19.2	19.7
	6H	19.3	19.6	19.8	20.1	20.6	18.6	18.9	19.1	19.4	19.9
	8H	19.2	19.5	19.8	20.0	20.6	18.7	19.0	19.2	19.5	20.0

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 852 B = 264	
C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
γ	Luminance in cd/m²						
45,0°	22560.1	21806.9	20824.6	19522.1	18265.0	17070.1	16688.0
50,0°	16912.6	16323.8	15632.4	14704.2	13601.7	12539.6	12184.6
55,0°	12271.8	11939.6	11525.9	10927.2	10085.5	9205.8	8835.8
60,0°	8419.9	8429.0	8585.7	8202.8	7715.1	6960.7	6613.3
65,0°	6464.6	6355.5	6499.6	6394.5	6259.3	5625.1	5317.1
70,0°	5008.5	4948.2	5315.8	5020.0	5209.6	4796.0	4583.5
75,0°	4390.7	4120.7	4130.0	4074.2	4203.3	4382.9	4375.1
80,0°	3203.2	3084.4	2983.7	3037.7	3394.3	4122.0	4205.8
85,0°	1185.5	1170.9	1224.7	1384.5	2125.4	3129.3	3546.2

Photometric test report

Family
Highbay 11

Order number: 51HN11DB3MMA
EAN: 4069025424273

LP number
59711_378

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Highbay 11	Order number: 51HN11DB3MMA EAN: 4069025424273	LP number 59711_378
Dimming levels table		environmental temperature: 25°C



Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]
100	254	254	28480	146.3
95	241	252	27090	138.5
90	227	250	25584	130.1
85	214	248	24180	122.4
80	201	245	22765	114.8
75	188	243	21347	107.2
70	175	240	19914	99.6
65	162	238	18482	92.1
60	149	234	17041	84.6
55	137	231	15704	77.8
50	124	228	14249	70.4
45	111	224	12780	62.9
40	99	219	11420	56.1
35	86	214	9936	48.8
30	74	209	8562	42.2
25	62	202	7174	35.5
20	49	194	5668	28.4
15	37	183	4265	21.7
10	25	169	2859	15.3
5	13	145	1442	8.4
2	5	110	495	3.9