

Photometric test report

Family
Highbay 11

Order number: 51HN11DB6PLA
EAN: 4069025424495

LP number
59711_400

serial
documentation
09.04.2025

siteco



Version primary light control with lens, PMMA, housing, white, for Licross® rail, narrow distribution

Lamps LED 6500 K | CRI ≥ 80

Controlgear ECG-DALI

Rated values Net luminous flux = 34160 lm
Power consumption = 177.6 W
Luminous efficacy = 192.3 lm/W

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 2679 cd/klm



Classifications

DIN 5040 A 7 0
CIE N1=85 N2=97 N3=100
N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 100.0%
 ϕ_o 0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Highbay 11	Order number: 51HN11DB6PLA EAN: 4069025424495	LP number 59711_400
Table of values for luminous intensities		Maximum luminous intensity

siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0,0°	2678.6	2678.6	2678.6	2678.6	2678.6	2678.6	2678.6	4.0	4.0
2,5°	2608.0	2619.4	2619.4	2616.5	2617.6	2616.2	2606.1	31.3	35.3
5,0°	2420.1	2415.7	2414.1	2408.4	2406.6	2402.3	2391.7	57.6	92.8
7,5°	2113.4	2116.1	2112.3	2103.0	2097.6	2090.5	2079.6	75.2	168.1
10,0°	1780.1	1768.7	1762.7	1751.6	1743.6	1735.2	1724.7	83.4	251.5
12,5°	1410.1	1409.3	1404.7	1395.9	1388.1	1380.5	1373.1	82.8	334.3
15,0°	1106.5	1097.8	1095.0	1089.4	1083.1	1078.4	1073.9	77.3	411.5
17,5°	830.1	840.2	835.5	831.1	826.6	824.9	824.1	68.5	480.0
20,0°	671.1	661.9	651.8	643.2	639.9	639.4	641.0	60.8	540.8
22,5°	531.9	530.5	514.2	498.9	497.0	496.6	496.8	53.4	594.2
25,0°	450.6	441.3	420.6	401.3	399.0	395.8	392.4	47.9	642.1
27,5°	370.8	368.7	351.4	331.7	326.8	321.1	316.0	43.1	685.2
30,0°	320.4	312.1	300.8	284.1	278.0	270.2	264.7	39.7	724.9
32,5°	271.0	266.8	259.0	245.6	238.0	229.0	224.7	36.5	761.4
35,0°	235.8	228.9	222.7	210.5	201.6	193.0	191.7	33.3	794.7
37,5°	204.4	197.8	191.5	181.1	172.0	164.3	162.4	30.3	825.0
40,0°	176.7	170.7	163.1	154.3	146.1	138.3	135.6	27.3	852.2
42,5°	147.6	145.5	138.6	130.6	123.2	115.8	113.3	24.2	876.4
45,0°	126.0	121.8	116.3	109.0	102.0	95.3	93.2	21.1	897.6
47,5°	103.2	101.5	97.1	90.9	84.6	78.4	76.7	18.3	915.9
50,0°	85.9	82.9	79.4	74.6	69.1	63.7	61.9	15.5	931.4
52,5°	69.0	67.2	64.5	61.0	56.2	51.6	49.7	13.0	944.4
55,0°	55.6	54.1	52.2	49.5	45.7	41.7	40.0	10.9	955.3
57,5°	43.6	43.1	41.8	39.8	37.0	33.6	32.2	9.0	964.3
60,0°	33.2	33.3	33.9	32.4	30.5	27.5	26.1	7.4	971.7
62,5°	25.9	26.0	27.0	26.2	25.1	22.4	21.3	6.1	977.8
65,0°	21.6	21.2	21.7	21.3	20.9	18.8	17.7	5.1	982.9
67,5°	17.0	17.1	17.8	17.0	17.3	15.6	14.8	4.3	987.2
70,0°	13.5	13.4	14.4	13.6	14.1	13.0	12.4	3.5	990.7
72,5°	11.0	10.8	10.9	10.9	11.0	10.7	10.6	2.8	993.5
75,0°	9.0	8.4	8.4	8.3	8.6	9.0	8.9	2.3	995.8
77,5°	6.6	6.4	6.2	6.2	6.6	7.3	7.4	1.8	997.5
80,0°	4.4	4.2	4.1	4.2	4.7	5.7	5.8	1.3	998.8
82,5°	2.0	2.1	2.2	2.4	3.0	3.9	4.1	0.8	999.6
85,0°	0.8	0.8	0.8	1.0	1.5	2.2	2.4	0.4	999.9
87,5°	0.3	0.3	0.3	0.3	0.3	0.4	0.5	0.1	1000.0
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Highbay 11			Order number: 51HN11DB6PLA EAN: 4069025424495							LP number 59711_400	
UGR-Table			Standard room							siteco	
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	19.3	20.5	19.7	20.8	21.2	18.2	19.3	18.5	19.6	20.0
	3H	19.6	20.6	20.0	20.9	21.3	18.4	19.5	18.8	19.8	20.2
	4H	19.7	20.6	20.1	21.0	21.3	18.6	19.5	19.0	19.9	20.3
	6H	19.7	20.5	20.1	20.9	21.3	18.7	19.6	19.1	19.9	20.3
	8H	19.8	20.5	20.2	20.9	21.3	18.8	19.6	19.3	19.9	20.4
	12H	19.7	20.4	20.2	20.8	21.2	18.8	19.5	19.3	19.9	20.3
4H	2H	19.4	20.4	19.8	20.7	21.1	18.4	19.3	18.8	19.6	20.0
	3H	19.7	20.5	20.2	20.9	21.3	18.8	19.5	19.2	19.9	20.3
	4H	19.8	20.5	20.3	20.9	21.4	18.9	19.6	19.4	20.0	20.5
	6H	19.9	20.5	20.4	20.9	21.4	19.1	19.7	19.6	20.2	20.6
	8H	19.9	20.4	20.4	20.9	21.4	19.2	19.7	19.7	20.2	20.7
	12H	19.9	20.3	20.4	20.8	21.3	19.3	19.7	19.8	20.2	20.7
8H	4H	19.8	20.3	20.3	20.8	21.3	19.0	19.5	19.4	19.9	20.4
	6H	19.9	20.3	20.4	20.8	21.3	19.2	19.6	19.7	20.1	20.6
	8H	19.9	20.3	20.4	20.8	21.3	19.3	19.7	19.8	20.2	20.7
	12H	19.9	20.2	20.4	20.7	21.2	19.4	19.7	19.9	20.2	20.7
12H	4H	19.8	20.2	20.3	20.7	21.2	19.0	19.4	19.5	19.8	20.3
	6H	19.9	20.2	20.4	20.7	21.3	19.2	19.5	19.7	20.0	20.6
	8H	19.9	20.2	20.4	20.7	21.2	19.3	19.6	19.8	20.1	20.6

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 852 B = 264	
C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
γ	Luminance in cd/m²						
45,0°	27059.4	26156.1	24977.8	23415.5	21907.8	20474.6	20016.2
50,0°	20285.6	19579.4	18750.1	17636.8	16314.4	15040.4	14614.7
55,0°	14719.3	14320.8	13824.6	13106.5	12096.9	11041.8	10598.0
60,0°	10099.1	10110.0	10298.1	9838.8	9253.8	8348.9	7932.2
65,0°	7753.8	7623.0	7795.9	7669.8	7507.7	6746.9	6377.5
70,0°	6007.4	5935.0	6376.0	6021.2	6248.5	5752.5	5497.7
75,0°	5266.4	4942.5	4953.6	4886.7	5041.6	5257.0	5247.6
80,0°	3842.1	3699.5	3578.8	3643.5	4071.2	4944.1	5044.6
85,0°	1421.9	1404.5	1468.9	1660.6	2549.3	3753.4	4253.5

Photometric test report

Family
Highbay 11

Order number: 51HN11DB6PLA
EAN: 4069025424495

LP number
59711_400

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Highbay 11	Order number: 51HN11DB6PLA EAN: 4069025424495	LP number 59711_400
Dimming levels table		environmental temperature: 25°C
		siteco

Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]
100	254	254	34160	177.6
95	241	252	32503	168.2
90	227	250	30707	158.1
85	214	248	29034	148.9
80	201	245	27342	139.5
75	188	243	25645	130.4
70	175	240	23938	121.1
65	162	238	22227	112.1
60	149	234	20500	103.0
55	136	231	18770	94.0
50	123	227	17022	85.0
45	111	224	15395	76.8
40	98	219	13625	67.9
35	86	214	11983	59.8
30	73	208	10195	50.9
25	61	202	8525	42.9
20	49	194	6851	35.0
15	37	183	5166	27.2
10	25	169	3471	19.3
5	13	145	1761	11.1
1	4	102	475	4.8