

Photometric test report

Family
Highbay 11

Order number: 51HN12DA6FLA
EAN: 4069025424693

LP number
59710_407



Version primary light control with lens, PMMA, housing, white, for Licross® rail, wide distribution

Lamps LED 6500 K | CRI ≥ 80

Controlgear ECG-DALI

Rated values Net luminous flux = 14220 lm
Power consumption = 73.2 W
Luminous efficacy = 194.3 lm/W

serial
documentation
09.04.2025

siteco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 772 cd/klm



Classifications

DIN 5040 A 6 0
CIE N1=88 N2=98 N3=100
N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 100.0%
 ϕ_o 0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Highbay 11	Order number: 51HN12DA6FLA EAN: 4069025424693	LP number 59710_407
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0,0°	643.6	643.6	643.6	643.6	643.6	643.6	643.6	1.0	1.0
2,5°	644.5	645.1	645.0	644.3	644.2	643.7	641.7	7.7	8.7
5,0°	651.5	652.3	650.7	647.5	645.3	643.2	640.4	15.5	24.1
7,5°	669.6	669.1	664.2	657.2	651.2	645.8	641.3	23.5	47.6
10,0°	693.4	691.0	681.5	670.0	659.9	651.2	645.8	31.9	79.6
12,5°	711.8	709.4	700.3	685.9	671.9	660.7	654.0	40.7	120.2
15,0°	721.3	721.7	717.1	704.9	689.4	675.9	667.7	49.7	169.9
17,5°	743.8	740.8	737.9	726.5	708.9	693.0	684.2	59.4	229.3
20,0°	761.9	761.9	759.6	745.2	724.0	705.6	696.8	69.2	298.5
22,5°	772.0	771.2	770.0	754.7	731.1	710.8	702.6	78.2	376.7
25,0°	758.1	756.6	756.3	743.6	722.7	703.3	695.6	85.1	461.8
27,5°	706.7	709.5	709.5	700.0	685.7	672.3	667.0	87.8	549.7
30,0°	640.4	635.6	633.7	626.6	621.7	614.1	609.9	85.8	635.5
32,5°	530.6	537.6	535.6	526.2	530.2	524.1	520.8	78.1	713.6
35,0°	428.2	426.4	425.9	411.9	420.8	414.2	411.4	66.0	779.6
37,5°	322.5	323.4	327.0	311.0	319.4	310.8	308.2	53.0	832.6
40,0°	236.1	234.0	241.6	230.8	230.9	219.8	218.4	40.7	873.3
42,5°	162.3	165.3	172.9	171.1	161.7	151.3	150.8	30.2	903.5
45,0°	117.3	114.9	119.4	122.5	109.3	102.6	102.3	21.9	925.4
47,5°	80.5	81.4	82.8	85.5	75.2	71.4	70.8	15.9	941.3
50,0°	59.4	58.0	58.0	59.0	52.9	50.5	49.6	11.7	953.0
52,5°	43.3	42.8	42.8	43.0	39.3	37.2	36.6	8.9	961.8
55,0°	33.3	32.4	32.9	33.7	30.5	28.7	28.3	7.1	968.9
57,5°	25.9	25.4	25.9	26.8	24.5	22.9	22.9	5.8	974.7
60,0°	20.9	20.2	21.2	21.8	20.4	18.9	19.2	4.9	979.5
62,5°	16.9	16.2	17.4	18.0	17.2	15.9	16.4	4.1	983.6
65,0°	14.9	13.6	14.4	15.1	14.8	13.6	14.4	3.6	987.2
67,5°	12.3	11.4	12.5	12.4	13.0	11.7	12.6	3.1	990.3
70,0°	10.4	9.5	10.5	10.1	11.1	10.1	11.0	2.7	993.0
72,5°	8.2	7.7	7.9	8.2	8.7	8.6	9.5	2.2	995.2
75,0°	6.5	6.0	6.0	6.4	6.6	7.1	7.9	1.7	996.9
77,5°	4.5	4.3	4.4	4.7	5.1	5.6	6.3	1.3	998.2
80,0°	2.9	2.7	2.9	3.1	3.5	4.1	4.7	0.9	999.1
82,5°	1.3	1.4	1.6	1.8	2.2	2.7	3.3	0.5	999.7
85,0°	0.6	0.6	0.6	0.7	1.0	1.4	1.8	0.3	999.9
87,5°	0.3	0.3	0.3	0.3	0.3	0.4	0.5	0.1	1000.0
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Highbay 11			Order number: 51HN12DA6FLA EAN: 4069025424693							LP number 59710_407	
UGR-Table			Standard room							siteco	
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	19.7	21.0	20.1	21.3	21.7	19.4	20.7	19.8	21.0	21.4
	3H	19.7	20.9	20.1	21.2	21.6	19.5	20.6	19.8	20.9	21.3
	4H	19.7	20.8	20.1	21.1	21.5	19.5	20.5	19.9	20.9	21.3
	6H	19.7	20.6	20.1	21.0	21.4	19.5	20.4	19.9	20.8	21.2
	8H	19.8	20.6	20.2	21.0	21.4	19.6	20.4	20.0	20.8	21.2
	12H	19.8	20.5	20.2	20.9	21.3	19.6	20.3	20.0	20.7	21.1
4H	2H	19.6	20.7	20.0	21.0	21.4	19.3	20.4	19.7	20.7	21.1
	3H	19.7	20.5	20.1	20.9	21.3	19.4	20.3	19.8	20.7	21.1
	4H	19.7	20.4	20.1	20.8	21.3	19.5	20.2	19.9	20.6	21.1
	6H	19.6	20.3	20.1	20.7	21.2	19.5	20.2	20.0	20.6	21.1
	8H	19.6	20.2	20.1	20.7	21.1	19.5	20.1	20.0	20.5	21.0
	12H	19.6	20.1	20.1	20.6	21.1	19.6	20.0	20.1	20.5	21.0
8H	4H	19.6	20.2	20.1	20.6	21.1	19.4	20.0	19.9	20.4	20.9
	6H	19.6	20.1	20.1	20.5	21.0	19.5	19.9	20.0	20.4	20.9
	8H	19.5	20.0	20.0	20.4	21.0	19.5	19.9	20.0	20.4	20.9
	12H	19.5	19.9	20.1	20.4	20.9	19.5	19.8	20.0	20.3	20.9
12H	4H	19.6	20.1	20.1	20.5	21.0	19.4	19.9	19.9	20.3	20.8
	6H	19.6	20.0	20.1	20.4	21.0	19.5	19.8	20.0	20.3	20.8
	8H	19.5	19.9	20.1	20.4	20.9	19.5	19.8	20.0	20.3	20.8

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 426 B = 264	
C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
γ	Luminance in cd/m²						
45,0°	20979.3	20542.5	21353.6	21900.9	19538.6	18344.9	18290.9
50,0°	11688.9	11412.5	11400.5	11604.1	10412.9	9928.4	9758.0
55,0°	7345.8	7149.4	7251.4	7417.9	6729.0	6325.4	6249.3
60,0°	5283.4	5100.4	5359.1	5519.9	5168.1	4786.0	4847.0
65,0°	4458.1	4055.4	4322.6	4509.0	4415.4	4083.3	4313.9
70,0°	3831.8	3496.1	3867.3	3741.6	4104.6	3736.4	4080.6
75,0°	3157.8	2924.8	2917.0	3119.7	3241.4	3469.5	3867.7
80,0°	2132.0	1989.3	2105.1	2274.0	2566.7	3018.9	3441.2
85,0°	851.6	847.2	874.8	1024.2	1514.6	2018.0	2614.2

Photometric test report

Family
Highbay 11

Order number: 51HN12DA6FLA
EAN: 4069025424693

LP number
59710_407

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Highbay 11	Order number: 51HN12DA6FLA EAN: 4069025424693	LP number 59710_407
Dimming levels table		environmental temperature: 25°C



Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]
100	254	254	14220	73.2
95	241	252	13521	69.3
90	228	250	12822	65.5
85	214	248	12066	61.5
80	201	245	11356	57.7
75	188	243	10649	53.8
70	175	240	9936	50.1
65	162	238	9216	46.4
60	150	235	8552	43.0
55	137	231	7828	39.2
50	124	228	7097	35.6
45	112	224	6424	32.2
40	99	219	5690	28.6
35	87	215	5004	25.2
30	74	209	4263	21.7
25	62	202	3574	18.3
20	49	194	2819	14.8
15	37	183	2123	11.5
10	25	169	1424	8.2
5	13	145	716	4.7
2	5	110	245	2.5