


# Photometric test report

<b>Family</b> <b>Highbay 11</b>	<b>Order number: 51HN12DA5FDA</b> <b>EAN: 4069025424617</b>	<b>LP number</b> <b>59710_442</b>
	<b>Version</b> primary light control with lens, PMMA, housing, white, wide distribution <b>Lamps</b> LED 5000 K   CRI ≥ 80 <b>Controlgear</b> ECG-DALI <b>Setting</b> DC mode (central or group accumulator) initial emergency light level <b>Rated values</b> Net luminous flux = 2290 lm Power consumption = 11.8 W Luminous efficacy = 194.1 lm/W	<b>serial documentation</b> <b>10.04.2025</b>



**Luminous intensity in cd/klm** C180-0 C270-90 **Imax: 772 cd/klm**



Classifications	
DIN 5040	A 6 0
CIE	N1=88 N2=98 N3=100 N4=100 N5=100

Luminaire light output ratios	
$\eta_{LB}$	100.0%
$\phi_u$	100.0%
$\phi_o$	0.0%

**Measurement conditions**  
DIN EN 13032 and DIN 5032

## Photometric test report

Family Highbay 11	Order number: 51HN12DA5FDA EAN: 4069025424617	LP number 59710_442
Table of values for luminous intensities		Maximum luminous intensity



C-planes $\gamma$	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm								Luminous flux in lm/klm	
0,0°	643.6	643.6	643.6	643.6	643.6	643.6	643.6	1.0	1.0
2,5°	644.5	645.1	645.0	644.3	644.2	643.7	641.7	7.7	8.7
5,0°	651.5	652.3	650.7	647.5	645.3	643.2	640.4	15.5	24.1
7,5°	669.6	669.1	664.2	657.2	651.2	645.8	641.3	23.5	47.6
10,0°	693.4	691.0	681.5	670.0	659.9	651.2	645.8	31.9	79.6
12,5°	711.8	709.4	700.3	685.9	671.9	660.7	654.0	40.7	120.2
15,0°	721.3	721.7	717.1	704.9	689.4	675.9	667.7	49.7	169.9
17,5°	743.8	740.8	737.9	726.5	708.9	693.0	684.2	59.4	229.3
20,0°	761.9	761.9	759.6	745.2	724.0	705.6	696.8	69.2	298.5
22,5°	772.0	771.2	770.0	754.7	731.1	710.8	702.6	78.2	376.7
25,0°	758.1	756.6	756.3	743.6	722.7	703.3	695.6	85.1	461.8
27,5°	706.7	709.5	709.5	700.0	685.7	672.3	667.0	87.8	549.7
30,0°	640.4	635.6	633.7	626.6	621.7	614.1	609.9	85.8	635.5
32,5°	530.6	537.6	535.6	526.2	530.2	524.1	520.8	78.1	713.6
35,0°	428.2	426.4	425.9	411.9	420.8	414.2	411.4	66.0	779.6
37,5°	322.5	323.4	327.0	311.0	319.4	310.8	308.2	53.0	832.6
40,0°	236.1	234.0	241.6	230.8	230.9	219.8	218.4	40.7	873.3
42,5°	162.3	165.3	172.9	171.1	161.7	151.3	150.8	30.2	903.5
45,0°	117.3	114.9	119.4	122.5	109.3	102.6	102.3	21.9	925.4
47,5°	80.5	81.4	82.8	85.5	75.2	71.4	70.8	15.9	941.3
50,0°	59.4	58.0	58.0	59.0	52.9	50.5	49.6	11.7	953.0
52,5°	43.3	42.8	42.8	43.0	39.3	37.2	36.6	8.9	961.8
55,0°	33.3	32.4	32.9	33.7	30.5	28.7	28.3	7.1	968.9
57,5°	25.9	25.4	25.9	26.8	24.5	22.9	22.9	5.8	974.7
60,0°	20.9	20.2	21.2	21.8	20.4	18.9	19.2	4.9	979.5
62,5°	16.9	16.2	17.4	18.0	17.2	15.9	16.4	4.1	983.6
65,0°	14.9	13.6	14.4	15.1	14.8	13.6	14.4	3.6	987.2
67,5°	12.3	11.4	12.5	12.4	13.0	11.7	12.6	3.1	990.3
70,0°	10.4	9.5	10.5	10.1	11.1	10.1	11.0	2.7	993.0
72,5°	8.2	7.7	7.9	8.2	8.7	8.6	9.5	2.2	995.2
75,0°	6.5	6.0	6.0	6.4	6.6	7.1	7.9	1.7	996.9
77,5°	4.5	4.3	4.4	4.7	5.1	5.6	6.3	1.3	998.2
80,0°	2.9	2.7	2.9	3.1	3.5	4.1	4.7	0.9	999.1
82,5°	1.3	1.4	1.6	1.8	2.2	2.7	3.3	0.5	999.7
85,0°	0.6	0.6	0.6	0.7	1.0	1.4	1.8	0.3	999.9
87,5°	0.3	0.3	0.3	0.3	0.3	0.4	0.5	0.1	1000.0
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

## Photometric test report

Family Highbay 11	Order number: 51HN12DA5FDA EAN: 4069025424617	LP number 59710_442
----------------------	--	------------------------

UGR-Table	Standard room	siteco	
-----------	---------------	--------	--

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	13.4	14.7	13.8	15.0	15.3	13.1	14.4	13.5	14.7	15.0
	3H	13.4	14.5	13.8	14.9	15.2	13.1	14.2	13.5	14.6	14.9
	4H	13.4	14.4	13.8	14.8	15.2	13.1	14.2	13.5	14.5	14.9
	6H	13.4	14.3	13.8	14.7	15.1	13.2	14.1	13.6	14.5	14.9
	8H	13.4	14.2	13.9	14.6	15.0	13.3	14.1	13.7	14.4	14.8
	12H	13.4	14.1	13.8	14.5	14.9	13.2	14.0	13.7	14.4	14.8
4H	2H	13.3	14.3	13.7	14.7	15.1	13.0	14.0	13.4	14.4	14.8
	3H	13.3	14.2	13.8	14.6	15.0	13.1	13.9	13.5	14.3	14.7
	4H	13.3	14.1	13.8	14.5	14.9	13.1	13.9	13.6	14.3	14.7
	6H	13.3	13.9	13.8	14.4	14.9	13.2	13.8	13.6	14.2	14.7
	8H	13.3	13.9	13.8	14.3	14.8	13.2	13.8	13.6	14.2	14.7
	12H	13.3	13.8	13.8	14.2	14.7	13.2	13.7	13.7	14.1	14.6
8H	4H	13.3	13.8	13.7	14.3	14.8	13.1	13.6	13.5	14.1	14.6
	6H	13.2	13.7	13.7	14.2	14.7	13.1	13.6	13.6	14.1	14.6
	8H	13.2	13.6	13.7	14.1	14.6	13.1	13.5	13.6	14.0	14.6
	12H	13.2	13.5	13.7	14.0	14.6	13.2	13.5	13.7	14.0	14.5
12H	4H	13.3	13.7	13.8	14.2	14.7	13.1	13.5	13.6	14.0	14.5
	6H	13.2	13.6	13.8	14.1	14.6	13.1	13.5	13.6	14.0	14.5
	8H	13.2	13.5	13.7	14.0	14.6	13.1	13.4	13.6	13.9	14.5

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 426 B = 264
-----------------	---------------------------------	-------------------------------	--------------------

C-planes	$\gamma$	Luminance in cd/m <sup>2</sup>								
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°		
45,0°		3378.5	3308.2	3438.8	3526.9	3146.5	2954.3	2945.6		
50,0°		1882.4	1837.9	1835.9	1868.7	1676.9	1598.9	1571.4		
55,0°		1183.0	1151.3	1167.8	1194.6	1083.6	1018.6	1006.4		
60,0°		850.8	821.4	863.0	888.9	832.3	770.7	780.6		
65,0°		717.9	653.1	696.1	726.1	711.1	657.6	694.7		
70,0°		617.1	563.0	622.8	602.6	661.0	601.7	657.1		
75,0°		508.5	471.0	469.8	502.4	522.0	558.7	622.9		
80,0°		343.3	320.4	339.0	366.2	413.3	486.2	554.2		
85,0°		137.1	136.4	140.9	164.9	243.9	325.0	421.0		

**Photometric test report**

**Family**  
Highbay 11

**Order number: 51HN12DA5FDA**  
**EAN: 4069025424617**

**LP number**  
59710\_442

**Luminance values in cd/m<sup>2</sup>**

$\gamma$  65°   
   $\gamma$  70°   
   $\gamma$  75°   
   $\gamma$  80°   
   $\gamma$  85°

