

Photometric test report

Family
Highbay 11

Order number: 51HN12DB5VLA
EAN: 4069025424938

LP number
59710_464

serial
documentation
10.04.2025

siteco



Version primary light control with lens, PMMA, housing, white, for Licross® rail, wide distribution

Lamps LED 5000 K | CRI ≥ 80

Controlgear ECG-DALI

Rated values Net luminous flux = 55810 lm
Power consumption = 294.9 W
Luminous efficacy = 189.3 lm/W

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 772 cd/klm



Classifications

DIN 5040 A 6 0
CIE N1=88 N2=98 N3=100
N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 100.0%
 ϕ_o 0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Highbay 11	Order number: 51HN12DB5VLA EAN: 4069025424938	LP number 59710_464
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0,0°	643.6	643.6	643.6	643.6	643.6	643.6	643.6	1.0	1.0
2,5°	644.5	645.1	645.0	644.3	644.2	643.7	641.7	7.7	8.7
5,0°	651.5	652.3	650.7	647.5	645.3	643.2	640.4	15.5	24.1
7,5°	669.6	669.1	664.2	657.2	651.2	645.8	641.3	23.5	47.6
10,0°	693.4	691.0	681.5	670.0	659.9	651.2	645.8	31.9	79.6
12,5°	711.8	709.4	700.3	685.9	671.9	660.7	654.0	40.7	120.2
15,0°	721.3	721.7	717.1	704.9	689.4	675.9	667.7	49.7	169.9
17,5°	743.8	740.8	737.9	726.5	708.9	693.0	684.2	59.4	229.3
20,0°	761.9	761.9	759.6	745.2	724.0	705.6	696.8	69.2	298.5
22,5°	772.0	771.2	770.0	754.7	731.1	710.8	702.6	78.2	376.7
25,0°	758.1	756.6	756.3	743.6	722.7	703.3	695.6	85.1	461.8
27,5°	706.7	709.5	709.5	700.0	685.7	672.3	667.0	87.8	549.7
30,0°	640.4	635.6	633.7	626.6	621.7	614.1	609.9	85.8	635.5
32,5°	530.6	537.6	535.6	526.2	530.2	524.1	520.8	78.1	713.6
35,0°	428.2	426.4	425.9	411.9	420.8	414.2	411.4	66.0	779.6
37,5°	322.5	323.4	327.0	311.0	319.4	310.8	308.2	53.0	832.6
40,0°	236.1	234.0	241.6	230.8	230.9	219.8	218.4	40.7	873.3
42,5°	162.3	165.3	172.9	171.1	161.7	151.3	150.8	30.2	903.5
45,0°	117.3	114.9	119.4	122.5	109.3	102.6	102.3	21.9	925.4
47,5°	80.5	81.4	82.8	85.5	75.2	71.4	70.8	15.9	941.3
50,0°	59.4	58.0	58.0	59.0	52.9	50.5	49.6	11.7	953.0
52,5°	43.3	42.8	42.8	43.0	39.3	37.2	36.6	8.9	961.8
55,0°	33.3	32.4	32.9	33.7	30.5	28.7	28.3	7.1	968.9
57,5°	25.9	25.4	25.9	26.8	24.5	22.9	22.9	5.8	974.7
60,0°	20.9	20.2	21.2	21.8	20.4	18.9	19.2	4.9	979.5
62,5°	16.9	16.2	17.4	18.0	17.2	15.9	16.4	4.1	983.6
65,0°	14.9	13.6	14.4	15.1	14.8	13.6	14.4	3.6	987.2
67,5°	12.3	11.4	12.5	12.4	13.0	11.7	12.6	3.1	990.3
70,0°	10.4	9.5	10.5	10.1	11.1	10.1	11.0	2.7	993.0
72,5°	8.2	7.7	7.9	8.2	8.7	8.6	9.5	2.2	995.2
75,0°	6.5	6.0	6.0	6.4	6.6	7.1	7.9	1.7	996.9
77,5°	4.5	4.3	4.4	4.7	5.1	5.6	6.3	1.3	998.2
80,0°	2.9	2.7	2.9	3.1	3.5	4.1	4.7	0.9	999.1
82,5°	1.3	1.4	1.6	1.8	2.2	2.7	3.3	0.5	999.7
85,0°	0.6	0.6	0.6	0.7	1.0	1.4	1.8	0.3	999.9
87,5°	0.3	0.3	0.3	0.3	0.3	0.4	0.5	0.1	1000.0
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Highbay 11			Order number: 51HN12DB5VLA EAN: 4069025424938						LP number 59710_464		
UGR-Table			Standard room						siteco		
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	22.1	23.4	22.4	23.7	24.0	21.8	23.1	22.1	23.4	23.7
	3H	22.1	23.2	22.5	23.5	23.9	21.8	22.9	22.2	23.3	23.6
	4H	22.1	23.1	22.5	23.5	23.8	21.8	22.9	22.2	23.2	23.6
	6H	22.0	23.0	22.5	23.4	23.7	21.8	22.8	22.3	23.2	23.6
	8H	22.1	22.9	22.5	23.3	23.7	21.9	22.7	22.4	23.1	23.5
	12H	22.1	22.8	22.5	23.2	23.6	21.9	22.7	22.4	23.1	23.5
4H	2H	22.0	23.0	22.4	23.4	23.7	21.7	22.7	22.1	23.1	23.5
	3H	22.0	22.9	22.4	23.3	23.7	21.8	22.6	22.2	23.0	23.4
	4H	22.0	22.8	22.5	23.2	23.6	21.8	22.6	22.3	23.0	23.4
	6H	22.0	22.6	22.5	23.1	23.5	21.8	22.5	22.3	22.9	23.4
	8H	22.0	22.5	22.4	23.0	23.5	21.9	22.4	22.3	22.9	23.4
	12H	22.0	22.4	22.5	22.9	23.4	21.9	22.4	22.4	22.8	23.3
8H	4H	21.9	22.5	22.4	23.0	23.5	21.7	22.3	22.2	22.8	23.3
	6H	21.9	22.4	22.4	22.9	23.4	21.8	22.3	22.3	22.7	23.3
	8H	21.9	22.3	22.4	22.8	23.3	21.8	22.2	22.3	22.7	23.2
	12H	21.9	22.2	22.4	22.7	23.2	21.8	22.2	22.4	22.7	23.2
12H	4H	22.0	22.4	22.5	22.9	23.4	21.8	22.2	22.2	22.7	23.2
	6H	21.9	22.3	22.4	22.8	23.3	21.8	22.2	22.3	22.7	23.2
	8H	21.9	22.2	22.4	22.7	23.3	21.8	22.1	22.3	22.6	23.2

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 852 B = 264	
C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
γ	Luminance in cd/m²						
45,0°	41169.4	40312.1	41903.8	42977.9	38342.2	35999.5	35893.6
50,0°	22938.0	22395.7	22372.1	22771.6	20433.9	19483.2	19148.9
55,0°	14415.2	14029.8	14230.1	14556.7	13204.8	12412.8	12263.5
60,0°	10368.1	10008.8	10516.5	10832.1	10141.8	9392.0	9511.6
65,0°	8748.5	7958.3	8482.6	8848.4	8664.6	8012.9	8465.6
70,0°	7519.5	6860.7	7589.1	7342.4	8054.8	7332.3	8007.7
75,0°	6196.9	5739.6	5724.3	6122.1	6360.8	6808.5	7589.8
80,0°	4183.8	3903.7	4130.9	4462.4	5036.8	5924.2	6752.9
85,0°	1671.1	1662.6	1716.7	2009.9	2972.2	3960.0	5130.1

Photometric test report

Family
Highbay 11

Order number: 51HN12DB5VLA
EAN: 4069025424938

LP number
59710_464

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Highbay 11	Order number: 51HN12DB5VLA EAN: 4069025424938	LP number 59710_464
Dimming levels table	environmental temperature: 25°C	siteco

Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]
100	254	254	55810	294.9
95	240	252	53025	277.9
90	226	250	50152	261.0
85	213	248	47487	245.4
80	199	245	44591	228.3
75	186	243	41867	213.0
70	173	240	39133	197.7
65	160	237	36347	182.3
60	147	234	33543	167.1
55	134	231	30723	152.1
50	121	227	27879	137.1
45	108	223	25022	122.4
40	96	218	22349	108.5
35	84	213	19642	95.1
30	71	207	16690	80.6
25	59	201	13932	67.4
20	47	192	11131	54.2
15	35	181	8303	41.2
10	24	168	5680	29.3
5	12	142	2780	15.7
2	5	110	1077	7.9