

Photometric test report

Family
Highbay 11

Order number: 51HN12DB6MDA
EAN: 4069025424969

LP number
59710_436

serial
documentation
10.04.2025

siteco



Version primary light control with lens, PMMA, housing, white, wide distribution
Lamps LED 6500 K | CRI ≥ 80
Controlgear ECG-DALI
Setting AC-mode
Rated values Net luminous flux = 28420 lm
Power consumption = 146.3 W
Luminous efficacy = 194.3 lm/W

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 772 cd/klm



Classifications

DIN 5040 A 6 0
CIE N1=88 N2=98 N3=100
N4=100 N5=100

Luminaire light output ratios

η_{LB} 100.0%
 ϕ_u 100.0%
 ϕ_o 0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family Highbay 11	Order number: 51HN12DB6MDA EAN: 4069025424969	LP number 59710_436
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C- planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
0,0°	643.6	643.6	643.6	643.6	643.6	643.6	643.6	1.0	1.0
2,5°	644.5	645.1	645.0	644.3	644.2	643.7	641.7	7.7	8.7
5,0°	651.5	652.3	650.7	647.5	645.3	643.2	640.4	15.5	24.1
7,5°	669.6	669.1	664.2	657.2	651.2	645.8	641.3	23.5	47.6
10,0°	693.4	691.0	681.5	670.0	659.9	651.2	645.8	31.9	79.6
12,5°	711.8	709.4	700.3	685.9	671.9	660.7	654.0	40.7	120.2
15,0°	721.3	721.7	717.1	704.9	689.4	675.9	667.7	49.7	169.9
17,5°	743.8	740.8	737.9	726.5	708.9	693.0	684.2	59.4	229.3
20,0°	761.9	761.9	759.6	745.2	724.0	705.6	696.8	69.2	298.5
22,5°	772.0	771.2	770.0	754.7	731.1	710.8	702.6	78.2	376.7
25,0°	758.1	756.6	756.3	743.6	722.7	703.3	695.6	85.1	461.8
27,5°	706.7	709.5	709.5	700.0	685.7	672.3	667.0	87.8	549.7
30,0°	640.4	635.6	633.7	626.6	621.7	614.1	609.9	85.8	635.5
32,5°	530.6	537.6	535.6	526.2	530.2	524.1	520.8	78.1	713.6
35,0°	428.2	426.4	425.9	411.9	420.8	414.2	411.4	66.0	779.6
37,5°	322.5	323.4	327.0	311.0	319.4	310.8	308.2	53.0	832.6
40,0°	236.1	234.0	241.6	230.8	230.9	219.8	218.4	40.7	873.3
42,5°	162.3	165.3	172.9	171.1	161.7	151.3	150.8	30.2	903.5
45,0°	117.3	114.9	119.4	122.5	109.3	102.6	102.3	21.9	925.4
47,5°	80.5	81.4	82.8	85.5	75.2	71.4	70.8	15.9	941.3
50,0°	59.4	58.0	58.0	59.0	52.9	50.5	49.6	11.7	953.0
52,5°	43.3	42.8	42.8	43.0	39.3	37.2	36.6	8.9	961.8
55,0°	33.3	32.4	32.9	33.7	30.5	28.7	28.3	7.1	968.9
57,5°	25.9	25.4	25.9	26.8	24.5	22.9	22.9	5.8	974.7
60,0°	20.9	20.2	21.2	21.8	20.4	18.9	19.2	4.9	979.5
62,5°	16.9	16.2	17.4	18.0	17.2	15.9	16.4	4.1	983.6
65,0°	14.9	13.6	14.4	15.1	14.8	13.6	14.4	3.6	987.2
67,5°	12.3	11.4	12.5	12.4	13.0	11.7	12.6	3.1	990.3
70,0°	10.4	9.5	10.5	10.1	11.1	10.1	11.0	2.7	993.0
72,5°	8.2	7.7	7.9	8.2	8.7	8.6	9.5	2.2	995.2
75,0°	6.5	6.0	6.0	6.4	6.6	7.1	7.9	1.7	996.9
77,5°	4.5	4.3	4.4	4.7	5.1	5.6	6.3	1.3	998.2
80,0°	2.9	2.7	2.9	3.1	3.5	4.1	4.7	0.9	999.1
82,5°	1.3	1.4	1.6	1.8	2.2	2.7	3.3	0.5	999.7
85,0°	0.6	0.6	0.6	0.7	1.0	1.4	1.8	0.3	999.9
87,5°	0.3	0.3	0.3	0.3	0.3	0.4	0.5	0.1	1000.0
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Highbay 11			Order number: 51HN12DB6MDA EAN: 4069025424969							LP number 59710_436	
UGR-Table			Standard room							siteco	
Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	19.7	21.0	20.1	21.3	21.7	19.4	20.7	19.8	21.0	21.4
	3H	19.7	20.9	20.1	21.2	21.6	19.5	20.6	19.8	20.9	21.3
	4H	19.7	20.8	20.1	21.1	21.5	19.5	20.5	19.9	20.9	21.3
	6H	19.7	20.6	20.1	21.0	21.4	19.5	20.4	19.9	20.8	21.2
	8H	19.8	20.6	20.2	21.0	21.4	19.6	20.4	20.0	20.8	21.2
	12H	19.7	20.5	20.2	20.9	21.3	19.6	20.3	20.0	20.7	21.1
4H	2H	19.6	20.7	20.0	21.0	21.4	19.3	20.4	19.7	20.7	21.1
	3H	19.7	20.5	20.1	20.9	21.3	19.4	20.3	19.8	20.7	21.1
	4H	19.7	20.4	20.1	20.8	21.3	19.5	20.2	19.9	20.6	21.1
	6H	19.6	20.3	20.1	20.7	21.2	19.5	20.2	20.0	20.6	21.1
	8H	19.6	20.2	20.1	20.6	21.1	19.5	20.1	20.0	20.5	21.0
	12H	19.6	20.1	20.1	20.6	21.1	19.6	20.0	20.1	20.5	21.0
8H	4H	19.6	20.2	20.1	20.6	21.1	19.4	20.0	19.9	20.4	20.9
	6H	19.6	20.0	20.1	20.5	21.0	19.5	19.9	20.0	20.4	20.9
	8H	19.5	20.0	20.0	20.4	21.0	19.5	19.9	20.0	20.4	20.9
	12H	19.5	19.9	20.1	20.4	20.9	19.5	19.8	20.0	20.3	20.9
12H	4H	19.6	20.1	20.1	20.5	21.0	19.4	19.9	19.9	20.3	20.8
	6H	19.6	19.9	20.1	20.4	21.0	19.5	19.8	20.0	20.3	20.8
	8H	19.5	19.9	20.1	20.4	20.9	19.5	19.8	20.0	20.3	20.8

Luminance table		Max. for $\gamma \geq 65^\circ$		Photometric dimensions in mm:		L = 852 B = 264	
C-planes	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°
γ	Luminance in cd/m²						
45,0°	20964.6	20528.0	21338.6	21885.5	19524.9	18332.0	18278.0
50,0°	11680.7	11404.5	11392.5	11595.9	10405.5	9921.4	9751.2
55,0°	7340.6	7144.4	7246.3	7412.7	6724.3	6320.9	6244.9
60,0°	5279.7	5096.8	5355.3	5516.0	5164.5	4782.7	4843.6
65,0°	4455.0	4052.6	4319.6	4505.8	4412.2	4080.4	4310.9
70,0°	3829.1	3493.7	3864.6	3739.0	4101.8	3733.8	4077.7
75,0°	3155.6	2922.8	2915.0	3117.5	3239.1	3467.1	3865.0
80,0°	2130.5	1987.9	2103.6	2272.4	2564.9	3016.8	3438.8
85,0°	851.0	846.6	874.2	1023.5	1513.5	2016.6	2612.4

Photometric test report

Family
Highbay 11

Order number: 51HN12DB6MDA
EAN: 4069025424969

LP number
59710_436

Luminance values in cd/m²

γ 65°


γ 70°

γ 75°

γ 80°

γ 85°

siteco



Photometric test report

Family Highbay 11	Order number: 51HN12DB6MDA EAN: 4069025424969	LP number 59710_436
Dimming levels table		environmental temperature: 25°C
		siteco

Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]
100	254	254	28420	146.3
95	241	252	27029	138.5
90	228	250	25629	130.7
85	214	248	24118	122.4
80	201	245	22703	114.8
75	188	243	21287	107.2
70	175	240	19855	99.6
65	162	238	18425	92.1
60	150	235	17098	85.1
55	137	231	15651	77.8
50	124	228	14198	70.4
45	112	224	12845	63.5
40	99	219	11377	56.1
35	86	214	9895	48.8
30	74	209	8525	42.2
25	62	202	7142	35.5
20	49	194	5641	28.4
15	37	183	4245	21.7
10	25	169	2845	15.3
5	13	145	1434	8.4
2	5	110	492	3.9