Photometric test report

Family
Lunis R LED



Order number: 51DC612MDD400A
EAN: 4069025359506

Version	Downlight for ceiling surface mounting or suspended mounting
Lamps	LED 4000 K | CRI ≥ 90
Controlgear	ECG Multilumen
Rated values	Net luminous flux = 3790 lm Power consumption = 26.2 W Luminous efficacy = 144.7 lm/W


LP number
59721_40

serial documentation
14.05.2025

siteco

Luminous intensity in cd/klm C180-0

Imax: 477 cd/klm



Classifications

DIN 5040	A 5 0
CIE	N1=62 N2=91 N3=99 N4=100 N5=100

Luminaire light output ratios

ηLB	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family	Order number: 51DC612MDD400A	LP number
Lunis R LED	**EAN: 4069025359506**	**59721_40**

siteco

Table of values for luminous intensities

Maximum luminous intensity

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm	Luminous flux in lm/klm	
0,0°	467.9	**0.7**	**0.7**
2,5°	468.8	**5.6**	**6.3**
5,0°	476.3	**11.4**	**17.7**
7,5°	476.9	**17.1**	**34.7**
10,0°	471.1	**22.4**	**57.2**
12,5°	462.5	**27.4**	**84.6**
15,0°	454.8	**32.3**	**116.9**
17,5°	447.5	**36.9**	**153.8**
20,0°	443.2	**41.6**	**195.3**
22,5°	435.9	**45.7**	**241.1**
25,0°	428.6	**49.7**	**290.7**
27,5°	413.5	**52.3**	**343.0**
30,0°	400.2	**54.8**	**397.9**
32,5°	377.0	**55.5**	**453.4**
35,0°	356.6	**56.1**	**509.5**
37,5°	329.5	**55.0**	**564.5**
40,0°	305.5	**53.8**	**618.3**
42,5°	276.3	**51.2**	**669.5**
45,0°	253.9	**49.2**	**718.7**
47,5°	221.7	**44.8**	**763.5**
50,0°	197.9	**41.6**	**805.1**
52,5°	169.3	**36.8**	**841.9**
55,0°	145.9	**32.8**	**874.6**
57,5°	121.3	**28.1**	**902.7**
60,0°	99.1	**23.5**	**926.2**
62,5°	75.2	**18.3**	**944.5**
65,0°	62.7	**15.6**	**960.1**
67,5°	47.9	**12.1**	**972.2**
70,0°	39.8	**10.2**	**982.5**
72,5°	29.5	**7.7**	**990.2**
75,0°	21.8	**5.8**	**996.0**
77,5°	9.4	**2.5**	**998.5**
80,0°	3.7	**1.0**	**999.5**
82,5°	0.8	**0.2**	**999.7**
85,0°	0.7	**0.2**	**999.9**
87,5°	0.4	**0.1**	**1000.0**
90,0°	0.0	**0.0**	**1000.0**

Photometric test report

Family	Order number: 51DC612MDD400A	LP number
Lunis R LED	**EAN: 4069025359506**	**59721_40**

siteco

UGR-Table

Standard room

Reflection factor of ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Reflection factor of walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reflection factor of floor		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions			View crosswise (C0)					View endwise (C90)			
x	y										
2H	2H	20.8	22.3	21.2	22.7	23.0	20.8	22.3	21.2	22.7	23.0
	3H	21.3	22.7	21.7	23.0	23.4	21.3	22.7	21.7	23.0	23.4
	4H	21.4	22.7	21.8	23.0	23.4	21.4	22.7	21.8	23.0	23.4
	6H	21.4	22.6	21.8	22.9	23.3	21.4	22.6	21.8	22.9	23.3
	8H	21.4	22.5	21.9	22.9	23.3	21.4	22.5	21.9	22.9	23.3
	12H	21.4	22.4	21.9	22.8	23.2	21.4	22.4	21.9	22.8	23.2
4H	2H	21.1	22.4	21.5	22.7	23.1	21.1	22.4	21.5	22.7	23.1
	3H	21.7	22.8	22.2	23.2	23.6	21.7	22.8	22.2	23.2	23.6
	4H	21.9	22.8	22.3	23.2	23.7	21.9	22.8	22.3	23.2	23.7
	6H	21.9	22.7	22.3	23.1	23.6	21.9	22.7	22.3	23.1	23.6
	8H	21.9	22.6	22.3	23.0	23.5	21.9	22.6	22.3	23.0	23.5
	12H	21.9	22.5	22.3	22.9	23.4	21.9	22.5	22.3	22.9	23.4
8H	4H	21.9	22.6	22.4	23.1	23.6	21.9	22.6	22.4	23.1	23.6
	6H	21.9	22.5	22.4	23.0	23.5	21.9	22.5	22.4	23.0	23.5
	8H	21.9	22.4	22.4	22.9	23.4	21.9	22.4	22.4	22.9	23.4
	12H	21.8	22.3	22.4	22.8	23.3	21.8	22.3	22.4	22.8	23.3
12H	4H	21.9	22.5	22.4	23.0	23.5	21.9	22.5	22.4	23.0	23.5
	6H	21.9	22.4	22.4	22.9	23.4	21.9	22.4	22.4	22.9	23.4
	8H	21.8	22.3	22.4	22.8	23.3	21.8	22.3	22.4	22.8	23.3

Luminance table

Max. for $\gamma >= 65°$

Photometric dimensions in mm: D = 308


C-planes	0°
γ	Luminance in cd/m²
45,0°	18263.1
50,0°	15663.8
55,0°	12941.5
60,0°	10085.6
65,0°	7550.2
70,0°	5912.7
75,0°	4287.3
80,0°	1085.0
85,0°	392.8

Photometric test report

Family	Order number: 51DC612MDD400A	LP number
Lunis R LED	**EAN: 4069025359506**	**59721_40**

Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85°

siteco



Photometric test report

Family	Order number: 51DC612MDD400A	LP number
Lunis R LED	**EAN: 4069025359506**	**59721_40**

siteco

Multilumen Table

environmental temperature: 25°C

DIP-Step	Switch Setting 1	2	3	Luminous flux [lm]	Power consumption [W]
7	ON	ON	ON	3790	26.2
6	OFF	ON	ON	3540	24.3
5	ON	OFF	ON	3280	22.4
4	OFF	OFF	ON	3030	20.6
3	ON	ON	OFF	2770	18.7
2	OFF	ON	OFF	2500	17.0
1	ON	OFF	OFF	2240	15.3
0	OFF	OFF	OFF	1970	13.5