



Photometric test report

Family Highbay 11	Order number: 51HN32TATFDA EAN: 4069025494429	LP number 59710_510
	Version primary light control with lens, PMMA, housing, black, wide distribution Lamps LED 4000 K CRI ≥ 80 Controlgear ECG-DALI Setting factory setting	serial documentation 02.07.2025
	Rated values Net luminous flux = 12780 lm Power consumption = 71.8 W Luminous efficacy = 178 lm/W	

Luminous intensity in cd/klm C180-0 C270-90 **Imax: 772 cd/klm**



Classifications	
DIN 5040	A 6 0
CIE	N1=88 N2=98 N3=100 N4=100 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions
 DIN EN 13032 and DIN 5032

Photometric test report

Family Highbay 11	Order number: 51HN32TATFDA EAN: 4069025494429	LP number 59710_510
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm							Luminous flux in lm/klm		
0,0°	643.6	643.6	643.6	643.6	643.6	643.6	643.6	1.0	1.0
2,5°	644.5	645.1	645.0	644.3	644.2	643.7	641.7	7.7	8.7
5,0°	651.5	652.3	650.7	647.5	645.3	643.2	640.4	15.5	24.1
7,5°	669.6	669.1	664.2	657.2	651.2	645.8	641.3	23.5	47.6
10,0°	693.4	691.0	681.5	670.0	659.9	651.2	645.8	31.9	79.6
12,5°	711.8	709.4	700.3	685.9	671.9	660.7	654.0	40.7	120.2
15,0°	721.3	721.7	717.1	704.9	689.4	675.9	667.7	49.7	169.9
17,5°	743.8	740.8	737.9	726.5	708.9	693.0	684.2	59.4	229.3
20,0°	761.9	761.9	759.6	745.2	724.0	705.6	696.8	69.2	298.5
22,5°	772.0	771.2	770.0	754.7	731.1	710.8	702.6	78.2	376.7
25,0°	758.1	756.6	756.3	743.6	722.7	703.3	695.6	85.1	461.8
27,5°	706.7	709.5	709.5	700.0	685.7	672.3	667.0	87.8	549.7
30,0°	640.4	635.6	633.7	626.6	621.7	614.1	609.9	85.8	635.5
32,5°	530.6	537.6	535.6	526.2	530.2	524.1	520.8	78.1	713.6
35,0°	428.2	426.4	425.9	411.9	420.8	414.2	411.4	66.0	779.6
37,5°	322.5	323.4	327.0	311.0	319.4	310.8	308.2	53.0	832.6
40,0°	236.1	234.0	241.6	230.8	230.9	219.8	218.4	40.7	873.3
42,5°	162.3	165.3	172.9	171.1	161.7	151.3	150.8	30.2	903.5
45,0°	117.3	114.9	119.4	122.5	109.3	102.6	102.3	21.9	925.4
47,5°	80.5	81.4	82.8	85.5	75.2	71.4	70.8	15.9	941.3
50,0°	59.4	58.0	58.0	59.0	52.9	50.5	49.6	11.7	953.0
52,5°	43.3	42.8	42.8	43.0	39.3	37.2	36.6	8.9	961.8
55,0°	33.3	32.4	32.9	33.7	30.5	28.7	28.3	7.1	968.9
57,5°	25.9	25.4	25.9	26.8	24.5	22.9	22.9	5.8	974.7
60,0°	20.9	20.2	21.2	21.8	20.4	18.9	19.2	4.9	979.5
62,5°	16.9	16.2	17.4	18.0	17.2	15.9	16.4	4.1	983.6
65,0°	14.9	13.6	14.4	15.1	14.8	13.6	14.4	3.6	987.2
67,5°	12.3	11.4	12.5	12.4	13.0	11.7	12.6	3.1	990.3
70,0°	10.4	9.5	10.5	10.1	11.1	10.1	11.0	2.7	993.0
72,5°	8.2	7.7	7.9	8.2	8.7	8.6	9.5	2.2	995.2
75,0°	6.5	6.0	6.0	6.4	6.6	7.1	7.9	1.7	996.9
77,5°	4.5	4.3	4.4	4.7	5.1	5.6	6.3	1.3	998.2
80,0°	2.9	2.7	2.9	3.1	3.5	4.1	4.7	0.9	999.1
82,5°	1.3	1.4	1.6	1.8	2.2	2.7	3.3	0.5	999.7
85,0°	0.6	0.6	0.6	0.7	1.0	1.4	1.8	0.3	999.9
87,5°	0.3	0.3	0.3	0.3	0.3	0.4	0.5	0.1	1000.0
90,0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family Highbay 11	Order number: 51HN32TATFDA EAN: 4069025494429	LP number 59710_510
----------------------	--	------------------------

UGR-Table	Standard room	siteco	
-----------	---------------	--------	--

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	19.4	20.7	19.7	21.0	21.3	19.1	20.4	19.4	20.7	21.0
	3H	19.4	20.5	19.8	20.8	21.2	19.1	20.2	19.5	20.6	20.9
	4H	19.4	20.4	19.8	20.8	21.1	19.1	20.2	19.5	20.5	20.9
	6H	19.3	20.3	19.7	20.6	21.0	19.1	20.1	19.5	20.4	20.8
	8H	19.4	20.2	19.8	20.6	21.0	19.2	20.0	19.7	20.4	20.8
	12H	19.4	20.1	19.8	20.5	20.9	19.2	20.0	19.7	20.3	20.8
4H	2H	19.3	20.3	19.7	20.7	21.0	19.0	20.0	19.4	20.4	20.7
	3H	19.3	20.2	19.7	20.5	21.0	19.0	19.9	19.5	20.3	20.7
	4H	19.3	20.1	19.7	20.5	20.9	19.1	19.9	19.5	20.3	20.7
	6H	19.3	19.9	19.7	20.4	20.8	19.1	19.8	19.6	20.2	20.7
	8H	19.2	19.8	19.7	20.3	20.8	19.1	19.7	19.6	20.2	20.7
	12H	19.3	19.7	19.8	20.2	20.7	19.2	19.7	19.7	20.1	20.6
8H	4H	19.2	19.8	19.7	20.3	20.7	19.0	19.6	19.5	20.1	20.5
	6H	19.2	19.7	19.7	20.2	20.7	19.1	19.6	19.6	20.0	20.5
	8H	19.2	19.6	19.7	20.1	20.6	19.1	19.5	19.6	20.0	20.5
	12H	19.2	19.5	19.7	20.0	20.5	19.1	19.4	19.7	20.0	20.5
12H	4H	19.2	19.7	19.7	20.2	20.7	19.0	19.5	19.5	20.0	20.5
	6H	19.2	19.6	19.7	20.1	20.6	19.1	19.5	19.6	19.9	20.5
	8H	19.2	19.5	19.7	20.0	20.5	19.1	19.4	19.6	19.9	20.5

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm:	L = 426 B = 264
-----------------	---------------------------------	-------------------------------	--------------------

C-planes	γ	Luminance in cd/m ²							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
45,0°		18854.8	18462.2	19191.2	19683.1	17560.0	16487.2	16438.6	
50,0°		10505.2	10256.8	10246.0	10429.0	9358.4	8923.0	8769.9	
55,0°		6601.9	6425.4	6517.1	6666.7	6047.6	5684.8	5616.5	
60,0°		4748.4	4583.9	4816.4	4960.9	4644.8	4301.4	4356.1	
65,0°		4006.7	3644.8	3884.9	4052.4	3968.2	3669.8	3877.1	
70,0°		3443.8	3142.1	3475.7	3362.7	3689.0	3358.1	3667.4	
75,0°		2838.1	2628.6	2621.6	2803.8	2913.1	3118.2	3476.0	
80,0°		1916.1	1787.8	1891.9	2043.7	2306.8	2713.2	3092.7	
85,0°		765.3	761.4	786.2	920.5	1361.2	1813.6	2349.5	

Photometric test report

Family
Highbay 11

Order number: 51HN32TATFDA
EAN: 4069025494429

LP number
59710_510

Luminance values in cd/m²

γ 65° γ 70° γ 75° γ 80° γ 85°

