Photometric test report

Family
Escape route lighting



Order number: 5SCC5ECAO
EAN: 4069025400925

LP number
59810_8

serial documentation
08.07.2025


Version	Escape route light, for recessed ceiling mounting, lens, corridor lighting, symmetric distribution
Lamps	LED 6000 K | CRI ≥ 80
Controlgear	ECG
Rated values	Net luminous flux = 330 lm Power consumption = 3.0 W Luminous efficacy = 110 lm/W

siteco

Luminous intensity in cd/klm

C180-0 C270-90

Imax: 848 cd/klm



Classifications

DIN 5040	A 3 0
CIE	N1=41 N2=73 N3=96 N4=100 N5=100

Luminaire light output ratios

ηLB	100.0%
ϕ_u	99.9%
ϕ_o	0.1%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family	Order number: 5SCC5ECAO	LP number
Escape route lighting	**EAN: 4069025400925**	**59810_8**

siteco

Table of values for luminous intensities

Maximum luminous intensity

C-planes	0° 180°	45° 135° 225° 315°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm			Luminous flux in lm/klm	
0,0°	449.2	449.2	449.2	0.7	0.7
2,5°	449.3	447.9	436.8	5.3	6.0
5,0°	449.9	434.1	417.6	10.4	16.4
7,5°	451.5	417.6	392.2	15.0	31.4
10,0°	451.8	399.6	366.2	19.2	50.6
12,5°	452.7	380.7	335.2	23.0	73.6
15,0°	451.7	360.9	306.1	26.2	99.9
17,5°	451.4	337.4	268.3	28.7	128.6
20,0°	449.6	317.1	235.9	30.9	159.5
22,5°	447.8	292.5	202.2	32.4	191.9
25,0°	444.1	264.6	154.2	32.7	224.6
27,5°	435.8	243.5	119.7	33.0	257.6
30,0°	426.4	213.6	61.0	31.3	288.9
32,5°	422.1	187.7	50.5	31.2	320.1
35,0°	420.2	151.0	50.9	30.4	350.5
37,5°	430.0	131.0	46.0	30.8	381.3
40,0°	448.7	81.0	48.9	29.1	410.4
42,5°	461.7	50.3	51.9	28.4	438.8
45,0°	514.2	51.3	53.7	32.5	471.3
47,5°	586.3	53.8	51.6	37.7	509.0
50,0°	638.4	44.9	52.2	41.0	549.9
52,5°	678.8	47.8	52.7	45.0	594.9
55,0°	757.4	49.8	54.3	51.2	646.1
57,5°	848.0	53.2	47.9	57.9	704.0
60,0°	836.5	55.0	42.6	58.7	762.7
62,5°	763.5	49.9	45.5	55.3	818.0
65,0°	627.8	44.0	41.6	47.1	865.0
67,5°	472.9	40.4	30.1	37.0	902.0
70,0°	273.7	42.1	19.7	24.3	926.3
72,5°	172.1	47.5	14.2	18.4	944.7
75,0°	124.5	52.2	8.2	15.7	960.4
77,5°	72.9	52.3	4.8	12.2	972.6
80,0°	60.4	46.3	3.3	10.6	983.1
82,5°	55.1	29.8	3.4	8.0	991.1
85,0°	42.5	17.4	5.1	5.6	996.8
87,5°	7.6	8.2	5.3	2.0	998.8
90,0°	1.6	1.3	2.9	0.5	999.3
92,5°	2.7	2.8	2.4	0.7	1000.0
95,0°	0.0	0.0	0.0	0.0	1000.0
97,5°	0.0	0.0	0.0	0.0	1000.0
100,0°	0.0	0.0	0.0	0.0	1000.0
102,5°	0.0	0.0	0.0	0.0	1000.0
105,0°	0.0	0.0	0.0	0.0	1000.0
107,5°	0.0	0.0	0.0	0.0	1000.0
110,0°	0.0	0.0	0.0	0.0	1000.0

Photometric test report

Family	Order number: 5SCC5ECAO	LP number
Escape route lighting	**EAN: 4069025400925**	**59810_8**

siteco

Table of values for luminous intensities

Maximum luminous intensity

C-planes	0° 180°	45° 135° 225° 315°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm			Luminous flux in lm/klm	
112,5°	0.0	0.0	0.0	**0.0**	**1000.0**
115,0°	0.0	0.0	0.0	**0.0**	**1000.0**
117,5°	0.0	0.0	0.0	**0.0**	**1000.0**
120,0°	0.0	0.0	0.0	**0.0**	**1000.0**
122,5°	0.0	0.0	0.0	**0.0**	**1000.0**
125,0°	0.0	0.0	0.0	**0.0**	**1000.0**
127,5°	0.0	0.0	0.0	**0.0**	**1000.0**
130,0°	0.0	0.0	0.0	**0.0**	**1000.0**
132,5°	0.0	0.0	0.0	**0.0**	**1000.0**
135,0°	0.0	0.0	0.0	**0.0**	**1000.0**
137,5°	0.0	0.0	0.0	**0.0**	**1000.0**
140,0°	0.0	0.0	0.0	**0.0**	**1000.0**
142,5°	0.0	0.0	0.0	**0.0**	**1000.0**
145,0°	0.0	0.0	0.0	**0.0**	**1000.0**
147,5°	0.0	0.0	0.0	**0.0**	**1000.0**
150,0°	0.0	0.0	0.0	**0.0**	**1000.0**
152,5°	0.0	0.0	0.0	**0.0**	**1000.0**
155,0°	0.0	0.0	0.0	**0.0**	**1000.0**
157,5°	0.0	0.0	0.0	**0.0**	**1000.0**
160,0°	0.0	0.0	0.0	**0.0**	**1000.0**
162,5°	0.0	0.0	0.0	**0.0**	**1000.0**
165,0°	0.0	0.0	0.0	**0.0**	**1000.0**
167,5°	0.0	0.0	0.0	**0.0**	**1000.0**
170,0°	0.0	0.0	0.0	**0.0**	**1000.0**
172,5°	0.0	0.0	0.0	**0.0**	**1000.0**
175,0°	0.0	0.0	0.0	**0.0**	**1000.0**
177,5°	0.0	0.0	0.0	**0.0**	**1000.0**
180,0°	0.0	0.0	0.0	**0.0**	**1000.0**

Photometric test report

Family	Order number: 5SCC5ECAO	LP number
Escape route lighting	EAN: 4069025400925	59810_8

siteco

UGR-Table

Standard room

Reflection factor of ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Reflection factor of walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reflection factor of floor		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions			View crosswise (C0)					View endwise (C90)			
x	y										
2H	2H	42.6	44.4	43.0	44.7	45.0	24.4	26.1	24.7	26.4	26.7
	3H	44.3	45.8	44.7	46.1	46.5	25.9	27.5	26.3	27.9	28.2
	4H	44.5	45.8	44.9	46.2	46.5	26.0	27.6	26.4	28.0	28.3
	6H	44.5	45.7	45.0	46.1	46.5	26.0	27.5	26.4	27.9	28.3
	8H	44.7	45.7	45.1	46.1	46.5	26.0	27.5	26.4	27.9	28.3
	12H	44.7	45.6	45.1	46.0	46.4	26.0	27.5	26.5	27.8	28.3
4H	2H	42.4	44.0	42.8	44.3	44.7	29.4	30.8	29.8	31.1	31.5
	3H	44.1	45.4	44.5	45.7	46.1	29.9	31.1	30.3	31.5	31.9
	4H	44.3	45.4	44.7	45.8	46.2	30.0	31.2	30.5	31.6	32.0
	6H	44.4	45.3	44.8	45.8	46.2	30.0	31.1	30.5	31.5	32.0
	8H	44.5	45.3	44.9	45.7	46.2	30.0	31.0	30.5	31.4	31.9
	12H	44.6	45.2	45.1	45.7	46.2	30.0	30.9	30.5	31.4	31.9
8H	4H	44.1	45.1	44.6	45.6	46.0	31.7	32.5	32.2	32.9	33.4
	6H	44.3	45.1	44.8	45.5	46.0	32.0	32.7	32.5	33.2	33.7
	8H	44.4	45.0	44.9	45.5	46.0	32.0	32.7	32.5	33.2	33.7
	12H	44.5	45.0	45.0	45.5	46.0	32.0	32.6	32.5	33.1	33.7
12H	4H	44.1	45.0	44.6	45.5	46.0	32.0	32.6	32.4	33.1	33.6
	6H	44.2	44.9	44.7	45.4	45.9	32.4	33.0	32.9	33.4	34.0
	8H	44.3	44.9	44.8	45.4	45.9	32.5	33.0	33.0	33.5	34.0

Luminance table

Max. for $\gamma >= 65°$

Photometric dimensions in mm: L = 10, B = 10, H(C0) = 5, H(C90) = 5, H(C180) = 5, H(C270) = 5

C-planes	0° 180°	45° 135° 225° 315°	90° 270°
γ	Luminance in cd/m²		
45,0°	1599858.5	140162.4	167006.7
50,0°	2053662.5	125169.9	167800.4
55,0°	2542150.0	142442.2	182300.9
60,0°	2958761.6	163304.2	150743.9
65,0°	2365686.9	136620.5	156885.0
70,0°	1112360.2	137999.0	80103.2
75,0°	553900.1	183035.6	36461.9
80,0°	299350.0	175781.3	16196.5
85,0°	239876.7	72639.3	28706.0

Photometric test report

Family	Order number: 5SCC5ECAO	LP number
Escape route lighting	**EAN: 4069025400925**	**59810_8**

Luminance values in cd/m²

γ 65° γ 70° γ 75° γ 80° γ 85°

