
Photometric test report

Family
Escape route lighting



Order number: 5SLC5SCC3
EAN: 4069025401335


LP number
59814_5

serial documentation
08.07.2025

Version	Escape route light, for wall and ceiling surface-mounting, lens, symmetric distribution
Lamps	LED 6000 K | CRI ≥ 80
Controlgear	ECG
Rated values	Net luminous flux = 290 lm Power consumption = 3.0 W Luminous efficacy = 96.7 lm/W

siteco

Luminous intensity in cd/klm C180-0 C270-90 **Imax: 379 cd/klm**



Classifications

DIN 5040	B 4 1
CIE	N1=46 N2=75 N3=91 N4=88 N5=100

Luminaire light output ratios

ηLB	100.0%
ϕ_u	87.7%
ϕ_o	12.3%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family	Order number: 5SLC5SCC3	LP number
Escape route lighting	**EAN: 4069025401335**	**59814_5**

siteco

Table of values for luminous intensities

Maximum luminous intensity

C-planes	0° 180°	45° 135° 225° 315°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm			Luminous flux in lm/klm	
0,0°	313.4	313.4	313.4	0.5	0.5
2,5°	313.1	343.0	378.7	4.1	4.6
5,0°	309.0	353.1	324.1	8.0	12.6
7,5°	302.3	323.2	318.6	11.3	23.9
10,0°	292.3	305.1	325.9	14.6	38.5
12,5°	282.6	285.1	306.2	17.2	55.7
15,0°	281.6	288.7	260.3	19.9	75.6
17,5°	281.6	275.9	256.2	22.5	98.0
20,0°	290.3	254.6	282.3	25.4	123.4
22,5°	294.7	248.3	320.9	29.2	152.6
25,0°	286.9	242.7	306.5	31.2	183.8
27,5°	278.2	247.9	260.5	32.7	216.6
30,0°	263.2	243.8	214.3	33.1	249.6
32,5°	238.9	251.9	219.7	35.4	285.1
35,0°	214.8	258.9	225.3	37.7	322.7
37,5°	197.5	251.5	253.8	39.8	362.5
40,0°	186.7	232.2	262.5	40.2	402.8
42,5°	169.1	203.9	233.5	37.5	440.3
45,0°	149.2	180.8	178.1	33.4	473.7
47,5°	139.1	165.7	154.6	31.6	505.3
50,0°	133.3	167.5	176.8	33.9	539.1
52,5°	117.9	168.8	183.9	34.8	573.9
55,0°	91.3	164.7	198.4	34.8	608.6
57,5°	68.3	165.2	187.6	33.9	642.5
60,0°	49.9	165.4	177.2	33.1	675.7
62,5°	37.9	149.5	125.5	28.1	703.8
65,0°	60.3	140.5	95.7	27.1	730.9
67,5°	40.8	119.4	68.5	22.0	752.9
70,0°	45.4	70.1	84.8	17.4	770.4
72,5°	50.7	52.2	113.6	17.6	787.9
75,0°	36.4	41.6	170.2	19.2	807.1
77,5°	20.4	42.0	91.4	13.1	820.2
80,0°	14.2	91.1	123.7	21.6	841.8
82,5°	11.0	60.2	50.2	12.3	854.2
85,0°	10.2	56.9	94.2	14.9	869.1
87,5°	13.3	31.6	27.1	7.1	876.1
90,0°	4.5	7.3	12.6	2.2	878.3
92,5°	5.3	12.2	15.5	3.1	881.4
95,0°	5.6	30.9	30.8	6.7	888.1
97,5°	4.5	45.9	44.4	9.6	897.7
100,0°	3.0	49.8	45.8	10.0	907.7
102,5°	3.0	48.9	52.6	10.3	918.0
105,0°	6.0	47.3	53.7	10.2	928.2
107,5°	9.5	47.4	48.8	10.0	938.2
110,0°	11.0	51.5	47.0	10.4	948.5

Photometric test report

Family	Order number: 5SLC5SCC3	LP number
Escape route lighting	**EAN: 4069025401335**	**59814_5**

siteco

Table of values for luminous intensities

Maximum luminous intensity

C-planes	0° 180°	45° 135° 225° 315°	90° 270°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm			Luminous flux in lm/klm	
112,5°	11.4	51.6	49.8	**10.4**	**959.0**
115,0°	8.4	43.5	63.9	**9.9**	**968.9**
117,5°	3.4	40.3	52.8	**8.3**	**977.2**
120,0°	3.8	29.4	63.5	**7.5**	**984.7**
122,5°	4.6	26.4	84.9	**8.2**	**992.9**
125,0°	3.5	25.0	27.9	**4.6**	**997.5**
127,5°	5.0	5.8	13.9	**1.7**	**999.1**
130,0°	5.3	3.2	5.1	**0.9**	**1000.0**
132,5°	0.0	0.0	0.0	**0.0**	**1000.0**
135,0°	0.0	0.0	0.0	**0.0**	**1000.0**
137,5°	0.0	0.0	0.0	**0.0**	**1000.0**
140,0°	0.0	0.0	0.0	**0.0**	**1000.0**
142,5°	0.0	0.0	0.0	**0.0**	**1000.0**
145,0°	0.0	0.0	0.0	**0.0**	**1000.0**
147,5°	0.0	0.0	0.0	**0.0**	**1000.0**
150,0°	0.0	0.0	0.0	**0.0**	**1000.0**
152,5°	0.0	0.0	0.0	**0.0**	**1000.0**
155,0°	0.0	0.0	0.0	**0.0**	**1000.0**
157,5°	0.0	0.0	0.0	**0.0**	**1000.0**
160,0°	0.0	0.0	0.0	**0.0**	**1000.0**
162,5°	0.0	0.0	0.0	**0.0**	**1000.0**
165,0°	0.0	0.0	0.0	**0.0**	**1000.0**
167,5°	0.0	0.0	0.0	**0.0**	**1000.0**
170,0°	0.0	0.0	0.0	**0.0**	**1000.0**
172,5°	0.0	0.0	0.0	**0.0**	**1000.0**
175,0°	0.0	0.0	0.0	**0.0**	**1000.0**
177,5°	0.0	0.0	0.0	**0.0**	**1000.0**
180,0°	0.0	0.0	0.0	**0.0**	**1000.0**

Photometric test report

Family	Order number: 5SLC5SCC3	LP number
Escape route lighting	**EAN: 4069025401335**	**59814_5**

siteco

UGR-Table

Standard room

Reflection factor of ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Reflection factor of walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reflection factor of floor		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		View crosswise (C0)					View endwise (C90)				
x	y										
2H	2H	14.0	15.6	14.5	16.0	16.5	16.9	18.5	17.4	18.9	19.4
	3H	14.9	16.4	15.4	16.8	17.4	18.0	19.4	18.5	19.9	20.4
	4H	15.5	16.9	16.0	17.3	17.9	20.5	21.8	21.0	22.3	22.8
	6H	15.6	16.8	16.2	17.4	18.0	21.9	23.0	22.5	23.6	24.2
	8H	15.7	16.8	16.2	17.3	18.0	22.4	23.5	23.0	24.1	24.7
	12H	15.7	16.7	16.3	17.3	18.0	23.1	24.1	23.7	24.7	25.4
4H	2H	15.8	17.1	16.3	17.6	18.1	17.7	19.0	18.2	19.5	20.0
	3H	16.8	17.9	17.3	18.4	19.0	18.9	20.1	19.5	20.6	21.2
	4H	17.2	18.2	17.8	18.8	19.4	21.4	22.4	21.9	22.9	23.6
	6H	17.3	18.2	17.9	18.8	19.5	23.1	23.9	23.7	24.6	25.3
	8H	17.5	18.3	18.1	18.9	19.6	23.7	24.5	24.3	25.1	25.8
	12H	17.5	18.2	18.1	18.8	19.6	24.6	25.2	25.2	25.9	26.6
8H	4H	17.7	18.5	18.3	19.1	19.8	21.4	22.2	22.0	22.9	23.5
	6H	18.9	19.6	19.6	20.3	21.0	23.8	24.5	24.4	25.1	25.8
	8H	19.3	19.9	19.9	20.5	21.3	24.4	25.0	25.0	25.6	26.3
	12H	19.3	19.8	20.0	20.5	21.3	25.6	26.1	26.3	26.7	27.5
12H	4H	18.1	18.8	18.8	19.5	20.2	21.4	22.1	22.0	22.7	23.5
	6H	19.6	20.1	20.3	20.8	21.6	23.7	24.3	24.4	25.0	25.8
	8H	20.1	20.6	20.8	21.3	22.1	24.4	24.9	25.1	25.6	26.4

Luminance table

Max. for $\gamma >= 65°$

Photometric dimensions in mm: L = 295, B = 82

C-planes	0° 180°	45° 135° 225° 315°	90° 270°
γ	Luminance in cd/m²		
45,0°	2529.3	3065.8	3019.0
50,0°	2485.6	3123.1	3297.6
55,0°	1907.8	3441.6	4147.2
60,0°	1197.4	3966.7	4249.2
65,0°	1709.5	3986.6	2713.6
70,0°	1589.9	2456.4	2972.0
75,0°	1687.4	1927.1	7883.6
80,0°	983.7	6291.6	8539.1
85,0°	1398.5	7823.3	12959.6

Photometric test report

Family	Order number: 5SLC5SCC3	LP number
Escape route lighting	**EAN: 4069025401335**	**59814_5**

Luminance values in cd/m²



