Photometric test report

Family
Lunis 21



Order number: 51DB11ED21B1D
EAN: 4069025442499

LP number
59852_19


serial documentation
13.10.2025

Version	surface-mounted luminaire, Combined lens and reflector optics, reflector, aluminium, highly specular, rotationally symmetrical narrow distribution, UGR≤19 (L65≤3000cd/m²)
Lamps	LED 3000 K | CRI ≥ 90
Controlgear	ECG Multilumen
Setting	factory setting: DIP-Step=0
Rated values	Net luminous flux = 2230 lm Power consumption = 14.3 W Luminous efficacy = 155.9 lm/W

siteco

Luminous intensity in cd/klm C180-0

Imax: 2279 cd/klm



Classifications

DIN 5040	A 7 0
CIE	N1=90 N2=99 N3=100 N4=100 N5=100

Luminaire light output ratios

ηLB	100.0%
ϕ_u	100.0%
ϕ_o	0.0%

Measurement conditions

DIN EN 13032 and DIN 5032

Photometric test report

Family	Order number: 51DB11ED21B1D	LP number
Lunis 21	EAN: 4069025442499	59852_19

siteco

Table of values for luminous intensities

Maximum luminous intensity

C-planes	0°	Phi-zone	Total Phi-zone
γ	Luminous intensity in cd/klm	Luminous flux in lm/klm	
0,0°	2278.6	3.4	3.4
2,5°	2238.1	26.8	30.2
5,0°	2156.8	51.5	81.7
7,5°	2001.4	71.6	153.3
10,0°	1754.2	83.5	236.8
12,5°	1481.2	87.9	324.7
15,0°	1225.4	86.9	411.6
17,5°	984.8	81.2	492.8
20,0°	774.0	72.6	565.4
22,5°	608.1	63.8	629.2
25,0°	482.9	56.0	685.2
27,5°	388.1	49.1	734.3
30,0°	319.1	43.7	778.0
32,5°	253.7	37.4	815.4
35,0°	204.7	32.2	847.6
37,5°	166.2	27.7	875.3
40,0°	134.4	23.7	899.0
42,5°	108.6	20.1	919.1
45,0°	88.9	17.2	936.4
47,5°	73.5	14.9	951.2
50,0°	60.9	12.8	964.0
52,5°	50.3	10.9	974.9
55,0°	38.4	8.6	983.6
57,5°	27.8	6.4	990.0
60,0°	19.0	4.5	994.5
62,5°	11.8	2.9	997.4
65,0°	7.3	1.8	999.2
67,5°	3.0	0.8	999.9
70,0°	0.2	0.1	1000.0
72,5°	0.0	0.0	1000.0
75,0°	0.0	0.0	1000.0
77,5°	0.0	0.0	1000.0
80,0°	0.0	0.0	1000.0
82,5°	0.0	0.0	1000.0
85,0°	0.0	0.0	1000.0
87,5°	0.0	0.0	1000.0
90,0°	0.0	0.0	1000.0

Photometric test report

Family	Order number: 51DB11ED21B1D	LP number
Lunis 21	EAN: 4069025442499	59852_19

siteco

UGR-Table

Standard room

Reflection factor of ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Reflection factor of walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reflection factor of floor		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions			View crosswise (C0)					View endwise (C90)			
x	y										
2H	2H	17.7	18.8	18.0	19.1	19.4	17.7	18.8	18.0	19.1	19.4
	3H	17.6	18.5	17.9	18.9	19.2	17.6	18.5	17.9	18.9	19.2
	4H	17.5	18.4	17.9	18.7	19.1	17.5	18.4	17.9	18.7	19.1
	6H	17.4	18.2	17.8	18.6	19.0	17.4	18.2	17.8	18.6	19.0
	8H	17.5	18.1	17.9	18.5	18.9	17.5	18.1	17.9	18.5	18.9
	12H	17.4	18.0	17.9	18.4	18.8	17.4	18.0	17.9	18.4	18.8
4H	2H	17.6	18.5	18.0	18.8	19.2	17.6	18.5	18.0	18.8	19.2
	3H	17.4	18.2	17.9	18.6	19.0	17.4	18.2	17.9	18.6	19.0
	4H	17.3	18.0	17.8	18.4	18.8	17.3	18.0	17.8	18.4	18.8
	6H	17.2	17.8	17.7	18.2	18.7	17.2	17.8	17.7	18.2	18.7
	8H	17.2	17.7	17.7	18.1	18.6	17.2	17.7	17.7	18.1	18.6
	12H	17.2	17.6	17.7	18.0	18.5	17.2	17.6	17.7	18.0	18.5
8H	4H	17.2	17.7	17.7	18.1	18.6	17.2	17.7	17.7	18.1	18.6
	6H	17.1	17.5	17.6	17.9	18.5	17.1	17.5	17.6	17.9	18.5
	8H	17.0	17.3	17.5	17.8	18.4	17.0	17.3	17.5	17.8	18.4
	12H	17.0	17.2	17.5	17.7	18.3	17.0	17.2	17.5	17.7	18.3
12H	4H	17.2	17.6	17.7	18.0	18.5	17.2	17.6	17.7	18.0	18.5
	6H	17.0	17.3	17.6	17.8	18.4	17.0	17.3	17.6	17.8	18.4
	8H	17.0	17.2	17.5	17.7	18.3	17.0	17.2	17.5	17.7	18.3

Luminance table

Max. for $\gamma >= 65°$

Photometric dimensions in mm: D = 134


C-planes	0°
γ	Luminance in cd/m²
45,0°	19876.7
50,0°	14980.3
55,0°	10592.7
60,0°	5996.5
65,0°	2740.0
70,0°	92.9
75,0°	0.0
80,0°	0.0
85,0°	0.0

Photometric test report

Family	Order number: 51DB11ED21B1D	LP number
Lunis 21	**EAN: 4069025442499**	**59852_19**

Luminance values in cd/m² γ 65° γ 70° γ 75° γ 80° γ 85°

siteco



Photometric test report

Family	Order number: 51DB11ED21B1D	LP number
Lunis 21	**EAN: 4069025442499**	**59852_19**

siteco

Multilumen Table

environmental temperature: 25°C

DIP-Step	Switch Setting 1	2	3	Luminous flux [lm]	Power consumption [W]
7	ON	ON	ON	4310	27.9
6	ON	ON	OFF	4020	25.9
5	ON	OFF	ON	3730	23.8
4	ON	OFF	OFF	3440	22.0
3	OFF	ON	ON	3140	20.2
2	OFF	ON	OFF	2840	18.1
1	OFF	OFF	ON	2540	16.2
0	OFF	OFF	OFF	2230	14.3